

## MAX4824PMB1 Peripheral Module

### General Description

The MAX4824PMB1 peripheral module provides the necessary hardware to interface the MAX4824 8-channel relay driver to any system that utilizes Pmod™-compatible expansion ports configurable for GPIO communication. Each independent channel in the IC features a 2.7Ω (typ) on-resistance and is guaranteed to sink 70mA (min) of load current. A zener kickback-protection circuit significantly reduces recovery time in applications where switching speed is critical. When driving relays, a unique power-save mode allows relay current to be reduced to a level just above the relay hold-current threshold. This mode keeps the relay activated while significantly reducing the power consumption.


Refer to the MAX4824 IC data sheet for detailed information regarding operation of the IC.

### Features

- ◆ Eight Independent Output Channels Capable of 70mA Sink Current
- ◆ Guaranteed 5Ω (max) R<sub>ON</sub>
- ◆ Drive Eight Relays (or Other Loads) Independently
- ◆ 4-Bit Parallel Interface (SPI Version of IC also Available)
- ◆ 12-Pin Pmod-Compatible Connector (GPIO)
- ◆ Example Software Written in C for Portability
- ◆ RoHS Compliant
- ◆ Proven PCB Layout
- ◆ Fully Assembled and Tested

[Ordering Information](#) appears at end of data sheet.

### MAX4824PMB1 Peripheral Module



*Pmod is a trademark of Digilent Inc.*

# MAX4824PMB1 Peripheral Module

## Component List

| DESIGNATION | QTY | DESCRIPTION                                                                          |
|-------------|-----|--------------------------------------------------------------------------------------|
| C1          | 1   | 1 $\mu$ F $\pm$ 10%, 10V X7R ceramic capacitor (0603)<br>TDK C1608X7R1A105K          |
| C2          | 1   | 0.1 $\mu$ F $\pm$ 10%, 16V X7R ceramic capacitor (0603)<br>Murata GRM188R71C104KA01D |
| C3          | 1   | 2.2 $\mu$ F $\pm$ 10%, 10V X5R ceramic capacitor (0603)<br>TDK C1608X5R1A225K/0.80   |

| DESIGNATION | QTY | DESCRIPTION                                               |
|-------------|-----|-----------------------------------------------------------|
| J1          | 1   | 12-pin (2 x 6) right-angle male header                    |
| J2          | 1   | 10-pin (2 x 5) straight male header                       |
| R1–R8       | 8   | 150 $\Omega$ $\pm$ 5% resistors (0603)                    |
| U1          | 1   | 8-channel relay driver (20 TQFN-EP*)<br>Maxim MAX4824ETP+ |
| —           | 1   | PCB: EPCB4824PM1                                          |

\*EP = Exposed pad.

## Component Suppliers

| SUPPLIER                               | PHONE        | WEBSITE                     |
|----------------------------------------|--------------|-----------------------------|
| Murata Electronics North America, Inc. | 770-436-1300 | www.murata-northamerica.com |
| TDK Corp.                              | 847-803-6100 | www.component.tdk.com       |

**Note:** Indicate that you are using the MAX4824PMB1 when contacting these component suppliers.

## Detailed Description

### GPIO Interface

The MAX4824PMB1 peripheral module can interface to the host by plugging directly into a Pmod-compatible port (configured for GPIO) through connector J1.

J1 provides connection of the module to the Pmod host through an interface similar to the Pmod Type 1 standard recommended by Digilent, but incorporates a 12in connector with eight I/O pins. See Table 1.

The J2 connector provides the connection to the open-drain relay outputs. See Table 2.

### Software and FPGA Code

Example software and drivers are available that execute directly without modification on several FPGA development boards, which support an integrated or synthesized microprocessor. These boards include the Digilent Nexys 3, Avnet LX9, and Avnet ZEDBoard, although other platforms can be added over time. Maxim provides complete Xilinx ISE projects containing HDL, Platform Studio, and SDK projects. In addition, a synthesized bit stream, ready for FPGA download, is provided for the demonstration application.

**Table 1. Connector J1 (GPIO Communication)**

| PIN | SIGNAL                  | DESCRIPTION                                                                                                                             |
|-----|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| 1   | $\overline{\text{CS}}$  | Chip-select input. This active-low signal latches in the values of LVL and A2, A1, A0.                                                  |
| 2   | LVL                     | Level input. When latched by $\overline{\text{CS}}$ , this signal determines whether a relay at a given address (A2, A1, A0) is active. |
| 3   | A1                      | A1 input. Relay address bit 1.                                                                                                          |
| 4   | A0                      | A0 input. Relay address bit 0.                                                                                                          |
| 5   | GND                     | Ground                                                                                                                                  |
| 6   | VCC                     | Power supply                                                                                                                            |
| 7   | A2                      | A2 input. Relay address bit 2.                                                                                                          |
| 8   | $\overline{\text{RES}}$ | Reset Input. This active-low pin sets all eight relays inactive.                                                                        |
| 9   | $\overline{\text{SET}}$ | Set Input. This active-low pin sets all eight relays active.                                                                            |
| 10  | PSAVE                   | Reduces coil current to relay hold-current threshold.                                                                                   |
| 11  | GND                     | Ground                                                                                                                                  |
| 12  | VCC                     | Power supply                                                                                                                            |

# MAX4824PMB1 Peripheral Module

**Table 2. Connector J2**

| PIN | SIGNAL | DESCRIPTION         |
|-----|--------|---------------------|
| 1   | OUT3   | Open-drain output 1 |
| 2   | OUT2   | Open-drain output 2 |
| 3   | OUT4   | Open-drain output 3 |
| 4   | OUT1   | Open-drain output 4 |
| 5   | OUT5   | Open-drain output 5 |
| 6   | OUT8   | Open-drain output 6 |
| 7   | OUT6   | Open-drain output 7 |
| 8   | OUT7   | Open-drain output 8 |
| 9   | GND    | Ground              |
| 10  | VCC    | Power supply        |

The software project (for the SDK) contains several source files intended to accelerate customer evaluation and design. These include a base application (maximModules.c) that demonstrates module functionality and uses an API interface (maximDeviceSpecificUtilities.c) to set and access Maxim device functions within a specific module.

The source code is written in standard ANSI C format, and all API documentation including theory/operation, register description, and function prototypes are documented in the API interface file (maximDeviceSpecificUtilities.h & .c).

The complete software kit is available for download at [www.maxim-ic.com](http://www.maxim-ic.com). Quick start instructions are also available as a separate document.




Figure 1. MAX4824PMB1 Peripheral Module Schematic

# MAX4824PMB1 Peripheral Module




Figure 2. MAX4824PMB1 Peripheral Module Component Placement Guide—Component Side




Figure 3. MAX4824PMB1 Peripheral Module PCB Layout—Component Side




Figure 4. MAX4824PMB1 Peripheral Module PCB Layout—Inner Layer 1 (Ground)

# MAX4824PMB1 Peripheral Module




Figure 5. MAX4824PMB1 Peripheral Module PCB Layout—Inner Layer 2 (Power)




Figure 6. MAX4824PMB1 Peripheral Module PCB Layout—Solder Side




Figure 7. MAX4824PMB1 Peripheral Module Component Placement Guide—Solder Side

# MAX4824PMB1 Peripheral Module

## ***Ordering Information***

| PART         | TYPE              |
|--------------|-------------------|
| MAX4824PMB1# | Peripheral Module |

#Denotes RoHS compliant.

# MAX4824PMB1 Peripheral Module

## Revision History

| REVISION<br>NUMBER | REVISION<br>DATE | DESCRIPTION     | PAGES<br>CHANGED |
|--------------------|------------------|-----------------|------------------|
| 0                  | 5/12             | Initial release | —                |

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

**Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600 \_\_\_\_\_ 7**

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А