Gas Springs Specification

Technical Specification

All gas springs packages are supplied with:

- 2 Gas springs **including a release valve**,
- 4 Metal eyes,
- 4 Metal ball joints with metric stud,
- 1 Gas release key (stud),
- 1 Instruction leaflet

Operating Temperature range : from -5ºc to +70ºc

Steel zinc or chrome plated metal end-fittings

Steel chrome plated rod

Steel black painted body

Manufactured in the United Kingdom


DO'S

- **Do use standard gas springs rod down.**
- **If springs are to be stored prior to use, it should be stored rod down to lubricate the rod seal.**
- **Do try to use ball joints to help avoid side load forces. If eyes are used, ensure a sloppy fit to allow lateral movement.**
- **Do ensure that the end-fittings are in line so that side load forces are not applied as a result of misalignement.**
- **Do try to use shorter springs close to the hinge rather than long stroke springs away from the hinge.**
- **Do provide physical stops to limit the spring's extremes. i.e. ensure that undue force is not applied to over compress or over extend the spring.**
- **Ensure the gas spring's end-fittings are fully screwed home.**
- **Where ball joints are used ensure the ball stud is flush with the surface and tightened.**

DON'TS

- **Do not scratch, dent, chip, bend or paint the rod.**
- **Do not puncture or incinerate. Please contact customer support for disposal instructions.**
- **Do not lubricate the gas spring.**
- **Do not cycle more than 15 times per minute.**
- **Under no circumstances attempt to regas a spring. This is an extremely hazardous operation.**
- **Do not reduce the force of the spring below its specified minimum working force**

Size 6 mm rod - Charged at 400N with Release Valve Minimum working force: 40N





Package Order Code	Stroke	Shoulder Length
7100668	60	184
7100670	100	264
7100681	150	364
7100693	200	464

Lengths in mm (+/- 2mm)

Gas Springs Specification


Size 8 mm rod - Charged at 600N with Release Valve Minimum working force: 100N







Package Order Code	Stroke	Shoulder Length
7100700	100	268
7100814	150	368
7100826	200	468
7100838	250	568

Lengths in mm (+/- 2mm)




Size 10 mm rod - Charged at 1200N with Release Valve Minimum working force: 150N







Package Order Code	Stroke	Shoulder Length
7100840	100	265
7100851	200	465
7100863	250	565
7100875	300	665

Lengths in mm (+/- 2mm)




Size 14 mm rod - Charged at 2500N with Release Valve Minimum working force: 250N





Package Order Code	Stroke	Shoulder Length
7100887	100	280
7100889	200	480
7100905	300	680
7100917	400	880
7100929	500	1080

Lengths in mm (+/- 2mm)



Gas Spring's Force Adjustement

ADJUSTING A STANDARD COMPRESSION GAS SPRING WITH A RELEASE VALVE

- ✦ Upon receipt fit the gas spring to the application, operate the springs and observe the movement. Care should be taken on this first compression. The supplied force in the spring might be so great that damage could occur to the part to which the gas springs are attached. For example, if the springs are attached to a sheet metal lid.
- ✦ Safely support the load and remove the gas springs. Unscrew the end-fitting from the body end (the piston chamber). There may be a threaded stud located in the body that will also need to be removed, please note that this stud has a hole drilled on one end of it to fit over the valve. The valve can now be seen by looking down into the gas spring.
- ✦ Hold the spring with the rod down and the valve facing away from you. Screw in the release valve key until you can feel the tip of the valve. In one flowing movement turn clockwise a quarter of a turn and immediately turn anti-clockwise a quarter of a turn. The sound of escaping gas should be heard (it is best to carry out this procedure in a quiet environment).
- ✦ The gas spring has a very small volume of nitrogen at high pressure. On the small size 6 and 8 mm springs, a release of nitrogen lasting more than a second could reduce the spring's force by 100 Newtons.
- ✦ Refit the gas springs to the application. If the force is still too great, repeat the above procedure until satisfied. If two gas springs are attached remove approximately the same amount of gas from each spring.
- ✦ If, as it occasionally happens, you let out too much gas, it is possible to re-charge release valved springs. Please contact Farnell InOne technical support.

FOR A VARIETY OF REASONS IT IS EXTREMELY DANGEROUS TO ATTEMPT TO REGAS THE GAS SPRINGS. THIS SHOULD NOT BE ATTEMPTED UNDER ANY CIRCUMSTANCES.

For technical support please contact:

Farnell InOne Technical Support

Tel: 08701 200 202 - Fax: 08701 200 203 - techsales@farnellinone.co.uk

www.farnellinone.co.uk

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А