

# Type AXLH -40 °C to +150 °C

## High Temperature Axial Leaded Aluminum Electrolytic Capacitors

### HIGH PERFORMANCE AXIAL LEADED ALUMINUM ELECTROLYTIC CAPACITORS



Type AXLH capacitors are a new generation of high performance aluminum electrolytic capacitors rated up to 2000 hours at 150 °C. They are designed for applications that place high demands on a capacitor. The capacitor's outstanding features include low ESR, low leakage current, a long shelf life and a high ripple current capability.

### Highlights

- 150 °C Operating Temperature
- Up to 28 Amps RMS Continuous Ripple Current
- Capacitance Range: 470 µF to 4700 µF
- High Vibration Resistance
- Very Long Shelf Life
- Low Leakage Current

### Specifications

|                                                 |                                                                                                                                                                |      |      |      |      |         |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|------|---------|
| Capacitance Range (100 Hz/+20 °C)               | 470 to 4700 µF                                                                                                                                                 |      |      |      |      |         |
| Capacitance Tolerance (100 Hz/+20 °C)           | -10/+30%                                                                                                                                                       |      |      |      |      |         |
| Rated Voltage                                   | 25, 40, 63 Vdc                                                                                                                                                 |      |      |      |      |         |
| Operating Temperature                           | -40 °C to +150 °C                                                                                                                                              |      |      |      |      |         |
| Leakage Current (at 20°C)                       | I = 0.003 CV +4.0 µA; after 5 minutes at rated voltage<br>I = leakage current in µAmps<br>C = rated capacitance in µF<br>V = rated DC Working voltage in Volts |      |      |      |      |         |
| Ripple Current vs. Frequency Correction Factors | Frequency (Hz)                                                                                                                                                 | 100  | 300  | 1000 | 5000 | 100 kHz |
|                                                 | Ripple Current Correction Factor                                                                                                                               | 0.35 | 0.57 | 0.8  | 1    | 1.04    |
| Shelf Life                                      | (+105 °C/0 Vdc): 5000 hours<br>(+40 °C/0 Vdc): 10 years                                                                                                        |      |      |      |      |         |
| Standard                                        | IEC 60384-4 long life grade 40/125/56                                                                                                                          |      |      |      |      |         |
| RoHS Compliant                                  |                                                                                                                                                                |      |      |      |      |         |

### Part Numbering System

AXLH

Type

222

Capacitance

222 = 2200 µF

P

Capacitance Tolerance

P = -10/+30%

025

Voltage Code

025 = 25 Vdc

040 = 40 Vdc

063 = 63 Vdc

E

Case Dia.Code

E = 20 mm

D

Case

Length Code

D = 27 mm

H = 35 mm

L = 43 mm

# Type AXLH -40 °C to +150 °C

## High Temperature Axial Leaded Aluminum Electrolytic Capacitors

|                                 |            |                                                                                                                                                                                                                                                                                           |
|---------------------------------|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Load Life Test                  | Test       | Mount the capacitor on a heat sink with a low thermal resistance path. Apply the maximum rated voltage for 2000 hrs at +150°C with the +150°C maximum ripple current applied to the capacitor. After the test, measure the capacitance, ESR, and DCL at +20°C.                            |
|                                 | ΔC         | Capacitance will be within ±15% of the initial value                                                                                                                                                                                                                                      |
|                                 | ESR        | ESR will be less than 2 times the initial value                                                                                                                                                                                                                                           |
|                                 | DCL        | The leakage current will be within the specified value                                                                                                                                                                                                                                    |
|                                 | Appearance | No electrolyte leakage or other visible damage. The markings will be legible.                                                                                                                                                                                                             |
| Vibration Test                  | Test       | Clamp the case to the test fixture.<br>Frequency range is 10 - 2000 Hz. Amplitude of 1.5mm or 20 g acceleration.<br>Duration of test is 22 hours in each of three directions.<br>After the test, measure the capacitance at +20°C.                                                        |
|                                 | ΔC         | Capacitance change from the initial measurement must not exceed 5%.                                                                                                                                                                                                                       |
|                                 | Appearance | No electrolyte leakage or other visible damage.                                                                                                                                                                                                                                           |
| Surge Voltage Test              | Test       | Subject the capacitor to 1000 surge voltage cycles at +150°C. For each cycle, apply 1.15 times the rated voltage for 30 seconds followed by no voltage for 5 min. and 30 seconds. The time constant for charging is 0.1 seconds. After one to two hours, measure the capacitance and esr. |
|                                 | ΔC         | Capacitance change from the initial measurement must not exceed 15%.                                                                                                                                                                                                                      |
|                                 | ESR        | The ESR will be < 2x initial value.                                                                                                                                                                                                                                                       |
|                                 | Appearance | No electrolyte leakage or other visible damage.                                                                                                                                                                                                                                           |
| Storage at Low Temperature Test | Test       | Subject the capacitor to 72 hours at -55°C. After 16 hours at room temperature, measure the capacitance and DCL.                                                                                                                                                                          |
|                                 | ΔC         | Capacitance change from the initial measurement must not exceed 10%.                                                                                                                                                                                                                      |
|                                 | DCL        | Leakage current will meet the initial specification.                                                                                                                                                                                                                                      |
|                                 | Appearance | No electrolyte leakage or other visible damage. The markings are to be legible.                                                                                                                                                                                                           |
| Charge and Discharge Test       | Test       | Subject the capacitor to 1 million charge/discharge cycles at +20°C. For each cycle, apply the rated voltage for 0.5 seconds using a 0.1 second charge/discharge time constant. After the test, the following will apply;                                                                 |
|                                 | ΔC         | Capacitance will be within ±10% of the initial value.                                                                                                                                                                                                                                     |
|                                 | Appearance | No electrolyte leakage or other visible damage.                                                                                                                                                                                                                                           |


# Type AXLH -40 °C to +150 °C

## High Temperature Axial Leaded Aluminum Electrolytic Capacitors

### Ratings

| Rated Capacitance<br>100Hz/+20°C<br>(μF) | Capacitance Tolerance<br>(%) | VDC | Cornell Dubilier<br>Part Number | Case Size<br>D x L<br>(mm) | Max. ESR<br>100 Hz/+20°C<br>(mΩ) | Max. ESR<br>100 kHz/+20°C<br>(mΩ) | Rated Ripple Current<br>≥ 5kHz/+125°C<br>(A) | Maximum Ripple Current<br>≥ 5kHz/+125°C<br>(A) |
|------------------------------------------|------------------------------|-----|---------------------------------|----------------------------|----------------------------------|-----------------------------------|----------------------------------------------|------------------------------------------------|
| 2200                                     | -10/+30                      | 25  | AXLH222P025ED                   | 20 x 27                    | 50                               | 25                                | 7.1                                          | 9.1                                            |
| 3300                                     | -10/+30                      | 25  | AXLH332P025EH                   | 20 x 35                    | 34                               | 17                                | 8.9                                          | 11.3                                           |
| 4700                                     | -10/+30                      | 25  | AXLH472P025EL                   | 20 x 43                    | 25                               | 13                                | 10.3                                         | 13.1                                           |
| 1500                                     | -10/+30                      | 40  | AXLH152P040ED                   | 20 x 27                    | 57                               | 22                                | 7.3                                          | 9.3                                            |
| 2200                                     | -10/+30                      | 40  | AXLH222P040EH                   | 20 x 35                    | 41                               | 17                                | 8.9                                          | 11.2                                           |
| 2700                                     | -10/+30                      | 40  | AXLH272P040EL                   | 20 x 43                    | 32                               | 13                                | 10.1                                         | 12.8                                           |
| 470                                      | -10/+30                      | 63  | AXLH471P063ED                   | 20 x 27                    | 125                              | 32                                | 5.5                                          | 7.0                                            |
| 680                                      | -10/+30                      | 63  | AXLH681P063EH                   | 20 x 35                    | 87                               | 23                                | 6.9                                          | 8.7                                            |
| 900                                      | -10/+30                      | 63  | AXLH901P063EL                   | 20 x 43                    | 67                               | 18                                | 8.1                                          | 10.2                                           |

### Outline Drawings & Dimensions Table



| Size Code | Dimensions in mm |      |        |     | Approximate Weight<br>(grams) |
|-----------|------------------|------|--------|-----|-------------------------------|
|           | D                | L    | d      | LL  |                               |
|           | ± 0.5            | ± 1  | ± 0.03 | ± 2 |                               |
| ED        | 20               | 26.5 | 1      | 40  | 13                            |
| EH        | 20               | 34.5 | 1      | 40  | 20                            |
| EL        | 20               | 42.5 | 1      | 40  | 24                            |

Note: Bend leads at least 3.5 mm from the case.

# Type AXLH -40 °C to +150 °C

## High Temperature Axial Leaded Aluminum Electrolytic Capacitors

### Heat-Sinked Ratings

| Cornell Dubilier<br>Part Number | Max.<br>ESR 5-100 kHz<br>125-150°C<br>(mΩ) | Maximum Ripple Current * |                       |                       |
|---------------------------------|--------------------------------------------|--------------------------|-----------------------|-----------------------|
|                                 |                                            | ≥ 5 kHz/+125°C<br>(A)    | ≥ 5 kHz/+140°C<br>(A) | ≥ 5 kHz/+150°C<br>(A) |
| AXLH222P025ED                   | 10.6                                       | 22.2                     | 14                    | 6.3                   |
| AXLH332P025EH                   | 7.8                                        | 25.8                     | 16.3                  | 7.3                   |
| AXLH472P025EL                   | 6.4                                        | 28.5                     | 18                    | 8.1                   |
| AXLH152P040ED                   | 10                                         | 22.8                     | 14.4                  | 6.5                   |
| AXLH222P040EH                   | 7.9                                        | 25.7                     | 16.2                  | 7.3                   |
| AXLH272P040EL                   | 6.7                                        | 27.9                     | 17.6                  | 7.9                   |
| AXLH471P063ED                   | 17.5                                       | 17.3                     | 10.9                  | 4.9                   |
| AXLH681P063EH                   | 13                                         | 20                       | 12.7                  | 5.7                   |
| AXLH901P063EL                   | 10.6                                       | 22.2                     | 14                    | 6.3                   |

\* When the capacitor is mounted to a heat-sink using low thermal resistance path.

### Capacitor Markings

#### Marking

-- CDM ++  
AXLH222P025ED  
2200 uF 25VDC  
160603

#### Description

Logo, Polarity Marks  
CDE Part Number  
Capacitance, Rated Voltage (VDC)  
Date Code (Year, Week), Batch Number

**Notice and Disclaimer:** All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А