







Product P/N	Wistron P/N	BGA Array Pattern
10129553-14430TxLF	550.00501.0011	6X25
10129553-14430MxLF	550.00501.0001	
10129553-14430WxLF	550.00501.0021	



spec ref -				dr Zhen Luo		2016/08/18		projection		MM		size A3		scale 1:1							
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng Michael Song		2016/12/07						ecn no ELX-DG-25561-1							
ASME Y14.5						chr Heaven Cen		2016/12/07													
						appr Pei-Ming Zheng		2016/12/07													
								product family -				rel level Released									
surface		linear		0.X ±0.30		0.XX ±0.20		0.XXX ±0.10		Amphenol FCI		title Flex Cable BGA Assembly		dwg no 10129553		rev B					
ASME Y14.5		angular		0° ±2°				cat. no. -		Product - Customer Drw		sheet 1 of 11									

Product P/N	Wistron P/N	BGA Array Pattern
10129553-14426TxLF	550.00609.0001	6X17
10129553-14426MxLF	550.00609.0011	
10129553-14426WxLF	550.00609.0021	



spec ref	-	dr	Zhen Luo	2016/08/18	projection	MM	size	A3	scale	1:1
tolerance std	ASME Y14.5	eng	Michael Song	2016/12/07	chr	Heaven Cen	2016/12/07	ecn no	ELX-DG-25561-1	
		appr	Pei-Ming Zheng	2016/12/07	product family	-	rel level	Released		
surface	linear	0.X	± 0.30	Amphenol FCi	title Flex Cable BGA Assembly		dwg no 10129553		rev B	
		0.XX	± 0.20							
		0.XXX	± 0.10							
ASME Y14.5	angular	0°	$\pm 2^\circ$		cat. no.	-	Product - Customer Drw	sheet 2 of 11		

RIGID(CNI)

RIGID(PAD_BPI)


SEE DETAIL C

SCALE 4:1



DETAIL C
SCALE 5:1


spec ref -				dr Zhen Luo		2016/08/18		projection		MM		size A3		scale 1:2							
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng Michael Song		2016/12/07						ecn no ELX-DG-25561-1							
ASME Y14.5						chr Heaven Cen		2016/12/07													
						appr Pei-Ming Zheng		2016/12/07								product family -		rel level Released			
surface 		linear		0.X ±0.30		0.XX ±0.20		0.XXX ±0.10		Amphenol FCI		title Flex Cable BGA Assembly		dwg no 10129553		rev B					
																		ASME Y14.5		angular	






Product P/N	Wistron P/N	BGA Array Pattern
10129553-14425TxLF	550.0060A.0001	6X14
10129553-14425MxLF	550.0060A.0011	
10129553-14425WxLF	550.0060A.0021	



Product P/N	Wistron P/N	BGA Array Pattern
10129553-14423TxLF	550.0060C.0001	6X17,6X24
10129553-14423MxLF	550.0060C.0011	
10129553-14423WxLF	550.0060C.0021	







spec ref -				dr	Zhen Luo	2016/08/18	projection			size	A3	scale	4:5
tolerance std				eng	Michael Song	2016/12/07				ecn no	ELX-DG-25561-1		
ASME Y14.5				chr	Heaven Cen	2016/12/07							
TOLERANCES UNLESS OTHERWISE SPECIFIED				appr	Pei-Ming Zheng	2016/12/07							product family -
surface 	linear	0.X	±0.30	Amphenol FCI	title Flex Cable BGA Assembly Brawn				dwg no	10129553		rev	B
		0.XX	±0.20										
		0.XXX	±0.10										
ASME Y14.5	angular	0°	±2°		cat. no. -		Product - Customer Drw				sheet 4 of 11		



Product P/N	Wistron P/N	BGA Array Pattern
10129553-14424TxLF	550.0060B.0001	6X25
10129553-14424MxLF	550.0060B.0011	
10129553-14424WxLF	550.0060B.0021	

spec ref	-	dr	Zhen Luo	2016/08/18	projection	MM	size	A3	scale	1:1
tolerance std	ASME Y14.5	eng	Michael Song	2016/12/07	chr	Heaven Cen	2016/12/07	ecn no	ELX-DG-25561-1	
		appr	Pei-Ming Zheng	2016/12/07	product family	-	rel level	Released		
surface	linear	0.X	±0.30	Amphenol FCi	title	Flex Cable BGA Assembly	dwg no	10129553	rev	B
		0.XX	±0.20							
		0.XXX	±0.10							
ASME Y14.5	angular	0°	±2°		cat. no.	-	Product - Customer Drw	sheet 5 of 11		


Product P/N	Wistron P/N	BGA Array Pattern
10129553-14428TxLF	550.00504.0011	6X24,6X17
10129553-14428MxLF	550.00504.0001	
10129553-14428WxLF	550.00504.0021	



SCALE 3:1

Ø0.61±0.10	Ø0.30	C	A-B	A
------------	-------	---	-----	---


SOLDER BALLS



SCALE 3:1

Ø0.61±0.10	Ø0.30	W	U-V	U
------------	-------	---	-----	---






SOLDER BALLS



DETAIL D
SCALE 4:1


spec ref	-	dr	Zhen Luo	2016/08/18	projection	MM	size	A3	scale	1:1
tolerance std	ASME Y14.5	eng	Michael Song	2016/12/07	chr	Heaven Cen	2016/12/07	ecn no	ELX-DG-25561-1	
surface	linear	appr	Pei-Ming Zheng	2016/12/07	product family	-	rel level	Released		
ASME Y14.5	angular	0°	±2°		cat. no.	-	Product - Customer Drw	sheet 6 of 11		
Amphenol FCi	linear	0.X	±0.30		title	Flex Cable BGA Assembly	dwg no	10129553	rev	B
ASME Y14.5	angular	0.XX	±0.20							
		0.XXX	±0.10							
		0°	±2°							

Product P/N	Wistron P/N	BGA Array Pattern
10129553-14429TxLF	550.00503.0031	6X25
10129553-14429MxLF	550.00503.0001	
10129553-14429WxLF	550.00503.0021	




spec ref	-	dr	Zhen Luo	2016/08/18	projection	MM	size	A3	scale	1:1
tolerance std	ASME Y14.5	eng	Michael Song	2016/12/07	chr	Heaven Cen	2016/12/07	ecn no	ELX-DG-25561-1	
surface	linear	appr	Pei-Ming Zheng	2016/12/07	product family	-	rel level	Released		
ASME Y14.5	angular	0°	±2°		cat. no.	-	Product - Customer Drw	sheet 7 of 11		

Printed: Dec 07, 2016



Product P/N	Wistron P/N	BGA Array Pattern
10129553-1453ITxLF	550.00507.0011	6X25
10129553-1453IMxLF	550.00507.0001	
10129553-1453IWxLF	550.00507.0021	



spec ref	-	dr	Zhen Luo	2016/08/18	projection	MM	size	A3	scale	1:2
tolerance std	ASME Y14.5	eng	Michael Song	2016/12/07	chr	Heaven Cen	2016/12/07	ecn no	ELX-DG-25561-1	
		appr	Pei-Ming Zheng	2016/12/07	product family	-	rel level	Released		
surface	linear	0.X	±0.30	Amphenol FCi	title	Flex Cable BGA Assembly	dwg no	10129553	rev	B
		0.XX	±0.20							
		0.XXX	±0.10							
ASME Y14.5	angular	0°	±2°		cat. no.	-	Product - Customer Drw	sheet 10 of 11		

PRODUCT PART NUMBER

10129553-□□□□XXLF

BASE NUMBER

LEAD FREE

PCB DESIGN:
O: STANDARD
I TO N: NEW STACKUP

SUPPLIER:
M: Multex
T: TTM
W: WuZhu

CODE (SEE TABLE)

CODE	Flex Cable code In Wistron
14430	14430
14426	14426
14425	14425
14423	14423
14424	14424
14428	14428
14429	14429
14460	14460
14461	14461
14531	14531

NOTES:
1.MATERIAL:
FLEX CABLE
SOLDER BALL: LEAD FREE 96.5Sn/3Ag/0.5Cu
VENDOR: ALPHA

2.SOLDER BALLS WILL NOT BE PERFECT SHPERICAL SHAPE
DUE TO REFLOW ATTACHMENT.

3.PRODUCT SPECIFICATION: GS-12-1183.

4.APPLICATION SPECIFICATION: GS-20-0391.

5.PACKAGE SPECIFICATION: GS-14-2365.

6.PRODUCT MEET EUROPEAN UNION DIRECTIVES AND
OTHER COUNTRY REGULATIONS DESCRIBED IN GS-22-08.

7.RATED VOLTAGE L80V-LESS THAN 80V

8.SHEAR FORCE OF SOLDER BALL:800GF MIN.

9.APPEARANCE STANDARD FOLLOWS IPC 6013 CLASS2
CRITERIA AND DELL PCB 10207.

10.MSL LEVEL:MULTEK:5 TTM:5A.

11.CONTACT RESISTANCE:
MULTEK:10 OHM TTM:10 OHM


12.INSULATION RESISTANCE:
MULTEK:10 MEGAOHM TTM:10 MEGAOHM

13.PCB WARPAGE CRITERIA:
0.7% OF PCB LENGTH MAX.(BEFORE REFLOW)

14.IMPEDANCE REQUIREMENT.

100 +/-10 OHMS RISE TIME=70PS (20% TO 80%)	85 +/-10 OHMS RISE TIME=70PS (20% TO 80%)	50 +/-5 OHMS RISE TIME=100PS (10% TO 90%)
SAS AND PCIE PAD (DIFFERENTIAL PAIR)	SATA PAD (DIFFERENTIAL PAIR)	SIDE BAND PAD (POWER,GND,SIDE BAND SIGNALS)

15.DIMENSION WITH THE "()" SYMBOL IS THE
REFERENCE DIMENSION.

spec ref -				dr Zhen Luo		2016/08/18		projection		MM		size A3		scale 1:1	
tolerance std ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng Michael Song		2016/12/07						ecn no ELX-DG-25561-1			
				chr Heaven Cen		2016/12/07									
				appr Pei-Ming Zheng		2016/12/07						product family - rel level Released			
surface ASME Y14.5		linear	0.X	±0.30	Amphenol FCi	title Flex Cable BGA Assembly Brawn				dwg no	10129553				rev B
			0.XX	±0.20											
			0.XXX	±0.10											
		angular	0°	±2°		cat. no. -		Product - Customer Drw				sheet 11 of 11			

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А