



NXP quad Class-AB amplifiers TDF854x for automotive

Continuous sound experience for stop/start cars

Designed for use in stop/start cars, these advanced Class-AB amplifiers support listening to audio streams while the car's internal power supply is down for engine start. They operate in the range of 6 to 18 V.

Key features

- ▶ Supports stop/start cars by operating voltage range of: 6 -18 V
- ▶ Low V_p mute level adjustable via I²C (6, 8 V)
- ▶ Optimized for low pop (switch-on pop guaranteed in test program)
- ▶ Full (start-up) diagnostics with flexible read-out
- ▶ Programmable DIAG pin
- ▶ Second clip-detect pin for additional front/rear detection (mid-tone/bass)
- ▶ Family approach with graduated output power (25, 28 W)
- ▶ Compatible with Best-Efficiency quad amplifier (25, 28 W)

Application

- ▶ Automotive infotainment

The TDF854x family reflects NXP's ongoing commitment to improving functionality and performance in automotive infotainment systems. Available in configurations with I²C-bus control or a Best Efficiency mode, they operate over a wide voltage range and reduce dissipation.

I²C-bus control

The TDF8541, TDF8542, and TDF8544 are quad Class-AB amplifiers with I²C-bus control. The TDF8541 uses an asymmetrical input configuration, delivers an output power of 25 W, and is available in a DBS27 or HSOP36 package. The TDF8542 uses a symmetrical input configuration, delivers an output power of 25 W, and is housed in an HSOP36 package. The TDF8544 uses an asymmetrical input configuration, delivers an output power of 28 W, and is available in a DBS27 or HSOP36 package.



All three devices offer the following features:

- ▶ Load dump/over voltage protection
- ▶ All amplifier outputs short circuit proof to ground, supply voltage and across the load, independent per channel
- ▶ All pins short circuit proof to ground
- ▶ Thermal protection to avoid thermal breakdown
- ▶ Selectable gain 16/26 dB
- ▶ No plops when switching:
 - Switch on/switch off
 - Standby and mute
 - Mute and operating
- ▶ Single mode control pin (standby, operating: mute/on)
- ▶ Low standby current
- ▶ Low power dissipation in any short-circuit condition
- ▶ Outputs short-circuit proof to ground
- ▶ Low V_p mute for fast mute V_p drops
- ▶ Line driver mode (16 dB gain in BTL mode)
- ▶ Line driver mode supports engine start down to 6 V (16 dB and midtap voltage $0.25 V_p$).

The bus-controlled features are as follows:

- ▶ Diagnostic output gives clip information at selectable THD levels (2, 5 and 10%)
- ▶ Indication of a short circuit at an amplifier output, short to battery and ground

- ▶ DC-load detection: open, short and present (woofer)
- ▶ AC-load detection: for tweeters via series capacitors
- ▶ Programmable clip detection: 2, 5 and 10%.
- ▶ Programmable thermal pre-warning
- ▶ Independent short-circuit protection per channel
- ▶ Soft thermal clipping to prevent audio holes

Best Efficiency mode

The TDF8546 and TDF8548 are compatible I²C bus controlled Class-AB amplifiers with the added intelligence of a Best Efficiency mode. In this mode, the devices will have 62% less dissipation compared to standard Class-AB amplifiers with correlated signals between front and rear channels. There is a 4 channel best efficiency mode built in which will have 17% less dissipation than the commonly used 2*2 channel high efficiency mode when there is uncorrelated signals between the front and the rear speakers. A patented best efficiency control will have a low distortion at higher signals.

The TDF8546 uses an asymmetrical input configuration, delivers 25 W of output power, and is available in a DBS27 or HSOP36 package. The TDF8548 uses an asymmetrical input configuration, delivers an output power of 28 W, and is available in a DBS27 or HSOP36 package.

| Output power 14.4 V; 10% THD @ 4 Ω | Input configuration | Package | Class-AB amplifier with I ² C control | Class-AB amplifier with Best Efficiency mode |
|---------------------------------------|---------------------|-------------------|--|--|
| 25 W | Asymmetrical | DBS27 (Best Watt) | TDF8541J/JS/SD | TDF8546J/JS/SD |
| 25 W | Asymmetrical | HSOP36 | TDF8541TH* | TDF8546TH* |
| 25 W | Symmetrical | HSOP36 | TDF8542TH* | |
| 28 W | Asymmetrical | DBS27 (Best Watt) | TDF8544J/JS/SD | TDF8548J/JS/SD |
| 28 W | Asymmetrical | HSOP36 | TDF8544TH* | TDF8548TH* |

* input pins and output pins on opposite configuration

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А