



Main

Product or component type	Ethernet unmanaged switch
---------------------------	---------------------------

Complementary

Range compatibility	Modicon M241 Modicon M251
Product compatibility	Modicon M241 logic controller Modicon M251 logic controller
Current consumption	360 mA at 5 V DC for communication bus
Integrated connection type	4 RJ45 Ethernet
Transmission rate	10/100 Mbit/s
Port Ethernet	10BASE-T/100BASE-TX - 4 port(s) copper cable
Web services	Web server
Communication service	FTP SNMP DHCP client Modbus TCP server Modbus TCP client IEC VAR ACCESS Modbus TCP slave device Ethernet/IP slave device NGVL Programming Downloading Updating firmware Monitoring
Maximum number of connections	8 Modbus server 16 Ethernet/IP device
Communication port protocol	SNMP TCP (Transmission Control Protocol) UDP (User Datagram Protocol) Ethernet IP/Modbus TCP
Redundancy	No
Local signalling	1 LED green PWR 1 LED per channel green/yellow Ethernet link 1 LED per channel green Ethernet port activity
Electrical connection	RJ45 - 4 connectors for connecting Ethernet network Screw connector - terminal for connecting the functional ground
Marking	CE
Surge withstand	1 kV (power lines (DC)) with common mode protection conforming to EN/IEC 61000-4-5 2 kV (power lines (AC)) with common mode protection conforming to EN/IEC 61000-4-5 2 kV (relay output) with common mode protection conforming to EN/IEC 61000-4-5 1 kV (I/O) with common mode protection conforming to EN/IEC 61000-4-5 1 kV (shielded cable) with common mode protection conforming to EN/IEC 61000-4-5 0.5 kV (power lines (DC)) with differential mode protection conforming to EN/IEC 61000-4-5 1 kV (power lines (AC)) with differential mode protection conforming to EN/IEC 61000-4-5

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

	61000-4-5 1 kV (relay output) with differential mode protection conforming to EN/IEC 61000-4-5 0.5 kV (I/O) with differential mode protection conforming to EN/IEC 61000-4-5
Mounting support	Top hat type TH35-15 rail conforming to IEC 60715 Top hat type TH35-7.5 rail conforming to IEC 60715 Plate or panel with fixing kit
Width	0.98 in (25 mm)
Height	3.54 in (90 mm)
Depth	3.54 in (90 mm)
Product weight	0.28 lb(US) (0.125 kg)

Environment

standards	EN/IEC 61131-2 UL 508
product certifications	C-Tick CULus
resistance to electrostatic discharge	4 kV (on contact) conforming to EN/IEC 61000-4-2 8 kV (in air) conforming to EN/IEC 61000-4-2 8 kV (in air) conforming to Marine specification (LR, ABS, DNV, GL) 6 kV (on contact) conforming to Marine specification (LR, ABS, DNV, GL)
resistance to electromagnetic fields	0.91 V/yd (1 V/m) (2...2.7 GHz) conforming to EN/IEC 61000-4-3 9.14 V/yd (10 V/m) (80 MHz...1 GHz) conforming to EN/IEC 61000-4-3 2.74 V/yd (3 V/m) (1.4 GHz...2 GHz) conforming to EN/IEC 61000-4-3
resistance to fast transients	2 kV (power lines) conforming to EN/IEC 61000-4-4 2 kV (relay output) conforming to EN/IEC 61000-4-4 1.5 kV (I/O) conforming to EN/IEC 61000-4-4 1 kV (Ethernet line) conforming to EN/IEC 61000-4-4 1 kV (serial link) conforming to EN/IEC 61000-4-4
resistance to conducted disturbances	10 V (0.15...80 MHz) conforming to EN/IEC 61000-4-6 3 V (0.1...80 MHz) conforming to Marine specification (LR, ABS, DNV, GL) 10 V (spot frequency (2, 3, 4, 6.2, 8.2, 12.6, 16.5, 18.8, 22, 25 MHz)) conforming to Marine specification (LR, ABS, DNV, GL)
electromagnetic emission	Conducted emissions - test level: 120...69 dBµV/m QP (power lines) at 10...150 kHz conforming to EN/IEC 55011 Conducted emissions - test level: 79 dBµV/m QP/66 dBµV/m AV (power lines (AC)) at 0.15...0.5 MHz conforming to EN/IEC 55011 Conducted emissions - test level: 73 dBµV/m QP/60 dBµV/m AV (power lines (AC)) at 0.5...300 MHz conforming to EN/IEC 55011 Conducted emissions - test level: 63 dBµV/m QP (power lines) at 1.5...30 MHz conforming to EN/IEC 55011 Radiated emissions - test level: 40 dBµV/m QP class A at 30...230 MHz conforming to EN/IEC 55011 Radiated emissions - test level: 60...54 dBµV/m QP at 30...100 MHz conforming to Marine specification (LR, ABS, DNV, GL) Radiated emissions - test level: 24 dBµV/m QP at 156...165 MHz conforming to Marine specification (LR, ABS, DNV, GL) Conducted emissions - test level: 79...63 dBµV/m QP (power lines) at 150...1500 kHz conforming to EN/IEC 55011 Radiated emissions - test level: 47 dBµV/m QP class A at 230...1000 MHz conforming to EN/IEC 55011 Radiated emissions - test level: 80...50 dBµV/m QP at 150...30000 kHz conforming to Marine specification (LR, ABS, DNV, GL) Radiated emissions - test level: 54 dBµV/m QP at 100...2000 MHz conforming to Marine specification (LR, ABS, DNV, GL)
ambient air temperature for operation	14...122 °F (-10...50 °C) vertical installation 14...131 °F (-10...55 °C) horizontal installation
ambient air temperature for storage	-13...158 °F (-25...70 °C)
relative humidity	10...95 % without condensation in operation 10...95 % without condensation in storage
IP degree of protection	IP20 with protective cover in place
pollution degree	2
operating altitude	0...6561.68 ft (0...2000 m)
storage altitude	0...9842.52 ft (0...3000 m)
vibration resistance	1 mm at 5...13.2 Hz on symmetrical rail 3 gn at 8.7...150 Hz on symmetrical rail 1 mm at 5...13.2 Hz on panel mounting 0.7 gn at 13.2...100 Hz on panel mounting
shock resistance	15 gn during 11 ms

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1408 - Schneider Electric declaration of conformity	Compliant - since 1408 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А