

# RADIAL LEADS

## SkyCap®/SR Series



### GENERAL INFORMATION

#### AVX SR Series

Conformally Coated Radial Ledged MLC

Temperature Coefficients: COG (NP0), X7R, Z5U

200, 100, 50 Volts (300V, 400V & 500V also available)

Case Material: Epoxy


Lead Material: RoHS Compliant, 100% Tin



### HOW TO ORDER

| SR21   | 5   | E                                   | 104   | M  | A   | R                              | TR1  |
|--|---|-------------------------------------|---|--|---|--------------------------------|--|
| <b>AVX Style</b>   | <b>Voltage</b>  | <b>Temperature Coefficient</b>      | <b>Capacitance</b>  | <b>Capacitance Tolerance</b>   | <b>Failure Rate</b>   | <b>Leads</b>                   | <b>Packaging</b>   |
| SR15<br>SR20<br>SR21<br>SR22<br>SR27<br>SR30<br>SR40<br>SR50 | 5 = 50V<br>1 = 100V<br>2 = 200V<br>9 = 300V<br>8 = 400V<br>7 = 500V | A = COG (NP0)<br>C = X7R<br>E = Z5U | First two digits are the significant figures of capacitance. Third digit indicates the additional number of zeros. For example, order 100,000 pF as 104. (For values below 10pF use "R" in place of decimal point, e.g., 1R4 = 1.4pF) | COG (NP0):<br>C = ±.25pF<br>D = ±.5pF<br>F = ±1% (>50pF only)<br>G = ±2% (>25pF only)<br>J = ±5%<br>K = ±10% | X7R:<br>J = ±5%<br>K = ±10%<br>M = ±20%<br>Z5U:<br>M = ±20%<br>Z = +80%<br>-20% | A = Not Applicable<br>R = RoHS | Blank: Bulk Packaging 1.0" minimum of lead length<br>T: Trimmed leads .230" ± .030" Bulk packaging<br>TR1: Tape and Reel Packaging<br>AP1: Ammopack packaging<br><br>See packaging specification pages 33-34 |

### MARKING



### PACKAGING REQUIREMENTS

|                          | Quantity per Bag |
|--------------------------|------------------|
| SR15, 20, 21, 22, 27, 30 | 1000 Pieces      |
| SR40, 50                 | 500 Pieces       |

Note: SR15, SR20, SR21, SR30, and SR40 available on tape and reel per EIA specifications RS-468. See Pages 33 and 34.



# RADIAL LEADS

## COG (NP0) Dielectric



### SIZE AND CAPACITANCE SPECIFICATIONS

EIA Characteristic

Dimensions: Millimeters (Inches)

| AVX Style                   | SR15                                 | SR20            | SR21            | SR22            | SR27            | SR30           | SR40            | SR50            |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
|-----------------------------|--------------------------------------|-----------------|-----------------|-----------------|-----------------|----------------|-----------------|-----------------|-----|----|------|-----|----|------|-----|----|------|----|-----|----|-----|----|--|
| AVX "Insertable"            | SR07                                 | SR29            | SR59            | N/A             | N/A             | SR65           | SR75            | N/A             |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| <b>Width (W)</b>            | 3.81<br>(.150)                       | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 6.604<br>(.260) | 7.62<br>(.300) | 10.16<br>(.400) | 12.70<br>(.500) |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| <b>Height (H)</b>           | 3.81<br>(.150)                       | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 6.35<br>(.250)  | 7.62<br>(.300) | 10.16<br>(.400) | 12.70<br>(.500) |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| <b>Thickness (T)</b>        | 2.54<br>(.100)                       | 3.175<br>(.125) | 3.175<br>(.125) | 3.175<br>(.125) | 4.06<br>(.160)  | 3.81<br>(.150) | 3.81<br>(.150)  | 5.08<br>(.200)  |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| <b>Lead Spacing (L.S.)</b>  | 2.54<br>(.100)                       | 2.54<br>(.100)  | 5.08<br>(.200)  | 6.35<br>(.250)  | 7.62<br>(.300)  | 5.08<br>(.200) | 5.08<br>(.200)  | 10.16<br>(.400) |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| <b>Lead Diameter (L.D.)</b> | .508<br>(.020)                       | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020) | .508<br>(.020)  | .635<br>(.025)  |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| Cap. in.*<br>pF             | Industry Preferred<br>Values in Blue | WVDC            |                 |                 | WVDC            |                |                 | WVDC            |     |    | WVDC |     |    | WVDC |     |    | WVDC |    |     |    |     |    |  |
|                             |                                      | 200             | 100             | 50              | 200             | 100            | 50              | 200             | 100 | 50 | 200  | 100 | 50 | 200  | 100 | 50 | 100  | 50 | 100 | 50 | 100 | 50 |  |
| 1.0-9.9                     | SR151A1R0DAR                         |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 10                          | <b>SR151A100KAR</b>                  |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 15                          | SR....A150KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 22                          | SR....A220KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 33                          | SR....A330KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 39                          | SR....A390KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 47                          | SR....A470KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 68                          | SR....A680KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 100                         | <b>SR151A101KAR</b>                  |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 150                         | SR....A151KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 220                         | SR....A221KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 330                         | SR....A331KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 390                         | SR....A391KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 470                         | SR....A471KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 680                         | SR....A681KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 1000                        | <b>SR211A102KAR</b>                  |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 1500                        | SR....A152KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 2200                        | SR....A222KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 3900                        | SR....A392KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 4700                        | SR....A472KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 6800                        | SR....A682KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 8200                        | SR....A822KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 10,000                      | SR....A103KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 15,000                      | SR....A153KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 22,000                      | SR....A223KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 33,000                      | SR....A333KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 39,000                      | SR....A393KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 47,000                      | SR....A473KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 68,000                      | SR....A683KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |
| 100,000                     | SR....A104KAR                        |                 |                 |                 |                 |                |                 |                 |     |    |      |     |    |      |     |    |      |    |     |    |     |    |  |

For other styles, voltages, tolerances and lead lengths see Part No. Codes or contact factory.

\*Other capacitance values available upon special request.

- = Industry preferred values
- = SR20 only

Capacitance ranges available for SR12 and SR07 same as SR15  
 SR62 and SR59 same as SR21  
 SR64 and SR65 same as SR30  
 SR75 same as SR40  
 SR13 same as SR21

**NOTE:** For others voltages, tolerances, electrical specifications and NPO typical characteristics, see the AVX Multilayer Ceramic Leaded Capacitors Catalog.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at [www.avx.com/disclaimer/](http://www.avx.com/disclaimer/) by reference and should be reviewed in full before placing any order.

# RADIAL LEADS

## X7R Dielectric



### SIZE AND CAPACITANCE SPECIFICATIONS

EIA Characteristic

Dimensions: Millimeters (Inches)

|                 | AVX Style                            | SR15             |                 |                 | SR20            |                 |                 | SR21           |                 |                 | SR22 |     |    | SR27 |     |    | SR30 |     |    | SR40 |     |    | SR50 |     |    |
|-----------------|--------------------------------------|------------------|-----------------|-----------------|-----------------|-----------------|-----------------|----------------|-----------------|-----------------|------|-----|----|------|-----|----|------|-----|----|------|-----|----|------|-----|----|
|                 |                                      | AVX "Insertable" | SR07            | SR29            | SR59            | N/A             | N/A             | SR65           | SR75            | N/A             |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
|                 | Width (W)                            | 3.81<br>(.150)   | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 6.604<br>(.260) | 7.62<br>(.300) | 10.16<br>(.400) | 12.70<br>(.500) |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
|                 | Height (H)                           | 3.81<br>(.150)   | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 6.35<br>(.250)  | 7.62<br>(.300) | 10.16<br>(.400) | 12.70<br>(.500) |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
|                 | Thickness (T)                        | 2.54<br>(.100)   | 3.175<br>(.125) | 3.175<br>(.125) | 3.175<br>(.125) | 3.175<br>(.125) | 4.06<br>(.160)  | 3.81<br>(.150) | 3.81<br>(.150)  | 5.08<br>(.200)  |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
|                 | Lead Spacing (L.S.)                  | 2.54<br>(.100)   | 2.54<br>(.100)  | 5.08<br>(.200)  | 5.08<br>(.200)  | 6.35<br>(.250)  | 7.62<br>(.300)  | 5.08<br>(.200) | 5.08<br>(.200)  | 10.16<br>(.400) |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
|                 | Lead Diameter (L.D.)                 | .508<br>(.020)   | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020)  | .508<br>(.020) | .508<br>(.020)  | .635<br>(.025)  |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| Cap. in.*<br>pF | Industry Preferred<br>Values in Blue | WVDC             |                 |                 | WVDC            |                 |                 | WVDC           |                 |                 | WVDC |     |    | WVDC |     |    | WVDC |     |    | WVDC |     |    | WVDC |     |    |
|                 |                                      | 200              | 100             | 50              | 200             | 100             | 50              | 200            | 100             | 50              | 200  | 100 | 50 | 200  | 100 | 50 | 200  | 100 | 50 | 200  | 100 | 50 | 200  | 100 | 50 |
| 470             | SR...C471KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 1000            | SR155C102KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 1500            | SR...C152KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 2200            | SR...C222KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 3300            | SR...C332KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 4700            | SR...C472KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 6800            | SR...C682KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 10,000          | SR215C103KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 15,000          | SR...C153KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 22,000          | SR...C223KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 33,000          | SR...C333KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 47,000          | SR...C473KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 68,000          | SR...C683KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 100,000         | SR215C104KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 150,000         | SR...C154KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 220,000         | SR215C224KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 330,000         | SR...C334KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 390,000         | SR...C394KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 470,000         | SR305C474KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 1.0 uF          | SR305C105KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 2.2 uF          | SR405C225KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 2.7 uF          | SR505C275KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 4.7 uF          | SR505C475KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |
| 10.0 uF         | SR655C106KAR                         |                  |                 |                 |                 |                 |                 |                |                 |                 |      |     |    |      |     |    |      |     |    |      |     |    |      |     |    |

For other styles, voltages, tolerances and lead lengths see Part No. Codes or contact factory.

- = Industry preferred values
- = Extended range
- = Extended range with 0.150" thickness maximum

# RADIAL LEADS

## Z5U Dielectric



### SIZE AND CAPACITANCE SPECIFICATIONS

EIA Characteristic

Dimensions: Millimeters (Inches)

| AVX Style                                   | SR15           | SR20         | SR21         | SR22         | SR27         | SR30        | SR40         | SR50         |      |    |      |    |      |    |      |    |  |
|---|----------------|--------------|--------------|--------------|--------------|-------------|--------------|--------------|------|----|------|----|------|----|------|----|--|
| AVX "Insertable"                            | SR07           | SR29         | SR59         | N/A          | N/A          | SR65        | SR75         | N/A          |      |    |      |    |      |    |      |    |  |
| Width (W)                                   | 3.81 (.150)    | 5.08 (.200)  | 5.08 (.200)  | 5.08 (.200)  | 6.604 (.260) | 7.62 (.300) | 10.16 (.400) | 12.70 (.500) |      |    |      |    |      |    |      |    |  |
| Height (H)                                  | 3.81 (.150)    | 5.08 (.200)  | 5.08 (.200)  | 5.08 (.200)  | 6.35 (.250)  | 7.62 (.300) | 10.16 (.400) | 12.70 (.500) |      |    |      |    |      |    |      |    |  |
| Thickness (T)                               | 2.54 (.100)    | 3.175 (.125) | 3.175 (.125) | 3.175 (.125) | 4.06 (.160)  | 3.81 (.150) | 3.81 (.150)  | 5.08 (.200)  |      |    |      |    |      |    |      |    |  |
| Lead Spacing (L.S.)                         | 2.54 (.100)    | 2.54 (.100)  | 5.08 (.200)  | 6.35 (.250)  | 7.62 (.300)  | 5.08 (.200) | 5.08 (.200)  | 10.16 (.400) |      |    |      |    |      |    |      |    |  |
| Lead Diameter (L.D.)                        | .508 (.020)    | .508 (.020)  | .508 (.020)  | .508 (.020)  | .508 (.020)  | .508 (.020) | .508 (.020)  | .635 (.025)  |      |    |      |    |      |    |      |    |  |
| Cap. in.* Industry Preferred Values in Blue | WVDC           |              | WVDC         |              | WVDC         |             | WVDC         |              | WVDC |    | WVDC |    | WVDC |    | WVDC |    |  |
| pF  | 100            | 50           | 100          | 50           | 100          | 50          | 100          | 50           | 100  | 50 | 100  | 50 | 100  | 50 | 100  | 50 |  |
| 10,000                                      | SR155E103ZAR   |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 47,000                                      | SR.....E473ZAR |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 100,000                                     | SR215E104ZAR   |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 150,000                                     | SR.....E154ZAR |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 220,000                                     | SR215E224ZAR   |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 330,000                                     | SR215E334ZAR   |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 470,000                                     | SR215E474ZAR   |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 680,000                                     | SR.....E684ZAR |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 1.0 µF                                      | SR.....105ZAR  |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 1.5 µF                                      | SR30E155ZAR    |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 2.2 µF                                      | SR30E225ZAR    |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 3.3 µF                                      | SR30E335ZAR    |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |
| 4.7 µF                                      | SR30E475ZAR    |              |              |              |              |             |              |              |      |    |      |    |      |    |      |    |  |

For other styles, voltages, tolerances and lead lengths see Part No. Codes or contact factory.

\*Other capacitance values available upon special request.

- = Industry preferred values
- = SR20 only

Capacitance ranges available for SR12 and SR07 same as SR15  
 SR62 and SR59 same as SR21  
 SR64 and SR65 same as SR30  
 SR75 same as SR40  
 SR13 same as SR21

**NOTE:** For others voltages, tolerances, electrical specifications and NPO typical characteristics, see the AVX Multilayer Ceramic Leaded Capacitors Catalog.

### AVX 500 VOLT SKYCAPS\*\*

| STYLE*               | MAXIMUM CAPACITANCE VALUE |         |
|----------------------|---------------------------|---------|
|                      | C0G (NPO)                 | X7R     |
| SR29                 | 900 pF                    | .015 µF |
| SR20                 | 1800 pF                   | .033 µF |
| SR28<br>SR59         | 900 pF                    | .015 µF |
| SR13<br>SR21         | 1800 pF                   | .033 µF |
| SR30<br>SR61<br>SR65 | 7200 pF                   | .12 µF  |
| SR40<br>SR75         | .015 µF                   | .27 µF  |
| SR22                 | 1800 pF                   | .033 µF |
| SR27                 | 1800 pF                   | .033 µF |
| SR76                 | .015 µF                   | .27 µF  |

\*Consult pages 27 and 28 for style sizes.

\*\*Voltage rating based on DWV of 150% of rated voltage.



The Important Information/Disclaimer is incorporated in the catalog where these specifications came from or available online at [www.avx.com/disclaimer/](http://www.avx.com/disclaimer/) by reference and should be reviewed in full before placing any order.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А