






PRODUCT NUMBER	PLATING PERFORMANCE LEVEL	APPLICATION	FOR REAR PLUG-UP APPLICATIONS USE SHROUD
60066-1ZZZ	TELCORDIA CO	STANDARD	84818-104
60066-1ZZZLF		LEAD FREE	84818-104LF
60066-5ZZZ	TELCORDIA UE	STANDARD	84818-504
60066-5ZZZLF		LEAD FREE	84818-504LF
60066-9ZZZ	TELCORDIA CO	STANDARD	84818-904
60066-9ZZZLF		LEAD FREE	84818-904LF




DETAIL A
SCALE 4:1
SEE NOTE 17



SEE DETAIL A



mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER		 www.fciconnect.com		
ltr	ecn no.	dr	date	linear	0.X ±0.3			projection 	title VERTICAL SIGNAL HDR 5 ROW P.F. 90 POS. SELECT LOAD STD.		
K	V06-0498	DCH	2006-05-30		0.XX ±0.13						
L	V06-0706	LP	2006-07-27	angles	.XXX ±.051						
M	V07-0502	DCH	2007-07-31		0° ±2°						
N	V07-0733	HTB	2007-12-21	dr	K. BELL	2000-03-15		product family		METRAL 1000	code
P	V08-0049	LP	2008-2-4	enrg	M. HAHN	2000-03-15		size	dwg no		213
-	-	-	-	chr	M. HAHN	2000-03-15	scale 1:1	A		60066	sheet 1 of 6
J	V05-0806	VS	2005-09-09	appd	M. HAHN	2000-03-15					
sheet index	revision sheet	P	P	P	P	P	P				
		1	2	3	4	5	6				



A

B



B

REV E - 2006-04-18






PIN NO.	DIM A MATING LENGTH	DIM B TAIL LENGTH	PCB THICKNESS RANGE ACCOMMODATED BY PIN LENGTH **				
			WHEN MATING TO A 73981 OR 84688 SERIES RECEPTACLE		WHEN MATING TO A 52057 SERIES METRAL 4000 RECEPTACLE		
			ROWS A,B,C,D,E	GROUND ROW	ROWS:A,B,D,E	ROW C	GROUND ROW
04*	7.25	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
46		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
33		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
08		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
38		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
51		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
42		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
67		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
12		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10
19*	8.00	4.30	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN	1.60 MIN
47		12.20	2.95 - 3.80	2.95 - 4.20	2.95 - 3.80	2.95 - 3.80	2.95 - 4.20
34		12.95	2.95 - 4.55	3.25 - 4.95	2.95 - 4.55	2.95 - 4.55	3.25 - 4.95
20		13.70	2.95 - 5.30	4.00 - 5.70	3.30 - 5.30	2.95 - 5.30	4.00 - 5.70
39		14.45	3.05 - 6.05	4.75 - 6.45	4.05 - 6.05	3.05 - 6.05	4.75 - 6.45
52		15.20	3.80 - 6.80	5.50 - 7.20	4.80 - 6.80	3.80 - 6.80	5.50 - 7.20
43		15.70	4.30 - 7.30	6.00 - 7.70	5.30 - 7.30	4.30 - 7.30	6.00 - 7.70
68		16.40	5.00 - 8.00	6.70 - 8.40	6.00 - 8.00	5.00 - 8.00	6.70 - 8.40
21		17.10	5.70 - 8.70	7.40 - 9.10	6.70 - 8.70	5.70 - 8.70	7.40 - 9.10

* STUB PINS - NO REAR PLUG-UP
 ** THE GREATEST RANGE OCCURS WHEN THE B DIMENSION OF
 PIN 'GND' IS ONE SIZE SHORTER THEN THE OTHER PINS.

mat'l code SEE NOTE 5				tolerances unless otherwise specified				CUSTOMER				 www.fciconnect.com					
ltr	ecm no.	dr	date	linear	0. X ±0.3				COPY				title VERTICAL SIGNAL HDR 5 ROW P.F. 90 POS. SELECT LOAD STD.				
P					0. XX ±0. 13				projection 								
					.XXX ±.051												
				angles	0° ±2°								product family METRAL 1000				code
				dr	K. BELL	2000-03-15			size				dwg no	213			
				enrg	M. HAHN	2000-03-15			scale				A	60066		sheet	
				chr	M. HAHN	2000-03-15										3	
				appd	M. HAHN	2000-03-15											
sheet index		revision sheet															

PRODUCT NUMBER
SEE SHEET 1

PRESS-FIT HOLES	OPTION 1
HOLE DIAMETER AFTER PLATING	0.65-0.80
DRILLED HOLE	0.81-0.86 (0.85 DRILL)
COPPER PLATING	0.025 MIN
SnPb PLATING	0.005-0.015



SEE PRINT 58351 FOR
ADDITIONAL PCB INFORMATION

mat'l code SEE NOTE 5				tolerances unless otherwise specified		CUSTOMER		FCI www.fciconnect.com	
ltr	ecm no.	dr	date	linear	0.X ±0.3	projection	COPY	title	VERTICAL SIGNAL HDR 5 ROW P.F. 90 POS. SELECT LOAD STD.
P					0.XX ±0.13				
					.XXX ±.051				
				angles	0° ±2°	MM 1:1	scale	product family	METRAL 1000
				dr	K. BELL 2000-03-15				
				engr	M. HAHN 2000-03-15				
				chr	M. HAHN 2000-03-15	A	size	dwg no	60066
				appd	M. HAHN 2000-03-15				
sheet index	revision sheet								

This document is the property of and embodies
CONFIDENTIAL and PROPRIETARY information of FCI.
No part of the information shown on this
document may be used in any way or disclosed
to others without the written consent of FCI.
Copyright FCI.

PRODUCT NUMBER

SEE SHEET 1

NOTES:

1. SEE APPLICATION SPECIFICATION GS-20-010 FOR INFORMATION ON AVAILABLE TOOLING, CURCUIT BOARD DESIGN CONSIDERATIONS, REPAIR PROCEDURES AND PRODUCT OFFERINGS.
2. SEE FCI PUBLICATION 950511-028 FOR "ELECTRICAL PERFORMANCE DATA FOR DIFFERENTIAL APPLICATIONS."
3. SEE FCI PUBLICATION 950511-029 FOR "ELECTRICAL PERFORMANCE DATA FOR SINGLE-ENDED APPLICATION."
4. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME Y14.5, 1994
5. HOUSING MATERIAL: LIQUID CRYSTAL POLYMER, 30% GLASS FILLED, FLAME RETARDANT PER UL 94-V0.
PIN MATERIAL: PHOSPHER BRONZE
GROUND SPRING MATERIAL: PHOSPHER BRONZE
6. PLATING INFORMATION: PLATING ON CONTACT AREA MEETS THE PERFORMANCE LEVELS SHOWN IN TABLE ON SHEET 1. PLATING OF "LF" TAILS IS Sn, PLATING ON ALL OTHER TAILS IS SnPb.
7. DIMENSIONAL RESTRICTIONS OF PINS IN HEADERS.
FOR MATING WITH METRAL 1000 RECEPTACLES
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROWS A-E
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
DIM C : 5.00mm MIN, 8.00mm MAX FOR ROWS A-E
DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A
FOR MATING WITH METRAL 4000 RECEPTACLES
DIM A : 5.00mm MIN, 6.50mm MAX FOR ROWS A, B, D & E
DIM A : 5.00mm MIN, 8.00mm MAX FOR ROW C
DIM A : 5.00mm MIN, 5.75mm MAX FOR ROW GND NEXT TO ROW A
DIM C : 5.00mm MIN, 7.00mm MAX FOR ROWS A, B, D NO
DIM C : 5.00mm MIN, 8.00mm MAX FOR ROW C
DIM C : 4.60mm MIN, 6.30mm MAX FOR ROW GND NEXT TO ROW A

8. THE MIN PCB THICKNESS FOR REAR PLUG-UP APPLICATIONS IS 2.9mm. SINCE THE COMPLIANT SECTIONS OF THE GROUND SPRING OF THE HEADER DIRECTLY OPPOSE THE GROUND SPRING OF THE SHROUD. THE MIN PCB THICKNESS FOR FRONT PLUG-UP ONLY APPLICATIONS IS 1.6mm.
9. THESE HOLES ARE NEEDED FOR REAR PLUG-UP DESIGNS USING A SHROUD AND MAY BE OMITTED FOR FRONT PLUG-UP ONLY DESIGNS.
10. THE 'CONNECTOR OUTLINE' IS THE MIN OUTLINE REQUIRED. TO DETERMINE THE OUTLINE NECESSARY TO PERMIT THE VARIOUS TYPES OF REPAIR OPERATIONS, SEE APPLICATION SPECIFICATION GS-20-010.
11. CURRENT RATING: 1 AMP PER PIN
12. TEMPERATURE RANGE: -55°C TO +105°C
13. P/N 60066-XXXXLF


LEAD FREE (OPTIONAL)
SELECT LOAD PATTERN
PLATING CODE
14. PIN CODE 55 CANNOT BE USED WITH METRAL 1000 SHROUDS. PIN CODE 55 HAS A DIM A=5.75mm, DIM B=11.55mm.
15. PART NUMBERS ENDING IN LF MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008. ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 260°C FOR 60 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
16. FOR LEAD FREE PART NUMBERS ADD 'LF' SUFFIX. EXAMPLE: 60066-XXXXLF
17. PIN TYPE IS AT THE MANUFACTURERS OPTION AND CAN BE EITHER BABY-H OR EYE OF THE NEEDLE STYLE

mat'l code SEE NOTE 5				tolerances unless otherwise specified			CUSTOMER		 www.fciconnect.com				
ltr	ecr no.	dr	date	linear	0. X ±0.3		COPY		title VERTICAL SIGNAL HDR 5 ROW P.F. 90 POS. SELECT LOAD STD				
P					0. XX ±0.13		projection						
				angles	. XXX ±. 051				product family METRAL 1000				
					0° ±2°								
				dr	K. BELL	2000-03-15			size		dwg no		code 213
				enrg	M. HAHN	2000-03-15			scale		A		
				chr	M. HAHN	2000-03-15							sheet 5
				appd	M. HAHN	2000-03-15							
sheet index		revision sheet											

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.





SELECT LOAD PATTERNS																			
PRODUCT #	ROW	COLUMN																	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
60066-X001 SEE NOTE 16 LEAD FREE OPTION	E	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01
	D	01	01	01	01	01	02	01	01	01	01	01	02	01	01	01	01	01	02
	C	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01
	B	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01
	A	01	01	03	01	01	03	01	01	03	01	01	03	01	01	03	01	01	03
	GND	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01	01
PRODUCT #	ROW	COLUMN																	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
60066-X002 SEE NOTE 14 *RPU SEE NOTE 16 LEAD FREE OPTION	E	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
	D	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
	C	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
	B	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
	A	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
	GND	55	02	02	02	02	55	55	55	02	02	02	02	55	55	55	55	55	55
PRODUCT #	ROW	COLUMN																	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
60066-X003 SEE NOTE 14 *RPU SEE NOTE 16 LEAD FREE OPTION	E	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55
	D	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55
	C	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55
	B	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55
	A	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55
	GND	55	55	55	55	55	55	55	55	55	55	55	55	55	02	02	02	02	55

* REAR PLUG-UP PART NUMBERS

mat'l code SEE NOTE 5				tolerances unless otherwise specified				CUSTOMER		www.fciconnect.com								
ltr	ecm no.	dr	date	linear	0.X ±0.3		projection	COPY		title VERTICAL SIGNAL HDR 5 ROW P.F. 90 POS. SELECT LOAD STD.								
P					0.XX ±0.13													
					.XXX ±.051													
				angles	0° ±2°			MM		product family METRAL 1000								
				dr	K. BELL	2000-03-15				size		code						
				engr	M. HAHN	2000-03-15				dwg no		213						
				chr	M. HAHN	2000-03-15	scale	1:1		A 60066								
				appd	M. HAHN	2000-03-15												
sheet index		revision sheet																

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А