

SVL Essential DIN Rail Series

SVL Series power supplies are perfect for high volume, controlled environment applications where essential features are the only requirement. When space inside an enclosure is at a premium, their small footprint makes these power supplies an excellent alternative to embedded open frame switchers. The DIN rail mounting capability provides quicker and easier installation while allowing for design flexibility. These power supplies range from 15 to 480 Watts in 5, 12, 24 and 48 Volt combinations.



Applications

- Test and Measure Equipment
- Scanners
- Instrumentation
- Printers Peripheral
- ATM Machines
- Semiconductor Fabrication Equipment
- Vending Machines

Features

- Universal Input
- Protection
 - Short Circuit
 - Over Voltage
 - Overload
 - Over Temperature
- Convection cooling
- DC OK LED
- DC OK Relay for >120 Watts models
- Two year warranty



Certifications and Compliances

All Models

-  Listed, Ind. Control Equipment, E61379
 - UL 508, CSA C22.2 No. 107.1
-  Recognized Component, ITE, E137632
 - UL 60950-1/CSA C22.2 No. 60950-1, 2nd Edition
- 
 - IEC/EN60950-1, 2nd Edition
 - Model SVL 1-24-100, SVL 3-5-100, SVL 4-12-100, SVL 2-24-100 were evaluated for NEC Class 2 outputs.
- RoHS Compliant

SVL Specifications <120W

| Description | Catalog Number | | |
|----------------------------------|---|------------------------------------|--|
| | SVL 3-5-100 | SVL 1-24-100 | SVL 6-5-100 |
| Input | | | |
| Input Voltage Range | 85-264 Vac | | |
| - AC Range | 100-240 Vac | | |
| - DC Range ¹ | 120-375 Vdc | | |
| - Frequency | 50/60 Hz | | |
| Nominal Current | 0.5 A @ 115 Vac 0.3 A @ 230 Vac | 0.8 A @ 115 Vac 0.4 A @ 230 Vac | 0.9 A @ 115 Vac 0.5 A @ 230 Vac |
| - Inrush Current max, | 35 A @ 115 Vac 65 A @ 230 Vac | 35 A @ 115 Vac 60 A @ 230 Vac | |
| Efficiency | 79% typ | 88% typ | 80% typ |
| Leakage Current | <1 mA @ 240 Vac | | |
| Output | | | |
| Nominal Voltage | 5 V | 24 V | 5 V |
| - Tolerance | +/-2% | | |
| Voltage Adjustable Range | 5-5.5 V | 24-28 V | 5-5.5 V |
| - Ripple (25 °C) | <75 mVp-p | | |
| PAR (25 °C) | <75 mVp-p | | |
| Nominal Current | 3 A | 1.25 A | 6 A |
| Max. Power | 15 W | 30 W | |
| Holdup Time at full load (25 °C) | 20 ms typ. @ 115 Vac 100 ms typ. @ 230 Vac | | |
| Rise Time at full load (25 °C) | <100 ms | | |
| Start Up at full load (25 °C) | <3000 ms @ 115 Vac, <1500 ms @ 230 Vac | | |
| Regulation | <0.5% Line and <1% Load | | |
| Environmental Data | | | |
| Operating Temperature | -20 °C to +70 °C | | |
| Relative Humidity | 5 to 95% RH Non-condensing | | |
| Storage temp | -40 °C to +85 °C | | |
| Power De-rating ² | >55 °C de-rate power by 3.33% / °C <-10 °C de-rate power by 2% / °C de-rate to 80% load for operation at -20°C | | |
| Shock | IEC60068-2-27: half sine wave 10 G, single axis for a duration of 11 ms operational and 50 G three axes for duration of 11 ms each non-operational | | |
| Vibration | IEC60068-2-6: sine wave; 10 Hz to 500 Hz at 2 g, 0.35 mm displacement, three axes for 60 min each operational and 5 Hz to 500 Hz at 2.09 grms, three axes for 20 min each non-operational | | |
| Protections | | | |
| Overvoltage Protection | 6.3-7.4 V, Latching | 30-34.8 V, Latching | 6.3-7.4 V, Latching |
| Overload Protection | Hiccup | | |
| Over Temperature Protection | No Component Damage, Latch Mode | | |
| Short Circuit | Hiccup Mode, Non-Latching (Auto-Recovery when the fault is removed) | | |
| Power Factor Correction | Meets EN61000-3-2 Class A | | |
| Reliability | | | |
| MTBF | >350 khrs (115 Vac/230 Vac @ 25 °C) as per Telcordia SR-332 issue 3 Jan 2011. | | |
| EMC | | | |
| Galvanic Isolation | I/P to O/P: 3 kVac; I/P to GND: 1.5 kVac; O/P to GND: 0.5 kVac | | |
| Emissions | EN55022 (CISPR22) Class B, EN55011 Class B, EN61000-6-3, EN61000-6-4, EN61000-3-3, EN61204-3, EN61000-3-2 Class A | | |
| Immunity | EN55024, EN61000-6-1, EN61000-6-2 (EN61000-4-2, 3, 4, 5, 6, 8, 11, 12) Level 3, Performance Criteria A | | |
| General | | | |
| H x W x D in (mm) | 2.95 x 0.82 x 3.52 (75.0 x 21.0 x 89.5) | | 2.95 x 1.18 x 3.52 (75.0 x 30.0 x 89.5) |
| Unit Weight | 0.242 lb (110 g) | | 0.352 lb (160 g) |
| LED Signals | GREEN light = DC OK , OCP = blinking | | |
| DC OK Relay Contact | No | | |
| Warranty | 2 year | | |

1. DC input range is not listed in safety file it is only to confirm product functional performance.

2. >120 Watts models measured at 230 VAC input and 25 °C ambient temperature. See manual for further details.

SVL Specifications <120W

| Description | Catalog Number | | |
|---|---|------------------------------------|--|
| | SVL 4-12-100 | SVL 2-24-100 | SVL 4-24-100 |
| Input | | | |
| Input Voltage Range | 85-264 Vac | | |
| - AC Range | 100-240 Vac | | |
| - DC Range¹ | 120-375 Vdc | | |
| - Frequency | 50/60 Hz | | |
| Nominal Current | 1.0 A @ 115 Vac 0.6 A @ 230 Vac | 1.0 A @ 115 Vac 0.6 A @ 230 Vac | 1.2 A @ 115 Vac 0.6 A @ 230 Vac |
| - Inrush Current max. | 35 A @ 115 Vac 60 A @ 230 Vac | | |
| Efficiency | 88% typ | | 89% typ |
| Leakage Current | <1 mA @ 240 Vac | | |
| Output | | | |
| Nominal Voltage | 12 V | 24 V | 24 V |
| - Tolerance | +/-2% | | |
| Voltage Adjustable Range | 12-15 V | 24-28 V | |
| - Ripple (25 °C) | <75 mVp-p | | |
| PARD (25 °C) | <75 mVp-p | | |
| Nominal Current | 4 A | 2.1 A | 4 A |
| Max. Power | 48 W | 50 W | 96 W |
| Holdup Time at full load (25 °C) | 20 ms typ. @ 115 Vac 90 ms typ. @ 230 Vac | | 25 ms typ. @ 115 Vac 50 ms typ. @ 230 Vac |
| Rise Time at full load (25 °C) | <100 ms | | |
| Start Up at full load (25 °C) | <3000 ms @ 115 Vac, <1500 ms @ 230 Vac | | |
| Regulation | <0.5% Line and <1% Load | | |
| Environmental Data | | | |
| Operating Temperature | -20 °C to +70 °C | | |
| Relative Humidity | 5 to 95% RH Non-condensing | | |
| Storage temp | -40 °C to +85 °C | | |
| Power De-rating² | >55 °C de-rate power by 3.33% / °C <-10 °C de-rate power by 2% / °C de-rate to 80% load for operation at -20°C | | |
| Shock | IEC60068-2-27: half sine wave 10 G, single axis for a duration of 11 ms operational and 50 G three axes for duration of 11 ms each non-operational | | |
| Vibration | IEC60068-2-6: 10 Hz to 500 Hz at 2 g, 0.35mm displacement, three axes for 60 min each operational and 5 Hz to 500 Hz at 2.09 grms, three axes for 20 min each non-operational | | |
| Protections | | | |
| Overvoltage Protection | 16-18.7 V, Latching | 30-34.8 V, Latching | |
| Overload Protection | Current foldforward and then hiccup | | |
| Over Temperature Protection | No Component Damage, Latch Mode | | |
| Short Circuit | Hiccup Mode, Non-Latching (Auto-Recovery when the fault is removed) | | |
| Power Factor Correction | Meets EN61000-3-2 Class A | | |
| Reliability | | | |
| MTBF | >350 khrs (115 Vac/230 Vac @ 25 °C) as per Telcordia SR-332 issue 3 Jan 2011. | | |
| EMC | | | |
| Galvanic Isolation | I/P to O/P: 3 KVac; I/P to GND: 1.5 KVac; O/P to GND: 0.5 KVac | | |
| Emissions | EN55022 (CISPR22) Class B, EN55011 Class B, EN61000-6-3, EN61000-6-4, EN61000-3-3, EN61204-3, EN61000-3-2 Class A | | |
| Immunity | EN55024, EN61000-6-1, EN61000-6-2 (EN61000-4-2, 3, 4, 5, 6, 8, 11, 12) Level 3, Performance Criteria A | | |
| General | | | |
| H x W x D in (mm) | 2.95 x 1.18 x 3.52 (75.0 x 30.0 x 89.5) | | 2.95 x 1.77 x 3.93 (75.0 x 45.0 x 100.0) |
| Unit Weight | 0.397 lb (180 g) | | 0.716 lb (325 g) |
| LED Signals | GREEN light = DC OK , OCP = blinking | | |
| DC OK Relay Contact | No | | |
| Warranty | 2 year | | |

1. DC input range is not listed in safety file it is only to confirm product functional performance.
2. >120 Watts models measured at 230 VAC input and 25 °C ambient temperature. See manual for further details.

SVL Specifications >120W

| Description | Catalog Number | | | |
|---|---|-----------------------|--|--|
| | SVL 2-48-100 | SVL 5-24-100 | SVL 10-24-100 | SVL 20-24-100 |
| Input | | | | |
| Input Voltage Range | 85-264 Vac | | | |
| – AC Range | 100-240 Vac | | | |
| – DC Range ¹ | 120-375 Vdc | | | |
| – Frequency | 50/60 Hz | | | |
| Nominal Current | 2.20 A @ 115 Vac 1.20 A @ 230 Vac | | 2.8 A @ 115 Vac 1.4 A @ 230 Vac | 5.4 A @ 115 Vac 2.7 A @ 230 Vac |
| – Inrush Current max. | 20 A typ.@ 115 Vac 40 A typ.@ 230 Vac | | | 40A typ.@ 115 Vac 80A typ.@ 230 Vac |
| Efficiency | 88% typ | | | |
| Leakage Current | <1 mA @ 240 Vac | | | |
| Output | | | | |
| Nominal Voltage | 48V | 24V | | |
| – Tolerance | +/-2% | | | |
| Voltage Adjustable Range | 44-56 V | 22-28 V | | |
| – Ripple (25 °C) | <120 mVp-p | <100 mVp-p | | |
| PARD (25 °C) | <150 mVp-p | <120 mVp-p | | |
| Nominal Current | 2.5 A | 5 A | 10 A | 20 A |
| Max. Power | 120 W | 120 W | 240 W | 480 W |
| Holdup Time at full load (25 °C) | 10 ms typ.@ 115 Vac 16 ms typ @ 230 Vac | | | |
| Rise Time at full load (25 °C) | <100 ms | | | |
| Start Up at full load (25 °C) | <1000 ms @ 115 Vac & 230 Vac | | | |
| Regulation | <0.5% Line and <1% Load | | | |
| Environmental Data | | | | |
| Operating Temperature | -20 °C to +70 °C | | | |
| Relative Humidity | 5 to 95% RH Non-condensing | | | |
| Storage temp | -40 °C to +85 °C | | | |
| Power De-rating² | >50 °C de-rate power by 2.5% / °C <-10 °C de-rate power by 2% / °C <100 Vac de-rate power by 1% / Vac | | | |
| Shock | IEC60068-2-27: half sine wave 10 G, single axis for a duration of 11 ms operational and 50 G three axes for duration of 11 ms each non-operational | | | |
| Vibration | IEC60068-2-6: sine wave; 10 Hz to 500 Hz at 2 g, 0.35 mm displacement, three axes for 60 min each operational and 5 Hz to 500 Hz at 2.09 grms, three axes for 20 min each non-operational | | | |
| Protections | | | | |
| Overvoltage Protection | 56-67.2 V, Latching | 28.8-35.2 V, Latching | | |
| Overload Protection | 105-150% of rated load; constant current at >20 V output and hiccup at <20 V output. SVL 2-48-100: constant current at >40 V output and hiccup at <40 V output. | | | |
| Over Temperature Protection | No Component Damage, Latch Mode | | | |
| Short Circuit | Hiccup Mode, Non-Latching (Auto-Recovery when the fault is removed) | | | |
| Power Factor Correction | Meets EN61000-3-2 Class A | | | |
| Reliability | | | | |
| MTBF | >700 khrs (115 Vac & 230 Vac @ 25 °C) as per Telcordia SR-332 issue 3 Jan 2011. | | | |
| EMC | | | | |
| Galvanic Isolation | I/P to O/P: 3 kVac; I/P to GND: 2 kVac; O/P to GND: 0.5 kVac | | | |
| Emissions | EN55022 (CISPR22) Class B, EN55011 Class B, EN61000-6-3, EN61000-6-4, EN61000-3-3, EN61204-3, EN61000-3-2 Class A | | | |
| Immunity | EN55024, EN61000-6-1, EN61000-6-2 (EN61000-4-2, 3, 4, 5, 6, 8, 11, 12) Level 3, Performance Criteria A, SEMI F47 @ 200 Vac | | | |
| General | | | | |
| H x W x D in (mm) | 4.84 x 1.57 x 4.63 (123.6 x 40.0 x 117.6) | | 4.87 x 2.36 x 4.63 (123.6 x 60.0 x 117.6) | 4.87 x 3.37 x 5.06 (123.6 x 85.5 x 128.5) |
| Unit Weight | 540 g (1.19 lb) | | 660 g (1.45 lb) | 1150 g (2.53 lb) |
| LED Signals | GREEN light = DC OK , OCP = blinking | | | |
| DC OK Relay Contact | Yes | | | |
| Warranty | 2 year | | | |

1. DC input range is not listed in safety file it is only to confirm product functional performance.

2. >120 Watts models measured at 230V AC input and 25°C ambient temperature. See manual for further details.

SVL Series Dimensions



| Catalog Number | Dimensions – inches (mm) | | |
|----------------------|--------------------------|-------------|--------------|
| | H | W | D |
| SVL 3-5-100 | 2.95 (75.0) | 0.82 (21.0) | 3.52 (89.5) |
| SVL 1-24-100 | 2.95 (75.0) | 0.82 (21.0) | 3.52 (89.5) |
| SVL 6-5-100 | 2.95 (75.0) | 1.18 (30.0) | 3.52 (89.5) |
| SVL 4-12-100 | 2.95 (75.0) | 1.18 (30.0) | 3.52 (89.5) |
| SVL 2-24-100 | 2.95 (75.0) | 1.18 (30.0) | 3.52 (89.5) |
| SVL 4-24-100 | 2.95 (75.0) | 1.77 (45.0) | 3.93 (100.0) |
| SVL 2-48-100 | 4.84 (123.6) | 1.57 (40.0) | 4.63 (117.6) |
| SVL 5-24-100 | 4.84 (123.6) | 1.57 (40.0) | 4.63 (117.6) |
| SVL 10-24-100 | 4.87 (123.6) | 2.36 (60.0) | 4.63 (117.6) |
| SVL 20-24-100 | 4.87 (123.6) | 3.37 (85.5) | 5.06 (128.5) |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А