FAIRCHILD SEMICONDUCTOR®

May 2001

QFET™

# FQT7N10


## 100V N-Channel MOSFET

### General Description


These N-Channel enhancement mode power field effect transistors are produced using Fairchild's proprietary, planar stripe, DMOS technology.
This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for low voltage applications such as audio amplifier, high efficiency switching DC/DC converters, and DC motor control.

### Features

- 1.7A, 100V, $R_{DS(on)}$ = 0.35Ω @$V_{GS}$ = 10 V
- Low gate charge ( typical 5.8 nC)
- Low Crss ( typical 10 pF)
- Fast switching
- Improved dv/dt capability




**SOT-223**
**FQT Series**




## Absolute Maximum Ratings

$T_C$ = 25°C unless otherwise noted

| Symbol | Parameter | | FQT7N10 | Units |
|---|---|---|---|---|
| $V_{DSS}$ | Drain-Source Voltage | | 100 | V |
| $I_D$ | Drain Current - Continuous ($T_C$ = 25°C) | | 1.7 | A |
| | - Continuous ($T_C$ = 70°C) | | 1.36 | A |
| $I_{DM}$ | Drain Current - Pulsed | (Note 1) | 6.8 | A |
| $V_{GSS}$ | Gate-Source Voltage | | ± 25 | V |
| $E_{AS}$ | Single Pulsed Avalanche Energy | (Note 2) | 50 | mJ |
| $I_{AR}$ | Avalanche Current | (Note 1) | 1.7 | A |
| $E_{AR}$ | Repetitive Avalanche Energy | (Note 1) | 0.2 | mJ |
| dv/dt | Peak Diode Recovery dv/dt | (Note 3) | 6.0 | V/ns |
| $P_D$ | Power Dissipation ($T_C$ = 25°C) | | 2.0 | W |
| | - Derate above 25°C | | 0.016 | W/°C |
| $T_J$, $T_{STG}$ | Operating and Storage Temperature Range | | -55 to +150 | °C |
| $T_L$ | Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds | | 300 | °C |

## Thermal Characteristics

| Symbol | Parameter | Typ | Max | Units |
|---|---|---|---|---|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient * | -- | 62.5 | °C/W |

* When mounted on the minimum pad size recommended (PCB Mount)

©2001 Fairchild Semiconductor Corporation

## Electrical Characteristics

$T_C$ = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|---|---|---|---|---|---|---|
| **Off Characteristics** | | | | | | |
| $BV_{DSS}$ | Drain-Source Breakdown Voltage | $V_{GS}$ = 0 V, $I_D$ = 250 μA | 100 | -- | -- | V |
| $\Delta BV_{DSS}$ / $\Delta T_J$ | Breakdown Voltage Temperature Coefficient | $I_D$ = 250 μA, Referenced to 25°C | -- | 0.1 | -- | V/°C |
| $I_{DSS}$ | Zero Gate Voltage Drain Current | $V_{DS}$ = 100 V, $V_{GS}$ = 0 V | -- | -- | 1 | μA |
| | | $V_{DS}$ = 80 V, $T_C$ = 125°C | -- | -- | 10 | μA |
| $I_{GSSF}$ | Gate-Body Leakage Current, Forward | $V_{GS}$ = 25 V, $V_{DS}$ = 0 V | -- | -- | 100 | nA |
| $I_{GSSR}$ | Gate-Body Leakage Current, Reverse | $V_{GS}$ = -25 V, $V_{DS}$ = 0 V | -- | -- | -100 | nA |
| **On Characteristics** | | | | | | |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{DS}$ = $V_{GS}$, $I_D$ = 250 μA | 2.0 | -- | 4.0 | V |
| $R_{DS(on)}$ | Static Drain-Source On-Resistance | $V_{GS}$ = 10 V, $I_D$ = 0.85 A | -- | 0.28 | 0.35 | Ω |
| $g_{FS}$ | Forward Transconductance | $V_{DS}$ = 40 V, $I_D$ = 0.85 A (Note 4) | -- | 1.85 | -- | S |
| **Dynamic Characteristics** | | | | | | |
| $C_{iss}$ | Input Capacitance | $V_{DS}$ = 25 V, $V_{GS}$ = 0 V, f = 1.0 MHz | -- | 190 | 250 | pF |
| $C_{oss}$ | Output Capacitance | | -- | 60 | 75 | pF |
| $C_{rss}$ | Reverse Transfer Capacitance | | -- | 10 | 13 | pF |
| **Switching Characteristics** | | | | | | |
| $t_{d(on)}$ | Turn-On Delay Time | $V_{DD}$ = 50 V, $I_D$ = 7.3 A, $R_G$ = 25 Ω (Note 4, 5) | -- | 7 | 25 | ns |
| $t_r$ | Turn-On Rise Time | | -- | 24 | 60 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | -- | 13 | 35 | ns |
| $t_f$ | Turn-Off Fall Time | | -- | 19 | 50 | ns |
| $Q_g$ | Total Gate Charge | $V_{DS}$ = 80 V, $I_D$ = 7.3 A, $V_{GS}$ = 10 V (Note 4, 5) | -- | 5.8 | 7.5 | nC |
| $Q_{gs}$ | Gate-Source Charge | | -- | 1.4 | -- | nC |
| $Q_{gd}$ | Gate-Drain Charge | | -- | 2.5 | -- | nC |
| **Drain-Source Diode Characteristics and Maximum Ratings** | | | | | | |
| $I_S$ | Maximum Continuous Drain-Source Diode Forward Current | | -- | -- | 1.7 | A |
| $I_{SM}$ | Maximum Pulsed Drain-Source Diode Forward Current | | -- | -- | 6.8 | A |
| $V_{SD}$ | Drain-Source Diode Forward Voltage | $V_{GS}$ = 0 V, $I_S$ = 1.7 A | -- | -- | 1.5 | V |
| $t_{rr}$ | Reverse Recovery Time | $V_{GS}$ = 0 V, $I_S$ = 7.3 A, $dI_F$ / dt = 100 A/μs (Note 4) | -- | 70 | -- | ns |
| $Q_{rr}$ | Reverse Recovery Charge | | -- | 150 | -- | nC |

**Notes:**
1. Repetitive Rating : Pulse width limited by maximum junction temperature
2. L = 26mH, $I_{AS}$ = 1.7A, $V_{DD}$ = 25V, $R_G$ = 25 Ω, Starting $T_J$ = 25°C
3. $I_{SD} \leq$ 7.3A, di/dt $\leq$ 300A/μs, $V_{DD} \leq BV_{DSS,}$ Starting $T_J$ = 25°C
4. Pulse Test : Pulse width $\leq$ 300μs, Duty cycle $\leq$ 2%
5. Essentially independent of operating temperature

©2001 Fairchild Semiconductor Corporation

## Typical Characteristics





**Figure 1. On-Region Characteristics**





**Figure 2. Transfer Characteristics**





**Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage**





**Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature**





**Figure 5. Capacitance Characteristics**





**Figure 6. Gate Charge Characteristics**

©2001 Fairchild Semiconductor Corporation

## Typical Characteristics (Continued)





**Figure 7. Breakdown Voltage Variation vs. Temperature**





**Figure 8. On-Resistance Variation vs. Temperature**





**Figure 9. Maximum Safe Operating Area**





**Figure 10. Maximum Drain Current vs. Case Temperature**







**Figure 11. Transient Thermal Response Curve**


©2001 Fairchild Semiconductor Corporation


## Gate Charge Test Circuit & Waveform








## Resistive Switching Test Circuit & Waveforms





## Unclamped Inductive Switching Test Circuit & Waveforms






$$E_{AS} = \frac{1}{2} L I_{AS}^2 \frac{BV_{DSS}}{BV_{DSS} - V_{DD}}$$




©2001 Fairchild Semiconductor Corporation

**Peak Diode Recovery dv/dt Test Circuit & Waveforms**





©2001 Fairchild Semiconductor Corporation

**Package Dimensions**

# SOT-223




©2001 Fairchild Semiconductor Corporation

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™
Bottomless™
CoolFET™
CROSSVOLT™
DenseTrench™
DOME™
EcoSPARK™
$E^2$CMOS™
EnSigna™
FACT™
FACT Quiet Series™
FAST®
FASTr™
FRFET™
GlobalOptoisolator™
GTO™
HiSeC™
ISOPLANAR™
LittleFET™
MicroFET™
MICROWIRE™
OPTOLOGIC™
OPTOPLANAR™
PACMAN™
POP™
PowerTrench®
QFET™
QS™
QT Optoelectronics™
Quiet Series™
SLIENT SWITCHER®
SMART START™
Stealth™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SyncFET™
TinyLogic™
UHC™
UltraFET®
VCX™

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status | Definition |
|---|---|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |

©2001 Fairchild Semiconductor Corporation

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А