

Communication Markets Division

# 3M™ No Polish SC/UPC Connector

## Singlemode and Multimode 250 μm/900 μm

3M™ No Polish SC/UPC Connector enables fast, on-site termination of 250 μm and 900 μm connections utilizing a one piece, pre-assembled design.

The SC compatible connector consists of a factory-polished ceramic fiber/ferrule assembly and a mechanical splice that is installed with a simple and reliable field tool. A bell-shaped boot is attached to the connector body, minimizing the chance of losing or forgetting to terminate the boot during the connection.

To maximize field termination yield, the splice in the connector can be opened and reused with a cap lifter. The assembly tool and cap lifter are included in every box of 60 connectors. The No Polish Connector is tested for premises and FTTP applications for indoor and outdoor locations and is available in singlemode, 62.5 μm, 50 μm and also 50 μm LOMMF (laser optimized multimode fiber) for 10 Gb applications.

The No Polish Connector is RoHS Compliant.\*



3M™ No Polish SC/UPC Connectors

Features	Benefits
Field termination	Right cable length with virtually no cable slack to store
One piece, pre-assembled design	No small, loose parts
Simple assembly tool	Fast, easy installation
Fiber holder for assembly	Aligns and guides fiber into connector with optimal insertion force
900 μm buffer strain relief	Excellent pull out strength
Factory-polished fiber stub	No on-site polish or adhesives required
Bell-shaped boot	Helps prevent fiber from bending below minimum bend radius



3M™ No Polish SC Connector Assembly Tool 8865-AT

### 3M™ No Polish SC Connector Specifications

	Multimode 6800-50	Multimode 6800-50/LOMF	Multimode 6800-62.5	Singlemode 8800
Insertion Loss (dB) typical	0.2	0.2	0.2	0.3
Reflectance (dB) typical at room temp	<-30	<-30	<-25	<-40
Reflectance (dB) over operating temperature range	<-30	<-30	<-25	<-35
Operating temperature range (°C)	0°C to 60°C	0°C to 60°C	-10°C to 60°C	-40°C to 75°C
Storage temperature (°C)	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C	-40°C to 85°C
Connector identification				
Backbone	Black	Black	Black	Black
Housing	Black	Aqua	Beige	Blue
Boot	White	White	White	White
Field termination kit (no power needed)	8865-C	8865-C	8865-C	8865-C



The 3M™ No Polish Connector Kit with 3M™ Cleaver 8865-C includes all the tools necessary for installation.



The 3M™ No Polish Connector Premium Kit 8865-C/PR has all of the tools of the 3M™ Cleaver 8865-C in a larger case that can hang by a hook and includes a work surface, fiber shard container, tweezers, brush and lint-free wipes in a tub.



3M™ Easy Cleaver is conveniently included in select packages of 3M™ No Polish SC Connectors.

### Ordering Information - 3M™ No Polish SC Connectors

Product Number	Connector, Kit and Tool Descriptions	Packaging	3M ID
8800	No Polish SC Connector SM 250/900 with tool (blue housing)	60/package	80-6113-2622-6
6800-50	No Polish SC Connector MM 50 µm 250/900 with tool (black housing)	60/package	80-6113-2623-4
6800-50/LOMMF	No Polish SC Connector MM 50 µm LOMMF 250/900 with tool (aqua housing)	60/package	80-6113-2624-2
6800-62.5	No Polish SC Connector MM 62.5 µm 250/900 with tool (beige housing)	60/package	80-6113-2625-9
8865-AT	No Polish SC Connector Assembly Tool 250/900 µm	1/package	80-6113-2630-9
8865-C	No Polish Connector Kit with cleaver	1/package	80-6113-2379-3
8865-C/PR	No Polish Connector Premium Kit with cleaver	1/package	80-6113-8783-0
8865-CL	No Polish Connector Cap Lifter Tool	25/package	80-6113-8065-2
<b>Connectors with 3M™ Easy Cleaver</b>			
8800/C	No Polish SC/UPC Connector SM with 3M™ Easy Cleaver	120/box	80-6114-9411-5
6800-50/C_60	No Polish SC Connector MM 50 µm with 3M Easy Cleaver	60/box	80-6114-9419-8
6800-50LOMMF/C_60	No Polish SC Connector MM 50 µm laser optimized with 3M Easy Cleaver	60/box	80-6114-9420-6
6800-62.5/C_60	No Polish SC Connector MM 62.5 µm with 3M Easy Cleaver	60/box	80-6114-9421-4

“\*RoHS 2011/65/EU” means that the product or part does not contain any of the substances in excess of the maximum concentration values (“MCVs”) in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M’s knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

3M is a trademark of 3M Company.

**Important Notice**

All statements, technical information, and recommendations related to 3M’s products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M’s current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of 12 months from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M’s option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



**Communication Markets Division**

6801 River Place Blvd.  
Austin, TX 78726-9000 USA

Phone 1-800-426-8688  
Fax 1-800-626-0329  
Web 3M.com/Telecom

Please recycle. Printed in USA © 3M 2015.  
All rights reserved. 80-6114-9881-9

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А