



### Main

|                               |                                                                               |
|-------------------------------|-------------------------------------------------------------------------------|
| Range of product              | OsiSense XC                                                                   |
| Series name                   | Standard format                                                               |
| Product or component type     | Limit switch                                                                  |
| Device short name             | XCKL                                                                          |
| Body type                     | Fixed                                                                         |
| Head type                     | Rotary head                                                                   |
| Material                      | Metal                                                                         |
| Body material                 | Zamak                                                                         |
| Fixing mode                   | By the body                                                                   |
| Movement of operating head    | Rotary                                                                        |
| Type of operator              | Spring return roller lever thermoplastic                                      |
| Type of approach              | Lateral approach 2 directions                                                 |
| Cable entry                   | 1 metal cable gland entry, cable outer diameter: 0.24...0.53 in (6...13.5 mm) |
| Number of poles               | 2                                                                             |
| Contacts type and composition | 1 NC + 1 NO                                                                   |
| Contact operation             | Snap action                                                                   |

### Complementary

|                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switch actuation                                          | By 30° cam                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Electrical connection                                     | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                   |
| Contacts insulation form                                  | Zb                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Number of steps                                           | 1                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Positive opening                                          | With                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Positive opening minimum torque                           | 2.21 lbf.in (0.25 N.m)                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Minimum torque for tripping                               | 0.88 lbf.in (0.1 N.m)                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Minimum actuation speed                                   | 0.01 m/min                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Maximum actuation speed                                   | 4.92 ft/s (1.5 m/s)                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Contact code designation                                  | A300, AC-15 (U <sub>e</sub> = 240 V, I <sub>e</sub> = 3 A) conforming to EN/IEC 60947-5-1 appendix A<br>Q300, DC-13 (U <sub>e</sub> = 250 V, I <sub>e</sub> = 0.27 A) conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                                                                                                |
| [I <sub>th</sub> e] conventional enclosed thermal current | 10 A AC                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| [U <sub>i</sub> ] rated insulation voltage                | 500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14                                                                                                                                                                                                                                                                                                                     |
| Resistance across terminals                               | <= 25 MOhm conforming to IEC 60255-7 category 3                                                                                                                                                                                                                                                                                                                                                                                                |
| [U <sub>imp</sub> ] rated impulse withstand voltage       | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                                 |
| Short-circuit protection                                  | 10 A by gG cartridge fuse                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Electrical durability                                     | 5000000 cycles, DC-13, inductive load type, 120 V, 4 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, inductive load type, 24 V, 7 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, inductive load type, 48 V, 10 W, operating rate: <= 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                                     | 15000000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Width                                                     | 2.05 in (52 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Height                                                    | 2.83 in (72 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Depth                                                     | 1.18 in (30 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product weight                                            | 0.63 lb(US) (0.285 kg)                                                                                                                                                                                                                                                                                                                                                                                                                         |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

### Environment

|                                       |                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------|
| shock resistance                      | 50 gn (duration = 11 ms) conforming to EN/IEC 60068-2-27                                |
| vibration resistance                  | 25 gn (f = 10...500 Hz) conforming to EN/IEC 60068-2-6                                  |
| IP degree of protection               | IP66 conforming to EN/IEC 60529                                                         |
| IK degree of protection               | IK05 conforming to EN 50102                                                             |
| electrical shock protection class     | Class I conforming to IEC 61140<br>Class I conforming to NF C 20-030                    |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                              |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                              |
| protective treatment                  | TC                                                                                      |
| product certifications                | CSA<br>UL                                                                               |
| standards                             | EN 60204-1<br>EN 60947-5-1<br>IEC 60204-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14 |


### Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Green Premium product                                                                                                      | Green Premium product                                                                                                      |
| Compliant - since 1005 - Schneider Electric declaration of conformity                                                      | Compliant - since 1005 - Schneider Electric declaration of conformity                                                      |
| Reference not containing SVHC above the threshold                                                                          | Reference not containing SVHC above the threshold                                                                          |
| Need no specific recycling operations                                                                                      | Need no specific recycling operations                                                                                      |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

### Dimensions




(1) Pg 13.5 cable gland

Ø : 2 elongated holes Ø 5.2 x 6.2

Mounting with Cable Entry


Position of Cable Gland



- (1) Recommended
- (2) To be avoided

Mounting with Rotary Heads and Levers


Type of Cam



- (1) Recommended
- (2) To be avoided


Wiring Diagram

2-pole NC + NO Snap Action




Characteristics of Actuation

Switch Actuation by 30° Cam



Functionnal Diagram



- (P) Positive opening point
- (1) NC contact with positive opening operation
- (2) Closed
- (3) Open
- (4) Tripping
- (5) Resetting

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А