

For more Information  
please call

1-800-Belden1



## General Description:

22 AWG stranded (7x29) .031" bare compacted copper conductor, gas-injected foam HDPE insulation, tinned copper double braid shield (95% coverage), PVC jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

| # Coax | AWG | Stranding | Conductor Material          | Dia. (in.) |
|--------|-----|-----------|-----------------------------|------------|
| 1      | 22  | 7x29      | BCC - Bare Compacted Copper | .031       |

Total Number of Conductors: 1

### Insulation

Insulation Material:

| Insulation Material                                 | Dia. (in.) |
|---|------------|
| Gas-injected FHDPE - Foam High Density Polyethylene | .145       |

### Outer Shield

Outer Shield Material:

| Layer # | Type  | Outer Shield Material | Coverage (%) |
|---------|-------|-----------------------|--------------|
| 1       | Braid | TC - Tinned Copper    | 95.000       |
| 2       | Braid | TC - Tinned Copper    | 95.000       |

### Outer Jacket

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

### Overall Cable

Overall Nominal Diameter: 0.242 in.

## Mechanical Characteristics (Overall)

|                                   |                 |
|-----------------------------------|-----------------|
| Operating Temperature Range:      | -35°C To +75°C  |
| UL Temperature Rating:            | 75°C            |
| Bulk Cable Weight:                | 41 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 88 lbs.         |
| Min. Bend Radius/Minor Axis:      | 2.500 in.       |

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

|                                       |            |
|---------------------------------------|------------|
| NEC/(UL) Specification:               | CM         |
| CEC/(UL) Specification:               | CM         |
| EU Directive 2011/65/EU (ROHS II):    | Yes        |
| EU CE Mark:                           | Yes        |
| EU Directive 2000/53/EC (ELV):        | Yes        |
| EU Directive 2002/95/EC (RoHS):       | Yes        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2005 |
| EU Directive 2002/96/EC (WEEE):       | Yes        |
| EU Directive 2003/11/EC (BFR):        | Yes        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes        |
| MII Order #39 (China RoHS):           | Yes        |
| RG Type:                              | 59/U       |

**Flame Test**

UL Flame Test: UL1685 UL Loading

**Suitability**

Suitability - Indoor: Yes

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)**

**Nom. Characteristic Impedance:**

Impedance (Ohm)

75

**Nom. Inductance:**

Inductance (µH/ft)

0.094

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)

17.0

**Nominal Velocity of Propagation:**

VP (%)

80

**Nominal Delay:**

Delay (ns/ft)

1.3

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

12.2

**Nominal Outer Shield DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

2.4

**Nom. Attenuation:**

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 1.000       | 0.200                    |
| 3.600       | 0.500                    |
| 5.000       | 0.600                    |
| 6.000       | 0.670                    |
| 7.000       | 0.730                    |
| 10.000      | 0.900                    |
| 12.000      | 0.980                    |
| 25.000      | 1.440                    |
| 67.500      | 2.400                    |
| 71.500      | 2.500                    |
| 88.500      | 2.800                    |
| 100.000     | 3.000                    |
| 135.000     | 3.500                    |
| 143.000     | 3.600                    |
| 180.000     | 4.100                    |
| 270.000     | 5.100                    |
| 360.000     | 6.000                    |
| 540.000     | 7.400                    |
| 720.000     | 8.700                    |
| 750.000     | 8.900                    |
| 1000.000    | 10.500                   |
| 1500.000    | 13.300                   |
| 2000.000    | 15.700                   |
| 2250.000    | 16.900                   |
| 3000.000    | 20.300                   |
| 4500.000    | 28.200                   |

**Max. Operating Voltage - UL:**

Voltage

300 V RMS

**Other Electrical Characteristic 1:**

Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination.

**Other Electrical Characteristic 2:**

Return Loss tested in accordance with ASIM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

**Minimum Return Loss:**

| Start Freq. (MHz) | Stop Freq. (MHz) | Min. RL (dB) |
|-------------------|------------------|--------------|
| 5.000             | 850.000          | 20.000       |
| 851.000           | 4500.000         | 15.000       |

**Sweep Test**

**Sweep Testing:**

100% Sweep tested 5 MHz to 4.5 GHz.

**Notes (Overall)**

**Notes:** Compacted conductor combines impedance uniformity of solid conductors and "nick-resistance" of stranded conductor.

**Put Ups and Colors:**

| Item #        | Putup    | Ship Weight | Color         | Notes | Item Desc               |
|---------------|----------|-------------|---------------|-------|-------------------------|
| 1505F B591000 | 1,000 FT | 45.000 LB   | BLACK, MATTE  | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F G7V1000 | 1,000 FT | 45.000 LB   | RED, MATTE    | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F G7W1000 | 1,000 FT | 45.000 LB   | GREEN, MATTE  | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F G7X1000 | 1,000 FT | 45.000 LB   | BLUE, MATTE   | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F G7Y1000 | 1,000 FT | 45.000 LB   | WHITE, MATTE  | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F G8L1000 | 1,000 FT | 45.000 LB   | ORANGE, MATTE | C     | #21 GIFHDLDPPE DBLB PVC |
| 1505F Z4B1000 | 1,000 FT | 45.000 LB   | VIO Z4B       |       | #21 GIFHDLDPPE DBLB PVC |
| 1505F 0041000 | 1,000 FT | 45.000 LB   | YELLOW        | C     | #21 GIFHDLDPPE DBLB PVC |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 10    Revision Date: 06-07-2016

© 2016 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А