OMRON

Ultra-Miniature Automotive PCB Relay

• Compact size.

- High performance PCB relay.
- Fully automated assembly.
- Fully sealed construction.
- Separate SPDT contacts.



Ordering Information

| Description | Model |
|--|---------|
| Standard type | G8NW-2 |
| High sensitivity (low pull-in voltage) | G8NW-2S |
| High temperature (150° C) | G8NW-2L |
| High temperature / high sensitivity | G8NW-2H |
| Flasher load switching | G8NW-2F |
| Ultra-high sensitivity | G8NW-2U |
| Reflow solder type | G8NW-2R |
| Pin in paste solder type | G8NW-2C |

· Seat adjustment

Sunroof

■ Typical Applications

- Power windows/power door lock
- Smart junction box and module applications

Specifications

Contact Data

| Max. switching current | 30 A |
|------------------------|--|
| Max. switching voltage | 16 V |
| Max. carry current | 25 A (at 20° C for 1 hour) |
| Min. carry current | 100 mA |
| Contact material | Silver tin alloy – cadmium free (PdRu for -F type) |

■ Coil Ratings (at 20° C)

| Туре | Rated voltage | Coil resistance (±10%) | Nominal power consumption | Pull in voltage | Dropout voltage |
|---------|---------------|---------------------------|------------------------------|-----------------|-----------------|
| G8NW-2 | 12 VDC | 225 Ω | 640 mW | < 7.2 V | > 1.0 V |
| G8NW-2L | | | | | |
| G8NW-2S | | 180 Ω | 800 mW | < 6.5 V | |
| G8NW-2H | | | | | |
| G8NW-2F | | 130 Ω | 1108 mW | < 7.2 V | |
| G8NW-2U | | | | < 5.5 V | |
| G8NW-2R | | - | - | - | - |
| G8NW-2C | | | | | |

OMRON

Characteristics

| Max. initial contact voltage drop/resistance | | 250 mV @ 10 A/50 mΩ @ 1 A | |
|--|------------------------|--|--|
| Operate time | | 10 ms max. (2.5 ms typical) @ 12 VDC | |
| Release time | | 10 ms max. (1.2 ms typical) (see Note) | |
| Bounce time | Operate | 5 ms max. (0.5 ms typical) | |
| | Release | 10 ms max. (4.0 ms typical) | |
| Switching frequency | Mechanical | 18,000 operations per hour | |
| | Electrical | 1,800 operations per hour (under rated loading) | |
| Insulation resistance | | 100 MΩ min. (@ 500 VDC) | |
| Dielectric strength | | 1.0 mA max. leakage at 500 VAC, 50-60 Hz for 1 minute between coil & contacts and between contacts | |
| Vibration | Mechanical durability | 10-500 Hz, 44.1 m/s ² | |
| | Malfunction durability | 10-500 Hz, 44.1 m/s ² | |
| Shock | Mechanical durability | 1000 m/s ² | |
| | Malfunction durability | 100 m/s ² min. | |
| Ambient operating temperature | | -40°C to 85°C (105°C max. for -L and -H types) | |
| Humidity | | 35% to 85% RH | |
| Service life | Mechanical | 1,000,000 operations | |
| | Electrical | 100,000 operations (load dependant) | |
| Weight | | 8.0 g (approx.) | |


Note: External coil suppression will cause a measurable increase in release times and may cause the relay's characteristics to fall out of the specifications given here.

Characteristics Reference Data


■ Durability Test Data

| Relay | Load type | Current | Cycles tested |
|--------|-----------------------------|-------------------------|---------------|
| G8NW / | Power window motor (locked) | 26 A | 200,000 |
| G8ND | | 27 A 8A Steady state | 130,000 |


Normalized Coil Resistance vs. Temperature (20° C reference)




Load Limit Curve




Overcurrent Energization (20°C, G8N-1 225Ω coil, 4 samples)



Operating Voltage Range (G8N-1, 180Ω coil)





Coil Temperature vs. Applied Voltage at 20°C (G8N-1, 225 Ω coil)




Overcurrent Energization


(85°C, G8N-1 225 Ω coil, 4 samples)








Dimensions



Note: G8NW-2C type terminals are 1.9+0.3mm (not 3.5mm) for pin in paste solder process.

■ Tube Packaging



36 relays per tube, 30 tubes per box (1080 relays per box).

Note: 1. For additional information, please contact Omron.

- 2. Prior to receipt of order, specifications subject to change without notice.
- 3. This specification sheet is intended to be a guideline for application of this product. The information contained is believed to be correct. However, it is impossible for Omron to evaluate every possible use. It is the user's responsibility to determine product suitability in any application.
- 4. Omron can meet some special performance characteristics upon request.
- 5. All data at 20° C unless otherwise noted.

4

6. If several relays are to be mounted on a single PCB, they must be given at least 3 mm clearance on all sides.

Omron Electronic Components, LLC

Terms and Conditions of Sales

I. GENERAL

- Definitions: The words used herein are defined as follows.
- Terms: These terms and conditions (a)
- Omron Electronic Components LLC and its subsidiaries Seller: (b)
- The buyer of Products, including any end user in section III through VI (c) Buyer: Products and/or services of Seller
- (d) Products: Including: Including without limitation (e)
- 2. Offer: Acceptance: These Terms are deemed part of all quotations, acknowledgments, invoices, purchase orders and other documents, whether electronic or in writing, relating to the sale of Products by Seller. Seller hereby objects to any Terms proposed in Buyer's purchase order or other documents which are inconsistent with, or in addition to, these Terms
- Distributor: Any distributor shall inform its customer of the contents after and including section III of these Terms. 3

II. SALES

- Prices: Payment: All prices stated are current, subject to change without notice by Seller. Buyer agrees to pay the price in effect at time of shipment. Payments for Products received are due net 30 days unless otherwise stated in the invoice. Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice.
- Discounts: Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only 2 if (a) the invoice is paid according to Seller's payment terms and (b) Buyer has no past due amounts owing to Seller.
- Interest: Seller, at its option, may charge Buyer 1.5% interest per month or the maximum 3 legal rate, whichever is less, on any balance not paid within the stated terms.
- Orders: Seller will accept no order less than 200 U.S. dollars net billing. Currencies: If the prices quoted herein are in a currency other than U.S. dollars, Buyer 5 shall make remittance to Seller at the then current exchange rate most favorable to Seller; provided that if remittance is not made when due, Buyer will convert the amount to U.S. dollars at the then current exchange rate most favorable to Seller available during the period between the due date and the date remittance is actually made.
- Governmental Approvals: Buyer shall be responsible for all costs involved in obtaining 6. any government approvals regarding the importation or sale of the Products. <u>Taxes</u>: All taxes, duties and other governmental charges (other than general real property
- 7. and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Seller or required to be collected directly or indirectly by Seller for the manufacture, production, sale, delivery, importation, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Seller.
- Financial: If the financial position of Buyer at any time becomes unsatisfactory to Seller, Seller reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise comply with these Terms or any related agreement, Seller may (without liability and in addition to other remedies) cancel any unshipped portion of Products sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid accounts.
- 9. Cancellation: Etc: Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Seller fully against all costs or expenses arising in connection therewith.
- 10. Force Majeure: Seller shall not be liable for any delay or failure in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots,
- delay in or lack of transportation or the requirements of any government authority.
 <u>Shipping: Delivery:</u> Unless otherwise expressly agreed in writing by Seller.
 (a) All sales and shipments of Products shall be FOB shipping point (unless otherwise stated in writing by Seller), at which point tille to and all risk of loss of the Products shall be shipping a count intervent in the products shall be shipping a count intervent in the products shall be shipping a count intervent in the products shall be shipping a count intervent in the products shall be shipping and the shall be shipping a count intervent in the products shall be shipping a count intervent in the products shall be shipping and the shall be pass from Seller to Buyer, provided that Seller shall retain a security interest in the Products until the full purchase price is paid by Buyer;
 - Delivery and shipping dates are estimates only; and
- Seller will package Products as it deems proper for protection against normal (c) handling and extra charges apply to special conditions. 12. <u>Claims:</u> Any claim by Buyer against Seller for shortage or damage to the Products
- occurring before delivery to the carrier must be presented in detail in writing to Seller within 30 days of receipt of shipment.

III. PRECAUTIONS

- Suitability: IT IS THE BUYER'S SOLE RESPOINSIBILITY TO ENSURE THAT ANY OMRON PRODUCT IS FIT AND SUFFICIENT FOR USE IN A MOTORIZED VEHICLE APPLICATION. BUYER SHALL BE SOLELY RESPONSIBLE FOR DETERMINING APPROPRIATENESS OF THE PARTICULAR PRODUCT WITH RESPECT TO THE BUYER'S APPLICATION INCLUDING (A) ELECTRICAL OR ELECTRONIC COMPONENTS, (B) CIRCUITS, (C) SYSTEM ASSEMBLIES, (D) END PRODUCT, (E) SYSTEM, (F) MATERIALS OR SUBSTANCES OR (G) OPERATING ENVIRONMENT. Buyer acknowledges that it alone has determined that the Products will meet their requirements of the intended use in all cases. Buyer must know and observe all prohibitions of use applicable to the Product/s.
- Use with Attention: The followings are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible use of any Product, nor to imply that any use listed may be suitable for any Product:
 - Outdoor use, use involving potential chemical contamination or electrical (a) interference.
 - Use in consumer Products or any use in significant quantities.

- (c) Energy control systems, combustion systems, railroad systems, aviatio medical equipment, amusement machines, vehicles, safety equipment,
- (d) Systems, machines, and equipment that could present a risk to life or p <u>Prohibited Use:</u> NEVER USE THE PRODUCT FOR AN APPLICATION INV SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT TH ADD FUNCTION INVERTIGATION IN 3 AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND TH PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED WITHIN THE OVERALL EQUIPMENT OR SYSTEM.
- Motorized Vehicle Application: USE OF ANY PRODUCT/S FOR A MOTOR VEHICLE APPLICATION MUST BE EXPRESSLY STATED IN THE SPECIFIC SELLER
- Programmable Products: Seller shall not be responsible for the Buyer's products 5. a programmable Product.

IV. WARRANTY AND LIMITATION

- Warranty: Seller's exclusive warranty is that the Products will be free from d materials and workmanship for a period of twelve months from the date of s (or such other period expressed in writing by Seller). SELLER MAKES NO \ OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT ALL OTHER WA NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTIC PURPOSE OF THE PRODUCTS.
- 2 Buyer Remedy: Seller's sole obligation hereunder shall be to replace (in the originally shipped with Buyer responsible for labor charges for removal or re thereof) the non-complying Product or, at Seller's election, to repay or credit amount equal to the purchase price of the Product; provided that there shall liability for Seller or its affiliates unless Seller's analysis confirms that the Pro handled, stored, installed and maintained and not subject to contamination, misuse or inappropriate modification. Return of any Products by Buyer mus
- Limitation on Liability: SELLER AND ITS AFFILIATES SHALL NOT BE LIAE SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES, LC 3 PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CON WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRA WARRANTY, NEGLIGENCE OR STRICT LIABILITY. FURTHER, IN NO EV LIABILITY OF SELLER OR ITS AFFILITATES EXCEED THE INDIVIDUAL I THE PRODUCT ON WHICH LIABILITY IS ASSERTED.
- Indemnities: Buyer shall indemnify and hold harmless Seller, its affiliates an employees from and against all liabilities, losses, claims, costs and expense attomey's fees and expenses) related to any claim, investigation, litigation or pr (whether or not Seller is a party) which arises or is alleged to arise from Buyer's omissions under these Terms or in any way with respect to the Products.

V. INFORMATION; ETC.

- Intellectual Property: The intellectual property embodied in the Products is the property of Seller and its affiliates and Buyer shall not attempt to duplicate it without the written permission of Seller. Buyer (at its own expense) shall inder hold harmless Seller and defend or settle any action brought against Seller that it is based on a claim that any Product made to Buyer specifications inf intellectual property rights of another party.
- Property: Confidentiality: Notwithstanding any charges to Buyer for enginee information and materials supplied by Seller to Buyer relating to the Product confidential and proprietary, and Buyer shall limit distribution thereof to its tr employees and strictly prevent disclosure to any third party. <u>Performance Data</u>: Performance data is provided as a guide in determining
- 3 and does not constitute a warranty. It may represent the result of Seller's tes and the users must correlate it to actual application requirements.
- Change In Specifications: Product specifications and description may be cha time based on improvements or other reasons. It is Seller's practice to char numbers when published ratings or features are changed, or when significa engineering changes are made. However, some specifications of the Produ changed without any notice.
- Errors And Omissions: The information on Seller's website or in other docur has been carefully checked and is believed to be accurate; however, no res assumed for clerical, typographical or proofreading errors or omissions.
- regarding (a) export of the Products or information provided by Seller; (b) sa 6 Products to forbidden or other proscribed persons or organizations; (c)discle non-citizens of regulated technology or information.

VI. MISCELLANEOUS

- <u>Waiver</u>: No failure or delay by Seller in exercising any right and no course o between Buyer and Seller shall operate as a waiver of rights by Seller.
- Assignment: Buyer may not assign its rights hereunder without Seller's writt Law: These Terms are governed by Illinois law (without regard to conflict of laws 3
- and state courts in Illinois have exclusive jurisdiction for any dispute hereun 4 Amendment: These Terms constitute the entire agreement between Buyer a relating to the Products, and no provision may be changed or waived unless signed by the parties.
- 5 Severability: If any provision hereof is rendered ineffective or invalid, such pr not invalidate any other provision.

Certain Precautions on Specifications and Use

- <u>Suitability for Use</u>. Seller shall not be responsible for conformity with any stan-dards, codes or regulations which apply to the combination of the Product in Buyer's application or use of the Product. At Buyer's request, Seller will provide applicable third party certification documents identifying ratings and limistations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in com-bination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the par-ticular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a non- (i) Outdoor use, uses involving potential chemical contamination or electrical
 - interference, or conditions or uses not described in this document.
 - Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
 - (iii) Use in consumer products or any use in significant quantities
 - (iv) Systems, machines and equipment that could present a risk to life or property. Please know and observe all prohibitions of use applicable to this

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE WITHIN THE OVERALL FOLIPMENT OR SYSTEM. INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

- Programmable Products. Seller shall not be responsible for the user's
- Programmable Products. Seller shall not be responsible for the users programmable product, or any consequence thereof. <u>Performance Data</u>. Performance data given in this publication is provided as a guide for the user in determining suitability and does not constitute a war-ranty. It may represent the result of Seller's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to 3 Seller's Warranty and Limitations of Liability
- <u>Change in Specifications</u>. Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our prac-4. tice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifica-tions of the Product may be changed without any notice. When in doubt, specal part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Seller representative at any time to confirm actual specifications of purchased Product.
- Errors and Omissions. The information in this publication has been carefully checked and is believed to be accurate; however, no responsibility is assumed 5.
- for clerical, typographical or proofreading errors, or omissions. <u>RoHS Compliance</u>. Where indicated, our products currently comply, to the best of our knowledge as of the date of this publication, with the requirements 6. Substances ("RoHS"), although the requirements of RoHS do not take effect until July 2006. These requirements may be subject to change. Please consult our website for current information.

Complete "Terms and Conditions of Sale" for product purchase and use are on Omron's website at http://www.components.omron.com - under the "About Us" tab, in the Legal Matters section.

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS. To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.



55 E. Commerce Drive, Suite B Schaumburg, IL 60173

OMRON ON-LINE

Global - http://www.omron.com USA - http://www.components.omron.com

847-882-2288

Cat. No. J01C-E-01

01/07

Specifications subject to change without notice

Printed in USA



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;

- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);

- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;

- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком):

- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный) Факс: 8 (812) 320-03-32 Электронная почта: ocean@oceanchips.ru Web: http://oceanchips.ru/ Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А