

# PNP - MJ15023, MJ15025\*

\*MJ15025 is a Preferred Device

## Silicon Power Transistors

The MJ15023 and MJ15025 are PowerBase power transistors designed for high power audio, disk head positioners and other linear applications.

### Features

- High Safe Operating Area (100% Tested) -2 A @ 80 V
- High DC Current Gain -  $h_{FE} = 15$  (Min) @  $I_C = 8$  Adc
- Pb-Free Packages are Available\*

### MAXIMUM RATINGS

| Rating                                                                                 | Symbol         | Value       | Unit                     |
|----------------------------------------------------------------------------------------|----------------|-------------|--------------------------|
| Collector-Emitter Voltage<br>MJ15023<br>MJ15025                                        | $V_{CEO}$      | 200<br>250  | Vdc                      |
| Collector-Base Voltage<br>MJ15023<br>MJ15025                                           | $V_{CBO}$      | 350<br>400  | Vdc                      |
| Emitter-Base Voltage                                                                   | $V_{EBO}$      | 5           | Vdc                      |
| Collector-Emitter Voltage                                                              | $V_{CEX}$      | 400         | Vdc                      |
| Collector Current - Continuous<br>- Peak (Note 1)                                      | $I_C$          | 16<br>30    | Adc                      |
| Base Current - Continuous                                                              | $I_B$          | 5           | Adc                      |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 250<br>1.43 | W<br>W/ $^\circ\text{C}$ |
| Operating and Storage Junction<br>Temperature Range                                    | $T_J, T_{stg}$ | -65 to +200 | $^\circ\text{C}$         |

### THERMAL CHARACTERISTICS

| Characteristics                      | Symbol          | Max  | Unit               |
|--------------------------------------|-----------------|------|--------------------|
| Thermal Resistance, Junction-to-Case | $R_{\theta JC}$ | 0.70 | $^\circ\text{C/W}$ |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.


1. Pulse Test: Pulse Width = 5 ms, Duty Cycle  $\leq 10\%$ .



ON Semiconductor®

<http://onsemi.com>

**16 AMPERES  
SILICON POWER TRANSISTORS  
200 – 250 VOLTS, 250 WATTS**



**TO-204AA (TO-3)  
CASE 1-07  
STYLE 1**

### MARKING DIAGRAM



MJ1502x = Device Code  
x = 3 or 5  
G = Pb-Free Package  
A = Assembly Location  
Y = Year  
WW = Work Week  
MEX = Country of Origin

### ORDERING INFORMATION

| Device   | Package             | Shipping         |
|----------|---------------------|------------------|
| MJ15023  | TO-204              | 100 Units / Tray |
| MJ15023G | TO-204<br>(Pb-Free) | 100 Units / Tray |
| MJ15025  | TO-204              | 100 Units / Tray |
| MJ15025G | TO-204<br>(Pb-Free) | 100 Units / Tray |

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

**Preferred** devices are recommended choices for future use and best overall value.

# PNP – MJ15023, MJ15025\*

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic                                                                                                                                                                                        | Symbol         | Min        | Max        | Unit            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------------|------------|-----------------|
| <b>OFF CHARACTERISTICS</b>                                                                                                                                                                            |                |            |            |                 |
| Collector–Emitter Sustaining Voltage (Note 2)<br>( $I_C = 100\text{ mAdc}$ , $I_B = 0$ )                                                                                                              | $V_{CEO(sus)}$ | 200<br>250 | –<br>–     | –               |
| Collector Cutoff Current<br>( $V_{CE} = 200\text{ Vdc}$ , $V_{BE(off)} = 1.5\text{ Vdc}$ )<br>( $V_{CE} = 250\text{ Vdc}$ , $V_{BE(off)} = 1.5\text{ Vdc}$ )                                          | $I_{CEX}$      | –<br>–     | 250<br>250 | $\mu\text{Adc}$ |
| Collector Cutoff Current<br>( $V_{CE} = 150\text{ Vdc}$ , $I_B = 0$ )<br>( $V_{CE} = 200\text{ Vdc}$ , $I_B = 0$ )                                                                                    | $I_{CEO}$      | –<br>–     | 500<br>500 | $\mu\text{Adc}$ |
| Emitter Cutoff Current<br>( $V_{CE} = 5\text{ Vdc}$ , $I_B = 0$ )                                                                                                                                     | $I_{EBO}$      | –          | 500        | $\mu\text{Adc}$ |
| <b>SECOND BREAKDOWN</b>                                                                                                                                                                               |                |            |            |                 |
| Second Breakdown Collector Current with Base Forward Biased<br>( $V_{CE} = 50\text{ Vdc}$ , $t = 0.5\text{ s}$ (non-repetitive))<br>( $V_{CE} = 80\text{ Vdc}$ , $t = 0.5\text{ s}$ (non-repetitive)) | $I_{S/b}$      | 5<br>2     | –<br>–     | Adc             |
| <b>ON CHARACTERISTICS</b>                                                                                                                                                                             |                |            |            |                 |
| DC Current Gain<br>( $I_C = 8\text{ Adc}$ , $V_{CE} = 4\text{ Vdc}$ )<br>( $I_C = 16\text{ Adc}$ , $V_{CE} = 4\text{ Vdc}$ )                                                                          | $h_{FE}$       | 15<br>5    | 60<br>–    | –               |
| Collector–Emitter Saturation Voltage<br>( $I_C = 8\text{ Adc}$ , $I_B = 0.8\text{ Adc}$ )<br>( $I_C = 16\text{ Adc}$ , $I_B = 3.2\text{ Adc}$ )                                                       | $V_{CE(sat)}$  | –<br>–     | 1.4<br>4.0 | Vdc             |
| Base–Emitter On Voltage<br>( $I_C = 8\text{ Adc}$ , $V_{CE} = 4\text{ Vdc}$ )                                                                                                                         | $V_{BE(on)}$   | –          | 2.2        | Vdc             |
| <b>DYNAMIC CHARACTERISTICS</b>                                                                                                                                                                        |                |            |            |                 |
| Current–Gain – Bandwidth Product<br>( $I_C = 1\text{ Adc}$ , $V_{CE} = 10\text{ Vdc}$ , $f_{test} = 1\text{ MHz}$ )                                                                                   | $f_T$          | 4          | –          | MHz             |
| Output Capacitance<br>( $V_{CB} = 10\text{ Vdc}$ , $I_E = 0$ , $f_{test} = 1\text{ MHz}$ )                                                                                                            | $C_{ob}$       | –          | 600        | pF              |

2. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2\%$ .




Figure 1. Active-Region Safe Operating Area

There are two limitations on the powerhandling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate  $I_C - V_{CE}$  limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 1 is based on  $T_{J(pk)} = 200^\circ\text{C}$ ;  $T_C$  is variable depending on conditions. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.

TYPICAL CHARACTERISTICS




Figure 2. Capacitances




Figure 3. Current-Gain — Bandwidth Product




Figure 4. DC Current Gain




Figure 5. "On" Voltages


# PNP – MJ15023, MJ15025\*

## PACKAGE DIMENSIONS

### TO-204 (TO-3)

CASE 1-07

ISSUE Z



#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH REFERENCED TO-204AA OUTLINE SHALL APPLY.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 1.550 REF |       | 39.37 REF   |       |
| B   | ---       | 1.050 | ---         | 26.67 |
| C   | 0.250     | 0.335 | 6.35        | 8.51  |
| D   | 0.038     | 0.043 | 0.97        | 1.09  |
| E   | 0.055     | 0.070 | 1.40        | 1.77  |
| G   | 0.430 BSC |       | 10.92 BSC   |       |
| H   | 0.215 BSC |       | 5.46 BSC    |       |
| K   | 0.440     | 0.480 | 11.18       | 12.19 |
| L   | 0.665 BSC |       | 16.89 BSC   |       |
| N   | ---       | 0.830 | ---         | 21.08 |
| Q   | 0.151     | 0.165 | 3.84        | 4.19  |
| U   | 1.187 BSC |       | 30.15 BSC   |       |
| V   | 0.131     | 0.188 | 3.33        | 4.77  |

#### STYLE 1:

1. BASE
  2. EMITTER
- CASE: COLLECTOR

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А