



Wire Connector T/R+ (Tan/Red)



Wire Connector



Canadian Standards Association
Standard NO. 22.2
NO. 188-M1983
3M File NO. LR15503



PASSPORT TO EUROPEAN UNION COUNTRIES

Data Sheet

Application

Use a 3M™ T/R+ Wire Connector to electrically connect two or more conductor ends in a pigtail application and insulate the connection.

Wire

AWG Range: COPPER conductors only, No. 22 thru No. 8 solid and/or stranded (see wire matrix for specific wire combinations).

METRIC Range: COPPER conductors only, 0,5 mm² thru 6,0 mm² ridged (solid) and flexible (stranded).

Construction

Spring - Spring steel, corrosion resistant coating
Insulator: - Flame retardant, polypropylene, tan and thermoplastic elastomer, red

Weight

.0068 lbs. (3.1 g)

Performance Test

The following tests were performed to the specification of UL Standard 486C and CSA Standard C22.2 No. 188-M1983.

Static-Heating	Pass
Secureness	Pass
Pullout	Pass
Dielectric Voltage Withstand	Pass
Secureness-of-Insulation	Pass
Flammability	Pass

Other Tests:

per MIL-STD-1344A	
Method 2005.1UV Exposure	Pass
Per ASTM G-53-77 Salt Spray	Pass

Fluid Immersion Test

Connectors were immersed in the following chemicals for seven days at 23°C±2°C with no affect on appearance or loss of material strength.



Typical Reagents and Materials

From ASTM D 543-87 and MIL-STD-1344A

Acetic Acid
Acetone
Detergent Solution, Heavy Duty
Ethyl Alcohol (95%)
Ethyl Alcohol (50%)
Heptane
Hydrogen Peroxide Solution 28%
Methyl Alcohol
Sodium Hydroxide Solution
Mineral Spirit
Lubricating Oil

Engineering Specification

3M T/R+ Wire Connector is capable of connecting two or more wires in a pigtail application, in the wire range of No. 22 thru No. 8 AWG solid and/or stranded copper conductors. The connector shall be constructed of an active (live) spring with a corrosion resistant coating. The connector shall be UL LISTED and CSA Certified as a pressure wire connector. The connector shall be voltage rated 600 volts maximum building wire and 1000 volts maximum signs and lighting fixtures (luminaries). The connector shall have a maximum operating temperature of 105°C (221°F).





Wire Connector T/R+

AWG Wire Combinations
Copper to Copper Conductors

How to read this chart:

Example 1:
1 No. 18 str
+ 4 No. 20 solid or str (5)

Example 2:
1 No. 12 sol
+ 2 No. 12 str (3)

22 SOL or STR	1 2 3 4																							
20 SOL or STR	1 2 3 4	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
18 STR	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
18 SOL	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
16 STR	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
16 SOL	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
14 STR	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
14 SOL	1 2 3 4 5	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
12 STR	1 2 3 4	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
12 SOL	1 2 3 4	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
10 STR	1 2	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
10 SOL	1 2	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
8 STR	1	1 2 3 4 5		1 2 3 4 5			1 2 3 4 5					1 2 3 4 5				1 2 3 4			1 2 3		1 2 3			
TR+		1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4 5	1 2 3 4	1 2 3 4	1 2 3	1 2 3										
		22 SOL or STR	20 SOL or STR	18 STR	18 SOL	16 STR	16 SOL	14 STR	14 SOL	12 STR	12 SOL	10 STR	10 SOL											

Installation Instructions

⚠ WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

1. Strip wire insulation 1/2".
2. Firmly grasp wires, making sure insulation ends are even and tightly bundled. (Wires may be twisted or untwisted.) Lead stranded wires slightly. Slip the connector over wire tips.
3. Turn connector onto wires in clockwise direction until secure.
4. To remove, turn connector counter- clockwise.

Regulatory Agencies

UL Listed as a Pressure Cable Connector

Tested per UL Standard 486C

UL File No. E23438

Operating Temperature: 105°C (221°F)

Voltage Rating: 600 volts max. building wire;

1000 volts max. signs and fixtures

Flammability Rating: UL94 V-2

CSA Certified-CSA Standard C22.2 No. 0, 188-M1983

CSA File No. LR15503

Operating Temperature: 105°C (221°F)

Voltage Rating: 600 volts max. building wire

1000 volts max. signs and luminaires.

Flammability Rating: C22.2 No. 0.6 V-2

Operating Temperature: 105°C (221°F)

Voltage Rating: 600 volts max. building wire;

1000 volts max. signs and fixtures

Flammability Rating: UL94 V-2

Federal Specification W-S-610:

“Commercial package only”

Type	Class	Kind	Style
1	1	cu	G

Metric Wire Combinations

Copper Conductors Only

Cross Section Capacity	
Minimum	Maximum
2.0mm ²	12.5mm ²

Conductor Combinations		
Quantity	Size	Type
6	0,5mm ²	sol/str
3-6	0,75mm ²	sol/str
2-6	1,0mm ²	sol/str
2-6	1,5mm ²	sol/str
2.5	2,5mm ²	sol/str
2.3	4.0 mm ²	sol/str

Only AWG combinations are UL Listed or CSA Certified.

3M is a trademark of 3M Company.



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.



is a trademark of the European Union.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture for a period of one (1) year from the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

3M

Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
<http://www.3M.com/elpd>

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А