

## Snap-in markers - US-EMP (29X8) - 0829436

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Snap-in markers, Card, white, Unlabeled, Can be labeled with: THERMOMARK CARD PLUS, THERMOMARK CARD, Mounting type: Snapped into marker carrier, Lettering field: 29 x 8 mm



The illustration shows a version of the product

### Why buy this product

- ✓ The US-EMP ... UniSheet labeling range includes markers that can be fitted into existing CARRIER EMP ... label frames
- ✓ The markers, which are supplied in uniform sheets, can be labeled quickly, easily, and cost-effectively using the THERMOMARK CARD
- ✓ The perforated markers are easy to separate and can be easily fitted
- ✓ The sheets provide space for including function texts

### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 PCE                                                                                                  |
| Minimum order quantity               | 10 PCE                                                                                                  |
| GTIN                                 | <br>4 046356 562232 |
| Weight per Piece (excluding packing) | 9.77 GRM                                                                                                |
| Weight per piece (including packing) | 9.77 GRM                                                                                                |
| Custom tariff number                 | 39204910                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Sales Key                            | B1 - Marking Assembly                                                                                   |

### Technical data

#### Dimensions

|            |        |
|------------|--------|
| Length (b) | 29 mm  |
| Height     | 0.5 mm |
| Width (a)  | 8 mm   |

#### Ambient conditions

|                                 |                             |
|---------------------------------|-----------------------------|
| Wipe resistance                 | DIN EN 61010-1 (VDE 0411-1) |
| Ambient temperature (operation) | -30 °C ... 80 °C            |
| Ambient temperature (assembly)  | 15 °C ... 25 °C             |

#### General

|       |       |
|-------|-------|
| Color | white |
|-------|-------|

# Snap-in markers - US-EMP (29X8) - 0829436

## Technical data

### General

|                                                              |                                  |
|--------------------------------------------------------------|----------------------------------|
| Inflammability class according to UL 94                      | V0                               |
| Components                                                   | Silicone-free                    |
| Material                                                     | PVC                              |
|                                                              | PVC                              |
| Number of individual labels                                  | 48                               |
| Number of individual labels per row                          | 3                                |
| RoHS compliant                                               | Yes                              |
| Halogen-free                                                 | No                               |
| Silicone-free                                                | Yes                              |
| Cadmium-free                                                 | Yes                              |
| File number                                                  | U9                               |
| Printability                                                 | Thermal transfer                 |
| Device                                                       | 5146464 THERMOMARK CARD          |
|                                                              | 5146451 THERMOMARK CARD-US-MAG1  |
| Ink ribbon                                                   | 0801371 THERMOMARK-RIBBON 110-TC |
| Test specification weathering-resistance                     | Following ISO 4892-2:2013-03     |
| Test duration                                                | 96 h                             |
| Wipe resistance test result                                  | Test passed                      |
| Salt spray test specification                                | DIN EN ISO 9227:2012-09          |
| Test duration                                                | 96 h                             |
| Salt spray testing result                                    | Test passed                      |
| Alternating condensation climate with SO2 test specification | DIN 50018:1997-06                |
| Climate level                                                | KFW 1.0 S                        |
| Cycles                                                       | 2                                |
| Condensation test result                                     | Test passed                      |
| Wipe resistance of test specification inscriptions           | IEC 61010-1:2010-06              |
| Result                                                       | Test passed                      |
| Burning behaviour                                            | self-extinguishing               |
| Foil strength                                                | 500 µm                           |

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001694 |
| ETIM 5.0 | EC001694 |

### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 11    | 39121410 |
| UNSPSC 12.01 | 39121410 |

## Snap-in markers - US-EMP (29X8) - 0829436

### Classifications

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 13.2   | 39121410 |
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |

### Accessories

#### Accessories

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А