

RELIABILITY REPORT  
FOR

**DS1961S**

**Dallas Semiconductor**

4401 South Beltwood Parkway  
Dallas, TX 75244-3292

Prepared by:

*Ken Wendel*

Ken Wendel  
Reliability Engineering Manager  
Dallas Semiconductor  
4401 South Beltwood Pkwy.  
Dallas, TX 75244-3292  
Email : ken.wendel@dalsemi.com  
ph: 972-371-3726  
fax: 972-371-6016  
mbl: 214-435-6610

**Conclusion:**

The following qualification successfully meets the quality and reliability standards required of all Dallas Semiconductor products and processes:

DS1961S

In addition, Dallas Semiconductor's continuous reliability monitor program ensures that all outgoing product will continue to meet Maxim's quality and reliability standards. The current status of the reliability monitor program can be viewed at <http://www.maxim-ic.com/TechSupport/dsreliability.html>.\*

**Module Description:**

A description of this Module can be found in the product data sheet. You can find the product data sheet at [http://dbserv.maxim-ic.com/l\\_datasheet3.cfm](http://dbserv.maxim-ic.com/l_datasheet3.cfm).\*

**Reliability Derating:**

A module device consists of one or more IC's in a single, upward integrated, package. This package is assembled to include batteries, crystals, and other piece parts that make up the configuration of the Module. Because of either the complexity of the package or the included piece parts, standard high temperature reliability testing is not possible. Therefore, in order to determine the reliability of module products, the reliability of each of the piece parts is individually determined, then summed to determine the reliability of the integrated module product. If there are "n" significant components in the module then:

$$\begin{aligned} Fr(\text{module}) &= Fr(1) + Fr(2) + Fr(3) + \dots + Fr(n) \\ Fr(\text{module}) &= \text{Failure rate of module} \\ Fr(n) &= \text{Failure rate of the nth component} \end{aligned}$$

Failure Rates are reported in FITs (Failures in Time) or MTTF (Mean Time To Failure). The FIT rate is related to MTTF by:

$$MTTF = 1/Fr$$

NOTE: MTTF is frequently used interchangeably with MTBF.

The calculated failure rate for this module/assembly is:

<b><u>Module Device:</u></b>	<b><u>Quantity:</u></b>	<b><u>MTTF (Yrs):</u></b>	<b><u>FITs:</u></b>
<b>DS1961</b>	<b>1</b>	<b>18096</b>	<b>6.3</b>
<b>Totals:</b>		<b>18096</b>	<b>6.3</b>

The parameters used to calculate the module failure rate are as follows:

**Cf: 60%**      **Ea: 0.7**      **B: 0**      **Tu: 25 °C**      **Vu: 5.5 Volts**

The reliability data follows. At the start of this data is the module assembly information. This is a description of the module. The next section is the detailed reliability data for each stress found in the qualification / monitor. If there are additional processes or assemblies used as part of this report, a description of each will follow which includes the respective reliability data for that process/ assembly. The reliability data section includes the latest data available. Some of this data may be generic with other packages or products.

\* Some proprietary products may be excepted from this requirement.

**Assembly Information:**

Assembly Site: Fastech  
 Pin Count: 2  
 Package Type: iButton F50  
 Body Size: 16.25mm  
 Glob Top: FP4323, Dexter Hysol  
 Lead Frame: PCB; FR4  
 Lead Finsh: Stainless Steel  
 Die Attach: Underfill FP4527, Dexter Hysol  
 Flammability: UL 94-V0  
 Date Code Range: 0230 to 0303

**ELECTRICAL CHARACTERIZATION**

DESCRIPTION	DATE CODE	CONDITION	READPOINT	QUANTITY	FAILS
ESD SENSITIVITY	0230	IEC 1000-4-2 CONTACT 2000 VOLTS	10 PUL'S	3	0
ESD SENSITIVITY	0230	IEC 1000-4-2 CONTACT 4000 VOLTS	10 PUL'S	3	0
ESD SENSITIVITY	0230	IEC 1000-4-2 CONTACT 8000 VOLTS	10 PUL'S	3	0
ESD SENSITIVITY	0230	IEC 1000-4-2 AIR 8000 VOLTS	10 PUL'S	3	0
ESD SENSITIVITY	0230	IEC 1000-4-2 AIR 10000 VOLTS	10 PUL'S	3	0
ESD SENSITIVITY	0230	IEC 1000-4-2 AIR 15000 VOLTS	10 PUL'S	3	3
ESD SENSITIVITY	0230	IEC 1000-4-2 AIR 20000 VOLTS	10 PUL'S	3	3
<b>Total:</b>					<b>6</b>

**OPERATING LIFE**

DESCRIPTION	DATE CODE	CONDITION	READPOINT	QUANTITY	FAILS
HIGH VOLTAGE LIFE	0230	125C, 6.0 VOLTS	1000 HRS	77	0
HIGH VOLTAGE LIFE	0303	125C, 6.0 VOLTS	1000 HRS	77	0
<b>Total:</b>					<b>0</b>

**TEMPERATURE CYCLE**

DESCRIPTION	DATE CODE	CONDITION	READPOINT	QUANTITY	FAILS
TEMP CYCLE	0240	-55C TO 125C	1000 CYS	77	0
TEMP CYCLE	0240	-55C TO 125C	1000 CYS	77	0
<b>Total:</b>					<b>0</b>

**W/E ENDURANCE AND DATA RET'N**

DESCRIPTION	DATE CODE	CONDITION	READPOINT	QUANTITY	FAILS
-------------	-----------	-----------	-----------	----------	-------

WRITE CYCLE STRESS	0230	85 C , 5.25 VOLTS	50	KCYS	77	1
STORAGE LIFE		150C	1000	HRS	66	0
WRITE CYCLE STRESS	0303	85 C , 5.25 VOLTS	20	KCYS	77	0
STORAGE LIFE		150C	1000	HRS	77	0
WRITE CYCLE STRESS	0303	85 C , 5.25 VOLTS	50	KCYS	77	0
STORAGE LIFE		150C	1000	HRS	77	2
WRITE CYCLE STRESS	0303	25 C, 5.25 VOLTS	50	KCYS	77	0
STORAGE LIFE		150C	1000	HRS	77	0
WRITE CYCLE STRESS	0303	25 C, 5.25 VOLTS	40	KCYS	77	0
STORAGE LIFE		150C	1000	HRS	77	1
				<b>Total:</b>		<b>4</b>

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А