DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO



ABDFTCXO/ABDFVCTCXO SERIES

9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

FEATURES

- Phase and frequency coherent dual output
- F0 and F0÷2 with integrated precision fanout buffers
- Meets ±280ppb Stratum-III stability requirements
- Excellent ±1ppm aging with ±4.6ppm guaranteed lifetime accuracy
- 5 to 52MHz standard and custom frequencies available
- TCXO or VCTCXO functionality available
- ±5ppm minimum pull with 0.5% typ linearity (VCTCXO only)
- LVCMOS outputs
- 10pin package
- -40°C to 85°C operation

APPLICATIONS

- Communications and Networking
- Synchronization
- PLL with Holdover
- Geolocation, RTLS, GPS
- Synchronous Ethernet
- IEEE1588
- Instrumentation, test and measurement
- Femtocells, picocells (BTS)
- Oil and gas exploration

TYPICAL OPERATING CIRCUIT

DIGITAL FPGA BASED PLL WITH PRECISION STRATUM-III HOLDOVER



OPTIONS AND PART IDENTIFICATION

ABDFTCXO OR ABDFVCTCXO - ☐ MHz - ☐ - ☐ - ☐

OUTPUT 1 (F_0) IN MHZ
Please specify the frequency Output 1 (F0) in MHz e.g. 16.384MHz

***F0 > 40MHz, available in Q4-2017**

OPERATING TEMP. RANGE
E: -20°C to +70°C
L: -40°C to +85°C

FREQ. STABILITY
1: ±100ppb*
2: ±280ppb

***Available Q4-2017**

PACKAGING
Blank: Bulk**
T5: 500 pcs/reel
T2: 250 pcs/reel
CT: Cut Tape***

****Bulk devices are not in MSL-3 compliant packaging**

*****Cut Tape devices available in 25pc, 50pc, & 100pc quantities (MSL-3 compliant)**

ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS ISO9001-2008 CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO

ABDFTCXO/ABDFVCTCXO SERIES



9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

STANDARD SPECIFICATIONS

PARAMETERS	RATING
Storage Temperature Range (Ts)	-55°C to +125°C
Supply Voltage (Vdd)	-0.5V to 6V
Control Voltage (Vc)	0V to 3V
ESD, HBM/CDM/MM	4kV/2kV/200V

PARAMETERS	MINIMUM	TYPICAL	MAXIMUM	UNITS	NOTES
Frequency Range	5.000		52.000	MHz	
Standard Frequencies [Output 1(F_0)/Output 2 (F_0/2)]	10.000/5.000 16.384/8.192 20.000/10.000 26.000/13.000 38.400/19.200 50.000/25.000	12.800/6.400 19.200/9.600 24.576/12.288 30.000/15.000 38.880/19.440 52.000/26.000	16.000/8.000 19.440/9.720 25.000/12.500 30.720/15.360 40.000/20.000	MHz	Custom frequencies available upon request. Please contact Abracon. *Note 1
Supply Voltage (Vdd)	+3.135	+3.3	+3.465	V	
Supply Current (Icc) (into 15pF load)			20	mA	Carrier dependent
Initial Frequency Tolerance @ +25°C	-0.50		+0.50	ppm	As received, Relative to carrier
Operating Temperature	-20		+70	°C	Option “E”
	-40		+85		Option “L”
Frequency Stability vs. Operating Temperature (ref. to +25°C)	-100		+100	ppb	Option “1” *Note 2
	-280		+280	ppb	Option “2”
Frequency Stability vs. Vdd Change	-100		+100	ppb	Vdd ±5%
Frequency Stability vs. Load Change	-200		+200	ppb	Load ±5%
Aging (1st year @ +25°C)	-1.0		+1.0	ppm	
Aging (10 years @ +25°C)	-3.0		+3.0	ppm	
All-inclusive frequency stability over 10 years product life (Stratum-III Compliant)	-4.60		+4.60	ppm	
LVCMOS Output (Square wave)					
V_{OH}	2.4			V	Load = 15pF
V_{OL}			0.4	V	Load = 15pF
Load			15	pF	
Duty Cycle	45		55	%	@ (V_{OH} - V_{OL})/2
Rise/Fall Time			6	ns	Load = 15pF
Control Port (Applicable for VCTCXO only)					
Center Control Voltage (Vc)		+1.50		V	
Control Voltage Range (Vc)	+0.50		+2.50	V	
Frequency Pull	±5.00		< ±13.00	ppm	Vc = 1.5V±1.0V
Tuning Slope		Positive			
Linearity Error		< 0.5	10	%	

***Note 1: F0 > 40MHz, available in Q4-2017 | *Note 2: Available Q4-2017**

ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS ISO9001-2008 CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO

ABDFTCXO/ABDFVCTCXO SERIES



9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

STANDARD SPECIFICATIONS (CONT.)

PARAMETERS	MINIMUM	TYPICAL	MAXIMUM	UNITS	NOTES
RMS Jitter (12kHz ~ 20MHz BW) @ 25°C					
16.384 MHz Carrier		650	1,300	fs	
20.000 MHz Carrier		525	1,300	fs	
10.000 MHz Carrier		650	1,300	fs	
26.000 MHz Carrier		450	1,300	fs	
13.000 MHz Carrier		775	1,300	fs	
40.000 MHz Carrier		325	1,300	fs	
20.000 MHz Carrier		450	1,300	fs	
Phase Noise					
F_0 @ 20.000 MHz		-85		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-135			Offset @1kHz
		-145			Offset @10kHz
		-150			Offset @100kHz
		-155			Offset @ 5MHz
F_0/2 @ 10.000 MHz		-90		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-135			Offset @1kHz
		-145			Offset @10kHz
		-150			Offset @100kHz
		-155			Offset @ 5MHz
F_0 @ 26.000 MHz		-85		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-135			Offset @1kHz
		-145			Offset @10kHz
		-150			Offset @100kHz
		-150			Offset @ 5MHz
F_0/2 @ 13.000 MHz		-75		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-135			Offset @1kHz
		-150			Offset @10kHz
		-150			Offset @100kHz
		-155			Offset @ 5MHz
F_0 @ 40.000 MHz		-80		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-125			Offset @1kHz
		-140			Offset @10kHz
		-150			Offset @100kHz
		-150			Offset @ 5MHz
F_0/2 @ 20.000 MHz		-80		dBc/Hz	Offset @10Hz
		-100			Offset @100Hz
		-135			Offset @1kHz
		-140			Offset @10kHz
		-145			Offset @100kHz
		-155			Offset @ 5MHz

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO



ABDFTCXO/ABDFVCTCXO SERIES

9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

TYPICAL PHASE NOISE & JITTER CHARACTERISTICS

16.384MHz
[Output 1 (F0)]



20.000MHz / 10.000MHz
[Output 1 (F0) / Output 2 (F0/2)]

20.000MHz



10.000MHz



ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS
ISO9001-2008
CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO



ABDFTCXO/ABDFVCTCXO SERIES

9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

TYPICAL PHASE NOISE & JITTER CHARACTERISTICS

26.000MHz / 13.000MHz
[Output 1 (F0) / Output 2 (F0/2)]

26.000MHz



13.000MHz



40.000MHz / 20.000MHz
[Output 1 (F0) / Output 2 (F0/2)]

40.000MHz



20.000MHz



Frequency	16.384MHz	20MHz	10MHz	26MHz	13MHz	40MHz	20MHz
Typical rms Phase Jitter (12kHz to 20MHz BW)	640 fs	498 fs	643 fs	429 fs	752 fs	311 fs	432 fs

ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS
ISO9001-2008
CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO

ABDFTCXO/ABDFVCTCXO SERIES



9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

FREQUENCY STABILITY VS. TEMPERATURE



FREQUENCY PULL VS. CONTROL VOLTAGE (VCTCXO MODE)



AGING PROFILE (ACCELERATED AGING @ +85°C)



ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS
ISO9001-2008
CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO

ABDFTCXO/ABDFVCTCXO SERIES



9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

TYPICAL PHASE NOISE & JITTER CHARACTERISTICS



RECOMMENDED LAND PATTERN



Pin	Function
1	NC (for TCXO) Vc (for VCTCXO)
2	GND
3	Output #1 (F0)
4	Vdd
5	Output #2 (F0/2)
*	For factory test only

Dimensions: mm

REFLOW PROFILE



Zone	Description	Temperature	Time
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 200°C	60 ~ 120 sec.
2	Reflow	T_L 220°C	60 ~ 150 sec.
3	Peak Heat	T_P 260°C	25 sec. MAX

ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS
ISO9001-2008
CERTIFIED

DUAL OUTPUT STRATUM-III SMD TCXO & VCTCXO



ABDFTCXO/ABDFVCTCXO SERIES

9.0 x 14.0 x 3.0mm

RoHS/RoHS II Compliant

ESD SENSITIVE

MSL = 3

PACKAGING

T5: 500 pcs/reel
T2: 250 pcs/reel
MSL - 3 compliant packaging applies to MOQ=25 units (cut tape) & T5 and T2 options
MSL - 3 compliant packaging DOES NOT apply to bulk quantities



W	A0	B0	K0	P	
24.0±0.3	9.6±0.10	14.5±0.10	3.9±0.10	16.0±0.1	
F	**E**	**D**	**P0**	**P2**	**T**
13.25±0.1	1.75±0.1	1.5+0.1	4.0±0.1	2.0±0.1	0.3±0.05







Detail 2:1

W	A	N	T	E	F	D
24.5±0.4	330±0.5	100±0.3	1.8±0.2	2.1±0.3	10.75±0.3	13.5+0.5/-0.2

Dimensions: mm

ABRACON LLC
The Power of Linking Together

5101 Hidden Creek Ln Spicewood TX 78669
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 05.19.2017

ABRACON IS
ISO9001-2008
CERTIFIED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ABRACON:

ABDFTCXO-26.000MHz-L-2-CT ABDFTCXO-16.384MHz-E-2-T5 ABDFTCXO-20.000MHz-E-2-T2 ABDFTCXO-25.000MHz-L-2-T5 ABDFTCXO-30.720MHz-E-2-T2 ABDFVCTCXO-50.000MHz-L-2-T2 ABDFVCTCXO-26.000MHz-L-2-T5 ABDFVCTCXO-52.000MHz-E-2-CT ABDFTCXO-19.200MHz-L-2-T5 ABDFVCTCXO-16.000MHz-L-2-T2 ABDFVCTCXO-26.000MHz-E-2-T2 ABDFTCXO-40.000MHz-L-2-CT ABDFTCXO-52.000MHz-E-2-T5 ABDFVCTCXO-24.576MHz-E-2-T2 ABDFTCXO-19.440MHz-L-2-CT ABDFVCTCXO-16.000MHz-L-2-T5 ABDFVCTCXO-38.400MHz-L-2-T2 ABDFTCXO-10.000MHz-E-2-T2 ABDFVCTCXO-52.000MHz-E-2-T2 ABDFVCTCXO-10.000MHz-L-2-CT ABDFVCTCXO-50.000MHz-E-2-T2 ABDFTCXO-19.200MHz-E-2-T2 ABDFTCXO-38.880MHz-E-2-T2 ABDFTCXO-10.000MHz-E-2-T5 ABDFTCXO-38.880MHz-L-2-CT ABDFTCXO-50.000MHz-L-2-T2 ABDFTCXO-19.200MHz-L-2-CT ABDFTCXO-50.000MHz-E-2-CT ABDFVCTCXO-16.000MHz-E-2-T5 ABDFVCTCXO-16.384MHz-E-2-T2 ABDFTCXO-30.000MHz-L-2-T2 ABDFTCXO-26.000MHz-L-2-T5 ABDFVCTCXO-38.400MHz-E-2-T5 ABDFTCXO-30.000MHz-L-2-T5 ABDFVCTCXO-40.000MHz-E-2-CT ABDFTCXO-19.200MHz-L-2-T2 ABDFVCTCXO-25.000MHz-L-2-T2 ABDFVCTCXO-16.000MHz-E-2-CT ABDFTCXO-12.800MHz-L-2-T5 ABDFVCTCXO-16.384MHz-E-2-CT ABDFVCTCXO-52.000MHz-L-2-T5 ABDFVCTCXO-20.000MHz-L-2-T5 ABDFTCXO-38.880MHz-E-2-CT ABDFTCXO-24.576MHz-E-2-T5 ABDFVCTCXO-25.000MHz-L-2-CT ABDFTCXO-20.000MHz-E-2-CT ABDFTCXO-25.000MHz-L-2-T2 ABDFTCXO-19.200MHz-E-2-T5 ABDFVCTCXO-40.000MHz-L-2-T5 ABDFTCXO-19.440MHz-L-2-T2 ABDFTCXO-30.720MHz-L-2-CT ABDFVCTCXO-10.000MHz-E-2-T2 ABDFTCXO-19.440MHz-E-2-T5 ABDFVCTCXO-24.576MHz-L-2-T5 ABDFTCXO-10.000MHz-L-2-T2 ABDFVCTCXO-30.720MHz-E-2-T2 ABDFTCXO-25.000MHz-E-2-T5 ABDFTCXO-40.000MHz-E-2-CT ABDFVCTCXO-12.800MHz-E-2-T5 ABDFVCTCXO-24.576MHz-L-2-T2 ABDFVCTCXO-50.000MHz-E-2-T5 ABDFTCXO-38.400MHz-E-2-CT ABDFVCTCXO-40.000MHz-E-2-T2 ABDFTCXO-26.000MHz-L-2-T2 ABDFVCTCXO-26.000MHz-E-2-T5 ABDFVCTCXO-50.000MHz-E-2-CT ABDFVCTCXO-38.880MHz-L-2-T5 ABDFVCTCXO-30.000MHz-L-2-T5 ABDFTCXO-40.000MHz-L-2-T5 ABDFVCTCXO-38.400MHz-E-2-T2 ABDFVCTCXO-30.000MHz-L-2-T2 ABDFVCTCXO-12.800MHz-L-2-T2 ABDFTCXO-19.440MHz-E-2-T2 ABDFTCXO-24.576MHz-E-2-T2 ABDFTCXO-52.000MHz-L-2-T5 ABDFTCXO-52.000MHz-E-2-CT ABDFTCXO-30.720MHz-E-2-T5 ABDFTCXO-12.800MHz-E-2-T2 ABDFTCXO-19.440MHz-L-2-T5 ABDFTCXO-38.400MHz-E-2-T5 ABDFVCTCXO-16.384MHz-L-2-T2 ABDFVCTCXO-16.000MHz-L-2-CT ABDFVCTCXO-40.000MHz-L-2-T2 ABDFVCTCXO-52.000MHz-L-2-T2 ABDFTCXO-12.800MHz-E-2-T5 ABDFTCXO-52.000MHz-E-2-T2 ABDFTCXO-24.576MHz-L-2-CT ABDFTCXO-38.880MHz-E-2-T5 ABDFVCTCXO-19.440MHz-E-2-CT ABDFVCTCXO-19.440MHz-L-2-T2 ABDFVCTCXO-10.000MHz-E-2-CT ABDFVCTCXO-38.400MHz-L-2-T5 ABDFVCTCXO-26.000MHz-E-2-CT ABDFVCTCXO-10.000MHz-L-2-T2 ABDFVCTCXO-19.200MHz-L-2-CT ABDFTCXO-30.720MHz-E-2-CT

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А