

# MPC8640 and MPC8640D Integrated Host Processor Hardware Specifications Addendum for the MC8640xTxxyyyyaC Series

This document describes part-number-specific changes to recommended operating conditions and revised electrical specifications, as applicable, from those described in the general *MPC8640 and MPC8640D Integrated Host Processor Hardware Specifications* (Document No. MPC8640DEC).

Specifications provided in this document supersede those in the *MPC8640 and MPC8640D Integrated Host Processor Hardware Specifications*, Rev. 1 or later, for the part numbers listed in [Table A](#) only. Specifications not addressed herein are unchanged.

Because this document is frequently updated, refer to the website listed on the back page of this document or contact your Freescale sales office for the latest version.

Note that headings and table numbers in this document are not consecutively numbered. They are intended to correspond to the heading or table affected in the general hardware specification.

## *Freescale Part Numbers Affected:*

MC8640DTHX1250HC  
 MC8640DTHX1000HC  
 MC8640DTHX1067NC  
 MC8640DTVU1250HC  
 MC8640DTVU1000HC  
 MC8640DTVU1067NC  
 MC8640THX1250HC  
 MC8640THX1000HC  
 MC8640THX1067NC  
 MC8640TVU1250HC  
 MC8640TVU1000HC  
 MC8640TVU1067NC

Part numbers addressed in this document are listed in [Table A](#).

**Table A. Part Numbers Addressed by This Data Sheet**

| Freescale<br>Part Number | Operating Conditions      |                      |                        | Significant Differences from<br>Hardware Specification        |
|--------------------------|---------------------------|----------------------|------------------------|---------------------------------------------------------------|
|                          | CPU<br>Frequency<br>(MHz) | V <sub>DD-Core</sub> | T <sub>j</sub><br>(°C) |                                                               |
| MC8640DTHX1250HC         | 1250                      | 1.05 V ± 50 mV       | -40 to 105             | Modified JTAG AC timing; extended junction temperature range. |
| MC8640DTHX1000HC         | 1000                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640DTHX1067NC         | 1067                      | 0.95 V ± 50 mV       |                        |                                                               |
| MC8640DTVU1250HC         | 1250                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640DTVU1000HC         | 1000                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640DTVU1067NC         | 1067                      | 0.95 V ± 50 mV       |                        |                                                               |
| MC8640THX1250HC          | 1250                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640THX1000HC          | 1000                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640THX1067NC          | 1067                      | 0.95 V ± 50 mV       |                        |                                                               |
| MC8640TVU1250HC          | 1250                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640TVU1000HC          | 1000                      | 1.05 V ± 50 mV       |                        |                                                               |
| MC8640TVU1067NC          | 1067                      | 0.95 V ± 50 mV       |                        |                                                               |

## 2 General Parameters

This section summarizes changes to the general parameters of the MPC8640 described in the *MPC8640 and MPC8640D Integrated Host Processor Hardware Specifications*.

- Modified JTAG AC timing
  - t<sub>JTDV<sub>KH</sub></sub> (min) = 15 ns
- Extended junction temperature range
  - T<sub>j</sub> = -40 to 105 °C

### 2.1 Overall DC Electrical Characteristics

#### 2.1.2 Recommended Operating Conditions

[Table 2](#) provides the recommended operating conditions for the MPC8640 part numbers described herein.

**Table 2. Recommended Operating Conditions**

| Characteristic             | Symbol         | Recommended Value | Unit | Notes |
|----------------------------|----------------|-------------------|------|-------|
| Junction temperature range | T <sub>j</sub> | -40 to 105        | °C   | —     |

## 11.2 JTAG AC Electrical Specifications

Table 43 provides the JTAG AC electrical specifications for the MPC8640 part numbers described herein.

**Table 43. JTAG AC Timing Specifications (Independent of SYSCLK) <sup>1</sup>**

At recommended operating conditions (see Table 3).

| Parameter                      | Symbol <sup>2</sup>          | Min     | Max    | Unit | Notes |
|--------------------------------|------------------------------|---------|--------|------|-------|
| Input setup times:             |                              |         |        | ns   |       |
| Boundary-scan data<br>TMS, TDI | $t_{JTDVKH}$<br>$t_{JTIVKH}$ | 15<br>0 | —<br>— |      | 4     |

**Notes:**

- All outputs are measured from the midpoint voltage of the falling/rising edge of  $t_{TCLK}$  to the midpoint of the signal in question. The output timings are measured at the pins. All output timings assume a purely resistive 50-Ω load (see Figure 32). Time-of-flight delays must be added for trace lengths, vias, and connectors in the system.
- The symbols used for timing specifications herein follow the pattern of  $t_{(\text{first two letters of functional block})(\text{signal})(\text{state})}$  (reference)(state) for inputs and  $t_{(\text{first two letters of functional block})(\text{reference})(\text{state})(\text{signal})(\text{state})}$  for outputs. For example,  $t_{JTDVKH}$  symbolizes JTAG device timing (JT) with respect to the time data input signals (D) reaching the valid state (V) relative to the  $t_{JTg}$  clock reference (K) going to the high (H) state or setup time. Also,  $t_{JTDXKH}$  symbolizes JTAG timing (JT) with respect to the time data input signals (D) went invalid (X) relative to the  $t_{JTg}$  clock reference (K) going to the high (H) state. Note that, in general, the clock reference symbol representation is based on three letters representing the clock of a particular functional. For rise and fall times, the latter convention is used with the appropriate letter: R (rise) or F (fall).
- Non-JTAG signal input timing with respect to  $t_{TCLK}$ .

## 21 Ordering Information

### 21.1 Part Numbers Addressed by This Specification

Table 73 provides the ordering information for the MPC8640 parts described in this document.

**Table 73. Part Numbering Nomenclature**

| uu              | nnnn            | D                                    | w                    | xx                                                              | yyyy                                        | a                                       | z                                                                                                               |
|-----------------|-----------------|--------------------------------------|----------------------|-----------------------------------------------------------------|---------------------------------------------|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Product Code    | Part Identifier | Core Count                           | Temp                 | Package <sup>1</sup>                                            | Core Processor Frequency <sup>2</sup> (MHz) | DDR speed (MHz)                         | Product Revision Level                                                                                          |
| MC <sup>5</sup> | 8640            | Blank = Single Core<br>D = Dual Core | T:<br>–40°C to 105°C | HX = High-lead HCTE FC-CBGA<br>VU = RoHS lead-free HCTE FC-CBGA | 1000, 1067, 1250                            | N = 533 MHz <sup>4</sup><br>H = 500 MHz | Revision C = 2.1<br>System Version Register Value for Rev C:<br>0x8090_0021 - MPC8640<br>0x8090_0121 - MPC8640D |

**Notes:**

1. See Section 16, “Package,” for more information on available package types.
2. Processor core frequencies supported by parts addressed by this specification only. Not all parts described in this specification support all core frequencies. Additionally, parts addressed by part number specifications may support other maximum core frequencies.
3. The P prefix in a Freescale part number designates a “Pilot Production Prototype” as defined by Freescale SOP 3-13. These parts have only preliminary reliability and characterization data. Before pilot production prototypes may be shipped, written authorization from the customer must be on file in the applicable sales office acknowledging the qualification status and the fact that product changes may still occur while shipping pilot production prototypes.
4. Part Number MC8640xxx1067NC is our low  $V_{DD\_Core}$  device.  $V_{DD\_Core} = 0.95\text{ V}$  and  $V_{DD\_PLAT} = 1.05\text{ V}$ .
5. MC - Qualified production

## Document Revision History

Table B provides a revision history for this hardware specification addendum.

**Table B. Document Revision History**

| Rev. Number | Date    | Substantive Change(s) |
|-------------|---------|-----------------------|
| 0           | 12/2008 | Initial release.      |

**THIS PAGE INTENTIONALLY LEFT BLANK**



**THIS PAGE INTENTIONALLY LEFT BLANK**



## **How to Reach Us:**

### **Home Page:**

[www.freescale.com](http://www.freescale.com)

### **Web Support:**

<http://www.freescale.com/support>

### **USA/Europe or Locations Not Listed:**

Freescale Semiconductor, Inc.  
Technical Information Center, EL516  
2100 East Elliot Road  
Tempe, Arizona 85284  
1-800-521-6274 or  
+1-480-768-2130  
[www.freescale.com/support](http://www.freescale.com/support)

### **Europe, Middle East, and Africa:**

Freescale Halbleiter Deutschland GmbH  
Technical Information Center  
Schatzbogen 7  
81829 Muenchen, Germany  
+44 1296 380 456 (English)  
+46 8 52200080 (English)  
+49 89 92103 559 (German)  
+33 1 69 35 48 48 (French)  
[www.freescale.com/support](http://www.freescale.com/support)

### **Japan:**

Freescale Semiconductor Japan Ltd.  
Headquarters  
ARCO Tower 15F  
1-8-1, Shimo-Meguro, Meguro-ku  
Tokyo 153-0064  
Japan  
0120 191014 or  
+81 3 5437 9125  
[support.japan@freescale.com](mailto:support.japan@freescale.com)

### **Asia/Pacific:**

Freescale Semiconductor China Ltd.  
Exchange Building 23F  
No. 118 Jianguo Road  
Chaoyang District  
Beijing 100022  
China  
+86 10 5879 8000  
[support.asia@freescale.com](mailto:support.asia@freescale.com)

### **For Literature Requests Only:**

Freescale Semiconductor  
Literature Distribution Center  
P.O. Box 5405  
Denver, Colorado 80217  
1-800 441-2447 or  
+1-303-675-2140  
Fax: +1-303-675-2150  
[LDCForFreescaleSemiconductor@hibbertgroup.com](mailto:LDCForFreescaleSemiconductor@hibbertgroup.com)

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Freescale and the Freescale logo are trademarks or registered trademarks of Freescale Semiconductor, Inc. in the U.S. and other countries. All other product or service names are the property of their respective owners. The Power Architecture and Power.org word marks and the Power and Power.org logos and related marks are trademarks and service marks licensed by Power.org.

© Freescale Semiconductor, Inc., 2008. All rights reserved.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А