



**RoHS HTxxx & HTMxxx & STxxx Series**



**Schematic Symbol**



**Applications**

DIACs are used to trigger Triacs and SCRs in phase control circuits for lamp dimming, universal motor speed control, and heat control. They are used also for triggering transistors in solid state ballast lighting controls.

**Description**

The HTM, HT, and ST series of bilateral trigger DIACs offer a range of voltage characteristics from 27V to 70V. A DIAC semiconductor is a full-wave or bidirectional Thyristor. It is triggered from a blocking state to a conduction state for either polarity of applied voltage whenever the amplitude of applied voltage exceeds the breakover voltage of the DIAC.

**Features & Benefits**

- **RoHS** compliant
  - Bilateral triggering device
  - Glass-passivated junctions
  - Wide voltage range selections
  - Long-term reliability
  - Parameter stability
  - Reliable barrier against junction contamination
- ST Series:**
- Epoxy SM package (DO-214)
  - High-temperature, solder bonded die attachment
- HTM/HT Series:**
- MINIMELF/DO-35 trigger package

**Absolute Maximum Ratings**

| Symbol      | Parameter                      | Test Conditions                                                       | Min | Max                        | Unit             |
|-------------|--------------------------------|-----------------------------------------------------------------------|-----|----------------------------|------------------|
| $I_{TRM}$   | Pulse On-State Current         | 120PPS, $T_A \leq 40^\circ\text{C}$<br>pulse width = 10 $\mu\text{s}$ |     | 2<br>1.5 <sup>(*)</sup>    | A                |
| $T_S$       | Storage Temperature Range      |                                                                       | -40 | +125                       | $^\circ\text{C}$ |
| $T_J$       | Operating Junction Temperature |                                                                       | -40 | +125                       | $^\circ\text{C}$ |
| $P_{D(AV)}$ | Device Power Dissipation       | $T_A = -40^\circ\text{C}$ to $+40^\circ\text{C}$                      |     | See Product Selector Table | mW               |

(\*)Only Applies to HT-60

Notes:

1. Service Dissipation (at  $T_A = -40^\circ\text{C}$  to  $+40^\circ\text{C}$ ): 250mW for DO-35 and MINIMELF/SOD-80 and 300mW for DO214
2. Above  $+40^\circ\text{C}$ , Derate: 3.6mW/ $^\circ\text{C}$  for DO-35 and MINIMELF/SOD-80 and 3mW/ $^\circ\text{C}$  for DO214

**Electrical Characteristics ( $T_J = 25^\circ\text{C}$ , unless otherwise specified)**

| Symbol          | Description                                                     | Test Conditions                      | Min                        | Max                        | Unit          |
|-----------------|-----------------------------------------------------------------|--------------------------------------|----------------------------|----------------------------|---------------|
| $V_{BO}$        | Breakover/Trigger Voltage                                       | 50/60Hz Sine Wave                    | See Product Selector Table | See Product Selector Table | V             |
| $\Delta V_{BO}$ | Breakover Voltage Symmetry                                      | $+V_{BO}$ to $-V_{BO}$               |                            | 2 <sup>(Note 1)</sup>      | V             |
| $V_{BB}$        | $\Delta$ Breakback Voltage <sup>(Note 4)</sup>                  | $V_{BO}$ to $V_{10mA}$               | 5                          |                            | V             |
|                 |                                                                 | $V_{BO}$ to $V_{6mA}$ <sup>(*)</sup> | 15                         |                            | V             |
| $V_{BB(DYN)}$   | Dynamic $\Delta$ Breakback Voltage <sup>(Notes 2 &amp; 3)</sup> | 120 PPS                              | 10                         |                            | V             |
| $I_{BO}$        | Breakover Current                                               | 50/60Hz Sine Wave                    |                            | 15                         | $\mu\text{A}$ |

(\*) Only Applies to HT-60

Electrical Characteristic Notes:

1. Breakover voltage symmetry as close as 1V is available from the factory for these products.

2. See Figure 4 and Figure 5 for test circuit and waveforms.

3. Typical switching time is 900 nano-seconds measured at  $I_{PK}$  (Figure 4) across a 20  $\Omega$  resistor (Figure 5). Switching time is defined as rise time of  $I_{PK}$  between the 10% to 90% points

4. See V-I Characteristics

Static Characteristics - Not Applicable

**Product Selector**

| Part Number   | Package Availability |        |        | $V_{BO}$ |     |
|---------------|----------------------|--------|--------|----------|-----|
|               | MINIMELF             | DO-35  | DO-214 | MIN      | MAX |
| XX-32         | —                    | HT-32  | ST-32  | 27V      | 37V |
| XX-32A/ 5761  | —                    | HT-32A | —      | 28V      | 36V |
| XX-32B/ 5761A | HTM-32B              | HT-32B | ST-32B | 30V      | 34V |
| XX-34B        | —                    | HT-34B | ST-34B | 32V      | 36V |
| XX-35         | —                    | HT-35  | ST-35  | 30V      | 40V |
| XX-36A/ 5762  | —                    | HT-36A | ST-36A | 32V      | 40V |
| XX-36B        | —                    | HT-36B | ST-36B | 34V      | 38V |
| XX-40         | —                    | HT-40  | ST-40  | 35V      | 45V |
| XX-60         | —                    | HT-60  | —      | 56V      | 70V |


"XX" = HTM for MINIMELF  
HT for DO-35  
ST for DO-214

**Thermal Resistances**


| Symbol            | Description         | Test Conditions                |          | Value | Unit |
|-------------------|---------------------|--------------------------------|----------|-------|------|
| $R_{\theta(J-L)}$ | Junction to Lead    | Maximum Lead Temperature: 85°C | DO-35    | 100   | °C/W |
|                   |                     | Maximum Lead Temperature: 90°C | DO-214   | 65*   | °C/W |
|                   |                     | Maximum Lead Temperature: 87°C | MINIMELF | 75    | °C/W |
| $R_{\theta(J-A)}$ | Junction to Ambient | Free-Air                       | DO-35    | 278   | °C/W |

\* Mounted on 1 cm<sup>2</sup> copper foil surface; two-ounce copper foil


**Figure 1: V-I Characteristics**




**Figure 2: Typical DIAC/Triac Full-wave Phase Control Circuit**




**Figure 3: Repetitive Peak On-state Current vs. Pulse Duration**




**Figure 4: Normalized  $V_{BO}$  Change vs. Junction Temperature**



**Figure 5: Test Circuit Waveforms (Refer to Figure 5)**




**Figure 6: Circuit Used to Measure DIAC Characteristics (Refer to Figure 4)**




\* Adjust for one firing in each half cycle. D.U.T. = Diac

**Figure 7: Peak Output Current vs. Triggering Capacitance (Per Figure 5 with  $R_L$  of 20  $\Omega$ )**



## Soldering Parameters

| Reflow Condition                                       |                                    | Pb – Free assembly |
|--------------------------------------------------------|------------------------------------|--------------------|
| Pre Heat                                               | - Temperature Min ( $T_{s(min)}$ ) | 150°C              |
|                                                        | - Temperature Max ( $T_{s(max)}$ ) | 200°C              |
|                                                        | - Time (min to max) ( $t_s$ )      | 60 – 190 secs      |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                    | 5°C/second max     |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                    | 5°C/second max     |
| Reflow                                                 | - Temperature ( $T_L$ ) (Liquidus) | 217°C              |
|                                                        | - Time (min to max) ( $t_s$ )      | 60 – 150 seconds   |
| Peak Temperature ( $T_p$ )                             |                                    | 260 °C             |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds    |
| Ramp-down Rate                                         |                                    | 5°C/second max     |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes Max.     |
| Do not exceed                                          |                                    | 280°C              |



### Physical Specifications

|                        |                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Terminal Finish</b> | 100% Matte-Tin Plated/ Pb-Free Solder Dipped                                                              |
| <b>Body Material</b>   | DO-214: UL recognized epoxy meeting flammability classification 94V-0.<br>DO-35/MINIMELF: Glass case body |
| <b>Lead Material</b>   | DO-214: Copper Alloy<br>DO-35/MINIMELF: Copper Clad Iron                                                  |


### Design Considerations

Careful selection of the correct device for the application's operating parameters and environment will go a long way toward extending the operating life of the Thyristor. Overheating and surge currents are the main killers of DIACs. Correct mounting, soldering, and forming of the leads also help protect against component damage.

### Reliability/Environmental Tests


| Test                                     | Specifications and Conditions                                                                                                     |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>High Temperature Voltage Blocking</b> | MIL-STD-750, M-1040, Cond A Applied 80% of Rated Min $V_{BO}$ (VAC-peak) @ 125°C for 1008 hours                                   |
| <b>Temperature Cycling</b>               | MIL-STD-750, M-1051, 100 cycles; -40°C to +150°C; 15-min dwell-time                                                               |
| <b>Temperature/Humidity</b>              | EIA / JEDEC, JESD22-A101 1008 hours; 80% of Rated Min $V_{BO}$ ( $V_{DC}$ ): 85°C; 85% rel humidity                               |
| <b>High Temp Storage</b>                 | MIL-STD-750, M-1031, 1008 hours; 150°C                                                                                            |
| <b>Low-Temp Storage</b>                  | 1008 hours; -40°C                                                                                                                 |
| <b>Thermal Shock</b>                     | MIL-STD-750, M-1056 10 cycles; 0°C to 100°C; 5-min dwell time at each temperature; 10 sec (max) transfer time between temperature |
| <b>Autoclave</b>                         | EIA / JEDEC, JESD22-A102 168 hours (121°C at 2 ATMs) and 100% R/H                                                                 |
| <b>Resistance to Solder Heat</b>         | MIL-STD-750 Method 2031                                                                                                           |
| <b>Solderability</b>                     | ANSI/J-STD-002, category 3, Test A                                                                                                |
| <b>Lead Bend</b>                         | MIL-STD-750, M-2036 Cond E                                                                                                        |
| <b>Burn-in</b>                           | 1 firing per 1/2 cycle, 168 hours                                                                                                 |

### Dimensions – MINIMELF / SOD-80 (MM Package)



| Dimensions | Inches |       |       | Millimeters |      |      |
|------------|--------|-------|-------|-------------|------|------|
|            | Min    | Typ   | Max   | Min         | Typ  | Max  |
| A          | 0.125  | 0.134 | 0.142 | 3.18        | 3.40 | 3.61 |
| B          | 0.066  | 0.068 | 0.070 | 1.68        | 1.73 | 1.78 |
| C          | 0.012  | 0.018 | 0.020 | 0.30        | 0.46 | 0.51 |
| D          | —      | 0.063 | —     | —           | 1.60 | —    |

### Dimensions – DO-35 (Y Package)







| Dimension  | Inches |       | Millimeters |       |
|------------|--------|-------|-------------|-------|
|            | Min    | Max   | Min         | Max   |
| A (Note 1) | 0.060  | 0.090 | 1.530       | 2.280 |
| B (Note 2) |        | 0.015 |             | 0.381 |
| C (Note 1) | 0.135  | 0.165 | 3.430       | 4.190 |
| D          | 0.018  | 0.022 | 0.458       | 0.558 |
| E          | 1.000  |       | 25.400      |       |

**Notes:**

- Package contour optional within dimensions A and C. Slugs, if any, shall be included within this cylinder but shall not be subject to the minimum limit of Dimension A.
- Lead diameter is not controlled in this zone to allow for flash, lead finish build-up and minor irregularities other than slugs.

## Dimensions – DO-214 (S Package)



Recommended Soldering Pad Outline  
(Reference Only)


| Dimension | Inches |       | Millimeters |      |
|-----------|--------|-------|-------------|------|
|           | Min    | Max   | Min         | Max  |
| A         | 0.140  | 0.155 | 3.56        | 3.94 |
| B         | 0.205  | 0.220 | 5.21        | 5.59 |
| C         | 0.077  | 0.083 | 1.96        | 2.11 |
| D         | 0.166  | 0.180 | 4.22        | 4.57 |
| E         | 0.036  | 0.063 | 0.91        | 1.60 |
| F         | 0.066  | 0.083 | 1.67        | 2.11 |
| G         | 0.004  | 0.008 | 0.10        | 0.20 |
| H         | 0.077  | 0.086 | 1.96        | 2.18 |
| J         | 0.043  | 0.053 | 1.09        | 1.35 |
| K         | 0.008  | 0.012 | 0.20        | 0.30 |
| L         | 0.039  | 0.049 | 0.99        | 1.24 |

## Packing Options

| Part Number | Marking | Package  | Weight/ Unit | Packing Mode | Base Quantity | Quantity |      |
|-------------|---------|----------|--------------|--------------|---------------|----------|------|
|             |         |          |              |              |               | Reel     | Box  |
| HTM-xxxRP   | —       | MINIMELF | 0.040g       | Tape & Reel  | 5000          | 2500     | —    |
| HT-xxxRP    | —       | DO35     | 0.150g       | Tape & Reel  | 5000          | 5000     | —    |
| HT-xxx      | —       | DO35     | 0.150g       | Bulk         | 5000          | —        | 5000 |
| ST-xxxRP    | STxxx   | DO214    | 0.075g       | Tape & Reel  | 2500          | 2500     | —    |


## DO-214 Embossed Carrier Reel Pack (RP) Specifications

Meets all EIA-481-1 Standards




## DO-35 Reel Pack (RP) Specifications


Meets all EIA-296 Standards



## MINIMELF Reel Pack (RP) Specifications



## Part Numbering System



## Part Marking System

DO-35 & MINIMELF: No marking

DO-214:



First Line: Part Number  
Second Line: Date Code



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А