


## MAC16HCDG, MAC16HCMG, MAC16HCNG




### Description

Designed primarily for full-wave ac control applications, such as motor controls, heating controls or dimmers; or wherever full-wave, silicon gate-controlled devices are needed.


### Features

- High Commutating di/dt and High Immunity to dv/dt @ 125°C
- Uniform Gate Trigger Currents in Three Quadrants, Q1, Q2, and Q3
- Blocking Voltage to 800 Volts
- On-State Current Rating of 16 Amperes RMS at 80°C
- High Surge Current Capability – 150 Amperes
- Industry Standard TO-220 Package for Ease of Design
- Glass Passivated Junctions for Reliability and Uniformity
- These Devices are Pb-Free and are RoHS Compliant

### Pin Out



### Functional Diagram



### Additional Information



**Datasheet**



**Resources**



**Samples**

### Maximum Ratings ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                                          | Symbol                               | Value             | Unit                   |
|-----------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------------|------------------------|
| Peak Repetitive Off-State Voltage (Note 1)<br>(– 40 to $125^\circ\text{C}$ , Sine Wave, 50 to 60 Hz, Gate Open) | $V_{\text{DRM}}$<br>$V_{\text{RRM}}$ | 400<br>600<br>800 | V                      |
| On-State RMS Current (Full Cycle Sine Wave, 50 to 60 Hz, $T_C = 80^\circ\text{C}$ )                             | $I_{\text{T (RMS)}}$                 | 16                | A                      |
| Peak Non-Repetitive Surge Current<br>(One Full Cycle Sine Wave, 60 Hz, $T_C = 125^\circ\text{C}$ )              | $I_{\text{TSM}}$                     | 150               | A                      |
| Circuit Fusing Consideration ( $t = 8.3 \text{ ms}$ )                                                           | $I^2t$                               | 93                | $\text{A}^2\text{sec}$ |
| Peak Gate Power ( $T_C = +80^\circ\text{C}$ , Pulse Width = $1.0 \mu\text{s}$ )                                 | $P_{\text{GM}}$                      | 20                | W                      |
| Average Gate Power ( $t = 8.3 \text{ ms}$ , $T_C = 80^\circ\text{C}$ )                                          | $P_{\text{G(AV)}}$                   | 0.5               | W                      |
| Operating Junction Temperature Range                                                                            | $T_J$                                | –40 to +125       | $^\circ\text{C}$       |
| Storage Temperature Range                                                                                       | $T_{\text{stg}}$                     | –40 to +125       | $^\circ\text{C}$       |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

- $V_{\text{DRM}}$  and  $V_{\text{RRM}}$  for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

### Thermal Characteristics

| Rating                                                                         | Symbol                                         | Value       | Unit               |
|--------------------------------------------------------------------------------|------------------------------------------------|-------------|--------------------|
| Thermal Resistance, Junction-to-Case (AC)<br>Junction-to-Ambient               | $R_{\theta\text{JC}}$<br>$R_{\theta\text{JA}}$ | 2.2<br>62.5 | $^\circ\text{C/W}$ |
| Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds | $T_L$                                          | 260         | $^\circ\text{C}$   |

### Electrical Characteristics - OFF ( $T_J = 25^\circ\text{C}$ unless otherwise noted ; Electricals apply in both directions)

| Characteristic                                                                             | Symbol                               | Min | Typ | Max  | Unit |
|--------------------------------------------------------------------------------------------|--------------------------------------|-----|-----|------|------|
| Peak Repetitive Blocking Current<br>( $V_D = V_{\text{DRM}} = V_{\text{RRM}}$ ; Gate Open) | $I_{\text{DRM}}$<br>$I_{\text{RRM}}$ | –   | –   | 0.01 | mA   |
|                                                                                            |                                      | –   | –   | 2.0  |      |

### Electrical Characteristics - ON ( $T_J = 25^\circ\text{C}$ unless otherwise noted; Electricals apply in both directions)

| Characteristic                                                                                              | Symbol          | Min | Typ  | Max | Unit |
|-------------------------------------------------------------------------------------------------------------|-----------------|-----|------|-----|------|
| Peak On-State Voltage (Note 2) ( $I_{\text{TM}} = \pm 21 \text{ A Peak}$ )                                  | $V_{\text{TM}}$ | –   | –    | 1.6 | V    |
| Gate Trigger Current<br>(Continuous dc)<br>( $V_D = 12 \text{ V}$ , $R_L = 100 \Omega$ )                    | $I_{\text{GT}}$ | 10  | 16   | 50  | mA   |
|                                                                                                             |                 | 10  | 18   | 50  |      |
|                                                                                                             |                 | 10  | 22   | 50  |      |
| Gate Trigger Voltage<br>(Continuous dc)<br>( $V_D = 12 \text{ V}$ , $R_L = 100 \Omega$ )                    | $V_{\text{GT}}$ | 0.5 | 0.75 | 1.5 | V    |
|                                                                                                             |                 | 0.5 | 0.72 | 1.5 |      |
|                                                                                                             |                 | 0.5 | 0.82 | 1.5 |      |
| Latching Current<br>( $V_D = 24 \text{ V}$ , $I_G = 35 \text{ mA}$ )                                        | $V_{\text{GD}}$ | –   | 33   | 60  | V    |
|                                                                                                             |                 | –   | 36   | 80  |      |
|                                                                                                             |                 | –   | 33   | 50  |      |
| Holding Current ( $V_D = 12 \text{ V}_{\text{dc}}$ , Gate Open, Initiating Current = $\pm 200 \text{ mA}$ ) | $I_{\text{H}}$  | –   | 20   | 50  | mA   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

- Indicates Pulse Test: Pulse Width  $\leq 2.0 \text{ ms}$ , Duty Cycle  $\leq 2\%$ .


### Dynamic Characteristics

| Characteristic                                                                                                                                                                                                                                                                | Symbol      | Min | Typ | Max | Unit             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----|-----|-----|------------------|
| Rate of Change of Commutating Current<br>( $V_D = 400\text{ V}$ , $I_{TM} = 6.0\text{ A}$ , Commutating $dV/dt = 24\text{ V}/\mu\text{s}$ , Gate Open, $T_J = 125^\circ\text{C}$ , $f = 250\text{ Hz}$ , $C_L = 10\text{ }\mu\text{F}$ , $L_L = 40\text{ mH}$ , with Snubber) | $(di/dt)_c$ | 9.0 | –   | –   | A/ms             |
| Critical Rate of Rise of Off-State Voltage<br>( $V_D = \text{Rated } V_{DRM}$ , Exponential Waveform, Gate Open, $T_J = 125^\circ\text{C}$ )                                                                                                                                  | $dv/dt$     | 750 | –   | –   | V/ $\mu\text{s}$ |
| Repetitive Critical Rate of Rise of On-State Current<br>IPK = 50 A; PW = 40 $\mu\text{sec}$ ; $di/dt = 200\text{ mA}/\mu\text{sec}$ ; $f = 60\text{ Hz}$                                                                                                                      | $di/dt$     | –   | –   | 10  |                  |

### Voltage Current Characteristic of SCR


| Symbol    | Parameter                                 |
|-----------|-------------------------------------------|
| $V_{DRM}$ | Peak Repetitive Forward Off State Voltage |
| $I_{DRM}$ | Peak Forward Blocking Current             |
| $V_{RRM}$ | Peak Repetitive Reverse Off State Voltage |
| $I_{RRM}$ | Peak Reverse Blocking Current             |
| $V_{TM}$  | Maximum On State Voltage                  |
| $I_H$     | Holding Current                           |

### Quadrant Definitions for a Triac




All polarities are referenced to MT1.


With in-phase signals (using standard AC lines) quadrants I and III are used




**Figure 1. Typical Gate Trigger Current vs Junction Temperature**




**Figure 2. Typical Gate Trigger Voltage vs Junction Temperature**




**Figure 3. Typical Holding Current vs Junction Temperature**




**Figure 4. Typical Latching Current vs Junction Temperature**




**Figure 5. Typical RMS Current Derating**




**Figure 6. On-State Power Dissipation**




**Figure 7. Typical On-State Characteristics**




**Figure 8. Typical Thermal Response**



### Dimensions



### Part Marking System



**TO-220AB  
CASE 221A  
STYLE 12**

x = D, M or N  
Y = Year  
M = Month  
A = Assembly Site  
XX = Lot Serial Code  
G = Pb-Free Package



| Dim | Inches |       | Millimeters |       |
|-----|--------|-------|-------------|-------|
|     | Min    | Max   | Min         | Max   |
| A   | 0.590  | 0.620 | 14.99       | 15.75 |
| B   | 0.380  | 0.420 | 9.65        | 10.67 |
| C   | 0.178  | 0.188 | 4.52        | 4.78  |
| D   | 0.025  | 0.035 | 0.64        | 0.89  |
| F   | 0.142  | 0.147 | 3.61        | 3.73  |
| G   | 0.095  | 0.105 | 2.41        | 2.67  |
| H   | 0.110  | 0.130 | 2.79        | 3.30  |
| J   | 0.018  | 0.024 | 0.46        | 0.61  |
| K   | 0.540  | 0.575 | 13.72       | 14.61 |
| L   | 0.060  | 0.075 | 1.52        | 1.91  |
| N   | 0.195  | 0.205 | 4.95        | 5.21  |
| Q   | 0.105  | 0.115 | 2.67        | 2.92  |
| R   | 0.085  | 0.095 | 2.16        | 2.41  |
| S   | 0.045  | 0.060 | 1.14        | 1.52  |
| T   | 0.235  | 0.255 | 5.97        | 6.47  |
| U   | 0.000  | 0.050 | 0.00        | 1.27  |
| V   | 0.045  | —     | 1.15        | —     |
| Z   | —      | 0.080 | —           | 2.04  |

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| Pin Assignment |                 |
|----------------|-----------------|
| 1              | Main Terminal 1 |
| 2              | Main Terminal 2 |
| 3              | Gate            |
| 4              | No Connection   |

### Ordering Information

| Device    | Package             | Shipping        |
|-----------|---------------------|-----------------|
| MAC16HCDG | TO-220<br>(Pb-Free) | 500 Units/ Rail |
| MAC16HCMG |                     |                 |
| MAC16HCNG |                     |                 |

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А