

SMD Wraparound Ultra Low Value Thin Film Resistors



With extremely low resistance and high power capabilities, these ultra low value resistors are available with solderable or weldable terminations.

FEATURES

- NiCr + Ta₂O₅ resistive layer
- Pre-soldered or gold terminations
- No inductance for high frequency applications
- Alumina substrates for high power handling capability
- Resistance range: 0.1 Ω to 9.99 Ω
- TCR down to 50 ppm/°C
- Power rating: Up to 2 W at + 70 °C
- Withstand AEC-Q200 humidity test
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS*
COMPLIANT
GREEN
(5-2008)
Available

Note

* Lead (Pb)-containing terminations are not RoHS-compliant. Exemptions may apply.

| STANDARD ELECTRICAL SPECIFICATIONS | | | | | | |
|------------------------------------|------|-----------------------|---|----------------------------------|------------------|--|
| MODEL | SIZE | RESISTANCE RANGE Ω | RATED POWER <i>P</i> _{70 °C} W | LIMITING ELEMENT VOLTAGE V | TOLERANCE ± % | TEMPERATURE COEFFICIENT ± ppm/°C |
| L0603 | 0603 | 0.1 to 9.99 | 0.125 | 50 | 1, 3, 5 | 50, 100, 200, 300 |
| L0805 | 0805 | 0.1 to 9.99 | 0.2 | 50 | 1, 3, 5 | 50, 100, 200, 300 |
| L1206 | 1206 | 0.1 to 9.99 | 0.33 | 50 | 1, 3, 5 | 50, 100, 200, 300 |
| L1505 | 1505 | 0.1 to 9.99 | 0.5 | 50 | 1, 3, 5 | 50, 100, 200, 300 |
| L2010 | 2010 | 0.1 to 9.99 | 1.0 | 50 | 1, 3, 5 | 50, 100, 200, 300 |
| L2512 | 2512 | 0.1 to 9.99 | 2.0 ⁽¹⁾ | 50 | 1, 3, 5 | 50, 100, 200, 300 |

Note

⁽¹⁾ With special assembly care


| CLIMATIC SPECIFICATIONS | |
|-----------------------------|-------------------|
| Operating temperature range | - 55 °C; + 155 °C |

| MECHANICAL SPECIFICATIONS | |
|---------------------------|---|
| Substrate | Alumina |
| Technology | NiCr + Ta ₂ O ₅ |
| Coating | Silicone |
| Terminations | Solderable B type: SnPb over nickel barrier N type: SnAg over nickel barrier G type: Gold over nickel barrier |


Note

- Refer to Application Note "Guidelines for Vishay Sfernice Resistive and Inductive Components" (document number: 52029) for recommended reflow profile. Profile #3 applies.

| TOLERANCE AND TCR VS. OHMIC VALUE | | | |
|-----------------------------------|------------------------|-------------------|--------------|
| OHMIC VALUE RANGE in Ω | TIGHTEST TOLERANCE (%) | BEST TCR (ppm/°C) | TERMINATIONS |
| 0R1 < 0R25 | 1 | 300 | N or B |
| 0R25 < 0R5 | 1 | 200 | N or B |
| 0R5 < 2R5 | 1 | 100 | N or B |
| 2R5 < 9R99 | 1 | 50 | N or B |
| 0R1 < 0R25 | 5 | 300 | G |
| 0R25 < 0R5 | 5 | 200 | G |
| 0R < 1R | 5 | 100 | G |
| 1R < 2R5 | 3 | 100 | G |
| 2R5 to 9R99 | 3 | 50 | G |

DIMENSIONS in millimeters (inches)


| CASE SIZE | A | B | C | D/E |
|-----------|-------------------------|-------------------------|-----------------------|-------------------------|
| | $\pm 0.152 (\pm 0.006)$ | $\pm 0.127 (\pm 0.005)$ | $\pm 0.127 (+ 0.005)$ | $\pm 0.127 (\pm 0.005)$ |
| 0603 | 1.52 (0.060) | 0.85 (0.033) | 0.5 (0.020) | 0.38 (0.015) |
| 0805 | 1.91 (0.075) | 1.27 (0.050) | | 0.40 (0.016) |
| 1206 | 3.06 (0.120) | 1.60 (0.063) | | 0.48 (0.019) |
| 1505 | 3.81 (0.150) | 1.32 (0.052) | | |
| 2010 | 5.08 (0.200) | 2.54 (0.100) | | |
| 2512 | 6.30 (0.248) | 3.30 (0.129) | | |

SUGGESTED LAND PATTERN in millimeters (inches) (to IPC-7351A)


| CASE SIZE | Z _{max.} | G _{min.} | X _{max.} |
|-----------|-------------------|-------------------|-------------------|
| 0603 | 2.37 (0.093) | 0.35 (0.014) | 0.98 (0.039) |
| 0805 | 2.76 (0.109) | 0.74 (0.029) | 1.40 (0.055) |
| 1206 | 3.91 (0.154) | 1.85 (0.073) | 1.73 (0.068) |
| 1505 | 4.66 (0.183) | 2.44 (0.096) | 1.45 (0.057) |
| 2010 | 5.93 (0.233) | 3.71 (0.146) | 2.67 (0.105) |
| 2512 | 7.15 (0.281) | 4.93 (0.194) | 3.43 (0.135) |


Option: Enlarged Terminations: 0063

For stringent and special power dissipation requirements, the thermal resistance between the resistive layer and the solder joint can be reduced using enlarged terminations chip resistors which are soldered on large and thick copper pads acting as heat sinks (see application note: "Power Dissipation in High Precision Vishay Sfernice Chip Resistors and Arrays (P Thin Film, PRA Arrays, CHP Thick Film)": www.vishay.com/doc?53048).

For enlarged terminations: Please consult Vishay Sfernice.

Option: AEC-Q200 withstanding

Please order option 0058.

POWER DERATING CURVE

PACKAGING

Several types of packaging are proposed: waffle-pack and tape and reel

| SIZE | MOQ | NUMBER OF PIECES PER PACKAGE | | TAPE WIDTH | |
|------|-----|------------------------------|---------------|------------|------|
| | | WAFFLE PACK 2" x 2" | TAPE AND REEL | | |
| | | | MIN. | | MAX. |
| 0603 | 100 | 100 | 100 | 5000 | |
| 0805 | | | | 4000 | |
| 1206 | | | | | |
| 1505 | | 60 | 2000 | | |
| 2010 | | 45 | | | |
| 2512 | | | | | |

PACKAGING RULES
Waffle Pack

Can be filled up to maximum quantity indicated in the table here above, taking into account the minimum order quantity. When quantity ordered exceeds maximum quantity of a single waffle pack, the waffle packs are stacked up on the top of each other and closed by one single cover.

To get "not stacked up" waffle pack in case of ordered quantity > maximum number of pieces per package: Please consult Vishay/Sfernice for specific ordering code.

Tape and Reel

Can be filled up to maximum quantity indicated in the table here above, taking into account the minimum order quantity. When quantity ordered is between the MOQ and the maximum reel capacity, only one reel is provided.

When several reels are needed for ordered quantity within MOQ and maximum reel capacity: Please consult Vishay Sfernice for specific ordering code.

| PERFORMANCE | | | |
|---------------------------|---|--------------------------|-----------------------|
| TESTS | CONDITIONS | VALUES AND DRIFT | |
| | | MIL-R-55342 REQUIREMENTS | TYPICAL PERFORMANCES |
| Thermal shock | MIL-R-55342 C MIL-STD-702, method 107 | ± 0.25 % | ± 0.02 % |
| Short time overload | MIL-R-55342 C PARA 3.10.4.7.5 | ± 0.10 % | ± 0.01 % |
| Low temperature operation | MIL-R-55342 C PARA 3.9 and 4.7.4 | ± 0.25 % | ± 0.01 % |
| Resistance to solder heat | MIL-R-55342 C PARA 3.12, 4.7.7, 4.7.1.2 | ± 0.25 % | ± 0.04 % |
| Moisture resistance | MIL-R-55342 C PARA 3.13 and 4.7.8 MIL-STD-202, method 106 | ± 0.40 % | ± 0.01 % |
| | AEC-Q200 85 °C/85 % RH/0.1 Pn 1000 h | - | Max. < 0.5 % + 0.05 Ω |
| High temperature | MIL-R-55342 C PARA 3.11 and 4.7.6 | ± 0.20 % | ± 0.075 % |
| Load life | MIL-R-55342 C 2000 h Pn at 70 °C MIL-STD-202, method 108 | ± 0.50 % | ± 0.15 % |



| GLOBAL PART NUMBER INFORMATION | | | | | | | | | | | | | | | | |
|---|--|---|-------|---|-------------|--|--------|---|---|--|---|--------------------------|---|---|---|---|
| New Global Part Numbering: L0805K1R00FBT0099 | | | | | | | | | | | | | | | | |
| L | 0 | 8 | 0 | 5 | K | 1 | R | 0 | 0 | F | B | T | 0 | 0 | 9 | 9 |
| GLOBAL MODEL | SIZE | TCR | | VALUE | | TOLERANCE | | TERMINATION | | PACKAGING ⁽¹⁾ | | OPTION | | | | |
| L | 0603 0805 1206 1505 2010 2512 | H = ± 50 ppm K = ± 100 ppm L = ± 200 ppm M = ± 300 ppm | | R designated decimal point For values under 1R if 3 significant digits: Rxxx if 2 significant digits: xRxx | | F = ± 1 % G = ± 2 % H = ± 3 % J = ± 5 % K = ± 10 % | | B: SnPb over nickel barrier N: SnAg over nickel barrier G: Gold over nickel barrier | | Blank: Waffle pack T: Tape and reel B: Lead bearing version N and G: Lead (Pb)-free/ RoHS version | | Leave blank if no option | | | | |
| Historical Part Number example: L 0805 K 1R00 1 % B T R0099 | | | | | | | | | | | | | | | | |
| L | 0805 | K | 1R00 | 1 % | B | T | R0099 | | | | | | | | | |
| MODEL | SIZE | TCR | VALUE | TOLERANCE | TERMINATION | PACKAGING ⁽¹⁾ | OPTION | | | | | | | | | |

Note

⁽¹⁾ For specific quantity of parts per packaging please consult Vishay Sfernice



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А