

A

B

C





D

A

B




C

D



CONNECTOR LINK WIDTH	#POS REF	N	DIM"A"	DIM"B"	DIM"C"	DIM"D"	DIM"E"
X1	36	6	7.65	25.00	12.30	34.8	6.00
X4	64	20	21.65	39.00	26.30	48.8	20.00
X8	98	37	38.65	56.00	43.30	65.8	37.00
X16	164	70	71.65	89.00	76.30	98.8	70.00



spec ref				dr		Jeny Ren	2016/06/20		projection		MM		size		A3	scale		2:1											
tolerance std ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		Jeny Ren					2016/12/09		ecn no						-								
						chr		-					-																
				appr		Nickor Zuo		2016/12/09		product family						rel level						Released							
surface ASME Y14.5		linear		0.X		±0.30		Amphenol FCi		title		PCI EXPRESS 3.0						dwg no		10140125						rev		A	
				0.XX		±0.20																							
				0.XXX		±0.1																							
angular		0°		±2°		www.fci.com		cat. no.				Product-Customer Drw						sheet 1 of 4											




RECOMMENDED PCB LAYOUT

POSITION	N	DIM"F"
36	6	12.30
64	20	26.30
98	37	43.30
164	70	76.30

spec ref				dr		Jeny Ren	2016/06/20		projection		MM		size		A3	scale		2:1						
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED				eng		Jeny Ren	2016/12/09						ecn no				-					
ASME Y14.5						chr		-	-															
						appr		Nickor Zuo		2016/12/09					product family				rel level				Released	
surface		linear		0.X		±0.30		Amphenol FCI		title		PCI EXPRESS 3.0						dwg no		10140125		rev		A
				0.XX		±0.20																		
				0.XXX		±0.1																		
ASME Y14.5		angular		0°		±2°		www.fci.com		cat. no.				Product-Customer Drw				sheet 2 of 4						



1. NO TIE BAR PERMITTED FROM CARD EDGE TO LEADING EDGE OF PAD FOR PINS AI AND PIN "I".
2. CHAMFER EDGES MUST BE FREE OF CUTTING BURRS.
3. TOLERANCE : ± 0.13



POSITION	N	DIM"H"	PIN"I" (SEE NOTE 1)
36	6	8.15	B17
64	20	22.15	B31
98	37	39.15	B48
164	70	72.15	B81

spec ref		dr		Jeny Ren	2016/06/20	projection 	MM 	size	A3	scale	2:1		
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED	eng		Jeny Ren	2016/12/09			ecn no	-				
ASME Y14.5		chr		-	-			rel level				Released	
		appr		Nickor Zuo	2016/12/09			product family					
surface  ASME Y14.5	linear	0.X	±	Amphenol FCi	title	PCI EXPRESS 3.0 STRADDLE MOUNT			dwg no	10140125		rev	A
		0.XX	±										
		0.XXX	±										
		angular	0°	±°	www.fci.com	cat. no.	Product-Customer Drw				sheet 3 of 4		

NOTES:

1. MATERIAL:
HOUSING: HIGH PERFORMANCE RESINS,BLACK.
CAP:HIGH PERFORMANCE RESINS,BLACK.
CONTACT: COPPER ALLOY.
2. PLATING:
UNDERPLATE: 50 u" MIN NICKEL OVER ALL
SOLDER AREA: 100 u" MIN TIN(LEAD FREE)
MATING AREA: SEE PRODUCT PART NUMBER.
3. PRODUCT SPECIFICATION: GS-12-1193
4. PACKAGE SPECIFICATION: GS-14-2401.
5. PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND
OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
6. ONLY P/N 10140125-XXXX10XX CAN GO IR REFLOW PROCESS.
7. DATE CODE BE PRINTED ON PROPER SURFACE.

PRODUCT PART NUMBER:

10140125- X X X X X X X X

NO. OF POSITION
36:36 POSITIONS
64:64 POSITIONS
98:98 POSITIONS
A4:164 POSITIONS


PCB THICKNESS OPTION
0:1.57 MM
1:2.0/2.08 MM
2:2.31/2.36/2.4 MM

LEAD FREE OPTION
LF:LEAD FREE

RESERVE
0

CAP OPTION (SEE NOTE 6)
0:WITHOUT CAP
1:CAP

CONTACT PLATING
0:15 u" Au
1:30 u" Au
2:15 u" GXT



DATA CODE INFORMATION

P X X X X X X X X X

PRODUCTION LINE CODE
DATE CODE THROUGH 01 TO 31
WEEK NUMBER 01 THROUGH 53
YEAR CODE; MOST RIGHT OF DIGIT
OF PRODUCTION.(e.g 2007=7)
MANUFACTURE SITE; 2 FOR DONGGUAN
SOURCE,P FOR CHINA

spec ref				dr	Jeny Ren	2016/06/20	projection		MM		size	A3	scale	2:1
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Jeny Ren	2016/12/09					ecn no	-		
ASME Y14.5				chr	-	-								
appr					Nickor Zuo	2016/12/09	product family			rel level	Released			
surface	linear	0.X	±0.30	Amphenol FCI	title	PCI EXPRESS 3.0			dwg no	10140125			rev	A
		0.XX	±0.20											
		0.XXX	±0.1											
ASME Y14.5	angular	0°	±2°	www.fci.com	cat. no.	Product-Customer Drw					sheet 4 of 4			

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А