# OVEN CONTROLLED CRYSTAL OSCILLATOR

## AOCJY1 Series

ESD Sensitive

RoHS / RoHS II Compliant

20.8 x 13.2 x 8.2 mm

## FEATURES:

- 20.8 x 13.2 x 8.2 mm Leaded- RoHS Compliant Reflow-able Package
- AT-Cut, High "Q" resonator based design
- Either Sinewave or CMOS RF output
- Available with ±500 ppb over -40°C to +75°C operating temperature Range
- Tighter Stabilities to ±50.0 ppb over 0°C to +50°C also available
- Exceptional long-term Aging of ±3 ppm max. over 10-Year Product Life
- Excellent close-in phase noise (-145 dBc/Hz Typical @1k Hz offset; 10MHz carrier)

## APPLICATIONS:

- Cellular Infrastructure
- Radar Systems
- Test & Measurement Equipment
- GPS Tracking with precision hold-over accuracy
- WiMax / WLAN

## STANDARD SPECIFICATIONS:

| Parameters | Minimum | Typical | Maximum | Units | Notes |
|---|---|---|---|---|---|
| **RF Output** | | | | | |
| Frequency | 10.00 | | 100.00 | MHz | Overall Frequency range |
| Standard Available Frequencies | 10.00, 12.80, 13.00, 26.00, 38.88, 40.00, 100.00 MHz | | | | |
| **Waveform** | **CMOS** | | | | |
| Level "1" (Logic High) | 0.9*Vdd | | | Volts | |
| Level "0" (Logic Low) | | | 0.1*Vdd | Volts | |
| Load | | 15 | | pf | |
| Rise & Fall Time | | | 6.0 | ns | |
| Duty Cycle | 45 | | 55 | % | |
| **Waveform** | **Sinewave** | | | | |
| Peak Power | 2.00 | | | dBm | |
| Output Load | | 50 | | Ω | |
| **Short Term Stability** | | **$1x10^{-9}$** | | **/second** | **Alan Variance** |
| **Operable Temperature Range** | -40 | | 75 | ° C | ***See Stability Options*** |
| **Frequency Stability Options** | | | | | |
| 0° C to +50°C | | | ±50.00 | ppb | Default Spec. |
| -20° C to +70°C | | | ±200.00 | ppb | Option "E" |
| -40° C to +75°C | | | ±500.00 | ppb | Option "F" |
| | | | | | |
| **Frequency Stability vs. Supply Voltage (Vdd ± 5%)** | | | ±50.00 | ppb | |
| **Warm-Up @ 25 °C** | | | ±500.00 | ppb | In ≤ 3-minutes |
| | | | | | |
| Power Consumption @ turn on | | | 2.00 | Watts | |
| Power Consumption Steady State | | | 1.00 | Watt | |
| Supply Voltage (Vdd) | 3.13 | 3.30 | 3.46 | Volts | ***See Options*** |
| **Aging** | | | | | |
| Yearly | | | ±500 | ppb | |
| 10-Years | | | ±3.00 | ppm | |
| Supply Voltage Variation | | | ±50 | ppb | VDD ± 5% change |
| **Spectral Content** | | | | | |
| Spurious Response | | | -35 | dBc | |
| Phase Noise (10MHz Carrier) @ 5V | | | | | |
| @ 10 Hz offset | | | -90 | dBc / Hz | |
| @ 100 Hz offset | | | -120 | dBc / Hz | |
| @ 1,000 Hz offset | | | -145 | dBc / Hz | |
| @ 10,000 Hz offset | | | -150 | dBc / Hz | |
| **Electrical Frequency Adjustment** | | | | | |
| Control Voltage Range (Vc) | 0.0 | | Vdd | Volts | |
| Frequency Pull Range | ±5.00 | | | ppm | |
| Frequency Pull Slope | | Positive | | | |
| Control Voltage Port Impedance | 10 | | | kΩ | |
| Center Control Voltage | (Vdd/2) -0.5 | Vdd/2 | (Vdd/2) +0.5 | Volts | |
| Control Port Linearity | | ±10 | | % | |
| **Storage Temperature** | **-40** | | **+100** | **° C** | |



30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000| fax 949-546-8001| www.abracon.com

# OVEN CONTROLLED CRYSTAL OSCILLATOR

AOCJY1 Series

ESD Sensitive

RoHS / RoHS II Compliant

20.8 x 13.2 x 8.2 mm

## OPTIONS AND PART IDENTIFICATION (Left blank if standard)

AOCJY1 -☐- ☐ MHz -☐- ☐☐

| Supply Voltage Option |
|---|
| Blank: 3.30V |
| A: 5.00V |

| Frequency in MHz |
|---|
| Such as; 10.000 MHz |
| 26.000 MHz |
| 100.000 MHz |

| Temperature Options |
|---|
| E: -20°C to +70°C |
| F *: -40°C to +75°C |

* For temp. option "F", 100MHz is only available with CMOS output

| RF Output Options |
|---|
| Blank: CMOS |
| SW: Sinewave |

## OUTLINE DIMENSIONS




| Pin | Function |
|---|---|
| 1 | Control Voltage |
| 7 | GND |
| 8 | Output |
| 14 | Power Supply |

# OVEN CONTROLLED CRYSTAL OSCILLATOR

## AOCJY1 Series

**ESD Sensitive**

**RoHS / RoHS II Compliant**

**20.8 x 13.2 x 8.2 mm**

## REFLOW PROFILE:




| | |
|---|---|
| $T_S$ max to $T_L$ (Ramp-up Rate) | 3°C/second max. |
| Preheat | |
| Temperature Min. ($T_S$ Min.) | 150°C |
| Temperature Typical ($T_S$ Typ.) | 175°C |
| Temperature Max. ($T_S$ Max.) | 200°C |
| Time ($t_S$) | 60 ~ 180 seconds |
| Ramp-up rate ($T_L$ to $T_p$) | 3°C/second max. |
| Time Maintained Above: | |
| --Temperature ($T_L$)/Time ($T_L$) | 217°C/60 ~ 150 seconds |
| Peak Temperature ($T_p$) | 250°C max. for 10 seconds |
| Target Peak Temperature ($T_p$ Target) | 250°C +0/-5°C |
| Time within 5°C of actual peak ($t_p$) | 20 ~ 40 seconds |
| Ramp-down Rate | 6°C/second max. |
| Tune 25°C to Peak Temperature (t) | 8 minutes max. |

## PACKAGING: (50) units per tray




ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000| fax 949-546-8001| www.abracon.com

# OCEAN CHIPS
## Океан Электроники
## Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

**«JONHON»** (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

**«FORSTAR»** (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А