


Organize Input and Output Device Wiring and Reduce Installation Errors with Pre-terminated Cables

- Omron screw terminals can be used with controllers from any manufacturer
- XW2B screw terminals support a wide variety of cable connections and I/O points to match most industrial control applications









## Ordering Information



### ■ SCREW TERMINAL BLOCKS

Product	Appearance	Specifications	Dimensions	Part number
General-purpose Screw Terminals, flat cable connector		20 contacts, M3 terminals	67.5 W x 45 H x 45.3 D mm	<b>XW2B-20G4</b>
		34 contacts, M3 terminals	112.5 W x 45 H x 45.3 D mm	<b>XW2B-34G4</b>
		40 contacts, M3 terminals	135.0 W x 45 H x 45.3 D mm	<b>XW2B-40G4</b>
		60 contacts, M3 terminals	292.5 W x 45 H x 45.3 D mm	<b>XW2B-60G4</b>
General-purpose Screw Terminals, multi-pole square connector		20 contacts, M3.5 terminals	112.5 W x 45 H x 45.3 D mm	<b>XW2B-20G5</b>
		34 contacts, M3.5 terminals	180.0 W x 45 H x 45.3 D mm	<b>XW2B-34G5</b>
		40 contacts, M3.5 terminals	202.5 W x 45 H x 45.3 D mm	<b>XW2B-40G5</b>
		60 contacts, M3.5 terminals	292.5 W x 45 H x 45.3 D mm	<b>XW2B-60G5</b>
General-purpose Screw Terminals, multi-pole square connector		20 contacts, M3 terminals	67.5 W x 45 H x 38.1 D mm	<b>XW2B-20Y4</b>
		34 contacts, M3 terminals	112.5 W x 45 H x 38.1 D mm	<b>XW2B-34Y4</b>
		50 contacts, M3 terminals	157.5 W x 45 H x 38.1 D mm	<b>XW2B-50Y4</b>
General-purpose Screw Terminals, multi-pole square connector		20 contacts, M3 terminals	112.5 W x 45 H x 43 D mm	<b>XW2B-20Y5</b>
		34 contacts, M3 terminals	180.0 W x 45 H x 43 D mm	<b>XW2B-34Y5</b>
		50 contacts, M3 terminals	247.5 W x 45 H x 43 D mm	<b>XW2B-50Y5</b>
General-purpose Screw Terminals, convenient cable features		20 contacts, M3.5 terminals, twin connectors	112.5 W x 45 H x 43 D mm	<b>XW2B-20X5</b>
		34 contacts, M3.5 terminals	180.0 W x 45 H x 43 D mm	<b>XW2B-34X5</b>
		50 contacts, M3.5 terminals	247.5 W x 45 H x 43 D mm	<b>XW2B-50X5</b>
General-purpose Screw Terminals, convenient cable features		40 contacts, M3.5 terminals, twin connectors	202.5 W x 45 H x 45.3 D mm	<b>XW2B-40G5-T</b>
		20 contacts, M3.5 terminals, daisy-chain connection	135 W x 45 H x 45.3 D mm	<b>XW2B-20G5-D</b>
		40 contacts, M3.5 terminals, PCB I/O connector	202.5 W x 45 H x 43.5 D mm	<b>XW2B-40F5-P</b>
Input Screw Terminal for Omron PLCs		16 input points, NPN (- common)	160 W x 50 H x 38.1 D mm	<b>XW2C-20G5-IN16</b>

## ■ CABLES FOR XW2B SCREW TERMINAL BLOCKS

Appearance	Applicable terminal block	Cable length	Part number
 <p>Single cable terminated with crimp hooks for connection to any manufacturer's controllers</p>	XW2B-20G5 XW2B-20G4	1 m (3.28 ft)	XW2Z-100F
		1.5 m (4.92 ft)	XW2Z-150F
		2 m (6.56 ft)	XW2Z-200F
		3 m (9.84 ft)	XW2Z-300F
		5 m (16.40 ft)	XW2Z-500F
 <p>Single cable for 32-point Omron I/O modules</p>	XW2B-20G5 XW2B-20G4 XW2B-20G5-T XW2B-20G5-D XW2B-20G5-IN16	0.5 m (1.64 ft)	XW2Z-050A
		1 m (3.28 ft)	XW2Z-100A
		1.5 m (4.92 ft)	XW2Z-150A
		2 m (6.56 ft)	XW2Z-200A
		3 m (9.84 ft)	XW2Z-300A
		5 m (16.40 ft)	XW2Z-500A
		 <p>Single cable for 32- and 64-point Omron I/O modules</p>	XW2B-40G5 XW2B-40G4
1 m (3.28 ft)	XW2Z-100B		
1.5 m (4.92 ft)	XW2Z-150B		
2 m (6.56 ft)	XW2Z-200B		
3 m (9.84 ft)	XW2Z-300B		
 <p>Single cable for Omron CS1W high-density I/O modules</p>	XW2B-60G5 XW2B-60G4	1 m (3.28 ft)	XW2Z-100H-1
		2 m (6.56 ft)	XW2Z-200H-1
		3 m (9.84 ft)	XW2Z-300H-1
		5 m (16.40 ft)	XW2Z-500H-1
 <p>Bifurcated cable for 32- and 64-point Omron I/O modules</p>	XW2C-20G5-IN16	1 m (3.28 ft) and 0.75 m (2.46 ft)	XW2Z-100D
		1.5 m (4.92 ft) and 1.25 m (4.10 ft)	XW2Z-150D
		2 m (6.56 ft) and 1.75 m (5.74 ft)	XW2Z-200D
		3 m (9.84 ft) and 2.75 m (9.02 ft)	XW2Z-300D
		5 m (16.40 ft) and 4.75 m (15.58 ft)	XW2Z-500D
 <p>Bifurcated cable for Omron CS1W high-density I/O modules</p>	XW2B-40G5 and XW2B-20G5	1 m (3.28 ft) and 1 m (3.28 ft)	XW2Z-100H-2
		2 m (6.56 ft) and 2 m (6.56 ft)	XW2Z-200H-2
		3 m (9.84 ft) and 3 m (6.56 ft)	XW2Z-300H-2
		5 m (16.40 ft) and 5 m (16.40 ft)	XW2Z-500H-2
 <p>Three-connector cable for Omron CS1W 48- and 96-point I/O modules</p>	Three XW2B-20G5	1 m (3.28 ft) and 0.75 m (2.45 ft) and 1 m (3.28 ft)	XW2Z-100H-3
		2 m (6.56 ft) and 1.75 m (5.74 ft) and 2 m (6.56 ft)	XW2Z-200H-3
		3 m (9.84 ft) and 2.75 m (9.02 ft) and 3 m (9.84 ft)	XW2Z-300H-3
		5 m (16.40 ft) and 4.75 m (15.58 ft) and 5 m (16.40 ft)	XW2Z-500H-3

## ■ CABLES FOR XW2C INPUT SCREW TERMINALS

Product	Appearance	Specification	Part number
1:1 Cables for XW2C Screw Terminals to Omron PLC I/O modules		0.5 m (1.64 ft) length 1 m (3.28 ft) length 1.5 m (4.92 ft) length 2 m (6.56 ft) length 3 m (9.84 ft) length 5 m (16.40 ft) length	XW2Z-050A XW2Z-100A XW2Z-150A XW2Z-200A XW2Z-300A XW2Z-500A
2:1 Cables for XW2C Screw Terminals to Omron PLC I/O modules		1 m (3.28 ft) and 0.75 m (2.46 ft) length 1.5 m (4.92 ft) and 1.25 m (4.10 ft) length 2 m (6.56 ft) and 1.75 m (5.74 ft) length 3 m (9.84 ft) and 2.75 m (9.02 ft) length 5 m (16.40 ft) and 4.75 m (15.58 ft) length	XW2Z-100D XW2Z-150D XW2Z-200D XW2Z-300D XW2Z-500D

---

**OMRON**<sup>®</sup>  
**OMRON ELECTRONICS, INC.**  
One East Commerce Drive  
Schaumburg, IL 60173  
**1-800-55-OMRON**

**OMRON CANADA, INC.**  
885 Milner Avenue  
Scarborough, Ontario M1B 5V8  
**416-286-6465**

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



## JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А