

# SCRs

## Nuclear Radiation Resistant, Planar

GA100  
GA101  
GA102

### FEATURES

- Optimized for Radiation Resistance
- Fully Characterized for "Worst Case" Design
- Post Radiation Design Limits Specified
- Passivated Planar Construction for Maximum Reliability and Parameter Uniformity
- Pulse Currents: to 30A
- Max. Trigger Current 20mA after  $3 \times 10^{14}$  NVT
- Max. Holding Current 30mA after  $3 \times 10^{14}$  NVT

### DESCRIPTION

The GA100 Series of Radiation Hard SCRs have been designed to provide significantly greater radiation tolerance than conventional SCRs or Transistors with the same current handling ability. This Series is capable of operation after exposure to  $10^{15}$  NVT.

The radiation resistant characteristics of the GA100 series devices make them particularly desirable for use under radiation environments in squib firing circuits; inverters and converters; pulse generators; relay drivers; and modulator discharge switches.

### ABSOLUTE MAXIMUM RATINGS

	GA100	GA101	GA102
Repetitive Peak Off-State Voltage, $V_{ORM}$	30V	60V	80V
D.C. On-State Current, $I_T$			
75°C Ambient		200mA	
100°C Case		400mA	
Repetitive Peak On-State Current, $I_{TRM}$		up to 30A	
Surge (non-rep.) On-State Current, $I_{TSM}$ (Sq. Pulse-50ms)		5A	
Peak Gate Current, $I_{GM}$		250mA	
Average Gate Current, $I_{G(AV)}$		25mA	
Reverse Gate Voltage, $V_{GR}$		5V	
Reverse Gate Current, $I_{GR}$		3mA	
Storage Temperature Range		-65°C to +200°C	
Operating Temperature Range		-65°C to +150°C	

### MECHANICAL SPECIFICATIONS

	GA100	GA101	GA102																														
<table border="1"> <thead> <tr> <th></th> <th>INCHES</th> <th>MILLIMETERS</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>.178-.195 DIA.</td> <td>4.52-4.95 DIA.</td> </tr> <tr> <td>B</td> <td>.170-.210</td> <td>4.31-5.33</td> </tr> <tr> <td>C</td> <td>.5 MIN.</td> <td>12.76 MIN.</td> </tr> <tr> <td>D</td> <td>.209-.230 DIA.</td> <td>5.31-5.84 DIA.</td> </tr> <tr> <td>E</td> <td>.017 ± .002 DIA. .001 DIA.</td> <td>.432 ± .051 .025</td> </tr> <tr> <td>F</td> <td>.020 MAX.</td> <td>.508 MAX.</td> </tr> <tr> <td>G</td> <td>.100 ± .010 DIA.</td> <td>2.54 ± .254 DIA.</td> </tr> <tr> <td>H</td> <td>.041 ± .005</td> <td>1.04 ± .127</td> </tr> <tr> <td>J</td> <td>.028-.048</td> <td>.711-1.22</td> </tr> </tbody> </table>					INCHES	MILLIMETERS	A	.178-.195 DIA.	4.52-4.95 DIA.	B	.170-.210	4.31-5.33	C	.5 MIN.	12.76 MIN.	D	.209-.230 DIA.	5.31-5.84 DIA.	E	.017 ± .002 DIA. .001 DIA.	.432 ± .051 .025	F	.020 MAX.	.508 MAX.	G	.100 ± .010 DIA.	2.54 ± .254 DIA.	H	.041 ± .005	1.04 ± .127	J	.028-.048	.711-1.22
	INCHES	MILLIMETERS																															
A	.178-.195 DIA.	4.52-4.95 DIA.																															
B	.170-.210	4.31-5.33																															
C	.5 MIN.	12.76 MIN.																															
D	.209-.230 DIA.	5.31-5.84 DIA.																															
E	.017 ± .002 DIA. .001 DIA.	.432 ± .051 .025																															
F	.020 MAX.	.508 MAX.																															
G	.100 ± .010 DIA.	2.54 ± .254 DIA.																															
H	.041 ± .005	1.04 ± .127																															
J	.028-.048	.711-1.22																															

## ELECTRICAL SPECIFICATIONS (at 25°C unless noted)


Test	Symbol	Preradiation Limits			Post $3 \times 10^{14}$ NVT Design Limits		Units	Test Conditions
		Min.	Typ.	Max.	Min.	Max.		
SUBGROUP 1 Visual and Mechanical	—	—	—	—	—	—	—	MIL-STD-750 Method 20/1
SUBGROUP 2 (25°C Tests)								
Off-State Current	$I_{DRM}$	—	.005	0.1	—	1.0	$\mu A$	$R_{GK} = 220\Omega, V_{DRM} = \text{Rating}$
Reverse Gate Current	$I_{CR}$	—	.01	0.1	—	1.0	$\mu A$	$V_{CE} = 2V$
Input Trigger Current (Note 2)	$I_{ST}$	1.8	2.3	3.5	—	20	mA	$R_{GK} = 220\Omega, V_D = 5V$
Gate Trigger Voltage	$V_{GT}$	0.4	0.5	0.7	—	1.5	V	$R_{GK} = 220\Omega, V_D = 5V$
On-State Voltage	$V_T$	0.8	1.1	1.5	—	3.0	V	$i_T = 1A$ (pulse test)
Holding Current	$I_{H}$	0.3	0.7	10	—	30	mA	$R_{GK} = 220\Omega$
SUBGROUP 3 (25°C Tests)								
Off-State Voltage-Critical Rate of Rise	$dv_c/dt$	20	40	—	—	—	V/ $\mu S$	$R_{GK} = 220\Omega, V_D = 30V$
Gate Trigger-on Pulse Width	$t_{pg}$ (on)	—	.02	.05	—	0.1	$\mu S$	$I_G = 25mA, I_T = 1A, V_D = 30V$
Delay Time	$t_d$	—	.02	—	—	—	$\mu S$	$I_G = 25mA, I_T = 1A, V_D = 30V$
Rise Time	$t_r$	—	.05	—	—	—	$\mu S$	$I_G = 25mA, I_T = 1A, V_D = 30V$
Circuit Commutated Turn-off Time	$t_q$	—	1.5	2.5	—	1.0	$\mu S$	$I_T = 1A, I_R = 1A, R_{GK} = 220\Omega$
SUBGROUP 4 (125°C Tests)								
High Temp Off-State Current	$I_{DRM}$	—	10	100	—	100	$\mu A$	$R_{GK} = 220\Omega, V_{DRM} = \text{Rating}$
High Temp Gate Trigger Voltage	$V_{GT}$	0.1	.17	—	0.1	—	V	$R_{GK} = 220\Omega, V_D = 5V$

- Notes: 1. Off-State voltage ratings apply over the operating temperature range provided the gate is connected to the cathode through an appropriate resistor, or other adequate bias is used.  
2. Total Input Trigger Current, including current required by 220 $\Omega$  gate bias resistance.


## DESIGN CONSIDERATIONS

- Curve 1 shows the off-state current,  $I_{DRM}$  of the SCR as a function of temperature.  $I_{DRM}$  is increased by radiation damage, but is not a design consideration at the recommended gate bias levels.  
In order to optimize for radiation tolerance, reverse blocking capability has not been retained as a design feature. Devices with reverse blocking capability can be provided.
- Minimum critical  $dv/dt$  levels are defined in Curve 2. The  $dv/dt$  capability is improved after radiation because of reduced triggering sensitivity.  $dv/dt$  is therefore a design consideration only prior to radiation.
- Curves 3 and 4 show the limits of Gate Trigger Voltage and Total Input Trigger Current prior to radiation. Maximum design limits after a total radiation dosage of  $3 \times 10^{14}$  NVT is also shown. Curves 5 and 6 show the maximum limits of Gate Trigger Voltage and Total Input Trigger Currents as a junction of neutron dosage. The minimum level of Trigger current prior to radiation is established by the shunting effect of a 220 ohm resistor between gate and cathode. After radiation the device is less sensitive and Total Trigger Current will increase to a level relatively independent of the bias resistance. The 220 ohm resistor is recommended since it raises the minimum preradiation trigger current to a level that is closer to the post radiation limit and minimizes the percentage change in this parameter.
- Current ratings shown in Curves 10, 11, and 12 apply after the device has been subjected to  $3 \times 10^{14}$  NVT. Current ratings prior to radiation are greater than the values indicated.
- Gamma radiation produces a reversible ionization (leakage) current within the device which is directly proportional to the Gamma flux level. When the Gamma flux level is in the range of 10 to 100 Roentgens per microsecond for burst durations greater than 1 microsecond, the device will self trigger ON. For the radiation bursts associated with nuclear explosions, the Gamma flux level will invariably cause device triggering at radiation levels significantly below the levels that would produce detectable permanent device damage due to cumulative neutron dosage. In applications where the burst effect triggering cannot be tolerated, it is necessary to reset the device after the radiation burst. Special circuit approaches such as additional SCRs to crowbar or otherwise cancel the output function may be used.


1. Off-State Current




2. Minimum Critical DV/DT vs. Neutron Dosage




3. Gate Trigger Voltage




4. Input Trigger Current




5. Max. Gate Trigger Voltage vs. Neutron Dosage




6. Max. Input Trigger Current vs. Neutron Dosage



7. Holding Current




8. Max. Holding Current vs. Neutron Dosage




8


9. Max. On-State Voltage vs. Neutron Dosage




10. Peak Current vs. Ambient Temperature



11. Peak Current vs. Case Temperature



12. Surge Current vs. Time



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А