

## PR1 Relay Base for:

- Relays With SPDT or DPDT Contacts
- Solid-State Relays With the Same Structure

### Universal Modular System

The 15 mm (0.591 in.) wide PR1 relay base range is a modular system consisting of PR1-B... relay bases, compact electromechanical relays with SPDT or DPDT contacts, solid-state relays, and a comprehensive range of accessories. These include:

- Plug-in input/interference suppression modules
- Relay retaining bracket with labeling field and eject function
- Labels
- Continuous jumpers

Depending on the application, complete coupling relays can be created, which are optimized in terms of cost, function, and service life.

### Base Versions

The relay bases are available in two versions with screw connections<sup>3)</sup> - the flat 2/2 level PR1-BSC2 and the "logical" 1/3 level PR1-BSC3. The second version has coil and contact connections that are located opposite one another and thus meets the requirements of modern control cabinet concepts with clear isolation of control signals and load. Both bases can be extended in terms of functions through the use of keyed plug-in modules with various display and interference suppression elements.


### Cost-Effective Electromechanical Relays







Powerful and cost-effective REL-MR electromechanical miniature power relays are recommended for standard applications. They are available in the following versions:

- With one 16 A PDT contact
  - With two 8 A PDT contacts
  - In all popular AC and DC coil voltages
  - In power contact and gold contact versions
- Additional suitable standard and special relays (e.g., for lamp loads) are available on request<sup>4)</sup>.

### Alternative: Wear-Resistant Solid-State Relays

In critical applications, electromechanical relays reach their maximum service life relatively quickly. This is why, as an alternative, PR1-B... bases can be fitted with OPT wear-resistant solid-state relays with the same structure. These relays provide optimum service life for applications with a high switching frequency and/or for switching high DC loads.



	①	②
	PR1-BSC2...	PR1-BSC3...
Nominal voltage U <sup>1)</sup>	300 V AC	300 V AC
Nominal current I <sup>1)</sup>	12 A	12 A
Conductor cross section		
– Solid	2 x 2.5 mm <sup>2</sup>	2 x 2.5 mm <sup>2</sup>
– Flexible	2 x 2.5 mm <sup>2</sup>	2 x 2.5 mm <sup>2</sup>
American Wire Gauge	2 x 14 AWG	2 x 14 AWG
Connection type	 M 3	 M 3
Approvals <sup>2)</sup>		
Stripping length	8 mm (0.31 in.) 	8 mm (0.31 in.) 
Height (a) with retaining bracket:		
– EL1-P16	63 mm (2.480 in.)	66 mm (2.598 in.)
– EL1-P25	71 mm (2.795 in.)	79 mm (3.110 in.)
Depth (b)	75 mm (2.953 in.)	78.5 mm (3.091 in.)
Width (c)	15.5 mm (0.610 in.)	15.5 mm (0.610 in.)
Ambient temperature	-25°C...+85°C (-13°F...+185°F)	-25°C...+85°C (-13°F...+185°F)













<sup>1)</sup> The maximum electrical data is relay dependent.

<sup>2)</sup> Details on request.

<sup>3)</sup> Spring-cage connections on request.



<sup>4)</sup> See INTERFACE catalog.

# PR1 Relay Base for Miniature Power Relays With SPDT or DPDT Contacts

Description	Type	Order No.	Pcs. Pkt.
<p><b>PR1 relay base</b>, for miniature power relays or miniature switching relays with SPDT or DPDT contacts or solid-state relays with a similar structure, 2/2 level version, screw connections, optional connection of input/interference suppression module, for mounting on , safe isolation of I/Os, including MP1 markers, 10 pcs. per pack</p> 	PR1-BSC2/2x21	28 33 51 8	10
<p><b>PR1 relay base</b>, for miniature power relays or miniature switching relays with SPDT or DPDT contacts or solid-state relays with a similar structure, 1/3 level version, screw connections, optional connection of input/interference suppression module, for mounting on , safe isolation of I/Os, including MP1 markers, 10 pcs. per pack</p> 	PR1-BSC3/2x21	28 33 52 1	10
<p><b>Relay retaining bracket</b>, with eject function and integrated device marking area (7.5 x 15 mm [0.295 x 0.591 in.]), suitable for PR1 relay base:          – For 16 mm (0.630 in.) high miniature power relays and solid-state relays<sup>1)</sup>          – For 25 mm (0.984 in.) high miniature switching relays<sup>1)</sup> and solid-state relays<sup>1)</sup></p> 	EL1-P16 EL1-P25	28 33 54 7 28 33 55 0	10 10
<p><b>Device marker</b>, 6 x 15 mm (0.236 x 0.591 in.) marking area</p> 	MP1	28 33 63 1	10
<p><b>Plug-in module</b>, for mounting on PR1 and PR2, with free-wheeling diode and yellow LED, polarity: <b>A1 +, A2 –</b>          Input voltage:          – 12 - 24 V DC ±20%          – 48 - 60 V DC ±20%          – 110 V DC ±20%</p> 	LDP-12-24DC LDP-48-60DC LDP-110DC	28 33 65 7 28 33 66 0 28 33 67 3	10 10 10
<p><b>Plug-in module</b>, for mounting on PR1 and PR2, with free-wheeling diode and yellow LED, polarity: <b>A1 –, A2 +</b> (Japanese standard)          Input voltage:          – 12 -24 V DC ±20%          – 48 - 60 V DC ±20%          – 110 V DC ±20%</p> 	LDM-12-24DC LDM-48-60DC LDM-110DC	28 33 68 6 28 33 69 9 28 33 70 9	10 10 10
<p><b>Plug-in module</b>, for mounting on PR1 and PR2, with varistor and yellow LED, input voltage:          – 12 - 24 V AC/DC ±20%          – 48 - 60 V AC/DC ±20%          – 120 - 230 V AC/110 V DC ±20%</p> 	LV-12-24UC LV-48-60UC LV-120-230AC/110 DC	(30 V varistor) (75 V varistor) (275 V varistor)	28 33 71 2 28 33 72 5 28 33 73 8
<p><b>Plug-in module</b>, for mounting on PR1 and PR2, with varistor          Input voltage:          – 12 - 24 V AC/DC ±20%          – 48 - 60 V AC/DC ±20%          – 120 - 230 V AC/DC ±20%</p> 	V-12-24UC V-48-60UC V-120-230UC	(30 V varistor) (75 V varistor) (275 V varistor)	28 33 86 4 28 33 87 7 28 33 88 0
<p><b>Plug-in module</b>, for mounting on PR1 and PR2, with RC element          Input voltage:          – 12 - 24 V AC/DC ±20%          – 48 - 60 V AC/DC ±20%          – 120 - 230 V AC/DC ±20%</p> 	RC-12-24UC RC-48-60UC RC-120-230UC	(220 nF/100 Ω) (220 nF/220 Ω) (100 nF/470 Ω)	28 33 74 1 28 33 75 4 28 33 76 7
<p><b>Wire jumper</b>, 50-pos., can be separated, maximum jumpering distance of 60 mm (2.36 in.), 0.5 mm<sup>2</sup> (20 AWG), insulation:          – Blue          – Black          – Gray</p> 	DB 50-90 BU DB 50-90 BK DB 50-90 GY	28 21 18 0 28 20 91 6 28 20 92 9	1 1 1

<sup>1)</sup> See INTERFACE catalog



# REL-MR Plug-In Miniature Power Relays<sup>1)</sup> With SPDT Contact, Suitable for PR1 Relay Base

Description	Type	Order No.	Pcs. Pkt.
<p><b>Plug-in miniature power relays, with power contact, SPDT contact, suitable for PR1-B... base</b></p> <p>Coil voltage:</p> <ul style="list-style-type: none"> <li>- 12 V DC</li> <li>- 24 V DC</li> <li>- 60 V DC</li> <li>- 110 V DC</li> </ul> <ul style="list-style-type: none"> <li>- 24 V AC</li> <li>- 120 V AC</li> <li>- 230 V AC</li> </ul> <p><b>As above, but with solid gold coating, SPDT contact</b></p> <p>Coil voltage:</p> <ul style="list-style-type: none"> <li>- 12 V DC</li> <li>- 24 V DC</li> <li>- 110 V DC</li> </ul> <ul style="list-style-type: none"> <li>- 24 V AC</li> <li>- 120 V AC</li> <li>- 230 V AC</li> </ul>	  <p>Pin assignment: view of the connections.</p>	<p><b>REL-MR- 12DC/21HC</b>      29 61 30 9</p> <p><b>REL-MR- 24DC/21HC</b>      29 61 31 2</p> <p><b>REL-MR- 60DC/21HC</b>      29 61 32 5</p> <p><b>REL-MR-110DC/21HC</b>      29 61 33 8</p> <p><b>REL-MR- 24AC/21HC</b>      29 61 40 6</p> <p><b>REL-MR-120AC/21HC</b>      29 61 41 9</p> <p><b>REL-MR-230AC/21HC</b>      29 61 42 2</p>	<p>10</p> <p>10</p> <p>10</p> <p>10</p> <p>10</p> <p>10</p> <p>10</p>
<p><b>Technical Data</b></p> <p><b>Coil Side DC Coils</b></p> <p>Nominal input voltage <math>U_N</math></p> <p>Permissible range</p> <p>Typical input current at <math>U_N</math></p> <p>Typical response time at <math>U_N</math></p> <p>Typical release time at <math>U_N</math></p> <p>DC coil resistance at 20°C (68°F)</p>	<p>12 V DC      24 V DC      60 V DC      110 V DC</p> <p>See diagram on page 5</p> <p>33 mA      17 mA      8.2 mA      4.1 mA</p> <p>7 ms      7 ms      7 ms      7 ms</p> <p>3 ms      3 ms      3 ms      3 ms</p> <p>360 <math>\Omega</math> <math>\pm</math>10%      1440 <math>\Omega</math> <math>\pm</math>10%      7340 <math>\Omega</math> -15+35%      26600 <math>\Omega</math> -15+35%</p>		
<p><b>Coil Side AC Coils (50 Hz/60 Hz)</b></p> <p>Nominal input voltage <math>U_N</math></p> <p>Permissible range (with reference to <math>U_N</math>)</p> <p>Typical input current at <math>U_N</math> (50 Hz/60 Hz)</p> <p>Typical response time at <math>U_N</math> (depending on phase relation)</p> <p>Typical release time at <math>U_N</math> (depending on phase relation)</p> <p>DC coil resistance at 20°C (68°F)</p>	<p>24 V AC      120 V AC      230 V AC</p> <p>See diagram on page 5</p> <p>32 mA/24 mA      7 mA/5 mA      3 mA/2.5 mA</p> <p>3 - 12 ms      3 - 12 ms      3 - 12 ms</p> <p>2 - 9 ms      2 - 9 ms      2 - 9 ms</p> <p>350 <math>\Omega</math> <math>\pm</math>10%      8100 <math>\Omega</math> <math>\pm</math>15%      32500 <math>\Omega</math> <math>\pm</math>15%</p>		
<p><b>Contact Side</b></p> <p>Contact type</p> <p>Contact material</p> <p>Maximum switching voltage</p> <p>Minimum switching voltage</p> <p>Limiting continuous current</p> <p>Maximum inrush current</p> <p>Minimum switching current</p> <p>Maximum shutdown power (ohmic load)</p>	<p><b>REL-MR...21HC</b></p> <p>Single contact, 1 Form C contact</p> <p>AgNi</p> <p>250 V AC/DC</p> <p>12 V</p> <p>16 A</p> <p>30 A (300 ms)</p> <p>100 mA</p> <p>4000 VA</p> <p>For additional data, see diagram on page 5</p> <p>1.2 W</p>	<p><b>REL-MR...21HCAU</b></p> <p>Single contact, 1 Form C contact</p> <p>AgNi + 5 <math>\mu</math> Au<sup>2)</sup></p> <p>30 V AC/36 V DC(250 V AC/DC)</p> <p>100 mV (12 V)</p> <p>50 mA (16 A)</p> <p>50 mA (30 A, 300 ms)</p> <p>1 mA (100 mA)</p> <p>– (4000 VA)</p> <p>100 <math>\mu</math>W (1.2 W)</p>	<p>250 V AC</p>
<p><b>General Data</b></p> <p>Test voltage: Winding/contact</p> <p>Ambient temperature</p> <p>Nominal operating mode</p> <p>Mechanical service life</p> <p>Electrical service life</p> <p>Standards/specifications</p>	<p>5 kV, 50 Hz, 1 minute</p> <p>-40°C to +85°C (-40°F to +185°F)</p> <p>100% ED</p> <p>3 x 10<sup>7</sup> cycles</p> <p>See diagram on page 5</p> <p>IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/ VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631, IEC 60 664/IEC 60 664 A/DIN VDE 0110, degree of pollution 3, Surge Voltage Category III</p> <p>UL; CSA; VDE</p> <p>Any/can be mounted without spacing</p>		
<p>Approvals</p> <p>Mounting position/mounting</p>			

<sup>1)</sup> Alternative: For REL/KSR miniature switching relay, OPT solid-state relay, see INTERFACE catalog.

<sup>2)</sup> If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the maximum values given in brackets will apply. This can then result in reduced service life, similar to simple power contacts.

# REL-MR Plug-In Miniature Power Relays<sup>1)</sup> With DPDT Contacts, Suitable for PR1 Relay Base

Description	
<b>Plug-in miniature power relays, with power contacts, DPDT contacts</b> Coil voltage: – 12 V DC – 24 V DC – 60 V DC – 110 V DC  – 24 V AC – 120 V AC – 230 V AC	
	
	
Pin assignment: view of the connections.	
<b>As above, but with solid gold coating, DPDT contacts</b> Coil voltage: – 12 V DC – 24 V DC – 60 V DC – 110 V DC  – 24 V AC – 120 V AC – 230 V AC	

Type	Order No.	Pcs. Pkt.
REL-MR- 12DC/21-21	29 61 25 7	10
REL-MR- 24DC/21-21	29 61 19 2	10
REL-MR- 60DC/21-21	29 61 27 3	10
REL-MR-110DC/21-21	29 61 20 2	10
REL-MR- 24AC/21-21	29 61 43 5	10
REL-MR-120AC/21-21	29 61 44 8	10
REL-MR-230AC/21-21	29 61 45 1	10
REL-MR- 12DC/21-21 AU	29 61 29 9	10
REL-MR- 24DC/21-21 AU	29 61 21 5	10
REL-MR- 60DC/21-21 AU	29 61 28 6	10
REL-MR-110DC/21-21 AU	29 61 22 8	10
REL-MR- 24AC/21-21 AU	29 61 46 4	10
REL-MR-120AC/21-21 AU	29 61 47 7	10
REL-MR-230AC/21-21 AU	29 61 48 0	10

## Technical Data

### Coil Side DC Coils

Nominal input voltage  $U_N$   
 Permissible range  
 Typical input current at  $U_N$   
 Typical response time at  $U_N$   
 Typical release time at  $U_N$   
 DC coil resistance at 20°C (68°F)

12 V DC	24 V DC	60 V DC	110 V DC
See diagram on page 5			
33 mA	17 mA	8.2 mA	4.1 mA
7 ms	7 ms	7 ms	7 ms
3 ms	3 ms	3 ms	3 ms
360 Ω ±10%	1440 Ω ±10%	7340 Ω -15+35%	26600Ω -15+35%

### Coil Side AC Coils (50 Hz/60 Hz)

Nominal input voltage  $U_N$   
 Permissible range (with reference to  $U_N$ )  
 Typical input current at  $U_N$  (50 Hz/60 Hz)  
 Typical response time at  $U_N$  (depending on phase relation)  
 Typical release time at  $U_N$  (depending on phase relation)  
 DC coil resistance at 20°C (68°F)

24 V AC	120 V AC	230 V AC
See diagram on page 5		
32 mA/24 mA	7 mA/5 mA	3 mA/2.5 mA
3 -12 ms	3 -12 ms	3 -12 ms
2 - 9 ms	2 - 9 ms	2 - 9 ms
350 Ω ±10%	8100 Ω ±15%	32500 Ω ±15%

### Contact Side

Contact type  
 Contact material  
 Maximum switching voltage  
 Minimum switching voltage  
 Limiting continuous current  
 Maximum inrush current  
 Minimum switching current  
 Maximum shutdown power (ohmic load) 250 V AC  
 Minimum switching power

REL-MR...21-21	REL-MR...21-21AU
Single contact, 2 Form C contacts	Single contact, 2 Form C contacts
AgNi	AgNi + 5 μ Au <sup>2)</sup>
250 V AC/DC	30 V AC/36 V DC(250 V AC/DC)
5 V	100 mV (5 V)
8 A	50 mA (8 A)
15 A (300 ms)	50 mA (15 A, 300 ms)
10 mA	1 mA (10 mA)
2000 VA	– (2000 VA)
For additional data, see diagram on page 5	
50 mW	100 μW (50 mW)

### General Data

Test voltage: Winding/contact  
 Contact/contact  
 Ambient temperature  
 Nominal operating mode  
 Mechanical service life  
 Electrical service life  
 Standards/specifications  
  
 Approvals  
 Mounting position/mounting

5 kV, 50 Hz, 1 minute  
 2.5 kV, 50 Hz, 1 minute  
 -40°C to +85°C (-40°F to +185°F)  
 100% ED  
 3 x 10<sup>7</sup> cycles  
 See diagram on page 5  
 IEC 60 255/DIN VDE 0435 (in relevant parts), DIN EN 50 178/  
 VDE 0160 (in relevant parts), EN 60 730/DIN VDE 0631,  
 IEC 60 664/IEC 60 664 A/DIN VDE 0110, degree of pollution 3,  
 Surge Voltage Category III  
 UL; CSA; VDE  
 Any/can be mounted without spacing

<sup>1)</sup> Alternative: For REL/KSR miniature switching relay, see INTERFACE catalog.


<sup>2)</sup> If the specified maximum values are exceeded, the gold coating will be damaged. In subsequent operation, the maximum values given in brackets will apply. This can then result in reduced service life, similar to simple power contacts.

# Diagrams for REL-MR... Miniature Power Relays

## REL-MR...21HC... (SPDT Contact)


### Operating voltage range

$$T_u = T_{coil}$$




- 1 DC coils
- 2 AC coils

### Shutdown power



- 1 AC, ohmic load
- 2 DC, ohmic load
- 3 DC, L/R = 40 ms


### Electrical service life



- 1 250 V AC, ohmic load (DC coils)
- 2 250 V AC, ohmic load (AC coils)

### Service life reduction factor


with varying cos φ



## REL-MR...21-21... (DPDT Contacts)


### Operating voltage range

$$T_u = T_{coil}$$




- 1 DC coils
- 2 AC coils

### Shutdown power



- 1 AC, ohmic load
- 2 DC, ohmic load, contacts in series
- 3 DC, ohmic load
- 4 DC, L/R = 40 ms


### Electrical service life



- 1 250 V AC, ohmic load (DC coils)
- 2 250 V AC, ohmic load (AC coils)

### Service life reduction factor

with varying cos φ



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А