


2300 to 2700 MHz/4900 to 5950 MHz 4-port MIMO Ceiling Mount Antenna




Patent Pending
CMQ23496



(TILE FLUSH MOUNT)
Standard



(ABOVE CEILING TILE MOUNT)
Part # HKIT-CMX-001



(HARD CEILING EXTENSION MOUNT)
Part # HKIT-CMX-002

4-PORT MIMO MULTI-BAND CEILING MOUNTED OMNIDIRECTIONAL ANTENNA

The Patent Pending CMQ23496 is an indoor broadband 4-port MIMO omnidirectional ceiling mount antenna. It is designed to provide pattern coverage that is optimized for indoor requirements at 2300-2700 MHz and 4900-5950 MHz frequency bands. The individual antenna elements are designed to radiate a pattern that has been specifically shaped to provide optimal radiation within a coverage zone.

FEATURES

- Low Profile aesthetically neutral housing
- Mounts directly and easily to ceiling tile
- Performance optimized using Laird proprietary RF optimization tools
- Excellent flame retardancy rating
- Four radiating elements optimized for indoor applications
- RoHS compliant

MARKETS

- WLAN - 802.11n & 802.11ac
- Building Operators – offices & meeting rooms
- Hospitality – hotels & casinos
- Transportation – airport, bus, & train terminals
- Retail – stores & indoor pedestrian malls
- Education – libraries & museums

BENEFITS

- Provides MIMO/MUMIMO capabilities for multiband 802.11n and 802.11ac applications
- Optional antenna mounting kits are available to accommodate a variety of installation requirements
- Attractive, compact design and form factor ideal for indoor solution applications.

PARAMETER	SPECIFICATION			
Frequency Bands, MHz	2300-2400	2400-2500	2500-2700	4900-5950
Peak Gain, dBi (Typ)	4.4	4.5	4.5	5.4
Peak Gain, dBi (Max)	4.9	5.6	5.6	6.3
VSWR (Typ)	<1.4:1	<1.4:1	<1.8:1	<1.8:1
VSWR (Max)	<2:1	<2:1	<2:1	<2:1
Isolation, dB (Max)	< -17	< -18	< -18	< -24
Port 1->Port 2, dB (Typ)	< -19	< -19	< -19	< -26
Port 1->Port 3, dB (Typ)	< -20	< -21	< -22	< -24
Port 1->Port 4, dB (Typ)	< -20	< -21	< -22	< -25
Port 2->Port 3, dB (Typ)	< -20	< -20	< -21	< -25
Port 2->Port 4, dB (Typ)	< -19	< -20	< -20	< -25
Port 3->Port 4, dB (Typ)	< -19	< -21	< -21	< -26
Number of Ports	4			
Polarization	Linear Vertical			
Azimuth Pattern Beamwidth	Omnidirectional			
Power	10 Watts			
Dimensions (diameter x height)	17.8 cm x 3.2 cm (7" x 1.26")			
Weight	1.18 kg (2.60 lbs.)			
Operating Temperature	-30° C to +70° C (-22° F to 158° F)			
Storage Temperature	-40° C to +85° C (-40° F to 185° F)			
Radome	PC/ABS, UL94-V0, UV STABLE, WHITE			
Cable Type	UltraLink, Plenum Rated			

MODEL NUMBER	CABLE LENGTH	CONNECTOR
CMQ23496-75RSM	4x - 75mm	4x - RSMA Male
CMQ23496-91NF	4x - 91mm	4x - Type N Female
CMQ23496-91RTN	4x - 91mm	4x - RTNC Male

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com


Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com


2300 to 2700 MHz/4900 to 5950 MHz 4-port MIMO Ceiling Mount Antenna

RADIATION PATTERNS


Radiation Pattern at 2300 MHz



Radiation Pattern at 2400 MHz






Radiation Pattern at 2500 MHz






2300 to 2700 MHz/4900 to 5950 MHz 4-port MIMO Ceiling Mount Antenna




Radiation Pattern at 2700 MHz



Radiation Pattern at 4900 MHz




Radiation Pattern at 5400 MHz



2300 to 2700 MHz/4900 to 5950 MHz 4-port MIMO Ceiling Mount Antenna

Radiation Pattern at 5900 MHz



Americas: +1.847 839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

IAS-ANT-DS-CMQ23496_0617

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А