





Weidmüller terminal - SAK-series- are proved in millions of applications for more than 50 years.

Available for the two rail systems TS32 and TS35, the SAK terminals are useable for every application and for all cross-sections. SAK terminals fulfill the requirements of EN 60 947-7-1.




Thermosetting plastic or Thermoplastic


Terminal of thermosetting plastic are normally used in applications where high continuous service temperature and high flammability level are necessary. The Weidmüller thermosetting plastic KRG is very resistant against infection through mould and micro-organisms.

The thermoplastic material Polyamide 66 has very good electrical and mechanical properties upto 100°C. PA66 is flexible and unsusceptible to fracture, even with low temperatures.

Polyamid 66 has improved fire resistance and is self-extinguishing with flammability level V2 according to UL 94.



Thermosetting plastic




Cross-connection systems

40% of all terminals are cross-connected for potential branching.

Weidmüller distinguishes between the following cross-connection units for SAK-series:

- type Q pre-assembled cross-connections
- type QL permanent cross-connections
- type VL removeable cross-connection straps
- type QS removeable cross-connection plugs

Cross-connection systems from the SAK and AKZ series, type Q, QL or VL or other freely accessible live components, must be protected with appropriate covers ADP 1 or 4 or TSK 31.5 as long as they are to be inserted safe from contact.



Approvals


The following approvals apply to SAK terminals:

UL-USA	UL-USA
CSA-Canada	CSA-Canada
GOST-Russia	GOST-Russia
SEV-Switzerland	SEV-Switzerland
KEMA-Netherlands	KEMA-Netherlands
Lloyds Register of Shipping	Lloyds Register of Shipping
Germanischer Lloyd	Germanischer Lloyd
Det Norske Veritas	Det Norske Veritas

SAK portfolio

- Feed-through terminals
- Protective conductor terminals
- Fuse terminals
- Disconnect-test terminals
- Feed-through terminals with tab, solder, WireWrap and Termi Point connections
- Initiator terminals, Actuator terminals
- Stud terminals

Accessories



An extensive assortment of accessories is available for Weidmüller SAK terminals:

- Partitions
- Cover plates
- Small partitions
- Test plugs
- Test adapters
- Marking material
- Cross-connections and
- Covers

Positioning of end plates or partitions between cross-connections

Operating voltage	Terminal width (in mm)					
	≤ 6	≤ 8	10	12	18	22
125 V ~	AP	—	—	—	—	—
250 V ~	AP	—	—	—	—	—
380 V ~	AP	AP	—	—	—	—
440 V ~	TW	AP	AP	AP	AP	—
500 V ~	TW	TW	AP	AP	AP	—
660 V ~	TW	TW	TW	TW	TW	AP
750 V ~	TW	TW	TW	TW	TW	AP

In PA terminals small partitions (TSch) have to be used up to 380 V.

Feed-through terminals

SAKD 2.5 N SAKD 2.5/10/35



SAK 2.5/35 SAK 2.5/10/35



SAK 2.5 SAK 2.5/10



SAK 4/35 SAK 4/10/35



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

UL	CSA	LR	Q
5/32.5/43.5	5/44/38	10/M 2.5/3.5 x 0.6	
500 V/24 A/2.5 mm ²	6 kV/3	0.4...0.6	1

UL	CSA	LR	Q
6/45/40	10/M 2.5/3.5 x 0.6	800 V/24 A/2.5 mm ²	8 kV/3
6/45/40	10/M 2.5/3.5 x 0.6	0.4...0.6	1

UL	CSA	LR	Q	DNV
6/36.5/46.5	10/M 2.5/3.5 x 0.6	800 V/24 A/2.5 mm ² 3)	8 kV/3	0.4...0.6
6/36.5/46.5	10/M 2.5/3.5 x 0.6	800 V/24 A/2.5 mm ²	8 kV/3	1

UL	CSA	LR	Q
6.5/40/51.5	6.5/45/44	12/M 3/3.5 x 0.6	
800 V/32 A/4 mm ²	8 kV/3	0.5...1.0	2

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	0.5...2.5
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 2
Continuous current of terminal for conductor size		30 A/4 mm ²
Continuous current rating of cross-connection 2...5-pole	A	24
Continuous current rating of cross-connection 6...10-pole	A	24

0.5...6	0.5...2.5	0.5...4	0.5...2.5/4 ³⁾	A 3	32 A/4 mm ²	32
---------	-----------	---------	---------------------------	-----	------------------------	----

0.5...6	0.5...2.5	0.5...4	0.5...2.5/4 ³⁾	A 3	32 A/4 mm ²	32
---------	-----------	---------	---------------------------	-----	------------------------	----

0.5...6	0.5...2.5	0.5...4	0.5...2.5/4 ³⁾	A 3	32 A/4 mm ²	32
---------	-----------	---------	---------------------------	-----	------------------------	----

0.5...6	0.5...4	0.5...4	0.5...4	A 4	41 A/6 mm ²	36
---------	---------	---------	---------	-----	------------------------	----

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/20 A/28...12 AWG
Voltage/current/conductor size	CSA	300 V/20 A/22...12 AWG

300 V/20 A/28...12 AWG	600 V/25 A/26...10 AWG	600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG
------------------------	------------------------	------------------------	------------------------

600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG	600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG
------------------------	------------------------	------------------------	------------------------

600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG	600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG
------------------------	------------------------	------------------------	------------------------

600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG	600 V/20 A/22...12 AWG	600 V/25 A/26...10 AWG
------------------------	------------------------	------------------------	------------------------

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0215560000	100 0268860000 100
Blue PA	0215580000	100 0268880000 100
Orange PA		
Terminal block with marking PA	0401060000	10 0523160000 10
Terminal block without marking PA	0401160000	10

Cat. No.	Qty.	Qty.
0380420000	100	
0380470000	100	
0380460000 ¹⁾	100	
0380480000 ¹⁾	100	
0499460000 ¹⁾	10	
0499560000 ¹⁾	10	

Cat. No.	Qty.	Qty.
0279620000	100	
0279670000	100	
0279630000	100	
0279660000 ¹⁾	100	
0279680000 ¹⁾	100	
1326360000 ¹⁾	100	
0322560000 ¹⁾	10	
0322860000 ¹⁾	10	

Cat. No.	Qty.	Qty.
0279620000	100	
0279670000	100	
0279630000	100	
0279660000 ¹⁾	100	
0279680000 ¹⁾	100	
1326360000 ¹⁾	100	
0322560000 ¹⁾	10	
0322860000 ¹⁾	10	

Cat. No.	Qty.	Qty.
0443620000	100	
0443670000	100	
0443660000 ¹⁾	100	
0443680000 ¹⁾	100	
1326360000 ¹⁾	100	
0530460000 ¹⁾	10	
0530360000 ¹⁾	10	

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Blue KrG		
KrS		
PA	AP (1.5) 0150960000	20
Blue PA	AP (1.5) 0150980000	20
PA		
Blue PA		

Type	Cat. No.	Qty.
AP (1.5)	0279520000	20
AP (1.5)	0279570000	20
AP (1.5)	0279530000	20
AP (1.5)	0460560000	20
AP (1.5)	0460580000	20

Type	Cat. No.	Qty.
AP (1.5)	0279520000	20
AP (1.5)	0279570000	20
AP (1.5)	0279530000	20
AP (1.5)	0279560000	20
AP (1.5)	0279580000	20

Type	Cat. No.	Qty.
AP (1.5)	0279520000	20
AP (1.5)	0279570000	20
AP (1.5)	0279530000	20
AP (1.5)	0279560000	20
AP (1.5)	0279580000	20

Type	Cat. No.	Qty.
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117930000	20
AP (1.5)	0117960000	20
AP (1.5)	0117980000	20

Partition (thickness mm)

TW	WTW	
		KrG
		Blue KrG
		KrS
		PA
		Blue PA
		PA
		Blue PA

TW	WTW	
		KrG
		Blue KrG
		KrS
		PA
		Blue PA
		HP

TW	WTW	
		KrG
		Blue KrG
		KrS
		PA
		Blue PA
		HP

TW	WTW	
		KrG
		Blue KrG
		KrS
		PA
		Blue PA
		HP

TW	WTW	
		KrG
		Blue KrG
		KrS
		PA
		Blue PA
		HP

Small partition

TSch 1	
TSch 3	0366860000 100

TSch 1	0319160000 100
--------	----------------

TSch 1	0319160000 100
--------	----------------

TSch 1	0319160000 100
--------	----------------

TSch 1	0319160000 100
--------	----------------

Cross-connection

Q 4		
2-pole	Q 2	0367800000 50
3-pole	Q 3	0367900000 50
4-pole	Q 4	0368000000 50
10-pole	Q 10	0368100000 20

Q 2	0337000000 50
Q 3	0337100000 50
Q 4	0337200000 50
Q 10	0368700000 20

Q 2	0337000000 50
Q 3	0337100000 50
Q 4	0337200000 50
Q 10	0368700000 20

Q 2	0337000000 50
Q 3	0337100000 50
Q 4	0337200000 50
Q 10	0368700000 20

Q 2	0336700000 50
Q 3	0336800000 50
Q 4	0336900000 50
Q 10	0368800000 20

Cover plates

AD 4	0303400000 50
BSKM3x22	0128900000 100

AD 4	0303400000 50
BSKM3x22	0128900000 100

AD 4	0303400000 50
BSKM3x22	0128900000 100

AD 4	0303400000 50
BSKM3x22	0128900000 100

AD 4	0285300000 50
BSKM3x22	0128900000 100

Switchable cross-connection link

VL 2	BS	VH

VL 2	0197000000 100
VH	0285100000 50
BS	0292500000 100

VL 2	0197000000 100
VH	0285100000 50
BS	0292500000 100

VL 2	0197000000 100
VH	0285100000 50
BS	0292500000 100

VL 2	0197000000 100
VH	0285100000 50
BS	0292500000 100

Marking tags

Print	
1 2 3 4 5 6	DEK Standard

DEK 5	see "Accessories"
-------	-------------------

DEK 6	see "Accessories"
-------	-------------------

DEK 6	see "Accessories"
-------	-------------------

DEK 6.5	see "Accessories"
---------	-------------------


Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ Contact-proof with ADP 4 cover profile (see section "Accessories")
²⁾ Not suitable for SST 3 safety pin

³⁾ Cat. No. 0279660000, 0279680000, 0380460000 and 0380480000, 41 A for 6 mm²

Feed-through terminals


SAK 4 SAK 4/10



DK 4 Q* DKB4 Q*/10*



DK 4 DK4/35



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor

Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Technical data

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Version	Cat. No.	Qty.
KrG	0128320000	100
Blue KrG	0128370000	100
KrS	0128330000	100
PA	0128360000 ¹⁾ 2)100	
Blue PA	0128380000 ¹⁾ 2)100	
Orange PA	0105060000 ¹⁾ 2)100	
Terminal block with marking PA	0322660000 ¹⁾ 2) 10	
Terminal block without marking PA	0308860000 ¹⁾ 2) 10	

End plate (thickness mm)



Type	Cat. No.	Qty.
KrG	AP (1.5) 0117920000	20
Blue KrG	AP (1.5) 0117970000	20
KrS	AP (1.5) 0117930000	20
PA	AP (1.5) 0117960000	20
Blue PA	AP (1.5) 0117980000	20
PA		
Blue PA		

Partition (thickness mm)



KrG	TW (2.5) 0130120000	20
Blue KrG	TW (2.5) 0103170000	20
KrS	TW (2.5) 0130130000	20
PA	TW (1.5) 0130160000	20
Blue PA	TW (1.5) 0130180000	20
HP	TW (1.0) 0197100000	20

Small partition



TSch 1	0319160000	100
--------	------------	-----

Cross-connection



Q 2	0336700000	50
Q 3	0336800000	50
Q 4	0336900000	50
Q 10	0368800000	20
2-pole		
3-pole		
4-pole		

Dimensions/approvals

Width/length/height (mm)	6/54/60
Width/length/height (mm)	6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade	9/M 3/3.5 x 0.6

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	500 V/2 x 32 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data

Tightening torque range	0.5...1.0
Torque setting with electric screwdriver type DMS 2	2

Clampable conductor

Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	32 A/4 mm ²
Continuous current rating of cross-connection 2...5-pole	32
Continuous current rating of cross-connection 6...10-pole	32

Technical data

Voltage/current/conductor size	300 V/27 A/22...12 AWG
Voltage/current/conductor size	300 V/10 A/26...12 AWG

Ordering data

Qty.	Qty.	Qty.
0590060000 ¹⁾ 100	0590160000 ¹⁾ 100	0355460000 ¹⁾ 100
0590080000 ¹⁾ 100	0590180000 ¹⁾ 100	0355480000 ¹⁾ 100
1323860000 ¹⁾ 10		

End plate (thickness mm)

Type	Cat. No.	Qty.
AP (1.5)	1397160000	20
AP (1.5)	1397180000	20

Partition (thickness mm)

WTW (Ex)	1058800000	20
----------	------------	----


Small partition

TSch 6	0190260000	100
--------	------------	-----

Cross-connection


Q 2	0336400000	50
Q 3	0336500000	50
Q 4	0336600000	50
Q 10	0368600000	20
QB 2	0482700000 ^{**} 100	
QB 3	0482800000 ^{**} 50	
QB 4	0482900000 ^{**} 50	

Switchable cross-connection link



VL 2	0197000000	100
VH	0285100000	50
BS	0292500000	100

Marking tags



DEK Standard

DEK6.5 see "Accessories"

DEK6 see "Accessories"

DEK6 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* Accepts LS 2.8 shield lugs Cat. No. 1056400000

** 2.5 mm² conductor connection when using QB

1) Contact-proof cross-connec. with ADP 4 over profile (see "Accessories")


2) Not suitable for fuse pin SST 3

Feed-through terminals

DK4 QV*
DK4 QV/35*



SAK 6 N
SAK 6/10/35



SAK 10
SAK 10/10/35



SAK 16
SAK 16/35



Dimensions/approvals		 	   	   	   		
Width/length/height (mm)	with TS 32 	6/54/60	8/40/51.5	10/40/51.5	12/50/57.5		
Width/length/height (mm)	with TS 35 x 7.5 	6/54/60.5	8/45/44	10/45/44	12/50/50		
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6	12 mm/M 3.5/4.0 x 0.8	12 mm/M 4/5.5 x 1.0	15 mm/M 4/5.5 x 1.0		
Rated data according to IEC 60 947-7-1							
Rated voltage/current/cross-section		500 V/32 A/4 mm²	800 V/41 A/6 mm²	800 V/57 A/10 mm²	1000 V/76 A/16 mm²		
Rated impulse voltage/pollution severity		6 kV/3	8 kV/3	8 kV/3	8 kV/3		
Further technical data							
Tightening torque range		Nm 0.5...1.0	0.8...1.6	1.2...2.0 ³⁾	1.2...2.4		
Torque setting with electric screwdriver type DMS 2		2	3	4	4		
Clampable conductor							
Solid H07V-U	mm²	0.5...4	0.5...10	1.5...10	2.5...10		
Stranded H07V-R	mm²	0.5...4	0.5...6	2.5...16	4...16 ²⁾		
Flexible H07V-K	mm²	0.5...4	0.5...10	1.5...10	4...16		
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²						
With/without plastic insulating collar	mm²	0.5...4	0.5...6	1.5...10	4...16		
Plug gauge according to 60 947-7-1	Size	A 3	A 5	B 6	B 6		
Continuous current of terminal for conductor size		32 A/4 mm²		76 A/16 mm²			
Continuous current rating of cross-connection 2...5-pole	A	32	41	57	76		
Continuous current rating of cross-connection 6...10-pole	A	32					
Rated data according to UL/CSA							
Voltage/current/conductor size		UL 300 V/27 A/22...12 AWG	600 V/40 A/22...8 AWG	600 V/60 A/14...6 AWG ³⁾	600 V/80 A/12...4 AWG		
Voltage/current/conductor size		CSA 300 V/10 A/26...12 AWG	600 V/47 A/20...8 AWG	600 V/65 A/14...6 AWG ³⁾	600 V/87 A/10...4 AWG		
Ordering data		Version	Qty.	Qty.	Qty.		
		KrG					
	Blue KrG						
	KrS						
	PA	0590260000 ¹⁾ 1000363660000 ¹⁾ 100	0193260000 ¹⁾ 1000380560000 ¹⁾ 100	0110060000 ¹⁾ 1000443760000 ¹⁾ 100	0271060000 ¹⁾ 500380660000 ¹⁾ 50		
	Blue PA	0590280000 ¹⁾ 1000363680000 ¹⁾ 100	0193280000 ¹⁾ 1000380580000 ¹⁾ 100	0110080000 ¹⁾ 1000443780000 ¹⁾ 100	0271080000 ¹⁾ 500380680000 ¹⁾ 50		
	Orange PA						
	Terminal block with marking		0322760000 ¹⁾ 10	0553860000 ¹⁾ 10			
	Terminal block without marking		0308960000 ¹⁾ 10	0353160000 ¹⁾ 10			
End plate (thickness mm)		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
AP	KrG			AP (1.5) 0117920000 20	AP (1.5) 0117920000 20	AP (3.0) 0271120000 20	
	Blue KrG			AP (1.5) 0117970000 20	AP (1.5) 0117970000 20		
	KrS			AP (1.5) 0117930000 20	AP (1.5) 0117930000 20	AP (3.0) 0271130000 20	
	PA	AP (1.5) 1397160000 20	AP (1.5) 0117960000 20	AP (1.5) 0117960000 20	AP (1.5) 0117960000 20	AP (1.5) 0271160000 20	
	Blue PA	AP (1.5) 1397180000 20	AP (1.5) 0117980000 20	AP (1.5) 0117980000 20	AP (1.5) 0117980000 20	AP (1.5) 0271180000 20	
Partition (thickness mm)		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
TW	KrG			TW (1.5) 0130120000 20	TW (1.5) 0130120000 20	TW (3.0) 0281120000 20	
WTW	Blue KrG				TW (1.5) 0130170000 20		
Small partition	KrS			TW (1.5) 0130130000 20	TW (1.5) 0130130000 20	TW (3.0) 0281130000 20	
	PA	WTW (Ex) 1058800000 20	TW (1.5) 0130160000 20	TW (1.5) 0130160000 20	TW (1.5) 0130160000 20	TW (1.5) 0303660000 10	
	Blue PA		TW (1.5) 0130180000 20	TW (1.5) 0130180000 20	TW (1.5) 0130180000 20	TW (1.5) 0303680000 10	
		TW (2.0) 0607000000 20	TW (1.5) 0197100000 20	TW (1.5) 0197100000 20	TW (1.5) 0197100000 20	TW (2.0) 0607000000 20	
	TSch 6	TSch 6 0190260000 100	TSch 1 0319160000 100	TSch 1 0319160000 100	TSch 1 0319160000 100	TSch 1 0319160000 100	
Cross-connection		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
Q 4	2-pole	Q 2 0336400000 50	Q 2 0456700000 50	Q 2 0457100000 50	Q 2 0457500000 50		
QB 4	3-pole	Q 3 0336500000 50	Q 3 0456800000 50	Q 3 0457200000 50	Q 3 0457600000 50		
	4-pole	Q 4 0336600000 50	Q 4 0456900000 50	Q 4 0457300000 50	Q 4 0457700000 50		
	10-pole	Q 10 0368600000 20	Q 10 0457000000 20	Q 10 0457400000 20	Q 10 0457800000 20		
		QB 2 0482700000** 100					
		QB 3 0482800000** 50					
		QB 4 0482900000** 50					
Cover		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
		AD 4 0303400000 50	AD 4 0196600000 50	AD 4 0178600000 50	AD 4 0518200000 50		
		BSK M 2.5 x18	BSKM3x22 0128900000 100	BSKM3x22 0128900000 100	BSKM3x22 0128900000 100		
		0303300000 100					
Switchable cross-connection link		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
VL 2	VL 2	VL 2 04467000000 50	VL 2 0194700000 50	VL 2 0135900000 50	VL 2 0135800000 50		
BS	BS	VH 10565000000 100	VH 0285100000 50	VH 0285100000 50	VH 0285100000 50		
VH	VH	BS 03431000000 100	BS 0292500000 100	BS 0292500000 100	BS 0292500000 100		
Marking tags		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
 1 2 3 4 5 6	DEK	DEK 6	see "Accessories"	DEK 8	see "Accessories"	DEK 5	see "Accessories"
	Standard						
Mounting rails, end brackets, further marking material see "Accessories"							


* Accepts LS 2.8 shield lugs Cat. No. **1056400000**
** 2.5 mm² conductor connection when using QB

¹⁾ Contact-proof with ADP 4 cover profile (see section "Accessories")

²⁾ Tightening torque for 16 mm² stranded: 2 Nm

³⁾ Tightening torque for 16 mm² and AWG6: 2 Nm

Feed-through terminals

	SAK 35 N SAK 35 N/35	SAK 35 SAK 35/35	SAK 70 SAK 70/35	SAK 95 SAK 95/35				
								
Dimensions/approvals	 DNV	 DNV	 DNV	 DNV				
Width/length/height (mm)	16/58/67.5	18/58/67.5	22/75/79.5	28/83.5/100.5				
Width/length/height (mm)	16/63/60	18/58/60	22/75/87	28/83.5/96.5				
Insulation stripping length/clamping screw/screwdriver blade	18 mm/M 6/6.5 x 1.2	20 mm/M 6/6.5 x 1.2	24 mm/M 8/S 6 D911	30 mm/M 10/S 8 D6911				
Rated data according to IEC 60 947-7-1								
Rated voltage/current/cross-section	1000 V/125 A/35 mm ²	800 V/125 A/35 mm ²	1000 V/192 A/70 mm ²	1000 V/232 A/95 mm ²				
Rated impulse voltage/pollution severity	8 kV/3	8 kV/3	8 kV/3	8 kV/3				
Further technical data								
Tightening torque range	Nm							
Torque setting with electric screwdriver type DMS 2	4.0...5.0/4.0...6.0***	4.0...5.0/4.0...6.0***	6.0...12.0	10.0...20.0				
Clampable conductor								
Solid H07V-U	mm ²	6...16	16	10...16				
Stranded H07V-R	mm ²	2.5...50	16...70 ¹⁾	10...120 ²⁾				
Flexible H07V-K	mm ²	2.5...35	16...70 ¹⁾	10...95 ²⁾				
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	2.5...35	16...35	10...35				
Plug gauge according to 60 947-7-1	Size	B 8	B 11	B 12				
Continuous current of terminal for conductor size	125 A/35 mm ²	125 A/35 mm ²	192 A/70 mm ²	232 A/95 mm ²				
Continuous current rating of cross-connection 2...5-pole	A	65	180	180				
Continuous current rating of cross-connection 6...10-pole	A	65						
Rated data according to UL/CSA								
Voltage/current/conductor size	UL	600 V/100 A/12...2 AWG	600 V/145 A/4...2/0 AWG	600 V/190 A/6...3/0 AWG				
Voltage/current/conductor size	CSA	600 V/120 A/12...2 AWG	600 V/145 A/6...2 AWG	600 V/260 A/6...3/0 AWG				
Ordering data	Version	Qty.	Qty.	Qty.				
	KrG	0550620000 20 0608220000 20	0303520000 20					
	Hexagon socket KrG	0555720000 20 0608320000 20	0476520000 20	0550520000 10 0662220000 10				
	Hexagon socket Blue KrG	0608370000 20						
	KrS	0550630000 20	0303530000 20					
	Hexagon socket KrS	0555730000 20						
	PA	0550660000 20 0608260000 20	0303560000 20 0380760000 20					
	Hexagon socket PA	0555760000 20 0608360000 20	0476560000 20 0582460000 20					
	Blue PA		0303580000 20 0380780000 20					
End plate (thickness mm)	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.		
	KrG	AP (3.0)	0303620000 10	AP (3.0)	0303620000 10	AP (3.0)	0550920000 10	
	Blue KrG	AP (3.0)	0303670000 10	AP (3.0)	0303670000 10	AP (3.0)	0550970000 10	
	KrS	AP (3.0)	0303630000 10	AP (3.0)	0303630000 10			
	PA	AP (1.5)	0303660000 10	AP (1.5)	0303660000 10			
	Blue PA	AP (3.0)	0303680000 10	AP (3.0)	0303680000 10			
	Orange PA							
Partition (thickness mm)								
	KrG	TW (3.0)	0304320000 10	TW (3.0)	0304320000 10			
	Blue KrG							
	KrS	TW (3.0)	0304330000 10	TW (3.0)	0304330000 10			
	PA	TW (1.5)	0304360000 10	TW (1.5)	0304360000 10			
	Blue PA							
Cross-connection								
QL 3	VH	BS	SS	2-pole	QL 2	0564900000 50	QL 2	0551200000 10
				3-pole	QL 3	0565000000 50	QL 3	0407600000 10
				4-pole	QL 4	0565100000 50	QL 4	0407700000 10
				10-pole	QL 10	0565200000 20		
					VH 17	0267000000 50	VH 30.5	0345500000 20
					BS M 4x30	0267100000 50	BS M 5x45	0345600000 20
					SS M 4	0136400000 100	SS M 5	0346100000 100
Switchable cross-connection link								
VL 2	BS	VH			VL 2	0124000000 50		
					VH 24.5	0298700000 50		
					BS M 4x35	0298900000 50		
Cover / test plug								
					AD 4	0576700000 50	AD 3	0344300000 10
					BSKM 4x32	0129100000 50	BSKM 5x45	0344400000 50
					PS 4	0299600000 20	PS 4	0299600000 20
Marking tags								
	DEK	Standard	DEK 5	see "Accessories"	DEK 5	see "Accessories"	DEK 5	see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"								


SAK-series

Feed-through terminals for thermocouples

Busbars made from thermocouple materials
according to DIN IEC 584

SAK 2.5 TC


DK 4 Q/TC



Weidmüller's **thermocouple-terminals** are specially designed for transmitting the smallest voltages in temperature measuring circuits. Special busbars ensure that no false signals occur in the terminal when temperature differences exist in the positive and negative path.

This high measuring precision is necessary for, e.g. test beds, air craft engines, for complicated chemical processes, controls, etc.

I. Configuration of a temperature measuring circuit



- 1 Thermocouple (sensor) 4 Reference point
2 Thermocouple terminals 5 Supply conductors (to and from)
3 Compensation conductor 6 Measuring device

The thermocouple terminals displayed in this measurement circuit are used to thermoelectrically transmit thermal e.m.f. of the thermocouple to the reference point and indicating device via the thermocouple.

Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Technical data/VDE

Rated voltage/current/cross-section

Tightening torque range

Nm

6/36.5/49.5

10 mm/M 2.5/3.5 x 0.6

~2.5 mm²

0.4...0.6

6/54/59.5

6/54/60.5

9 mm/M 3/3.5 x 0.6

~4 mm²

0.5...1

Ordering data

Version Type

NiCr

Ni

CuNi

Fe

Cu

NiCr/Ni

Cu/CuNi

Fe/CuNi

Cat. No.

Qty.

0107260000

100

0107160000

100

0189860000

100

0190060000

100

0189960000

100

1284160000

100

1285660000

100

1284060000

100

End plate (thickness mm)



KrG

Blue KrG

KrS

PA

Blue PA

Orange PA

Type

Cat. No.

Qty.

AP (1.5)

0279560000

20

AP (1.5)

1397160000

20

Partition (thickness mm)



KrG

Blue KrG

KrS

PA

WEM

for TS 32 HP

Type

Cat. No.

Qty.

TW (1.5)

0302860000

20

TW (Ex)e

1058800000

20

TW HP (2.0)

0607000000

20

II. Symbols

Thermocouples according to IEC 584 DIN 43710

Terminal Busbar material trade name

a) Type J

Fe (positive leg)		Iron
CuNi (negative leg)		Constantan


b) Type T

Cu (positive leg)		Copper
CuNi (negative leg)		Constantan

c) Type K

NiCr (positive leg)		Chromel
Ni (negative leg)		Alumel

Marking tags



DEK

Print

Standard

DEK 6

see "Accessories"

DEK 6

see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

SAK-series

Feed-through terminals

Terminals/Accessories

SAKG 28 I


SAKG 28 II




The Weidmüller SAKG range offers the following connection variants:

- clamping yoke/flat lug as a combination, Version I.
- flat lug, Version II.
Two types of threading are provided here.
a) screw set with lock nut
b) with thread in busbar
- clamping yoke connection, Version III.
The stripped conductor can be connected without further preparation.

Versions




Version I




Version II

without thread



Version II G

with thread




Version III

Cables with cable lugs are connected to SAKG terminals of Version I and to SS stud terminals.

Fitting instructions for SAKG terminals

When tightening the clamping screw, it is recommended that the conductor be held against the direction of tightening to prevent deformation of the mounting rail and so as not to place the terminal foot under undue torsional forces.



Cover

To ensure shock protection following connections of **conductors**, AH covers can be clipped onto the terminal.

Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor

Solid H07V-U	mm²
Stranded H07V-R	mm²
Flexible H07V-K	mm²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Type	KrG
------	-----



28/70/63.5

15 mm/M 6/-

1000 V~/125 A/35 mm²

8 kV/3

3...6

6...35

6...35

10...35

6...35

B 9

125 A/35 mm²

(QL 2) 125

600 V/95 A/2 AWG

600 V/110 A/6...1 AWG

Cat. No. Qty.

0170020000 10



28/70/53

-/M 6/-

1000 V~/125 A/35 mm²

8 kV/3

3...6

6...35

6...35

10...35

6...35

B 9

125 A/35 mm²

(QL 2) 125

600 V/115 A/2 AWG

600 V/110 A/6...1 AWG

Cat. No. Qty.

0170320000 10

End plate, hard paper

0205100000	
0205200000	tropic-proof



0180700000, 0205300000

0180800000, 0205400000 tropic-proof



Partition, hard paper (thickness in mm)

0151400000	
0164600000	tropic-proof



0177100000 B/L/H (incl. TS 32) mm

0179900000 B/L/H (incl. TS 35) mm



Cross-connection

2-pole	QL 2	0193900000	5
3-pole	QL 3	0407600000	5
4-pole	QL 4	0407700000	5



Cover

AH 28	0326660000	5
-------	------------	---



Marking tags

1	2	3	4	5	6	DEK	Standard
---	---	---	---	---	---	-----	----------

Mounting rails, end brackets, further marking material see "Accessories"

During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

Feed-through terminals

SAKG 28 II G



28/70/53
-/M 6/-
1000 V*/125 A/35 mm ²
8 kV/3
3...6
125 A/35 mm ²
(QL 2) 125

	Cat. No.	Qty.
	0185020000	10

	Cat. No.	Qty.
EP 1 (2)	0205100000	10
EP 1 (2)	0205200000	10

	Cat. No.	Qty.

	Cat. No.	Qty.
TW 1 (2)	0151400000	10
TW 1 (2)	0164600000	10

2/120/75.5

QL 2	0193900000	5
QL 3	0407600000	5
QL 4	0407700000	5

AH 28	0326660000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 28 III



28/70/63.5
15 mm/M 6/-
1000 V*/125 A/35 mm ²
8 kV/3
3...6
6...35
6...35
10...35
6...35
B 9
125 A/35 mm ²

600 V/95 A/2 AWG		
600 V/135 A/8...2 AWG		
	Cat. No.	Qty.
	0170820000	10

	Cat. No.	Qty.
EP 1 (2)	0205100000	10
EP 1 (2)	0205200000	10

	Cat. No.	Qty.

	Cat. No.	Qty.
TW 1 (2)	0151400000	10
TW 1 (2)	0164600000	10

2/120/75.5

AH 28	0326660000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 I SAKG 32/35 I



32/87/84
32/87/84.5
26 mm/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
10...70
10...70
10...70
10...35
B 11
150 A/50 mm ²
(QL 2) 150

600 V/165 A/3 AWG			
600 V/170 A/1...2/0 AWG			
	Qty.		Qty.
0286620000	0637120000	10	

	Cat. No.	Qty.
EP 1 (2)	0205300000	10
EP 1 (2)	0205400000	10

	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

	Cat. No.	Qty.
TW 2 (2)	0177100000	10
TW 2 (2)	0179900000	10

2/160/90.5
2/160/90.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 II SAKG 32/35 II



32/80/53
32/80/51
-/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
150 A/50 mm ²
(QL 2) 150

600 V/200 A/3 AWG			
600 V/170 A/1...2/0 AWG			
	Qty.		Qty.
	10		10

	Cat. No.	Qty.
EP 1 (2)	0205100000	10
EP 1 (2)	0205200000	10

	Cat. No.	Qty.
EP 1/35 (2)	0180700000	10
EP 1/35 (2)	0180600000	10

	Cat. No.	Qty.
TW 1 (2)	0151400000	10
TW 1 (2)	0164600000	10

2/120**/75.5
2/120**/75.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 II G SAKG 32/35 II G



32/80/53
32/80/53
-/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
150 A/50 mm ²
(QL 2) 150

600 V/170 A/1...2/0 AWG			
			Qty
0185120000	10	0637420000	10

	Cat. No.	Qty.
EP 1 (2)	0205100000	10
EP 1 (2)	0205200000	10

	Cat. No.	Qty.
EP 1/35 (2)	0180700000	10
EP 1/35 (2)	0180600000	10

	Cat. No.	Qty.
TW 1 (2)	0151400000	10
TW 1 (2)	0164600000	10


2/120**/75.5
2/120**/75.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 III SAKG 32/35 III



32/94/84
32/94/84.5
26 mm/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
10...70
10...70
10...70
10...35
B 11
150 A/50 mm ²

600 V/165 A/3 AWG			
600 V/185 A/1...2/0 AWG			
	Qty.		Qty.
0286720000	10	0637220000	10

	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

	Cat. No.	Qty.
TW 2 (2)	0177100000	10
TW 2 (2)	0179900000	10

2/160/90.5
2/160/90.5

































AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAK-series

* During conductor connection, observe clearance and creepage distances. Insert partitions if necessary
 ** For Cat. No. **0180600000** and **0180700000**: length = 160 mm.

Feed-through terminals

	SAKG 70 II G SAKG 70/35 II G	SAKG 40 I SAKG 40/35 I	SAKG 40 II SAKG 40/35 II	SAKG 40 II G SAKG 40/35 II G
				
Dimensions/approvals	 DNV		 DNV	
Width/length/height (mm) with TS 32	32/84/54	40/95/84	40/90/53	40/90/55
Width/length/height (mm) with TS 35 x 7.5	32/84/53	46/95/85.5	46/90/53	46/90/55
Insulation stripping length/clamping screw/screwdriver blade	~M 8/-	27 mm/M 10/-	~M 10/-	~M 10/-
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section	1000 V*/192 A/70 mm ²	1000 V*/232 A/95 mm ²	1000 V*/232 A/95 mm ²	1000 V*/232 A/95 mm ²
Rated impulse voltage/pollution severity	8 kV/3	8 kV/3	8 kV/3	8 kV/3
Further technical data				
Tightening torque range Nm	6...12	10...20	10...20	10...20
Torque setting with electric screwdriver type DMS 2				
Clampable conductor				
Solid H07V-U mm ²		10...95		
Stranded H07V-R mm ²		10...95		
Flexible H07V-K mm ²		10...95		
Flexible H07V-K and ferrule according to DIN 46 228/1 mm ²		10...35		
Plug gauge according to 60 947-7-1 Size		B 12		
Continuous current of terminal for conductor size	192 A/90 mm ²	232 A/95 mm ²	232 A/95 mm ²	232 A/95 mm ²
Continuous current rating of cross-connection 2...5-pole A	(QL 2) 192	(QL 2) 232	(QL 2) 232	(QL 2) 232
Continuous current rating of cross-connection 6...10-pole A				
Rated data according to UL/CSA				
Voltage/current/conductor size UL		600 V/195 A/4/0 AWG	600 V/230 A/4/0 AWG	600 V/230 A/4/0 AWG
Voltage/current/conductor size CSA	600 V/200 A/2/0...4/0 AWG	600 V/250 A/2/0...4/0 AWG	600 V/250 A/2/0...4/0 AWG	600 V/250 A/2/0...4/0 AWG
Ordering data Version				
KrG	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.
	0150420000 10 0636620000 10	0286820000 10 0637520000 5	0170520000 10 0637720000 5	0185220000 10 0637820000 5
End plate, hard paper (thickness mm)				
 0205100000, 0180500000	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.
0205200000, 0180600000 tropic-proof	EP 1 (2) 0205100000 10 EP 1 (2) 0205200000 10	EP 2 (2) 0205300000 10 EP 2 (2) 0205400000 10	EP 2 (2) 0205300000 10 EP 2 (2) 0205400000 10	EP 2 (2) 0205300000 10 EP 2 (2) 0205400000 10
 0180700000, 0205300000	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.	 Cat. No. Qty.  Cat. No. Qty.
0180800000, 0205400000 tropic-proof	EP 1/35 (2) 0180500000 10 EP 1/35 (2) 0180600000 10	EP 2/35 (2) 0180700000 10 EP 2/35 (2) 0180800000 10	EP 2/35 (2) 0180700000 10 EP 2/35 (2) 0180800000 10	EP 2/35 (2) 0180700000 10 EP 2/35 (2) 0180800000 10
Partition, hard paper (thickness mm)				
 0151400000	 Qty.  Qty.	 Qty.  Qty.	 Qty.  Qty.	 Qty.  Qty.
0164600000 tropic-proof	TW 1 (2) 0151400000 10 TW 1 (2) 0164600000 10	TW 2 (2) 0177100000 10 TW 2 (2) 0179900000 10	TW 2 (2) 0177100000 10 TW 2 (2) 0179900000 10	TW 2 (2) 0177100000 10 TW 2 (2) 0179900000 10
 0177100000 B/L/H (incl. TS 32) mm	2/120/75.5	2/160/90.5	2/160/90.5	2/160/90.5
0179900000 B/L/H (incl. TS 35) mm	2/120/75.5	2/160/90.5	2/160/90.5	2/160/90.5
Cross-connection				
 2-pole, QL 2	 Qty.  Qty.	 Qty.  Qty.	 Qty.  Qty.	 Qty.  Qty.
 3-pole, QL 3	0194000000 10 0194100000 10	0263500000 10 0444900000 10	0263500000 10 0444900000 10	0263500000 10 0444900000 10
 4-pole, QL 4	0441500000 10 0441600000 10	0409800000 10 0445000000 10	0409800000 10 0445000000 10	0409800000 10 0445000000 10
Cover				
 AH 32	0326760000 5	AH 40 0326860000 5	AH 40 0326860000 5	AH 40 0326860000 5
Marking tags				
 1 2 3 4 5 6 DEK Standard	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

*During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

Feed-through terminals

SAKG 40 III
SAKG 40/35 III



	  	(B)
40/100/84		
46/100/85.5		
27 mm/M 10/-		
1000 V~/232 A/95 mm ²		
8 kV/3		
10...20		
10...95		
10...95		
10...95		
10...35		
B 12		
232 A/95 mm ²		
600 V/195 A/4/0 AWG		
600 V/230 A/2/0...4/0 AWG		
	Qty.	 Qty.
0286920000	10	0637620000 5
	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10
	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10
	+ 	Qty.
TW 2 (2)	0177100000	10
TW 2 (2)	0179900000	10
2/160/90.5		
2/160/90.5		
AH 40	0326860000	5
DEK 5	see "Accessories"	

SAKG 46 II
SAKG 46/35 II




			
46/106/55			
46/106/54.5			
-/M 12/-			
1000 V~/309 A/150 mm ²			
8 kV/3			
14...31			
309 A/150 mm ²			
600 V/285 A/4/0 AWG			
600 V/365 A/300 MCM			
	Qty.	 Qty.	
0170620000	10	0637920000	5
	Cat. No.		Qty.
EP 2 (2)	0205300000	10	
EP 2 (2)	0205400000	10	
	Cat. No.		Qty.
EP 2/35 (2)	0180700000	10	
EP 2/35 (2)	0180800000	10	
	Cat. No.		Qty.
TW 2 (2)	0177100000	10	
TW 2 (2)	0179900000	10	
2/160/90.5			
2/160/90.5			
QL 2	0247000000	5	
QL 3	0444400000	5	
QL 4	0444500000	5	
AH 46	0326960000	5	
DEK 5	see "Accessories"		

SAKG 46 II G
SAKG 46/35 II G




46/106/57.5		
46/106/57		
-/M 12/-		
1000 V~/309 A/150 mm ²		
8 kV/3		
14...31		
309 A/150 mm ²		
(QL 2) 309		
600 V/285 A/4/0 AWG		
600 V/365 A/300 MCM		
	Qty.	 Qty.
0185320000 10 0638020000 5		
	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10
	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10
	Cat. No.	Qty.
TW 2 (2)	0177100000	10
TW 2 (2)	0179900000	10
2/160/90.5		
2/160/90.5		
QL 2	0247000000	5
QL 3	0444400000	5
QL 4	0444500000	5
AH 46		
0326960000		
DEK 5		
see "Accessories"		

SAKG 54 II
SAKG 54/35 II



			
54/122/57			
54/122/57			
-/M 16/-			
1000 V~/415 A/240 mm ²			
8 kV/3			
25...60			
415 A/240 mm ²			
(QL 2) 415			
600 V/380 A/500 MCM			
600 V/600 A/300...500 MCM			
	Qty.		Qty.
0170720000	10	0638120000	5
			
Cat. No.			
Qty.			
EP 2 (2)	0205300000	10	
EP 2 (2)	0205400000	10	
			
Cat. No.			
Qty.			
EP 2/35 (2)	0180700000	10	
EP 2/35 (2)	0180800000	10	
			
Cat. No.			
Qty.			
TW 2 (2)	0177100000	10	
TW 2 (2)	0179900000	10	
2/160/90.5			
2/160/90.5			
QL 2			
0264400000			
5			
QL 3			
0408000000			
5			
QL 4			
0247400000			
5			
DEK 5			
see "Accessories"			

SAKG 54 II G
SAKG 54/35 II G

[illegible]

SAKG 46/I AL
SAKG 46/II AL



46/112/74		
23 mm/M 12/M 14/-		
1000 V*/309 A/150 mm ²		
8 kV/3		
14...31/25...40		
50...240		
35...185		
 Qty.  Qty.		
1287920000** 5		
 Cat. No. Qty.		
EP 2 (2) 0205300000 10		
EP 2 (2) 0205400000 10		
 Cat. No. Qty.		
		
Qty.		
TW 2 (2) 0177100000 10		
TW 2 (2) 0179900000 10		
2/160/90.5		
2/160/90.5		
QL 2 0194000000 5		
QL 3 0441500000 5		
QL 4 0441600000 5		
AH 46 0326960000 5		
DEK 5 see "Accessories"		

SAK-series

** Suitable for connection of 1 aluminium conductor of max 185 mm²


*** Suitable for connection of 2 aluminium conductors of max. 185 mm²

Stud terminals

* Depends on cable lug 1) with partition 2) Left AP is required only once at beginning of terminal strip


Stud terminals

KST 10
KST 10/35



	
34/60/82	34/60/82
34/62.5/74.5	34/62.5/74.5
-/M 10/-	-/M 12/-
1000 V ¹⁾ /192 A/70 mm ²	1000 V ¹⁾ /232 A/95 mm ²
8 kV/3	8 kV/3
10...20	14...31
207 A/70 mm ²	250 A/95 mm ²
200	200
600 V/175 A/12...2/0	600 V/200 A/12...3/0
 Qty.  Qty.	 Qty.  Qty.
9501330000 20	
9506960000 20	9506970000 20
9528330000 20	9528340000 20
 + 	 + 
TW right 1718530000 10	TW right 1718530000 10
TW left 1752800000 10	TW left 1752800000 10
2/160/83.5	2/160/83.5
2/160/78.5	2/160/78.5
QL 2 9501370000 1	QL 2 9501380000 1
DEK 5 see "Accessories"	DEK 5 see "Accessories"

PE terminals

		EK 2.5 N EK 2.5/35	EK 4 EK 4/35	EK 6/35	EK 10 EK 10/35									
														
Dimensions/approvals		 	  	 	 									
Width/length/height (mm)	with TS 32 	6/36.5/49.5	8/40/51.5		10/40/51.5									
Width/length/height (mm)	with TS 35 x 7.5 	6/56/40	6.5/56/44	8/56/44	10/56/44									
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6	12 mm/M 3/3.5 x 0.6	12 mm/M 3.5/4.0/0.8	12 mm/M 4/5.5 x 1.0									
Rated data according to IEC 60 947-7-2														
Rated voltage/current with PEN/cross-section		-/-/2.5 mm ²	-/-/4 mm ²	-/-/6 mm ²	-/-/10 mm ²									
Rated voltage/rated impulse voltage acc. to VDE 0110/1.89/ pollution severity														
Further technical data														
Tightening torque range	Nm	0.4...0.8/0.5...1.0*	0.5...1.0/0.5...1.0*	1.2...1.6/0.5...1.0*	1.2...2.4/0.5...1.0*									
Clampable conductor														
Solid H07V-U	mm ²	0.5...4	0.5...6	0.5...10	0.5...10									
Stranded H07V-R	mm ²	0.5...2.5	0.5...4	1.5...6	1.5...6									
Flexible H07V-K	mm ²	0.5...4	0.5...4	0.5...10	0.5...10									
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...2.5	0.5...4	0.5...6	0.5...10									
Cable AWG	Nr.	22...14	22...10	20...8	20...8									
Plug gauge according to 60 947-7-1	Size	A 3	A 4	A 5	B 6									
Ordering data														
	Version	 Qty.  Qty.	 Qty.  Qty.	 Qty.	 Qty.  Qty.									
	Green/yellow PA	0474360000 100 0661060000 100	0354560000 100 0661160000 100	0661260000 100	0354660000 80 0661360000 100									
	Blank													
	Two clamping yokes blank													
	Hexagon socket blank													
Support block														
	For insulation of mounting rails in insulated-earth installations	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	
		SH 2	0494920000	10	SH 2	0494920000	10	SH 2	0494920000	10	SH 2	0494920000	10	
SK - key, 8mm														
Marking tags														
		DEK	Standard	DEK 6	see "Accessories"	DEK 6.5	see "Accessories"	DEK 8	see "Accessories"	DEK 5	see "Accessories"			
Mounting rails, end brackets, further marking material see "Accessories"														

* For centre screw

PE terminals

EK 16
EK 16/35



UL	CE
12/50/57.5	
12/56/50	
16 mm/M 4/5.5 x 1.0	
-/-/16 mm²	

1.2...2.4/0.8...1.0*

2.5...16

2.5...16

2.5...16

4...16

12...6

B 6

	Qty.		Qty.
0374660000	50	0190160000	50

Type	Cat. No.	Qty.
SH 2	0494920000	10

DEK 5 see "Accessories"

EK 35**
EK 35/35



UL	CE
18/58/67.5	
16/58/60	
20 mm/M 6/6.5 x 1.2	
-/-/35 mm²	

2.5...5.0/ **

6...16

16...50

10...35

10...35

10...2

B 9

	Qty.		Qty.
0354760000	20	0661460000	20

Type	Cat. No.	Qty.
SH 2	0494920000	10

DEK 5 see "Accessories"

EK 2



CE	
10/52/38	
14 mm/M 4/-	
-/-/10	

1.2...2.4/2.0...4.0*

1.5...10

1.5...10

1.5...10

1.5...10

16...8

B 6

	Qty.
0323100000	20

Type	Cat. No.	Qty.
------	----------	------

SAKE 35



CE	
14/46/39	
16 mm/M 6/-	
-/-/35 mm²	

2.5...5.0/2.0...4.0*

6...35

6...35

6...16

10...35


8...2

B 8

	Qty.	Qty.
0144400000	20	

Type	Cat. No.	Qty.
SH 2	0494920000	10

SAKE 70



CE	
18/94/59.5	
25 mm/M 8/-	
-/-/70 mm²	

6.0...12/2.0...4.0*

10...70

10...70

10...70

10...70

6...0

B 10

	Qty.		Qty.
0213200000	20		
1338300000	10		

Type	Cat. No.	Qty.
SH 2	0494920000	10

EK 95/35



25/76/100/92	
25/76/100/92	
27 mm/M 10/-	
-/-/95 mm²	

10.0...20.0/1.2...2.4*

10...120

10...95

10...95

10...95

6...4/0

B 12

			Qty.


0235000000

SAK-series


** ADm f. EK 35/35 = 1.2 - 2.4 Nm
ADm f. EK 35 = 0.8 - 1.6 Nm

Fuse terminals

ASK 1¹⁾
ASK 1/35¹⁾



KDKS 1¹⁾
KDKS 1/35¹⁾




SAKS 1
SAKS 1/35



SAKS 1/G25
SAKS 1/35/G25



Dimensions/approvals		UL  	UL 	UL   	 		
Width/length/height (mm)	with TS 32 	8/58/45.5	8/73.5/59,8	13/54/61	13/54/61		
Width/length/height (mm)	with TS 35 x 7.5 	8/58/44	8/73.5/55,7	13/54/54	13/54/54		
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	12 mm/M 4/5.5 x 1.0	12 mm/M 4/5.5 x 1.0		
Rated data/feed through-terminal base							
Rated voltage/current/cross-section		500 V/6.3 A ² /4 mm ²	500 V/6.3 A/4 mm ²	500 V/6.3 A ³ /10 mm ²	500 V/6.3 A ³ /10 mm ²		
Rated impulse voltage/pollution severity		6 kV/3	6 kV/3	6 kV/3	6 kV/3		
Further technical data							
Tightening torque range		Nm 0.5...1.0	0.5...1.0	1.2...2.4	1.2...2.4		
Torque setting with electric screwdriver type DMS 2		2	2	4	4		
Clampable conductor							
Solid H07V-U	mm ²	0.5...4	0.5...4	0.5...16	0.5...16		
Stranded H07V-R	mm ²	1.5...4		1.5...10	1.5...10		
Flexible H07V-K	mm ²	0.5...4	0.5...4	0.5...10	0.5...10		
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4	0.5...4	0.5...10	0.5...10		
Plug gauge according to 60 947-7-1	Size	A 3	A 4	B 6	B 6		
Continuous current rating of cross-connection 2...5-pole	A	(QB 2...4) 10	(QB 2...4) 10	(QL 2...5) 47	(QL 2...5) 47		
Continuous current rating of cross-connection 6...10-pole	A			(QL 6...10) 36	(QL 6...10) 36		
Rated data according to UL/CSA							
Voltage/current/conductor size	UL	300 V/6.3 A/12 max. AWG	300 V/15 A/12 max. AWG	300 V/6.3 A/22...10 AWG			
Voltage/current/conductor size	CSA	300 V/6.3 A/26...12 AWG		600 V/10 A/26...10 AWG	600 V/10 A/26...10 AW		
Ordering data		Version	 Qty.	 Qty.	 Qty.		
		PA	0474560000 100	9503300000 50 9503310000 50			
		KrG			0191220000 20 0501620000 20		
		Beige Wemid			0191120000 20 0501520000 20 0501500000 20		
End plate/partition (thickness mm)		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
		AP (1.5)	0380360000	20	AP 1 KDKS	9503330000	25
					Wemid	9532470000	25
					for  TW (2.0)		
						0607000000	20
G-fuse inserts		5 x 20 mm			5 x 20 mm		
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1) rated current (A):		0.10 fast	0430300000	10	0430300000	10	0430300000 10
Rated voltage 250 V		0.20 fast	0430400000	10	0430400000	10	0430400000 10
Fast switching capacity 1500 A		0.25 fast	0430500000	10	0430500000	10	0430500000 10
(at 250 V, 50 Hz, cos φ = 0.7)		0.50 fast	0430600000	10	0430600000	10	0430600000 10
		1.0 fast	0430700000	10	0430700000	10	0430700000 10
		1.6 fast	0430800000	10	0430800000	10	0430800000 10
		2.0 fast	0430900000	10	0430900000	10	0430900000 10
		2.5 fast	0431000000	10	0431000000	10	0431000000 10
		3.15 fast					
		4.0 fast					
		5.0 fast					
		6.3 fast					
		Contact sleeve	0553300000	100	0553300000	100	
Screw cap/disconnector lever (spare)							
		TH	0377060000	100	TH	0377060000	100
		SIHA	1593020000	100	SIHA	1593020000	100
Marking tags		Red pull lever					
		Print					
		DEK	Standard	DEK 8	see "Accessories"	DEK 5	see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"							

¹⁾ Multipole interruptable with group marking carrier
Sch2 2-pole Cat. No. **1359500000**, 1000 mm Cat. No. **0337400000**

Fuse terminals

KSKM 1 KSKM 1/35



13/69/62
13/69/63
12 mm/-/-
250 V/6.3 A ¹⁾ /10 mm ²

0.5...16
0.5...10
B 6

600 V/10 A/22...8 AWG

Qty. Qty.

9509570000 20 9509600000 20


Type	Cat. No.	Qty.
AP (3)	9509630000	20

5 x 20 mm
0.10 (f) 0430300000 10
0.20 (f) 0430400000 10
0.25 (f) 0430500000 10
0.50 (f) 0430600000 10
1.00 (f) 0430700000 10
1.60 (f) 0430800000 10
2.00 (f) 0430900000 10
2.50 (f) 0431000000 10
3.15 fast 0431100000 10
4.0 fast 0431200000 10
5.0 fast 0431300000 10
6.3 fast 0431400000 10

5 x 20 SBL 0446100000 40

DEK 5 see "Accessories"

KSKM 2 KSKM 2/35



13/69/62
13/69/63
12 mm/-/-
250 V/13 A ²⁾ /10 mm ²

0.5...16
0.5...10
B 6

600 V/15 A/22...8 AWG

Qty. Qty.

9509580000 20 9509610000 20

Type	Cat. No.	Qty.
AP (3)	9509630000	20

1 x 1/4"
1 x 1/4" SBL 0446200000 40

DEK 5 see "Accessories"

KSKM 3 KSKM 3/35



13/69/62
13/69/63
12 mm/-/-
440 V/10 A/10 mm ²

0.5...16
0.5...10
B 6

600 V/15 A/22...8 AWG

Qty. Qty.

9509620000 20

Type	Cat. No.	Qty.
AP (3)	9509630000	20

1 1/4 x 1/4"
E 2 A 0294500000 10
E 3 A 0295700000 10
E 5 A 0294600000 10
E 7 A 0295800000 10
E 10 A 0293900000 10


1 1/4 x 1/4" SBL 0446300000 40

DEK 5 see "Accessories"

¹⁾ Max. fuse rating according to DIN 41 660, IEC 127 CEE4 Type 1
²⁾ Fuse according to BS 1362

Fuse terminals

SAKS 3
SAKS 3/35



SAKS 4
SAKS 4/35



SAKS 5
SAKS 5/35



SAKS 2
SAKS 2/35



Dimensions/approvals		  	 	 	  
Width/length/height (mm)	with TS 32 	13/54/61	24/75/73	28/80/80.5	28/80/81.5
Width/length/height (mm)	with TS 35 x 7.5 	13/54/55	24/75/66	28/80/66	28/80/75
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 4/5,5 x 1	14 mm/M 4/5,5 x 1	13 mm/M 4/5,5 x 1	12 mm/M 4/5,5 x 1
Rated data/feed through-terminal base					
Rated voltage/current/cross-section		500 V/10 A/10 mm ²	400 V**/16 A/10 mm ²	400 V/63 A**/16 mm ²	500 V/10 (25) A**/10 mm ²
Rated impulse voltage/pollution severity		6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range	Nm	1.2...2.4	1.2...2.4	1.2...2.4	1.2...2.4
Torque setting with electric screwdriver type DMS 2		4	4	4	4
Clampable conductor					
Solid H07V-U	mm ²	0.5...16	0.5...16	1.5...16	0.5...16
Stranded H07V-R	mm ²	1.5...10	1.5...10	1.5...16	0.5...10
Flexible H07V-K	mm ²	0.5...10	0.5...10	1.5...16	0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...10	0.5...10	1.5...16	0.5...10
Plug gauge according to 60 947-7-1	Size	B 6	B 6	B 7	B 6
Continuous current rating of cross-connection 2...5-pole	A	(QL 2...5) 47	(QL 2...5) 47	(QL 2...5) 47	(QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A	(QL 6...10) 36	(QL 6...10) 36	(QL 6...10) 36	(QL 6...10) 36

Rated data according to UL/CSA									
Voltage/current/conductor size	UL	300 V/10 A/22...10 AWG							
Voltage/current/conductor size	CSA	600 V/10 A/22...10 AWG		600 V/30 A/22...8 AWG		600 V/63 A/14...6 AWG		600 V/25 A/22...8 AWG	
Ordering data	Version		Qty.		Qty.		Qty.		Qty.

KrG	<u>0248920000³⁾ 20 0667520000³⁾ 20</u>	<u>0321320000 20 0501820000 20</u>	<u>0359420000 20 0502120000 20</u>	<u>0206820000 20 1368720000 20</u>
KrG	<u>0297520000⁴⁾ 20 0328920000⁴⁾ 20</u>			

[illegible]

Cross-connection							
			QL 2	0328000000	20	QL 2	0207800000 20
			QL 3	0328100000	20	QL 3	0207900000 20
			QL 4	0328200000	20	QL 4	0208000000 20
			QL 10	0339000000	20	QL 10	0338900000 20

Fixing screws for cross-connections					BS M 4x9	0103300000	100	BS M 4x9	0103300000	100	BS M 4x9	0103300000	100		
Fuse inserts			Fuse insert		Gauge ring			Gauge ring			Gauge ring				
					Amp. Colour	Cat. No.	Qty.	Amp. Colour	Cat. No.	Qty.	Amp. Colour	Cat. No.	Qty.		
1 1/4" x 1/4"	Nominal current (A): 0.5 fast	E 0.5 A	0533800000		P 14/2	pink	0138000000	50							
	1.0 fast	E 1 A	0525500000		P 14/4	brown	0138100000	50				P 16/10	red 0208900000	100	
	2.0 fast	E 2 A	0294500000		P 14/6	green	0328600000	50				P 16/16	grey 0209000000	100	
	3.0 fast	E 3 A	0295700000		P 14/10	red	0328700000	50	P 18/20	Blue	0361800000	50	P 16/20	Blue 0209100000	100
	5.0 fast	E 5 A	0294600000						P 18/25	yellow	0361900000	50			
	7.0 fast	E 7 A	0295800000						P 18/35	black	0362000000	50			
	10.0 fast	E 10 A	0293900000						P 18/50	white	0362100000	50			

G fuse inserts 5 x 30 mm
(500 V~/0.032...6.3 A).
Available from Wickmann-Werke GmbH,
Annstr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts	Rated voltage 400 V				Rated voltage 400 V				Rated voltage 500 V			
	E 14/2		0137400000	10	E 18/20		0361300000	10	E 10 A		0208500000	25
	E 14/4		0137500000	10	E 18/25		0361400000	10	E 16 A		0208600000	25
	E 14/6		0328300000	10	E 18/35		0361500000	10	E 20 A		0208700000	25
	E 14/10		0328400000	10	E 18/50		0361600000	10	E 25 A		0208800000	25

[illegible]

Marking tags		Print		Accessories		Accessories		Accessories	
1	2 3 4 5 6	DEK	Standard	DEK 5	see "Accessories"	DEK 5	see "Accessories"	DEK 5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

*only for TS 32

*** Current for overload up to 10 A, for short circuit up to 25 A

3) For fuse inserts 1 1/4 x 1/4" DEF 63
4) For fuse inserts 5 x 30

Fuse terminals

SAKS 4 USA



UL
24/75/73
24/75/66
14 mm/M 4/5.5 x 1
400 V/30 A/10 mm ²
6 kV/3
1.2...2.4
4
0.5...16
1.5...10
0.5...10
0.5...10
B 6
(QL 2...5) 47
(QL 6...10) 36
600 V/30 A/20...8 AWG
600 V/30 A/22...8 AWG
Qty. Qty.
0162220000 20 0178220000 20
10.3 x 38,1
Type Cat. No. Qty.
TW HP (2.0) 0607000000*20
QL 2 0328000000 20
QL 3 0328100000 20
QL 4 0328200000 20
QL 10 0339000000 20
SS M 4 0136400000 100
BS M 4 x 9 0103300000 100
SK (w. spring) 0161730000 20
DEK 5 see "Accessories"


Fuse terminals with fault indicator



Dimensions/approvals	
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length	mm
Connection data	
Screw connection, solid	
Screw connection, flexible/ferrule with/without plastic collar	
Conductor cross-section	
VDE rated data	
Current	
Voltage	
LED-current (24...60 V)	
LED-current (115...230 V)	
LED-current (24...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	
Ordering data	
24 V~	ASK 1 LD 8050810000 25
24 V~	ASK 1 LD 0222760000 25
48 V~	ASK 1 LD 0225260000 25
60 V~	ASK 1 LD 0226460000 25
115 V~	ASK 1 LD 0225460000 25
230 V~	ASK 1 LD 0225660000 25
24 V~	ASK 1 LD 0222860000 25
48 V~	ASK 1 LD 0225360000 25
60 V~	ASK 1 LD 0226360000 25
115 V~	ASK 1 LD 0225560000 25
230 V~	ASK 1 LD 0225760000 25
Mountable on	TS 32 and TS 35
TS 32	0122800000
TS 35x7.5	0383400000
TS 35x15	0498000000
EWK 1	0206160000 50
EW 35	0383560000 50
AP PA (1.5)	0380360000 20
QB 2 ¹⁾	0461100000 100
QB 3 ¹⁾	0461200000 50
QB 4 ¹⁾	0461300000 50
QB 58 ¹⁾	0545400000
QB 58 ¹⁾	0545300000
Fixing screw (fits QL)	TH (spare) 0377060000 100
Disconnect lever (spare)	
Accessories	
Mounting rail	
End brackets (thickness mm)	
End plate/End plate (thickness mm)	
Cross-connections	
Type 'QL'	
Cross-connection	
Type 'QB'	
Fixing screw (fits QL)	
Disconnect lever (spare)	
Mounting rails, end brackets, further marking material see "Accessories"	

¹⁾When using QB, the rated cross-current reduces to max. 2.5 mm²

ASK 1 LD




Warning:
In the event of a faulty fuse, the connection system is live!


UL
8
9
0.5...4 mm ²
0.5...4 mm ²
AWG 22...12
6.3 A
24...230 V (depending on terminal)
≤ 2 mA
≤ 2 mA
4 mm ²
Type Cat. No. Qty.
ASK 1 LD 8050810000 25
ASK 1 LD 0222760000 25
ASK 1 LD 0225260000 25
ASK 1 LD 0226460000 25
ASK 1 LD 0225460000 25
ASK 1 LD 0225660000 25
ASK 1 LD 0222860000 25
ASK 1 LD 0225360000 25
ASK 1 LD 0226360000 25
ASK 1 LD 0225560000 25
ASK 1 LD 0225760000 25
Mountable on
TS 32 and TS 35
TS 32 0122800000
TS 35x7.5 0383400000
TS 35x15 0498000000
EWK 1 0206160000 50
EW 35 0383560000 50
AP PA (1.5) 0380360000 20
QB 2 ¹⁾ 0461100000 100
QB 3 ¹⁾ 0461200000 50
QB 4 ¹⁾ 0461300000 50
QB 58 ¹⁾ 0545400000
QB 58 ¹⁾ 0545300000
TH (spare) 0377060000 100

KDKS 1

Fuse insert 5 x 20



AC model



DC model

Warning:
In the event of a faulty fuse, the connection system is live!

UL
8
9
0.5...4 mm ²
0.5...4 mm ²
AWG 22...12
6.3 A
24...230 V (depending on terminal)
≤ 2 mA
≤ 2 mA
4 mm ²
Type Cat. No. Qty.
KDKS 1 8146450000 25
KDKS 1 8148930000 25
KDKS 1 8148920000 25
KDKS 1 8142840000 25
KDKS 1 8148910000 25
Mountable on
TS 32 and TS 35
TS 32 0122800000
TS 35x7.5 0383400000
TS 35x15 0498000000
EWK 1 0206160000 50
EW 35 0383560000 50
AP PA (1.5) 0380360000 20
QB 2 ¹⁾ 0461100000 100
QB 3 ¹⁾ 0461200000 50
QB 4 ¹⁾ 0461300000 50
QB 58 ¹⁾ 0545400000
QB 58 ¹⁾ 0545300000
TH (spare) 0377060000 100

Fuse terminals

with fault indicator



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	

Connection data

Screw connection, solid
Screw connection, flexible
Conductor cross-section

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

VDE rated data

Voltage/current	~10 A
LED-current (24...60 V)	≤ 5 mA
LED-current (115...230 V)	
Incandescent lamp-current	≤ 50 mA
Neon lamp-current	≤ 0.5 mA
Cross-section	10 mm ²

Ordering data


Fuse insert	Voltage	
5 x 20	LED	24 V~
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)		24 V~
without indicator		48 V~
		48 V~
	Incandescent lamp	24 V=
		48 V=
	Neon lamp	115 V=
		230 V=
Fuse insert		
5 x 25	LED	24 V~
Acc. to DIN 41576		
without indicator	Incandescent lamp	48 V=
	Neon lamp	115 V=
		230 V=

Accessories

Mounting rail	
End brackets (thickness mm)	for TS 32
	for TS 35
End plate (thickness mm)	
Cross-connection	
Type 'QL'	
Cross-connection	
Type 'QB'	
Fixing screw (fits QL)	
Screw cap (spare)	
Neon lamp	

SAKS 1

Fuse insert 5x20/5x25



Warning:


In the event of a faulty fuse, the connection system is live!

UL & CE

13
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

SAKS 4

Fuse insert E14/D 01
(e.g. Neozed D 01)



Warning:


In the event of a faulty fuse, the connection system is live!

UL & CE

24
14
0.5...16 mm ²
0.5...10 mm ²
AWG 20...7

SAKS 6

Fuse insert 1 1/4" x 1/4"
acc. to DEF 63



Warning:


In the event of a faulty fuse, the connection system is live!

UL & CE

12
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

SAKS 7

Fuse insert 5x20/5x25



Warning:

In the event of a faulty fuse, the connection system is live!

UL & CE

12
12
0.5...16 mm ²
0.5...10 mm ²
AWG 20...8

Type	Cat. No.	Qty.
SAKS 4		
TS 32 Neon lamp		
Voltage		
115 V=	0101820000	10
480 V=	0102120000	10

Type	Cat. No.	Qty.
SAKS 6 KrG	0531820000	40
for 1 1/4" x 1/4" acc. to DEF 63		
exchangeable neon lamps		
(please order separately)		

Type	Cat. No.	Qty.
SAKS 7 KrG		
for 5 x 25	0576120000	40
SAKS 7 KrG		
for 5 x 20	0573120000	40
exchangeable neon lamps		
(please order separately)		

Type	Cat. No.	Qty.
SAKS 1 LD		
0371420000	10	0225820000
1111220000	10	1111320000
		0214020000
SAKS 1 GL		
		0173220000
0378920000	10	
SAKS 1 GL		
0385320000	10	8068330000
0306120000	10	0199920000
SAK 1 LD		
on demand		
SAKS GL		
on demand		
SAKS 1 GL		
0309320000	10	0198620000

Type	Cat. No.	Qty.
TS 32	0122800000	
TS 35x7.5	0383400000	
TS 35x15	0498000000	
EWK 1 (8.5)	0206160000	50
EW 35 (8.5)	0383560000	50
AP KrG (3)	0191320000	20
SK (5 x 20)	0282100000	20
SK (5 x 25)	0282000000	100

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG	0146720000	20
QL 2	0191400000	50
QL 3	0191500000	50
QL 4	0191600000	20
QL 10	0338800000	20
BSM 3x6 m.SS	0346200000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG (3)	0146720000	20
QL 2	0207800000	20
QL 3	0207900000	20
QL 4	0208000000	20
QL 10	0338900000	20
BSM 4x9 m.SS	0133300000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

Fuse inserts and gauge rings for Weidmüller fuse terminals

Fuse inserts

for terminal type	Size (mm)	Rated voltage (V)	Rated current (A)	Type	Cat. No.	Qty.
G fuse inserts 5 x 20 without indicator acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)						
SAKS 1	5 x 20 Breaking capacity 1500 A (at 250 V, 50 Hz, cos φ 0.7)	250	0.1 (F)	G 20/0.10A/F	0430300000	10
SAKS 7			0.2 (F)	G 20/0.20A/F	0430400000	10
ASK 1			0.25 (F)	G 20/0.25A/F	0430500000	10
WSI 6			0.5 (F)	G 20/0.50A/F	0430600000	10
			0.63 (F)	G 20/0.63A/F	0430900000	10
			1.0 (F)	G 20/1.00A/F	0430700000	10
			1.6 (F)	G 20/1.60A/F	0430800000	10
			2.0 (F)	G 20/2.00A/F	0430900000	10
			2.5 (F)	G 20/2.50A/F	0431000000	10
			3.15 (F)	G 20/3.15A/F	0431100000	10
			4.0 (F)	G 20/4.00A/F	0431200000	10
			5.0 (F)	G 20/5.00A/F	0431300000	10
			6.3 (F)	G 20/6.30A/F	0431400000	10
G fuse inserts 5 x 25 with indicator acc. to DIN 41576¹)						
SAKS 1	5 x 25 m. K.1) Breaking capacity 80 A (at 250 V, 50 Hz, cos φ = 1)	250	0.25 (M)	G 25/0.25A/M	0546900000	10
SAKS 7			0.5 (M)	G 25/0.50A/M	0510300000	10
WSI 6			0.8 (M)	G 25/0.80A/M	0646400000	10
			1 (M)	G 25/1.00A/M	0265800000	10
			10 (M)⁵)	G 25/10.0A/M	0193100000	10
			2 (F)	G 25/2.00A/F	0192700000	10
			4 (F)	G 25/4.00A/F	0192800000	10
			6.3 (F)	G 25/6.30A/F	0192900000	10
Fuse inserts 1¼" x ¼" without indicator acc. to BS 88						
SAKS 3²)	33 kA Breaking capacity 33 kA fast	440	0.5	GZ 0.5A/F	0533800000	10
SAKS 6			1	GZ 1.0A/F	0525500000	10
			2	GZ 2.0A	0294500000	10
			3	GZ 3.0A	0295700000	10
			5	GZ 5.0A	0294600000	10
			7	GZ 7.0A	0295800000	10
			10	GZ 10.0A	0293900000	10
D fuse inserts E 16 with indicator acc. to DIN 49360 (diazed)						
SAKS 2	E 10 A	500	10	E 16/10A RT	0208500000	25
			16	E 16/16A GR	0208600000	25
			20	E 16/20A BL	0208700000	25
			25	E 16/25A GE	0208800000	25
D fuse inserts E 14 Size D 01 and E 18 size D 02 with indicator acc. to DIN 49522 (neozed)³)						
SAKS 4⁴)	E 14/2	400	2	E 14/2A RS	0137400000	10
			4	E 14/4A BR	0137500000	10
			6	E 14/6A GN	0328300000	10
			10	E 14/10A RT	0328400000	10
			16	E 14/16A GR	0328500000	10
			20	E 18/20A BL	0361300000	10
SAKS 5	E 18/25	400	25	E 18/25A GE	0361400000	10
			35	E 18/35A SW	0361500000	10
			50	E 18/50A WS	0361600000	10
			63	E 18/63A KU	0361700000	10
						

(F) = fast

(M) = medium-delayed action




(F) = fast
(M) = medium-delayed action

- Note:**
- 1) The SIBA company also supplies 5 x 25 G fuse inserts with indicators in a shipbuilding model for 450 V AC.
 - 2) 5 x 30 (500 V AC) fuse inserts for SAKS 3 are available from the WICKMANN company
 - 3) The LINDNER company also supplies neozed fuse cartridges in an additional shipbuilding mode for 440 V AC.
 - 4) Fuse cartridges with the dimensions 1"x1/4" ≙ 25.4x6.35 mm and 13/32"x1 1/2" ≙ 10.3x38.1 mm are not included in product line.
 - 5) Only for SAKS 1 and SAKS 7.

Gauge rings

For terminal type	Gauge ring type	Amp.	Colour	Type	Cat. No.	Qty.
SAKS 4 and 4/35	P 14/2	2	Pink	P 14/2D01 RS	0138000000	50
	P 14/4	4	Brown	P 14/4D01 BR	0138100000	50
	P 14/6	6	Green	P 14/6D01 GN	0328600000	50
	P 14/1	10	Red	P 14/10D01 RT	0328700000	50
SAKS 5 and 5/35	P 18/20	20	Blue	P 18/20D02 BL	0361800000	50
	P 18/25	25	Yellow	P 18/25D02 GE	0361900000	50
	P 18/35	35	Black	P 18/35D02 SW	0362000000	50
	P 18/50	50	White	P 18/50D02 WS	0362100000	50
SAKS 2 and 2/35	P 16/10	10	Red	P 16/10 RT	0208900000	100
	P 16/16	16	Grey	P 16/16 GR	0209000000	100
	P 16/20	20	Blue	P 16/20 BL	0209100000	100

Disconnect test terminals

			SAKR SAKR/35			SAKR-D SAKR-D/35		DKT 4 DKT 4/35		DKT 4 V DKT 4 V/35	
Dimensions/approvals				 				 			
Width/length/height (mm)				with TS 32 	6.5/42/40.5/54.5 (opened)	6.5/42/40.5/57 (with DLS 2)	6/65/56.5/70 (opened)	6/65/56.5/70 (opened)	6/65/56.5/70 (opened)	6/65/56.5/70 (opened)	6/65/56.5/70 (opened)
Width/length/height (mm)				with TS 35 x 7.5 	6.5/46/38/52	6.5/46/38/54.5	6/65/56.5/70	6/65/56.5/70	6/65/56.5/70	6/65/56.5/70	6/65/56.5/70
Insulation stripping length/clamping screw/screwdriver blade					8 mm/M 3/3.5 x 0.6	8 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data											
Rated voltage/current/cross-section					400 V ⁶⁾ /10 A/4 mm ²	400 V/10 A/4 mm ²	400V/10 A/4 mm ²	400V/10 A/4 mm ²	400V/10 A/4 mm ²	400 V/10 A/4 mm ²	400 V/10 A/4 mm ²
Rated impulse voltage/pollution severity					6 kV/3	6 kV/3	6 kV/3	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data											
Tightening torque range				Nm	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB	0.5...1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2					2/1	2/1	2/1	2/1	2/1	2/1	2/1
Clampable conductor											
Solid H07V-U				mm ²	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4
Stranded H07V-R				mm ²	1.5...4	1.5...4	1.5...4	1.5...4	1.5...4	1.5...4	1.5...4
Flexible H07V-K				mm ²	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1				mm ²							
With/without plastic insulating collar				mm ²	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	0.5...4
Plug gauge according to 60 947-7-1				Size	A 3	A 3	A 3	A 3	A 3	A 3	A 3
Continuous current rating of cross-connection 2...5-pole				A	(QB 2...25) 10	(QB 2...25) 10	(QB 2...25) 10	(QB 2...4) 10	(QB 2...4) 10	(QB 2...4) 10	(QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole				A							
Rated data according to UL/CSA											
Voltage/current/conductor size				UL	300 V/10 A/26...12 AWG	300 V/10 A/26...12 AWG	300 V/10 A/26...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG
Voltage/current/conductor size				CSA	300 V/10 A/26...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/26...12 AWG	300 V/10 A/26...12 AWG	300 V/10 A/26...12 AWG	300 V/10 A/26...12 AWG
Ordering data											
				Type	 Qty. 	 Qty. 	 Qty. 	 Qty. 	 Qty. 	 Qty. 	 Qty. 
				KrG	0412120000 100						
				PA	0412160000 100 0172160000 100	0412960000 ¹⁾ 100 0299960000 ¹⁾ 50	0687360000 50 0687460000 50				
				Without diode PA		0413060000 ²⁾ 50 0185760000 ²⁾ 50					
				With diode PA		0263660000 ³⁾ 50 0299560000 ³⁾ 50					
				Blue PA	0412180000 100 0172180000 100						
				Orange PA	1461960000 100						
				KrG	0412220000 100						
				PA	0412260000 100 0183360000 100	0546460000 ¹⁾ 100	0327860000 50 0327960000 50	1304860000 50 1304960000 50			
				without diode PA		0413160000 ²⁾ 50					
				Blue	0412280000 100 0183380000 100						
End plate (thickness mm)					Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
				KrG	AP (1.5) 0211320000 20	AP (1.5) 0211360000 20	AP (1.5) 0211360000 20	AP (1.5) 0687560000 20	AP (1.5) 0687560000 20		
				PA	AP (1.5) 0211360000 20						
				Blue PA	AP (1.5) 0211380000 20						
Partition (thickness mm)											
											
					TW HP (1.0) 0297100000 20	TW HP (1.0) 0297100000 20	TW HP (2.0) 0607000000 20	TW HP (2.0) 0607000000 20			
Cross-connection											
QB 4 				2-pole	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100	QB 2 ⁴⁾ 0482700000 100
				3-pole	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50	QB 3 ⁴⁾ 0482800000 50
				4-pole	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50	QB 4 ⁴⁾ 0482900000 50
				25-pole	QB 25 blank ⁴⁾ 0134000000 20	QB 25 blank ⁴⁾ 0134000000 20					
Contact sleeve (spare)											
											
Test plug											
				PS 2.3	0180400000 20	PS 2.3	0180400000 20	PS 2.3	0180400000 20	PS 2.3	0180400000 20
Diode plug (spare)											
without diode						DLS 2 0321060000 50					
with diode 1N4007						DLS 2 +  - 0630160000 50					
with diode 1N4007						DLS 2 -  + 0547760000 50					
with jumper						DLS 2 0547660000 25					
Marking tags											
				DEK	Standard	DEK 6.5 see "Accessories"	DEK 6.5 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"											


- 1) without DLS
- 2) with DLS empty

⁴⁾ When using QB the rated cross-current reduces to max. 2.5 mm²

⁶⁾ As disconnect test terminal rated voltage 250 V

Disconnect test terminals

ASK 1
ASK 1/35



UL  

8/58/49

8/58/44

9 mm/M 3/3.5 x 0.6

500 V/19 A/4 mm²

6 kV/3

0.5...1.0

2

0.5...4

1.5...4

0.5...4

0.5...4

A 3

(QB 2...4) 10

300 V/15 A/12 max. AWG

300 V/6.3 A/26...12 AWG

 Qty.

0456360000 100

0105260000 100

Type	Cat. No.	Qty.
------	----------	------

AP (1.5)	0380360000	20
----------	------------	----

TW HP (2.0)	0607000000	20
-------------	------------	----

QB 2 ⁴)	0461100000	100
---------------------	------------	-----

QB 3 ⁴)	0461200000	50
---------------------	------------	----


QB 4 ⁴)	0461300000	50
---------------------	------------	----

multipole interruptable with
group marking carrier SchS 2;
2-pole (Cat. No. 1359500000)
1000 mm (Cat. No. 0337400000)

K sleeve	0553300000	100
----------	------------	-----

DEK 5 FW	see "Accessories"
----------	-------------------

Feed-through terminals with tab connection

			AST 1 AST1/35	AST 3 AST 3/35	AST 4 AST 4/35	AST 5 AST 5/35					
			6.3 2.8	6.3 2.8	6.3 2.8	6.3 2.8					
											
Dimensions/approvals			   	   	  	   					
Width/length/height (mm)		with TS 32 	6.5/58/53.5	6.5/40/47.5	6.5/40/47.5	6.5/58/53.5					
Width/length/height (mm)		with TS 35 x 7.5 	6.5/58/46	6.5/44/40	6.5/44/40	6.5/58/46					
Insulation stripping length/clamping screw/screwdriver blade					9 mm/M 2.5/3.5 x 0.6	12 mm/M 3/3.5 x 0.6					
Rated data											
Rated voltage/-current			500 V ¹⁾ /-	500 V ¹⁾ /-	500 V ¹⁾ /-	500 V ¹⁾ /-					
Rated cross-section for clamping yokes			-	-	2.5 mm ²	4 mm ²					
Rated cross-section tab		6.3/2.8 mm	2.5/1.0 mm ²	2.5/1.0 mm ²	2.5/1.0 mm ²	2.5/1.0 mm ²					
Rated Voltage VDE 0110/1.89/pollution severity			6 kV/3	6 kV/3	6 kV/3	6 kV/3					
Further technical data											
Tightening torque range		Nm			0.4...0.7	0.5...1.0					
Torque setting with electric screwdriver type DMS 2					1	2					
Clampable conductor											
Solid H07V-U		mm ²			0.5...4	0.5...6					
Stranded H07V-R		mm ²			1.5...2.5	1.5...4					
Flexible H07V-K		mm ²			0.5...2.5	0.5...4					
Flexible H07V-K and ferrule according to DIN 46 228/1		mm ²			0.5...2.5	0.5...4					
Plug gauge according to 60 947-7-1		Size			A 3	A 4					
Continuous current of terminal for conductor size											
Continuous current rating of cross-connection 2...5-pole		A	(QL 2...10) 20	(QL 2...10) 20	(QL 2...10) 20	(QL 2...10) 20					
Continuous current rating of cross-connection 6...10-pole		A									
Rated data according to UL/CSA											
Voltage/current/conductor size		UL	300 V/13 A/-	300 V/13 A/-	300 V/13 A/22...12 AWG	300 V/13 A/22...12 AWG					
Voltage/current/conductor size		CSA	300 V/16 A/-	300 V/16 A/-	300 V/16 A/24...12 AWG	300 V/16 A/24...12 AWG					
Ordering data		Version	 Qty.	 Qty.	 Qty.	 Qty.					
		Slotted KrG	0478220000	50	0439120000	100					
		Slotted blue KrG									
		Slotted PA	0478260000 ²⁾ 50	0699660000 ²⁾ 50	0460360000 ²⁾ 100						
		Unslotted KrG	0266320000	50	0321220000	100					
		Unslotted blue KrG			0321270000	100					
		Unslotted PA	0266360000 ²⁾ 50	0664860000 ²⁾ 50	0479460000	100					
End plate/partition/small partition (thickness mm)			Type	Cat. No.	Qty.	Type	Cat. No.	Qty.			
AP	TW	TSCH 1	KrG	AP (3.0)	0266420000	20	AP (3.0)	0298120000	20		
			Blue KrG								
			PA	AP (1.5)	0266460000	20	AP (1.5)	0460560000	20		
			PA				TW (1.5)	0130160000	20		
			HP	TW (0.5)	0474700000	20	TW (1.0)	0297100000	20		
			HP	TW (2.0)	0607000000	20					
			Only for PA	TSch 1	0319160000	100	TSch 1	0319160000	100		
Cross-connection											
Q4		2-pole	Q 2	0336700000	50	Q 2	0336700000	50	Q 2	0336700000	50
		3-pole	Q 3	0336800000	50	Q 3	0336800000	50	Q 3	0336800000	50
		4-pole	Q 4	0336900000	50	Q 4	0336900000	50	Q 4	0336900000	50
		10-pole	Q 10	0368800000	20	Q 10	0368800000	20	Q 10	0368800000	20
		25-pole									
Plug adapter											
		2-pole		STA 2.5/2	0165860000	100	STA 2.5/2	0165860000	100		
		3-pole		STA 2.5/3	0165960000	50	STA 2.5/3	0165960000	50		
		4-pole		STA 2.5/4	0190360000	50	STA 2.5/4	0190360000	50		
		5-pole		STA 2.5/5	0166060000	50	STA 2.5/5	0166060000	50		
		8-pole		STA 2.5/8	0166160000	50	STA 2.5/8	0166160000	50		
Test plug/socket											
		Plug-test socket without using QL for TS 32	StB 14	0168600000	50	StB 14	0168600000	50	StB 14	0168600000	50
		PS	PS 2.3	0180400000	20	PS 2.3	0180400000	20	PS 2.3	0180400000	20
		StB									
Insulation sleeve											
			IH 2.8	0386060000	100	IH 2.8	0386060000	100	IH 2.8	0386060000	100
			IH 6.3	0386260000	100	IH 6.3	0386260000	100	IH 6.3	0386260000	100
Marking tags											
		Print									
		DEK	DEK 6.5	see "Accessories"		DEK 6	see "Accessories"		DEK 6	see "Accessories"	
		Standard									
Mounting rails, end brackets, further marking material see "Accessories"											

¹⁾ with insulation sleeve

²⁾ shock proof with ADP 4 cover profiles ADP4 (see section "Accessories")

Feed-through terminals with tab connection

SAK 4 S SAK 4 S/35

6.3
2.8



SAK 4 SS SAK 4 SS/35

6.3
2.8



SAKR F SAKR F/35

2.8



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

6.5/40/51.5
6.5/40/49.5
12 mm/M 3/3.5 x 0.6

6.5/40/51.5
6.5/40/49.5

6.5/42/40.5/54.5 (opened)
6.5/42/40.5/32.5
8 mm/M 3/3.5 x 0.6

Rated data

Rated voltage/-current	500 V ¹⁾ /16 A
Rated cross-section for clamping yokes	4 mm ²
Rated cross-section tab	6.3/2.8 mm
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

500 V ¹⁾ /16 A
4 mm ²
2.5/1.0 mm ²
6 kV/3

500 V ¹⁾ /16 A
-
2.5/1.0 mm ²
6 kV/3

250 V ¹⁾ /10 A
4 mm ²
-/1.0 mm ²
6 kV/3

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

0.5...1.0
2

0.5...1.0
1

Clampable conductor

Solid H07V-U	mm ²	0.33...6
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 4
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QL 2...10) 36 A at 6 mm ²
Continuous current rating of cross-connection multipole	A	

0.33...6
1.5...4
0.5...4
0.5...4
A 4
(QL 2...10) 36 A at 6 mm ²

(QL 2...10) 36 A at 6 mm ²

0.5...4
1.5...4
0.5...4
0.5...2.5
A 3
(QB 2...25) 10

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

300 V/13 A/26...12 AWG
300 V/13 A/26...12 AWG

300 V/13 A/18...14 AWG
300 V/13 A/18...14 AWG

300 V/10 A/22...12 AWG
300 V/10 A/26...12 AWG

Ordering data

Version

Slotted KrG
Slotted blue KrG
Slotted PA
Unslotted KrG

Qty.	Qty.
0401220000	100
0401260000	100
0630360000	100

Qty.	Qty.
0479620000	10
0479660000	100
0630460000	100
0352920000	10

Qty.	Qty.
0663660000	100
6382870000	100
with 1 StB 6	

End plate/partition/small partition (thickness mm)

AP	TW	TSch 1	KrG
			Blue KrG
			PA
			PA
			HP



Type	Cat. No.	Qty.
AP (1.5)	0117920000	20
AP (1.5)	0117960000	20
AP (1.5)	0130160000	20
TW (1.0)	0297100000	20

Type	Cat. No.	Qty.
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117960000	20
TW (1.5)	0130160000	20
TW (1.0)	0297100000	20

Type	Cat. No.	Qty.
AP (1.5)	0211360000	20
TW (1.0)	0297100000	20

Cross-connection

QL	QB 4	2-pole
		3-pole
		4-pole
		10-pole
		25-pole



QL 2	0130600000	100
QL 3	0130700000	100
QL 4	0130800000	50
QL 10	0338200000	20

QL 2	0130600000	100
QL 3	0130700000	100
QL 4	0130800000	50
QL 10	0338200000	20

QB 2*	0482700000	100
QB 3*	0482800000	50
QB 4*	0482900000	50
QB 25 blank*	0134000000	20

BS M 3 x 4.5



BS M 3 x 24



BS M 3x4.5 1593210000 100

BS M 3x4.5 1593210000 100

Test plug/socket



PS

PS 2.3 0180400000 20

Insulation sleeve



IH 2.8	0386060000	100
IH 6.3	0386260000	100

IH 2.8	0386060000	100
IH 6.3	0386260000	100

IH 2.8 0386060000 200

Marking tags

Print

1	2	3	4	5	6	DEK	Standard
---	---	---	---	---	---	-----	----------

DEK 6.5 see "Accessories"

DEK 6.5 see "Accessories"

DEK 6.5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ With insulation sleeve

*The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used

Feed-through terminals with tab connection

DK 4 SS/35



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data

Rated voltage/-current	400 V ¹⁾ /2 x 16 A
Rated cross-section for clamping yokes	-
Rated cross-section tab	6.3/2.8 mm
Rated Voltage VDE 0110/1.89/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor

Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulation collar	
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2 pole	A
Continuous current rating of cross-connection multipole	A

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Version	PA
---------	----

Cat. No.	Qty.
0217160000	100

DK 4 SS/35 only 2.8



Cat. No.	Qty.
0297060000	100

DK 4 S DK 4 S/35



Width/length/height (mm)	6/54/59.5
Width/length/height (mm)	6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6

Rated voltage/-current	400 V ¹⁾ /2 x 10
Rated cross-section for clamping yokes	4 mm ²
Rated cross-section tab	1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Tightening torque range	0.5...1.0
Torque setting with electric screwdriver type DMS 2	2

Solid H07V-U	0.5...4
Stranded H07V-R	1.5...4
Flexible H07V-K	0.5...4

With/without plastic insulation collar	0.5...4
Plug gauge according to 60 947-7-1	A 3

Continuous current rating of cross-connection 2 pole	(QL 2...10) 20
--	----------------

Voltage/current/conductor size	300 V/10 A/22...12 AWG
Voltage/current/conductor size	300 V/10 A/22...12 AWG

Cat. No.	Qty.
0631260000	100

DK 4 S only 2.8 DK 4 S/35 only 2.8



Width/length/height (mm)	6/54/59.5
Width/length/height (mm)	6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6

Rated voltage/-current	400 V ¹⁾ /2 x 10
Rated cross-section for clamping yokes	4 mm ²
Rated cross-section tab	1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Tightening torque range	0.5...1.0
Torque setting with electric screwdriver type DMS 2	2

Solid H07V-U	0.5...4
Stranded H07V-R	1.5...4
Flexible H07V-K	0.5...4

With/without plastic insulation collar	0.5...4
Plug gauge according to 60 947-7-1	A 3

Continuous current rating of cross-connection 2 pole	(QL 2...10) 20
--	----------------

Voltage/current/conductor size	300 V/10 A/22...12 AWG
Voltage/current/conductor size	300 V/10 A/22...12 AWG

Cat. No.	Qty.
0631160000	100

End plate (thickness mm)



PA

Type	Cat. No.	Qty.
AP (1.5)	0631360000	20

Type	Cat. No.	Qty.
AP (1.5)	0631360000	20

Type	Cat. No.	Qty.
AP (1.5)	0631360000	20

Type	Cat. No.	Qty.
AP (1.5)	0631360000	20

Partition



for TS 32 HP

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000	20

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000	20

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000	20

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000	20

Small partition



TSch 6

Type	Cat. No.	Qty.
TSch 6	0190260000	100

Type	Cat. No.	Qty.
TSch 6	0190260000	100

Type	Cat. No.	Qty.
TSch 6	0190260000	100

Type	Cat. No.	Qty.
TSch 6	0190260000	100

Cross-connection



Q 3

Type	Cat. No.	Qty.
2-pole	Q 2	0336400000 50
3-pole	Q 3	0336500000 50
4-pole	Q 4	0336600000 50
10-pole	Q 10	0368600000 20

Type	Cat. No.	Qty.
2-pole	Q 2	0336400000 50
3-pole	Q 3	0336500000 50
4-pole	Q 4	0336600000 50
10-pole	Q 10	0368600000 20

Type	Cat. No.	Qty.
2-pole	Q 2	0336400000 50
3-pole	Q 3	0336500000 50
4-pole	Q 4	0336600000 50
10-pole	Q 10	0368600000 20

Type	Cat. No.	Qty.
2-pole	Q 2	0336400000 50
3-pole	Q 3	0336500000 50
4-pole	Q 4	0336600000 50
10-pole	Q 10	0368600000 20

Test plug/socket



StB

Plug test socket without using QL
Plug test socket for use with QL


Type	Cat. No.	Qty.
StB 8.5	0215700000	50

Type	Cat. No.	Qty.
StB 8.5	0215700000	50

Type	Cat. No.	Qty.
StB 8.5	0215700000	50

Type	Cat. No.	Qty.
StB 8.5	0215700000	50

Insulation sleeve



PS


Type	Cat. No.	Qty.
PS 2.3	0180400000	20
IH 2.8	0386060000	100
IH 6.3	0386260000	100

Type	Cat. No.	Qty.
PS 2.3	0180400000	20
IH 2.8	0386060000	100
IH 6.3	0386260000	100

Type	Cat. No.	Qty.
PS 2.3	0180400000	20
IH 2.8	0386060000	100
IH 6.3	0386260000	100

Type	Cat. No.	Qty.
PS 2.3	0180400000	20
IH 2.8	0386060000	100
IH 6.3	0386260000	100

Marking tags



DEK

Print

Type	Cat. No.	Qty.
DEK 6	see "Accessories"	

Type	Cat. No.	Qty.
DEK 6	see "Accessories"	

Type	Cat. No.	Qty.
DEK 6	see "Accessories"	

Type	Cat. No.	Qty.
DEK 6	see "Accessories"	

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ With insulation sleeve

Feed-through terminals for wrap termination

DIN 41 611, Part 2 and for spring-clip termination DIN 41 611, Part 4

SAK 2.5 T

Pin 1 x 1



SAK 2.5 T


Pin 0.8 x 1.6



SAK 2.5 T

Pin 0.8 x 2.4



Dimensions/approvals			SAK 2.5 T			SAK 2.5 T			SAK 2.5 T		
Width/length/height (mm)			with TS 32 			6/36.5/47.5/67			6/36.5/47.5/62		
Insulation stripping length/clamping screw/screwdriver blade						12 mm/M 2.5/3.5 x 0.6			12 mm/M 2.5/3.5 x 0.6		
Rated data											
Rated voltage/current/cross-section			250 V/8 A/2.5 mm²			250 V/10 A/2.5 mm²			250 V/10 A/2.5 mm²		
Rated impulse voltage VDE 0110/1.89/pollution severity			4 kV/3			4 kV/3			4 kV/3		
Further technical data											
Tightening torque range			Nm			0.4...0.7			0.4...0.7		
Torque setting with electric screwdriver type DMS 2			1			1			1		
Clampable conductor											
Solid H07V-U			mm²			0.5...6			0.5...6		
Stranded H07V-R			mm²			0.5...2.5			0.5...2.5		
Flexible H07V-K			mm²			0.5...4			0.5...4		
Flexible H07V-K and ferrule according to DIN 46 228/1			mm²			0.5...2.5			0.5...2.5		
Plug gauge according to IEC 60 947-1			Size			A 3			A 3		
Continuous current of terminal for conductor size											
Continuous current rating of cross-connection 2-pole			A			(Q 2...10) 24			(Q 2...10) 24		
Continuous current rating of cross-connection multipole			A								
Rated data according to UL/CSA											
Voltage/current/conductor size			UL			300 V/10 A/22...12 AWG			300 V/10 A/22...12 AWG		
Voltage/current/conductor size			CSA			300 V/10 A/22...12 AWG			300 V/10 A/22...12 AWG		
Ordering data			Version			Cat. No. Qty.			Cat. No. Qty.		
	Horizontal assembly	Pin	Right	KrG	0108520000 100						
			Horizontal right	KrG				0485920000 100			
			Vertical left	KrG				0478820000 100			
			Vertical right	KrG				0371020000 100			
			2x vertical	KrG				0485020000 100			
	Vertical assembly		Right	PA	0108560000 100						
End plate (thickness mm)			Type			Cat. No. Qty.			Type Cat. No. Qty.		
		KrG	AP (1.5)	0279520000 20	AP (1.5) 0279520000 20			AP (1.5) 0279520000 20			
		PA	AP (1.5)	0279560000 20	AP (1.5) 0279560000 20			AP (1.5) 0279560000 20			
Partition (thickness mm)			KrG			TW (2.5) 0302820000 20			TW (2.5) 0302820000 20		
		PA	TW (1.5)	0302860000 20	TW (1.5) 0302860000 20			TW (1.5) 0302860000 20			
		HP	TW (0.5)	0197100000 20	TW (0.5) 0197100000 20			TW (0.5) 0197100000 20			
		HP	TW (2.0)	0607000000 20	TW (2.0) 0607000000 20			TW (2.0) 0607000000 20			
Small partition			TSch 1			0319160000 100			TSch 1 0319160000 100		
Cross-connection			2-pole			Q 2 0337000000 50			Q 2** 0337000000 50		
		3-pole	Q 3	0337100000 50	Q 3 0337100000 50			Q 3** 0337100000 50			
		4-pole	Q 4	0337200000 50	Q 4 0337200000 50			Q 4** 0337200000 50			
		10-pole	Q 10	0368700000 20	Q 10 0368700000 20			Q 10** 0368700000 20			
Test plug/socket			Plug-test socket without using QL			StB 8.5 (ø 23) 0280600000 50			StB 8.5 (ø 2.3) 0280600000 50		
		PS	PS 2.3	0180400000 20	PS 2.3 0180400000 20			PS 2.3 0180400000 20			
		StB									
Marking tags			Print								
		DEK	Standard	DEK 6	see "Accessories"			DEK 6 see "Accessories"			
Mounting rails, end brackets, further marking material see "Accessories"											

¹⁾ Shock-proof with ADP4 cover profile (see section "Accessories")

** Not for Type 2 x vertical

Feed-through terminals

**Disconnect terminals
for wrap connection
acc. to DIN 41 611, Part 2 and
for spring-clip connection
acc. to DIN 41 611, Part 4**

DK 4 T

Pin 1 x 1



DK 4 T

Pin 0.8 x 1.6



DK 4 T

Pin 0.8 x 2.4



SAKRT

Pin 1 x 1/0.8 x 2.4
and 0.8 x 1.6



Dimensions

Width/length/height (mm) with TS 32 
Insulation stripping length/clamping screw/screwdriver blade

6/50/58.5/75.5
9 mm/M 3/3.5 x 0.6

6/50/60.5/77.5
9 mm/M 3/3.5 x 0.6

6/50/67.5/84.5
9 mm/M 3/3.5 x 0.6

6/42/40.5/54.5
8 mm/M 3/3.5 x 0.6

Rated data

Rated voltage/current/cross-section
Rated impulse voltage VDE 0110/1.89/pollution severity

250 V/8 A/4 mm²
4 kV/3

250 V/10 A/4 mm²
4 kV/3

250 V/10 A/4 mm²
4 kV/3

250 V/6/8 A/4 mm²
4 kV/3

Further technical data

Tightening torque range Nm
Torque setting with electric screwdriver type DMS 2

0.5...1.0
1

0.5...1.0
1

0.5...1.0
1

0.5...1.0
2

Clampable conductor

Solid H07V-U mm²
Stranded H07V-R mm²
Flexible H07V-K mm²
Flexible H07V-K and ferrule according to DIN 46 228/1
With/without plastic insulating collar mm²
Plug gauge according to IEC 60 947-1 Size
Continuous current of terminal block for conductor size
Continuous current rating of cross-connection 2-pole A
Continuous current rating of cross-connection multipole A

0.5...4
1.5...4
0.5...4
0.5...4
A3
(Q 2...10) 32

0.5...4
1.5...4
0.5...4
0.5...4
A3
(Q 2...10) 32

0.5...4
1.5...4
0.5...4
0.5...4
A3
(Q 2...10) 32

0.5...4
1.5...4
0.5...4
0.5...4
A3
(QB 2...10) 10

Rated data according to UL/CSA

Voltage/current/conductor size UL
Voltage/current/conductor size CSA

—
—


—
—

—
—

—
—

Ordering data

Pin Type
Right PA
Links PA
Horizontal right PA
Vertical right PA
Vertical right Blue PA
Vertical PA
Vertical left PA



Cat. No. Qty.
0536560000 50
0370460000¹⁾ 50
0370360000¹⁾
1398460000¹⁾ 50

Cat. No. Qty.
0370460000¹⁾ 50
0370360000¹⁾

Cat. No. Qty.
0527760000¹⁾ 50

Cat. No. Qty.
1 x 1 **0587460000** 100
0.8 x 2.4 **0545060000** 100
0.8 x 1.6 **0469360000** 100

DK 4 QT
bridgeable on
both levels

Right

PA

End plate/partition (thickness mm)

PA
Blue PA



Type Cat. No. Qty.
AP (1.5) **0359260000** 20
AP (DK4 QT) **1397160000** 20
AP (1.5) **0359280000** 20
TW (2.0) **0607000000** 20

Type Cat. No. Qty.
AP (1.5) **0359260000** 20
AP (1.5) **0359280000** 20
TW (2.0) **0607000000** 20

Type Cat. No. Qty.
AP (1.5) **0359260000** 20
TW (2.0) **0607000000** 20

Type Cat. No. Qty.
AP (1.5) **0211360000** 20
TW (2.0) **0607000000** 20

Small partition

TSch 4



TSch 4 **0363360000** 100

TSch 4 **0363360000** 100

TSch 4 **0363360000** 100

Cross-connection/covers

Q 3 QB 4 2-pole
3-pole
4-pole
10-pole
25-pole



Q 2 **0336400000** 50
Q 3 **0336500000** 50
Q 4 **0336600000** 50
Q 10 **0368600000** 20
QB 2* **0482700000** 100
QB 3* **0482800000** 50
QB 4* **0482900000** 50

Q 2 **0336400000** 50
Q 3 **0336500000** 50
Q 4 **0336600000** 50
Q 10 **0368600000** 20
QB 2* **0482700000** 100
QB 3* **0482800000** 50
QB 4* **0482900000** 50

Q 2 **0336400000** 50
Q 3 **0336500000** 50
Q 4 **0336600000** 50
Q 10 **0368600000** 20
QB 2* **0482700000** 100
QB 3* **0482800000** 50
QB 4* **0482900000** 50

QB 2* **0482700000** 100
QB 3* **0482800000** 50
QB 4* **0482900000** 50
QB 25 blank* **0134000000** 20

Test plug/socket

Plug-test socket without using QL
StB
PS



StB 8.5 (ø23) **0215700000** 50
PS 2.3 **0180400000** 20

StB 8.5 (ø23) **0215700000** 50
PS 2.3 **0180400000** 20

StB 8.5 (ø2.3) **0215700000** 50
PS 2.3 **0180400000** 20

FW/FS

dekafix 6 see "Accessories"

dekafix 6 see "Accessories"

dekafix 6 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.
** Only to be used with PA-version

¹⁾ Shock-proof with ADP4 cover profile (see section "Accessories")

Disconnect test terminals with solder connections


SAKR L

With 2 StB 6



SAKR LL

With 2 StB 6



SAKR LL

With 2 StB 6



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data

Rated voltage/current/cross-section	250 V/10 A/4/1.5 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	1

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46228/1		
With/without plastic insulating collar	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current of terminal block for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QB 2...25) 10
Continuous current rating of cross-connection multipole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Type	Qty.
KrG	
Blue KrG	
KrS	
PA	0518160000*100 0183560000 100
Blue PA	
KrG	
KrS	
PA	0572660000 100
Blue PA	

6.5/50/40.5/54.5 (opened)

8 mm/M 3/3.5 x 0.6

0.5...1.0

1

0.5...4

1.5...4

0.5...4

0.5...4

A 3

(QB 2...25) 10

A



6.5/58/40.5/54.5 (opened)

250 V/10 A/1.5 mm²

4 kV/3

0.5...1.0

1

0.5...4

1.5...4

0.5...4

0.5...4

A 3

(QB 2...25) 10

A

300 V/10 A/22...12 AWG

Qty.

6.5/58/40.5/54.5 (opened)

250 V/10 A/1.5 mm²

4 kV/3

0.5...1.0

1

0.5...4

1.5...4

0.5...4

0.5...4

A 3


(QB 2...25) 10

A

Qty.

Qty.

End plate/partition (thickness mm)



AP	TW
	

Type Cat. No. Qty.

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

TW (0.5) 0474700000 20

TW (2.0) 0607000000 20

Type Cat. No. Qty.

AP (1.5) 0211320000 20

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

AP (1.5) 0211380000 20

TW (0.5) 0474700000 20

TW (2.0) 0607000000 20

Type Cat. No. Qty.

AP (1.5) 0211320000 20

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

AP (1.5) 0211380000 20

TW (0.5) 0474700000 20

TW (2.0) 0607000000 20

Small partition



Cross-connection



QB 3	QB 4	QB 2**	0482700000 100
	2-pole	QB 3**	0482800000 50
	3-pole	QB 4**	0482900000 50
	4-pole		
	10-pole	QB 25 blank**	0134000000 20
	25-pole		


Test plug/socket



PS

PS 2.3 0180400000 20

Marking tags



DEK

Print

Standard

DEK 6.5 see "Accessories"

DEK 6.5 see "Accessories"

PS 2.3 0180400000 20

DEK 6.5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* Soldering lug on left-hand side

** The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.

Disconnect test terminals with solder connections

TAL

2 solder connections



TAL

4 solder connections



SAKK 4

Ceramic feed-through terminals for use in high temperature ranges up to max. 210°C



SAKK 10



Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data

Rated voltage/current/cross-section	63 V/10 A/1.5 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	1.5 kV/3

Further technical data

Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor

Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal block for conductor size	
Continuous current rating of cross-connection 2 pole	A
Continuous current rating of cross-connection multipole	A

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Type	Cat. No.	Qty.
KrG		
Blue KrG		
KrS		
PA	0212060000	100
Blue PA		
KrG		
KrS		
PA		
Blue PA		
Ceramic		

End plate/partition (thickness mm)

Type	Cat. No.	Qty.
AP		
TW		
KrG		
Blue KrG		
PA	0212260000	20
Blue PA		
PA		

Small partition



Cross-connection

Q 3	2-pole
QB 4	3-pole
	4-pole
	10-pole
	25-pole

Additional accessories

Marking tags

Print	DEK	Standard	On demand
1	2	3	4
5	6		

Mounting rails, end brackets, further marking material see "Accessories"

4/48/36/50 (opened)

4/54/36/50 (opened)

8/40/53

11.5/40/53

12 mm/M3/3.5 x 0.6

12 mm/M 4/5.5 x 1.0

IEC 60 947-7-1

IEC 60 947-7-1

800 V/32 A/4 mm²

800 V/57 A/10 mm²

0.5...1

1.2...2

0.5...6 mm²

2.5...16 mm²

0.5...4 mm²

2.5...10 mm²

A 4

B 6

35 A/6 mm²

63 A/16 mm²

36

47

36

36

Cat. No. Qty.

Cat. No. Qty.

Cat. No. Qty.

SAKK 4 1598080000 50

SAKK 10 1598090000 50

Type Cat. No. Qty.

Type Cat. No. Qty.

AP/SAKK 4/10 9502630000 10

AP/SAKK 4/10 9502630000 10

Type Cat. No. Qty.

AP (1.5) 0212260000 20

AP (1.5) 0212260000 20

Type Cat. No. Qty.

Type Cat. No. Qty.

QL 2 9509420000 100

QL 2 9509470000 100

QL 3 9509430000 100

QL 3 9509480000 50

QL 4 9509440000 50

QL 4 9509490000 50

QL 10 9509450000 20

QL 10 9509500000 20

VH 13.5 0248500000 100

VH 12.5 9509510000 50

BS (M3 X 20) 0303000000 100

BS (M3 X 20) 0303000000 100

SST 0152700000

SST 0152700000

MEW 1/32 0445600000


MEW 1/32 0445600000

EK 2 0323100000

EK 2 0323100000


Feed-through terminals for initiators and actuators

DLI 2.5



		6/65/49
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.5 x 0.6

DLI 2.5 LD PNP



		6/65/49
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.5 x 0.6

DLI 2.5 LD NPN



		6/65/49
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.5 x 0.6

DLD 2.5



		6/82/49
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.5 x 0.6

Dimensions/approvals

Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	250 V/20 A/2.5 mm ²
Rated impulse voltage/pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm	0.4...0.6
Torque setting with electric screwdriver type DMS 2		1

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	0.5...2.5
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current of terminal for conductor size		20 A/2.5 mm ²
Continuous current rating of cross-connection 2...5-pole	A	(Q 2...10) 20
Continuous current rating of cross-connection 6...10-pole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/26...12 AWG

Ordering data

	Standard	Cat. No.	Qty.
		1313360000	100
	with diode 1N4007		
	with LED red (5...30 V)	1578510000	100
	with LED green (5...30 V)	1578520000	100
	with LED and diode 1N4007		
	with LED and diode 1N4007		
	Block of 10 ¹⁾	(w/o) 1411360000	10
	Block of 10 ¹⁾	(with dekafix) 1579070000	10
	Fuse inserts		

End plate/Small partition

AP-DLI	AP-DLD	Part-AP	TSch 1
			(thickness 1.5 mm)

Test plug/plug socket

	StB 8.5	PS

Cross-connection

Q 3	
Q 2	
Q 3	
Q 4	
Q 10	
Q 20	

VQB



Snap fit, external cross-connection VQB 1.5.

For cross-connections for more than 20 terminals, replace VH with VH 4.2 (134580) without internal thread

Group marking

WT 4	
SF 10	
SG 10	

Cover

HP 4



Marking tags

						DEK	Standard
--	--	--	--	--	--	-----	----------

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000

ADP	0485400000	20
HP 4	0485860000	20

ADP	0485400000	20
HP 4	0485860000	20

ADP	0485400000	20
HP 4	0485860000	20


ADP	0485400000	20
HP 4	0485860000	20

Mounting rails, end brackets, further marking material see "Accessories"

1) DLI 2.5/35/10 = Block of 10 with built-in cross-connections * only in upper busbar

Feed-through terminals for initiators and actuators

DLA 2.5



6/65/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm²
4 kV/3

0.4...0.6
1

0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG

	Cat. No.	Qty.
	1565970000	100

(w. dekafix) **1578380000** 10
(w/o dekafix) **1578390000** 10

Type	Cat. No.	Qty.
AP	1313260000	20

TSch 1	0319160000	100
--------	-------------------	-----

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20


Q 2	1312500000	50
Q 3	1312600000	50
Q 4	1312700000	50
Q 10	1313100000	20
Q 20	1399800000	20

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 6	see "Accessories"
-------	-------------------

DLA 2.5/D



6/65/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm²
4 kV/3

0.4...0.6
1

0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG

	Cat. No.	Qty.
	1578400000	100

Type	Cat. No.	Qty.
AP	1313260000	20

TSch 1	0319160000	100
--------	-------------------	-----

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20


Q 2	1312500000	50
Q 3	1312600000	50
Q 4	1312700000	50
Q 10	1313100000	20
Q 20	1399800000	20

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 6	see "Accessories"
-------	-------------------

DLA 2.5/LD



6/65/49
7 mm/M 2.5/3.5 x 0.6

5-30 V/17.5 A/2.5 mm²
0.8 kV/3

0.4...0.6
1

0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm²
(Q 2...20) 20

300 V/10 A/26...12 AWG
5-30 V/10 A/26...12 AWG

	Cat. No.	Qty.
	1578430000	100
	1578440000	100

Type	Cat. No.	Qty.
AP	1313260000	20

TSch 1	0319160000	100
--------	-------------------	-----

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20


Q 2	1312500000	50
Q 3	1312600000	50
Q 4	1312700000	50
Q 10	1313100000	20
Q 20	1399800000	20

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 6	see "Accessories"
-------	-------------------

DLA 2.5/LD/D



6/65/49
7 mm/M 2.5/3.5 x 0.6

5-30 V/17.5 A/2.5 mm²
0.8 kV/3

0.4...0.6
1

0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm²
(Q 2...20) 20

300 V/10 A/26...12 AWG
5-30 V/10 A/26...12 AWG

	Cat. No.	Qty.
	1578470000	100
(LED red)	1578480000	100
(LED green)	1578490000	10
(LED red)	1578500000	10
(LED green)	1578510000	10

Type	Cat. No.	Qty.
AP	1313260000	20

TSch 1	0319160000	100
--------	-------------------	-----

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20


Q 2	1312500000	50
Q 3	1312600000	50
Q 4	1312700000	50
Q 10	1313100000	20
Q 20	1399800000	20

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 6	see "Accessories"
-------	-------------------

DLD 2.5/PE



6/74.5/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm²
4 kV/3

0.4...0.6
1

0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG

	Cat. No.	Qty.
	1595950000	100

Type	Cat. No.	Qty.
AP	1595960000	20

AP (Part-AP)	1595970000	
--------------	-------------------	--

TSch 1	0319160000	100
--------	-------------------	-----

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20


Q 2	1312500000	50
Q 3	1312600000	50
Q 4	1312700000	50
Q 10	1313100000	20
Q 20	1399800000	20

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 6	see "Accessories"
-------	-------------------

KDKS1/PE



8/91/65
8 mm/M 3 ² /M 2.5 ³ /3.5 x 0.6

500 V/6.3 A/4 mm²
6 kV/3

0.5...1²/0.4...0.7³
2/1***

0.5...4
0.5...4
0.5...4
0.5...4
A 4²/A 3³

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG

	Cat. No.	Qty.
	9528110000	50

not combine with
DLI / DLA
Wernid **9532450000** 50

5 x 20 without core indicator
Type Cat. No. Qty.

AP	9503330000	50
AP Wernid	9532470000	50

StB8.5*(ø23) **0215700000** 50
PS 2.3 **0180400000** 20

QB 2	0461100000	50
QB 3	0461200000	50
QB 4	0461300000	50

QL 2	0297200000	100
VH 4.2	1345800000	100
VQB 1.5/50 BL	1633280000	5
VQB 1.5/50 RT	1633290000	5
VQB 1.5/50 SW	1635120000	5

WT 4	1341060000	100
SF 10	0332400000	1000
SG 10	0332500000	1000
ADP	0485400000	20
HP 4	0485860000	20

DEK 8	see "Accessories"
-------	-------------------

** If the cross-connection runs via the PE connection of the DLA, or if a pole is generally skipped, the rated voltage is reduced to 30 V-

² A4 clamping position = max 4 mm² ... ³ A3 clamping position = max 2.5 mm² ... ferrule with/without plastic insulating collar

Disconnect test terminal against induced high voltage

Measures to minimize risks of electric voltage peaks in control systems of power plants and transforming stations:

- Insulation between installation and control cable by pulling disconnect plugs.
- Grounding of control cable is possible on an appropriate location of the workplace.
- Easy connection of electric isolation of counting, control and communication circuits.

Electricity Supply Industry Standard ESI 12-4 1973

The Electricity Supply Industry Standard ESI 12-4 1973 defines a detailed specification of control and protection equipment. The main functions of these installations are as follows:

- Insulation of the control cables located in front of ground or installation lines with increased potential, which is required to prevent unintentional contact of service staff with live parts.
- Separation of control cables from local control circuits.
- Application also includes test connections for auxiliary control circuits and / or local control circuits.
- Grounding of control cables and / or auxiliary control circuits.
- Bundled disconnection of all auxiliary control circuits from potential earth.
- A test voltage can be applied using the screening connection of the control cable, which is normally routed on the enclosure, with the help of an appropriate separation. This permits to check whether the screening line is correctly functioning. For this test, an insulated feed-through plate is required.

ESI 12-4:

"Terminating Equipment for Pilot Cables subject to Induced Transient Voltages exceeding 650 V rms".

PPT/35



SAKH 6



Dimensions/approvals								
Width/length/height (mm)	with TS 35 x 7.5			15/138/79				
Insulation stripping length/clamping screw/screwdriver blade			12 mm		12 mm			
Rated data according to IEC 60 947-7-1								
Rated voltage/current			15 kV ac (ESI 12-4)**/30 A		1 kV ac / 1.5 kV dc / 47 A			
Rated impulse voltage/pollution severity					>15 kV (from terminal to terminal)			
Clampable conductor								
Solid H07V-U			mm ²	0.5...10	0.5... 6			
Stranded H07V-R			mm ²	0.5...10*	0.5... 6			
Ordering data		Version		Cat. No.	Qty.		Cat. No.	Qty.
		EP	PPT/35	3835020000	10	SAKH 6	0126600000	50
			incl. disconnect plug and displacement tool (if min. 10 items are ordered)					
End plate		EP	AP/PPT (3)	3835120000	10	AP	0131700000	20
Disconnect plug			TST/PPT	3835360000	10			
Displacement tool		PA	PH/PPT	3835260000	10			
			The disconnect plug may only be removed with the displacement tool.					
Test plug/socket			PS (4)	0299600000	20			
			StB 17	0147100000	50			
Insulated mounting rail		PVC 35 x 1.5 mm	TSK 35	0514300000	1			
Marking tags		Print						
		DEK	Standard	DEK 5 see "Accessories"		DEK 5 see "Accessories"		
Mounting rails, end brackets, further marking material see "Accessories"								

* Also two push-on tabs are possible
** mounted on an insulated mounting rail

Rail mounting TS 15

Feed-through terminals
Protective conductor terminals
Fuse terminals
Disconnect test terminals

AKZ 1.5
AKZ 1.5/10



AKZ 2.5



AKZ 4
AKZ 4/10
AKZ 4 Wemid



AKZ 4 for test adapter
AKZ 4/10 for test adapter



Max. technical data

Dimensions/approvals

Width/length/height (mm) with TS 15

Insulation stripping length/clamping screw/screwdriver blade

Rated data VDE 0611 Part 1/8.92/IEC 60 947-7-1

Rated voltage/current/cross-section

Rated impulse voltage / pollution severity

Further technical data

Tightening torque range

Torque setting with electric screwdriver type DMS 2

Clampable conductor

Solid H07V-U

Stranded H07V-R

Flexible H07V-K

Flexible H07V-K and ferrule DIN 46 228/1

Flexible H07V-K and ferrule with plastic insul. collar

Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size

Continuous current rating of cross-connection 2-pole

Continuous current rating of cross-connection multipole

Rated data according to UL/CSA

Voltage/current/conductor size

Voltage/current/conductor size

Ordering data

Type	TS 15	Cat. No.	Qty.
KrG			
PA		0340460000	100
Blue PA		0340480000	100
PA	(10pol./no mk.)	0358060000	10
PA	(10pol./w.mk.)	0358160000	10

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Wemid		
PA	AP (1.5)	0340560000 50
Blue PA		

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG		
PA		
Blue PA		

Small partition

Type	Cat. No.	Qty.
PA		

Cross-connection

Q 2	Q 3	Q 4	Q 5	Q 10
0368200000	0368300000	0368400000	0660300000	0368500000

Switchable cross-connection link

VL	BS	VH

Cover/Profiled material for covers for finger-safety*

AD 4	AD 4
0303400000	0303400000

Test plug/socket

StB	StB
0215700000	0215700000

Marking tags

DEK	DEK
0180400000	0180400000

Mounting rails, end brackets, further marking material see "Accessories"

* not for terminals made from PA

Rail mounting TS 15

AK 4 AK 4/10



38.5 A / 6 mm²

UL	CE
60/32/34	
9 mm/M 3/3.5 x 0.6	
690 V/32 A/4 mm ²	
8 kV/3	
0.5...1.0	
2	
0.5...6	
1.5...4	
0.5...4	
0.5...4	
0.5...4	
0.5...4	
0.2...6.0 / A 3	
20	
20	
TS 15	Cat. No. Qty.
0489560000	100
(10pol./no.mk.)	0366560000 10
(10pol./w.mk.)	0469560000 10

Type	Cat. No.	Qty.
BB 3 (8.0)	0366660000	50
combined AP + end brackets		
TW/AP (1.5)	1331760000	20
TSch 4	0363360000	100
Q 2	0369000000	50
Q 3	0369100000	50
Q 4	0369200000	50
Q 10	0369300000	20
AD 4	0303400000	50
BSKM 25x18	0303300000	100
StB 8.5	0215700000	50
PS 2.3	0180400000	20
DEK 6	see "Accessories"	

AKE 2.5



UL	CE
5/28/27	
7 mm/M 2.5/3.0 x 0.5	
IEC 60 947-7-2	
-/-/2.5 mm ²	
4 kV/3	
0.4...0.6	
1	
0.5...4	
1.5...2.5	
0.5...4	
0.5...2.5	
0.5...2.5	
0.13...4.0 / A 3	
-/-/26...12 AWG	
-/-/26...12 AWG	
TS 15	Cat. No. Qty.
1303360000	100
(green/yellow)	

Type	Cat. No.	Qty.
TS 15	Cat. No. Qty.	
1303360000	100	
(green/yellow)		

AKE 4



UL	CE
7/32/34	
9 mm/M 3/3.5 x 0.6	
IEC 60 947-7-2	
-/-/4 mm ²	
8 kV/3	
0.5...1.0	
2	
0.5...6	
1.5...4	
0.5...4	
0.5...2.5	
0.5...2.5	
0.13...4.0 / A 3	
-/-/22...12 AWG	
-/-/26...12 AWG	
TS 15	Cat. No. Qty.
0380260000	100
(green/yellow)	

Type	Cat. No.	Qty.
TS 15	Cat. No. Qty.	
0380260000	100	
(green/yellow)		

AKE 4 MS



		
7/27.5/30		
9 mm/M 3/3.5 x 0.6		
-/-/4 mm ²		
0.8...1.6		
3		
0.5...4		
1.5...4		
0.5...4		
0.5...4		
0.5...4		
0.5...4.0 / A 3		
-/-/22...14 AWG		
	TS 15	Cat. No. Qty.
0211200000		50

Type	Cat. No.	Qty.
TS 15	Cat. No. Qty.	
0211200000	50	

ASK 1 Fuse terminal



UL	CE
8/58/34	
9 mm/M 3/3.5 x 0.6	
500 V/6.3 A ¹ /4 mm ²	
6 kV/3	
0.5...1.0	
2	
0.5...4	
1.5...4	
0.5...4	
0.5...2.5	
0.5...2.5	
0.13...4.0 / A 3	
(QB 2...4) 10	
300 V/10 A/22...12 AWG	
300 V/6.3 A/26...12 AWG	
TS 15	Cat. No. Qty.
0376860000	100
5 x 20 without indicator	

Type	Cat. No.	Qty.
AP (1.5)	0380360000	20
QB 2 ¹⁾ insul.	0461100000	50
QB 3 ¹⁾ insul.	0461200000	50
QB 4 ¹⁾ insul.	0461300000	50
3-pole ganging with tag bar SchS 2, snapped onto three disconnect levers (Cat. No. 0337400000)		
K sleeve	0553300000	100
DEK 6.5	see "Accessories"	

SAKR Isolating blade terminal with 2 sockets or with 2 clamping screws



6.5/42/45		
8 mm/M 3/3.5 x 0.6		
400 V ²⁾ /10 A/4 mm ²		
6 kV/3		
0.5...1.0		
2		
0.5...4		
1.5...4		
0.5...4		
0.5...4		
0.5...4		
0.13...4.0 / A 3		
(QB 2...4) 10		
 TS 15	Cat. No.	Qty.
with 2 StB	0412860000	100
w. clamp.screw	0412760000	100

Type	Cat. No.	Qty.
AP (1.5)	0211360000	20
QB 2 ¹⁾ insul.	0482700000	50
QB 3 ¹⁾ insul.	0482800000	50
QB 4 ¹⁾ insul.	0482900000	50
QB 25 ¹⁾ blank	0134000000	20
PS 2.3	0180400000	20
DEK 6.5	see "Accessories"	

¹⁾ The conductor cross-section is * With contact sleeve 19 A reduced to max. 2.5 mm² when QB is used.

²⁾ As disconnect test terminal: rated voltage 250 V

Feed-through terminals for TS 15

Tab connection Solder connection

AKZ 4 SS

AKZ 4 SS

AKZ 4 S

AKZ 4 SF



Dimensions/approvals		UL ®	UL ®	UL ®	®
Width/length/height (mm)	with TS 15	6/28.5/30.5	6/28.5/30.5	6/27/30	6/27/30
Insulation stripping length/clamping screw/screwdriver blade				9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data					
Rated voltage*/current/cross-section		400 V/8 A/2.5/1 mm ²	400 V/8 A/1 mm ²	400 V/8 A/4/1 mm ²	400 V/8 A/4/1 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data					
Tightening torque range Nm				0.5...1.0	0.5...1.0
Torque setting with electric screwdriver type DMS 2				2	2
Clampable conductor					
Solid H07V-U mm ²				0.5...4	0.5...4
Stranded H07V-R mm ²				1.5...4	1.5...4
Flexible H07V-K mm ²		Tab connec. 6.3 and 2.8 mm	Tab connection 2.8 mm	0.5...4	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1 mm ²				0.5...4	0.5...4
Flexible H07V-K and ferrule with plastic insul. collar mm ²				0.5...4	0.5...4
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size				0.2...4/A 3	0.2...4/A 3
Continuous current rating of cross-connection 2-pole A		20	20	20	20
Continuous current rating of cross-connection multipole A		20	20	20	20
Rated data according to UL/CSA					
Voltage/current/conductor size UL		150 V/10 A/22...12 AWG	150 V/10 A/22...12 AWG	150 V/20 A/22...12 AWG	
Voltage/current/conductor size CSA		300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG
Ordering data		Type	Type	Type	Type
		TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.	TS 15 Cat. No. Qty.
		KrG			
		PA	0324560000 100	0324460000 100	0324460000 100
		Blue PA			0158760000 100
		PA			
End plate (thickness mm)		Type	Type	Type	Type
		PA AP (1.5) 0294460000 20	PA AP (1.5) 0294460000 20	PA AP (1.5) 0294460000 20	PA AP (1.5) 0294460000 20
		PA			
		Blue PA			
		HP			
		HP			
		BB			
Partition (thickness mm)		Type	Type	Type	Type
		PA TW (0.5) 0348260000 50	PA TW (0.5) 0348260000 50	PA TW (0.5) 0348260000 50	PA TW (0.5) 0348260000 50
		HP			
		HP			
Small partition					
Cross-connection					
		Q 2 0369000000 50	Q 2 0369000000 50	Q 2 0336400000 50	Q 2 0336400000 50
		Q 3 0369100000 50	Q 3 0369100000 50	Q 3 0336500000 50	Q 3 0336500000 50
		Q 4 0369200000 50	Q 4 0369200000 50	Q 4 0336600000 50	Q 4 0336600000 50
		Q 10 0369300000 20	Q 10 0369300000 20	Q 10 0368600000 20	Q 10 0368600000 20
Switchable cross-connection link					
		VL 2 0446700000 50	VL 2 0446700000 50	VL 2 0446700000 50	VL 2 0446700000 50
		BS 0446600000 50	BS 0446600000 50	BS 0446600000 50	BS 0446600000 50
		VH 10 0266800000 100	VH 10 0266800000 100	VH 10 0266800000 100	VH 10 0266800000 100
		BS M 25x14 0266800000 100	BS M 25x14 0266800000 100	BS M 25x14 0266800000 100	BS M 25x14 0266800000 100
Test plug/socket					
		StB 8.5 0215700000 50	StB 8.5 0215700000 50	StB 8.5 0215700000 50	StB 8.5 0215700000 50
		PS 2.3 0180400000 20	PS 2.3 0180400000 20	PS 2.3 0180400000 20	PS 2.3 0180400000 20
Cover					
Insulation sleeves					
		IH 2.8 0386060000 100	IH 2.8 0386060000 100	IH 2.8 0386060000 100	IH 2.8 0386060000 100
		IH 6.3 0386260000 100	IH 6.3 0386260000 100	IH 6.3 0386260000 100	IH 6.3 0386260000 100
Marking tags		Print	Print	Print	Print
		DEK Standard	DEK 6 see "Accessories"	DEK 6 see "Accessories"	DEK 6 see "Accessories"
		1 2 3 4 5 6			
Mounting rails, end brackets, further marking material see "Accessories"					

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

Feed-through terminals for TS 15

AL 1


[illegible]

AKZ 1.5 L



		
5/34.5/25		
7 mm / M 2.5 / 3.0 x 0.5		
250 V/16 A/1.5 mm ²		
4 kV/3		
0.4...0.7		
1		
0.5...2.5		
1.5		
0.5...1.5		
0.5...1.5		
0.2...2.5 / A 1		
24		
24		
150 V/10 A/24...16 AWG		
	TS 15	Cat. No. Qty.
	0340160000	100
Type	Cat. No.	Qty.
AP (1.5)	0329660000	20
TW (0.5)		
	0166800000	50
Q 2		
	0368200000	50
Q 3		
	0368300000	50
Q 4		
	0368400000	50
Q 10		
	0368500000	20
StB 8.5		
	0215700000	50
PS 2.3		
	0180400000	20
DEK 5		
see "Accessories"		

AKZ 4 L



		
6/35.5/30		
9 mm / M 3 / 3.5 x 0.6		
250 V/16 A/4/1.5 mm ²		
4 kV/3		
0.5...1.0		
2		
0.5...4		
1.5...4		
0.5...4		
0.5...4		
0.5...4		
0.2...4.0 / A 3		
20		
20		
300 V/20 A/22...12 AWG		
300 V/10 A/24...12 AWG		
 TS 15	Cat. No.	Qty.
	0334820000	100
	0334860000	100
Type	Cat. No.	Qty.
AP (1.5)	0294420000	20
AP (1.5)	0294460000	20
AP (1.5)	0294480000	20
TW (0.5)	0348260000	50
TSch 4	0363360000	100
Q 2	0336400000	50
Q 3	0336500000	50
Q 4	0336600000	50
Q 10	0368600000	20
VL 2	0446700000	50
VH 10	0446600000	50
BS M2.5 x 14	0266800000	100
StB 8.5	0215700000	50
PS 2.3	0180400000	20
AD 4	0303400000	50
BSKM 25x18	0303300000	100
DEK 6 see "Accessories"		

AKZ 4 LL



		
6/44/30		
250 V/16 A/1.5 mm ²		
4 kV/3		
0.5...1.5		
1.5		
0.5...1.5		
0.2...2.5 / -		
20		
20		
300 V/20 A/22...12 AWG		
300 V/10 A/24...12 AWG		
	TS 15	Cat. No. Qty.
0346460000		100
Type	Cat. No.	Qty.
AP (1.5)	0294460000	20
TW (0.5)	0348260000	50
TSch 4	0363360000	100
Q 2	0336400000	50
Q 3	0336500000	50
Q 4	0336600000	50
Q 10	0368600000	20
VL 2	0446700000	50
VH 10	0446600000	50
BSM 2.5x14	0266800000	100
StB 8.5	0215700000	50
PS 2.3	0180400000	20
AD 4	0303400000	50
BSK M 25x18	0303300000	100
DEK 6		
see "Accessories"		

SAK-series

Feed-through terminals for TS 15

Solder connection Spring-clip connection

acc. to DIN 41611 Part 4

Wrap connection

acc. to DIN/IEC 352 Part 1

AKZ 1.5 T



AKZ 1.5 T



AKZ 1.5 T



AKZ 2.5 K



Dimensions/approvals

Width/length/height (mm) with TS 15

Pin size

Insulation stripping length/clamping screw/screwdriver blade

Rated data

Rated voltage/current/cross-section

Rated impulse voltage VDE 0110/1.89/pollution severity

Further technical data

Tightening torque range

Torque setting with electric screwdriver type DMS 2

Clampable conductor

Solid H07V-U

Stranded H07V-R

Flexible H07V-K

Flexible H07V-K and ferrule DIN 46 228/1

Flexible H07V-K and ferrule with plastic insul. collar

Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size

Continuous current rating of cross-connection 2-pole

Continuous current rating of cross-connection multipole

Rated data according to UL/CSA

Voltage/current/conductor size

Voltage/current/conductor size

Ordering data

Pin versions



Mounting,
horizontal

Mounting,
vertical

0.6 x 0.6

1.0 x 1.0

0.8 x 1.6 horizont.

0.8 x 1.6 vertical

0.8 x 2.4 horizontal

0.8 x 2.4 vertical



5/25/45

0.8 x 1.6

7 mm/M 2.5/3.0 x 0.5

125 V/8 A/1.5 mm²

2.5 kV/3

0.4...0.7

1

0.5...2.5

1.5

0.5...1.5

0.5...1.5

0.5...1.5

0.13...2.5 / A1

24

24

300 V/10 A/26...14 AWG

300 V/10 A/24...16 AWG

Type Cat. No. Qty.

AKZ 1.5 T 0442560000 100

AKZ 1.5 T 0357960000 100

AKZ 1.5 W 0329460000 100

* 035786 = 45 mm



5/25/39.5

1 x 1

7 mm/M 2.5/3.0 x 0.5

125 V/8 A/1.5 mm²

2.5 kV/3

0.4...0.7

1

0.5...2.5

1.5

0.5...1.5

0.5...1.5

0.5...1.5

0.13...2.5 / A1

24

24

300 V/10 A/26...14 AWG

Type Cat. No. Qty.

AKZ 1.5 T 0483660000 100

AKZ 1.5 T 0357860000 100



5/28/44

0.8 x 1.6

7 mm/M 2.5/3.0 x 0.5

125 V/8 A/1.5 mm²

2.5 kV/3

0.4...0.7

1

0.5...2.5

1.5

0.5...1.5

0.5...1.5

0.5...1.5

0.13...2.5 / A1

24

24

300 V/10 A/26...14 AWG

300 V/10 A/24...16 AWG

Type Cat. No. Qty.

AKZ 1.5 T 0400460000 100

AKZ 1.5 T 0400360000 100



5/26/46.7

0.8 x 1.6

7 mm/M 2.5/3.0 x 0.5

125 V/10 A/2.5 mm²

2.5 kV/3

0.4...0.6

1

0.5...4

1.5...2.5

0.5...2.5

0.5...2.5

0.5...2.5

0.13...4.0 / A3

24

24

300 V/10 A/26...14 AWG

300 V/10 A/26...10 AWG

Type Cat. No. Qty.

AKZ 2.5 K 0696260000 100

End plate (thickness mm)



PA

AP (1.5) 0340560000 50

AP (1.5) 0340560000 50

AP (1.5) 0340560000 50

AP (2.5) 0697260000 50

Partition (thickness mm)



PA

TW (1.5) 0318560000 20

Small partition



Cross-connection



Q 3

2-pole

Q 2 0368200000 50

3-pole

Q 3 0368300000 50

4-pole

Q 4 0368400000 50

10-pole

Q 10 0368500000 20

Q 2 0368200000 50

Q 3 0368300000 50

Q 4 0368400000 50

Q 10 0368500000 20

Q 2 0368200000 50

Q 3 0368300000 50

Q 4 0368400000 50

Q 10 0368500000 20

Q 2 0368200000 50

Q 3 0368300000 50

Q 4 0368400000 50

Q 10 0368500000 20

Switchable cross-connection link



VL



BS



VH

Test plug/socket



StB

Plug test socket ø 2.3

StB 8.5 0215700000 50

StB 8.5 0215700000 50

StB 8.5 0215700000 50

StB 8.5 0215700000 50



PS

PS 2.3 0180400000 20


PS 2.3 0180400000 20

PS 2.3 0180400000 20

PS 2.3 0180400000 20

Marking tags

Print



DEK

Standard

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"


Mounting rails, end brackets, further marking material see "Accessories"

Feed-through terminals for TS 15

AKZ 2.5 K



AKZ 2.5 K



AKZ 4 T



AKZ 4 T



AKZ 4 T



AKZ 4 ST



					
5/26/46.7	5/47.5/27	6/27/48.5	6/27/50.5	6/27/57,8	6/27/50.2
0.8 x 1.6	0.8 x 1.6	1 x 1	0.8 x 1.6	0.8 x 2.4	0.8 x 1.6
7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6	–
250 V/8 A/2.5 mm²	250 V/8 A/2.5 mm²	250 V/10 A/4 mm²	250 V/10 A/4 mm²	250 V/10 A/4 mm²	250 V/10 A/2.5 mm²
4 kV/3	4 kV/3	4 kV/3	4 kV/3	4 kV/3	4 kV/3
0.4...0.6	0.4...0.6	0.5...1.0	0.5...1.0	0.5...1.0	
1	1	2	2	2	
0.5...4	0.5...4	0.5...4	0.5...4	0.5...4	
1.5...2.5	1.5...2.5	1.5...4	1.5...4	1.5...4	
0.5...2.5	0.5...2.5	0.5...4	0.5...4	0.5...4	
0.5...2.5	0.5...2.5	0.5...4	0.5...4	0.5...4	
0.5...2.5	0.5...2.5	0.5...4	0.5...4	0.5...4	
0.13...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3	0.5...2.5 / -
24	24	20	20	20	20
24	24	20	20	20	20
300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	
300 V/10 A/26...10 AWG	300 V/10 A/26...10 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG
TypeCat. No.Qty.	TypeCat. No.Qty.	TypeCat. No.Qty.	TypeCat. No.Qty.	TypeCat. No.Qty.	TypeCat. No.Qty.
AKZ 2.5 K0695460000100		AKZ 4 T0445860000100			AKZ 4 ST0439260000100
	AKZ 2.5 K0695960000100		AKZ 4 T0344160000100		
			AKZ 4 T0344060000100		
AKZ 2.5 K0695660000100	AKZ 2.5 K0696160000100			AKZ 4 T0366460000100	
				AKZ 4 T0461660000100	
AP (2.5)069726000050	AP (2.5)069726000050	AP (1.5)029446000020	AP (1.5)029446000020	AP (1.5)029446000020	AP (1.5)029446000020
TW (1.5)031856000020	TW (1.5)031856000020	TW (1.5)034826000050	TW (1.5)034826000050	TW (1.5)034826000050	TW (1.5)034826000050
		TSch 40363360000100	TSch 40363360000100	TSch 40363360000100	
Q 2036820000050	Q 2036820000050	Q 2033640000050	Q 2033640000050	Q 2033640000050	Q 2036900000050
Q 3036830000050	Q 3036830000050	Q 3033650000050	Q 3033650000050	Q 3033650000050	Q 3036910000050
Q 4036840000050	Q 4036840000050	Q 4033660000050	Q 4033660000050	Q 4033660000050	Q 4036920000050
Q 10036850000020	Q 10036850000020	Q 10036860000020	Q 10036860000020	Q 10036860000020	Q 10036930000020
		VL 2044670000050	VL 2044670000050	VL 2044670000050	
		VH 10044660000050	VH 10044660000050	VH 10044660000050	
		BS M2.5x140266800000100	BS M2.5x140266800000100	BS M2.5x140266800000100	
StB 8.5021570000050	StB 8.5021570000050	StB 8.5021570000050	StB 8.5021570000050	StB 8.5021570000050	StB 8.5021570000050
PS 2.3018040000020	PS 2.3018040000020	PS 2.3018040000020	PS 2.3018040000020	PS 2.3018040000020	PS 2.3018040000020
DEK 5see "Accessories"	DEK 5see "Accessories"	DEK 6see "Accessories"	DEK 6see "Accessories"	DEK 6see "Accessories"	DEK 6see "Accessories"

Feed-through terminals for TS 15

for temperature measuring circuits


AKZ 4/TC



Weidmüller's thermocouple terminals are specially designed for transmitting the smallest voltages in temperature measuring circuits. Special busbars ensure that no false signals occur in the terminal when temperature differences exist in the positive and negative path. This high measuring precision is necessary for, e.g. test beds for aircraft engines, for complicated chemical processes, control systems, etc.

- Busbar material corresponds to thermal and compensating conductors
- Clear thermocouple marking
- 2-pole blocks per thermocouple
- Row width 14 mm, incl. end plate

Configuration of a temperature measuring circuit



The thermocouple terminals displayed in this measurement circuit are used to thermoelectrically transmit thermal e.m.f. of the thermocouple to the reference point and indicating device. Thermocouple terminals are required for the construction of temperature measuring circuits.

Dimensions		
Width/length/height (mm)	with TS 15	14/27/30
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6
Rated data		
Rated voltage/current/cross-section		-/-/4 mm ²
Further technical data		
Tightening torque range	Nm	0.5...1
Torque setting with electric screwdriver type DMS 2		2
Clampable conductor		
Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...2.5
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...2.5
Plug gauge acc. to IEC 60 947-1	Size	A 3
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2-pole	A	
Continuous current rating of cross-connection multipole	A	
Ordering data		
Version		TS 15 Cat. No. Qty.
for thermocouples	Type J Fe – CuNi	1627010000 20
Acc. to IEC 584	Type T Cu – CuNi	on demand
(DIN 43710)	Type K NiCr – Ni	1677130000 20
	Type E NiCr – CuNi	on demand

End plate		Cat. No.	Qty.
AP (thickness 1.5 mm)	PA	0294460000	20
Partition			
TW (thickness 0.5 mm)	PA	0348260000	50

Thermocouple, type J	
Thermocouple acc. to IEC 584 (DIN 43 710)	Busbar
	Constantan (CuNi)
	Iron (Fe)



Marking tags		Print
Material V0	DEK 5/6	1789590000 500



Mounting rails, end brackets, further marking material see "Accessories"

Multipole terminal blocks



Screw connection

MK 2/12

MK 10/14

MK 3/12

MK 4/16

[illegible]

Multipole terminal blocks

Screw/tab connection

MK 5/2

KS 2...10

BK 2...12

MK 6/2...6/6



Dimensions/approvals

Width/length/height (mm)		40/18/15.5	see table below	see table below	see table below
Insulation stripping length/clamping screw/screwdriver blade		5 mm/M 2.5/3.5 x 0.6	8 mm/M 3/4.0 x 0.8	8 mm/M 3/4.0 x 0.8	9 mm/M 4/4.0 x 0.8
Rated data according to IEC 60 947-7-1					
Rated voltage/current/cross-section		500 V/24 A/2.5 mm ²	500 V/24 A/2.5 mm ²	400 V/32 A/4 mm ²	690 V/41 A/6 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	6 kV/3	6 kV/3	8 kV/3
Further technical data					
Tightening torque range	Nm	0.4...0.45	0.5...0.7	0.5...0.7	1.2...2.0
Torque setting with electric screwdriver type DMS 2		1	2	2	4
Clampable conductor					
Solid H07V-U	mm ²	0.5...4	0.5...4	0.5...4	0.5...6
Stranded H07V-R	mm ²	1.5...2.5	1.5...2.5	1.5...4	1.5...6
Flexible H07V-K	mm ²	0.5...2.5	0.5...2.5	0.5...4	0.5...6
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...1.5	0.5...1.5	0.5...4	0.5...4
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...1.5	0.5...1.2	0.5...4	0.5...4
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size		0.2...4.0 / A 2	0.2...4.0 / A 2	0.33...4.0 / A 3	0.33...6.0 / A 3

Rated data according to UL/CSA

Voltage/current/conductor size	UL		300 V/20 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/30 A/22...10 AWG
Voltage/current/conductor size	CSA		300 V/25 A/24...12 AWG	300 V/10 A/22...12 AWG	300 V/40 A/22...10 AWG

Ordering data

Versions

		2-pole	MK 5/2 KrG	0243820000	100	KS 2 KrG ²⁾	0134420000	100	BK 2 KrG	0624720000	50	MK 6/2 KrG	0620420000	50
		3-pole							BK 3 KrG	0624920000	50	MK 6/3 KrG	0620320000	50
		4-pole				KS 4 KrG ²⁾	0140320000	50	BK 4 KrG	0625120000	50	MK 6/4 KrG	0620220000	20
		4-pole												
		6-pole				KS 6 KrG ²⁾	0140620000	50	BK 6 KrG	0625220000	50	MK 6/6 KrG	0620120000	20
		6-pole												
		8-pole												
		8-pole												
		10-pole				KS 10 KrG ²⁾	0141620000	20						
		12-pole	Cover			Cover			BK 12 KrG	0625320000	50			
		12-pole	D2 (for MK 5/2)	0244060000	50	D 2 (for KS 2)	0134500000	100						
		12-pole				D 4 (for KS 4)	0140500000	50						
						D 6 (for KS 6)	0140800000	50						
						D 10 (for KS 10)	0141800000	20						



Cover D 2
(for MK 5/2)




Cover D 4
(for KS 4)




Cover D 2
(for MK 5/2)



Cover D 4
(for KS 4)




Marking tag cover



Dimensions


Type	a	b
KS 2	42	32
KS 4	66	56
KS 6	90	80
KS 10	138	128



Dimensions

Type	a	b
BK 2	20	—
BK 3	31	11
BK 4	38	18
BK 6	52	32
BK 12	92	72.5

SN 0200100000 500



Dimens. Length/attach. dim.

Type	KRG
MK 6/2	23.5
MK 6/3	36.5
MK 6/4	49.5
MK 6/6	75.5

Expansion rivet

Marking strips

printed
1 ...

unprinted

ELSb 2	0143200000	50
ELSb 4	0143300000	50
ELSb 6	0143400000	50
ELSb 10	0143500000	50

ELSo 2	0142800000	50
ELSo 4	0142900000	50
ELSo 6	0143000000	50
ELSo 10	0143100000	50

BSTb 28/2	0203600000	50
BSTb 28/3	0203800000	50
BSTb 28/4	0197300000	50
BSTb 28/6	0197500000	50
BSTb 28/12	0198800000	50
BSTo 28/2	0203500000	50
BSTo 28/3	0203700000	50
BSTo 28/4	0197200000	50
BSTo 28/6	0197400000	50
BSTo 28/12	0198700000	50

BSTb 17/6 0304600000 50


Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ Projecting length = 1 mm. To be considered for the last terminal in a row!
Printed on top on request

²⁾ Please order cover and marking strips separately.

Multipole terminal blocks


MF 1/6...1/12



SLS 2/2



SLS 2/4



Max. technical data

Dimensions/approvals

Width/length/height (mm)

Insulation stripping length/clamping screw/screwdriver blade

Rated data according to IEC 60 947-7-1

Rated voltage²⁾/current/cross-section

Rated impulse voltage VDE 0110/1.89/pollution severity

Further technical data

Tightening torque range

Nm

Torque setting with electric screwdriver type DMS 2

Clampable conductor

Solid H07V-U

mm²

Stranded H07V-R

mm²

Flexible H07V-K

mm²

Flexible H07V-K and ferrule DIN 46 228/1

mm²

Flexible H07V-K and ferrule with plastic insul. collar

mm²

Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size

Rated data according to UL/CSA

Voltage/current/conductor size

UL

Voltage/current/conductor size

CSA

Ordering data

PA



see below



see below

8 mm/M 3.5/4.0 x 0.8

400 V²⁾/16 A/2.5/1 mm²

6 kV/3

0.8...1.6

3

0.5...4

1.5...4

0.5...4

0.5...4

0.5...4

0.33...4.0 / A 3

300 V/10 A/24...12 AWG

300 V/10 A/22...10 AWG

300 V/10 A/22...10 AWG

Type Cat. No. Qty.

MF 1/6 KrG³⁾ **0479720000** 100

MF 1/6 KrG³⁾ **0480020000** 100

MF 1/8 KrG³⁾ **0479820000** 50

MF 1/8 KrG³⁾ **0480120000** 50

MF 1/12 KrG³⁾ **0479920000** 50

MF 1/12 KrG³⁾ **0480220000** 50


Type Cat. No. Qty.

SLS 2/2 KrG **0213420000** 100

SLS 2/4 KrG **0240420000** 50



SLS 2/4 KrG **0480320000** 50

Slotted



Dimensions

Type	a	b	c	d
MF 1/6	52	34	9.5	6.5
MF 1/8	68	50	9.5	6.5
MF 1/12 113 ^{+0.5}	102	8	7.5	



Expansion rivet/insulation sleeve

IH

IH 2.8 **0386060000** 100

IH 6.3 **0386260000** 100

SN **0200100000** 500

IH 2.8 **0386060000** 100

IH 6.3 **0386260000** 100

Cover/marking strips

BSTb 10/6 **0240900000** 50

BSTb 10/8 **0241100000** 50

BSTb 10/12 **0209500000** 50

BSTo 10/6 **0240800000** 50

BSTo 10/8 **0241000000** 50

BSTo 10/12 **0209400000** 100

Mounting rails, end brackets, further marking material see "Accessories"

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

²⁾ Single tab
³⁾ Double tab

Multipole terminal blocks


Screw, solder, tab connection

MKL 2/12

MF 2/12

MKL 3/12

MKL 4/16


[illegible]

1) Rated voltage 250 V


Multipole terminal blocks

Screw, solder, tab
connection
Modular design

AKB 4



AKZ 2.5



ASK 1



Max. technical data

Dimensions/approvals		AKB 4	AKZ 2.5	ASK 1
Width/length/height (mm)		6/27/23	5/25.5/26.5	8/58/30.5
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6	7 mm/M 2.5/3 x 0.5	9 mm/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1				
Rated voltage/current/cross-section		400 V/32 A/4 mm ²	250 V/24 A/2.5 mm ²	500 V/6.3 A*/4 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity		6 kV/3	4 kV/3	6 kV/3
Further technical data				
Tightening torque range Nm		0.5...1.0	0.4...0.6	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2	1	2
Clampable conductor				
Solid H07V-U mm ²		0.5...6	0.5...4	0.5...4
Stranded H07V-R mm ²		1.5...4	1.5...2.5	1.5...4
Flexible H07V-K mm ²		0.5...4	0.5...2.5	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1 mm ²		0.5...4	0.5...2.5	0.5...2.5
Flexible H07V-K and ferrule with plastic insul. collar mm ²		0.5...4	0.5...2.5	0.5...2.5
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size		0.33...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3
Continuous current rating of cross-connection 2-pole A		32	24	(QB 2...4) 10
Continuous current rating of cross-connection multipole A		32	24	
Rated data according to UL/CSA				
Voltage/current/conductor size UL		300/250 V/27 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG
Voltage/current/conductor size CSA		300 V/10 A/22...12 AWG	300 V/10 A/26...10 AWG	300 V/6.3 A/26...12 AWG
Ordering data		Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
PA		AKB 4 PA 0321560000 100	AKZ 2.5 0697160000 100	ASK 1 PA 0376960000 100
Blue PA		0321580000 100	AKZ 2.5 0697180000 100	
		Direct mounting with BB 1 please order separately	Direct mounting with BB 4 please order separately	(for G fuse inserts 5x 20 without indicator)

End plate/attachment bracket (thickness mm)

	AP	BB 1 (7) 0320560000 50	BB 4 (7.5) 0697560000 50	
	PA Blue PA	BS M 3 x 15 0359000000 100		
			AP (2.5) 0697360000 50	AP (1.5) 0380360000 20
			AP (2.5) 0697380000 50	

Partition (thickness mm)

	TW PA (0.5) 0348260000 50			
---	---------------------------	--	--	--

Small partition

	TSch 4 0363360000 100			
---	-----------------------	--	--	--

Cross-connection

	Q 2	0336400000 50	Q 2	0368200000 50	QB 2 ¹⁾ 0461100000 50
	Q 3	0336500000 50	Q 3	0368300000 50	QB 3 ¹⁾ 0461200000 50
	Q 4	0336600000 50	Q 4	0368400000 50	QB 4 ¹⁾ 0461300000 50
	Q 10	0368600000 20	Q 10	0368500000 20	

Switchable cross-connection link

	VL 2	0446700000 50			
	VH 10	0446600000 50			
	BS M 2.5x14	0266800000 100			


Test plug/socket

	PS	StB 8.5 0215700000 50	StB 8.5 0215700000 50		
	StB	PS 2.3 0180400000 20	PS 2.3 0180400000 20		

Cover/contact sleeve

	AD 4	0303400000 50			
	BSK M 2.5x18	0303300000 100			K sleeve 0553300000 100

Marking tags

	DEK	Print	DEK 6	see "Accessories"	DEK 5	see "Accessories"	DEK 6.5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ The conductor cross-section is reduced to max. 2.5 mm² when QB is used.

* With contact sleeve 19 A

Screw connection
Solder connection
Tab connection
Spring-clip connection
 acc. to DIN 41 611 Part 4
Wrap connection
 acc. to DIN/IEC 352 Part 1

ADK 1 S



* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

Feed-through terminals

ADK 1 T



6/22/50.5
19.5...21.9
9 mm/M 3/3.5 x 0.6
400 V/8 A/4 mm ²
6 kV/3
0.5...1.0
2
0.5...4
1.5...4
0.5...4
0.5...2.5
0.5...2.5
0.13...4.0 / A3
10
300/250 V/10 A/26...12 AWG
300 V/15 A/26...12 AWG
1.5 Qty. 2.5 Qty.
0372260000 100
0366360000 100

Type	Cat. No.	Qty.
AP (3)	0476260000	50
TW (0.5)	0442300000	50
PS 2.3	0180400000	20
SST 1.2	0306600000	
DEK 6	see "Accessories"	

AKZ 2.5 K



0109160000 solder tag

5/26/45.5
22.4...23.6
7 mm/M 2.5/3.0 x 0.5
250 V/8 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...2.5
0.5...2.5
0.13...2.5 / A2
10
300/250 V/10 A/22...12 AWG
300 V/10 A/26...10 AWG
Cat. No. Qty.
0109160000 solder tag 100
0108960000 100

Type	Cat. No.	Qty.
AP (3)	0697260000	50
TW (1.5)	0318560000	20
PS 2.3	0180400000	20
StB 8.5	0215700000	50
IH 2.8	0386060000	100
DEK 5	see "Accessories"	


ADK 1 FT



6/22/52
24
11 mm/M 2.5/3.5 x 0.6
250 V/10 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...1.5
0.5...1.5
0.33...2.5 / A2
10
300 V/3 A/22...14 AWG
Cat. No. 1.5 Qty.
0176960000 100

Type	Cat. No.	Qty.
AP (3)	0476260000	50
TW (0.5)	0442300000	50
SST 1.2	0306600000	
DEK 6	see "Accessories"	

MK 2/12



86/15/23
8
5
63 V/20 A/2.5/1.5 mm ²
1.5 kV/3
0.4...0.45
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...2.5
0.5...2.5
0.2...2.5 / A2
10
300 V/10 A/24...12 AWG
300 V/10 A/24...12 AWG
Cat. No. Qty.
0241460000 50

Type	Cat. No.	Qty.
SN	0200100000	500
BSTb 28/12	024570...	50
BSTo 28/12	024560...	50

Rack-mounted interface systems



Dimensions														
Width/length/height (mm)		40.2/110.6/29.5			42/46.5/170/28			40/45.5/162.5/110			40/45.5/228.5/110			
Hole spacing/mounting dimensions		mm 101.6/20.3			147			151/90			217/90			
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6												
Rated data														
Rated voltage*/current/cross-section		250* V/6 A/1.5/1 mm²			1000* V/16 A/2.5/1.5 mm²			400* V/16 A/2.5/1.5 mm²			400* V/16 A/2.5/1.5 mm²			
Rated impulse voltage VDE 0110/1.89/pollution severity		4 kV/3			6 kV/3			6 kV/3			6 kV/3			
Further technical data														
Tightening torque range		Nm 0.4...0.7												
Torque setting with electric screwdriver type DMS 2		1												
Clampable conductor														
Solid H07V-U		mm² 0.5...2.5												
Stranded H07V-R		mm² 1.5												
Flexible H07V-K		mm² 0.5...1.5												
Flexible H07V-K and ferrule DIN 46 228/1		mm² 0.5...1.5												
Flexible H07V-K and ferrule with plastic insul. collar		mm² 0.5...1.5												
Plug gauge acc. to IEC 60 947-1		Size A1												
Ordering data		Version	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
Pin 1.0 x 1.0		PA	TOP 1.5 F/32	0443160000 ¹⁾	5									
Pin 0.8 x 2.8 (push-on), unprinted		PA												
Pin 0.8 x 2.8 (push-on), printed, 1...32		PA												
Pin 0.8 x 2.8 (push-on), printed, 1...32, blue		PA												
6 x plug (6.3 x 0.8)		KrG				SP 10 FF	0456220000	10	SP 60 FF ⁴⁾	0340320000	1	SP 90 FF**	0248120000	1
6 x plug (6.3 x 0.8), blue		KrG							SP 60 FF ⁴⁾	0340370000	1			
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted		KrG										SP 90 FF**	0608920000	1
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted, blue		KrG												
3 x plug (6.3x0.8)/1 x solder per pole		KrG							SP 60 LF ⁴⁾	0343720000	1	SP 90 LF**	0248220000	1
3 x plug (6.3x0.8)/1 x solder per pole, blue		KrG							SP 60 LF ⁴⁾	0343770000	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8)/1 x solder		KrG							SP 60 LF ⁵⁾	0124520000	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8)/1 x solder, blue		KrG							SP 60 LF ⁵⁾	0124570000	1	printed:		
2 x direct connection, 1 x Pin 0.8 x 1.6		PA										** A...F / 1...15		
									printed:					
									⁴⁾ A...F / 1...10					
									⁵⁾ 00...50 / 1...10					
Insulation sleeves		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	
		IH 2.8	0386060000	100	IH 2.8	0386060000	100	IH 2.8	0386060000	100	IH 2.8	0386060000	100	
					IH 6.3	0386260000	100	IH 6.3	0386260000	100	IH 6.3	0386260000	100	
Marking tags		Print												
dekafix		for group markers				FW 5	see "Accessories"							
Mounting rails, end brackets, further marking material see "Accessories"														

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

1) Rated voltage 125 V

2) FF = Tab- Tab
3) LF = Solder - Tab

Rack-mounted interface systems

RV 8/8 long



RV 8/8 short



RV 8/9 long



RV 8/9 short



Technical data acc. to VDE

Pin versions (intern)

0.8 x 2.4/1 x 1
0.8 x 2.4/0.8 x 2.4

Plug adapter



1-pole

for connection of solid and flexible conductors from 0.75 to 1.5 mm² directly on to the pins of the interface system.


125 V/-/-			125 V/-/-		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	0468860000	1		0467160000	1
	0468960000	1		0467260000	1
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
DSA 1	0576060000	50	DSA 1	0576060000	50

105 V/-/-			125 V/-/-		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	0498960000	1		0444060000	1
	0499060000	1		0545960000	1
with shield pins			with shield pins		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
DSA 1	0576060000	50	DSA 1	0576060000	50

RV 8/20 short



RV 8/56 short



Technical data acc. to VDE


Pin versions (internal)

0.8 x 2.4/1 x 1
0.8 x 2.4/0.8 x 2.4

Additional versions on request

125 V/-/-		
Cat. No.	Qty.	
0544460000	1	

125 V/-/-		
Cat. No.	Qty.	
0462260000	1	
0533060000	4	



Type	Size A	Size B
	in mm	in mm
RV 8/8 K	81	40.64
RV 8/9 K	89	40.64
RV 8/8 L	93	40.64
RV 8/9 L	100	40.64
RV 8/20 K	187,62/31.5	63
RV 8/56 K	460/31.5	63

Cat. No.	RV	a	b	c
0468860000	8/8 L	26	20	200
0468960000	8/8 L	26	26	206
0467160000	8/8 K	26	20	84
0467260000	8/8 K	26	26	89
0119360000	8/20 K	26	20	84
0544460000	8/20 K	26	26	89
0462260000	8/56 K	26	20	84
0533060000	8/56 K	26	26	89

Mounting rails, end brackets, further marking material see "Accessories"

SAK-series

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А