

Circuit Breaker for Equipment thermal, Rotary knob actuation, 2 pole



Thermal circuit breaker  
Rotary Switch, 2-pole  
Standard version

See below:

## Approvals and Compliances

### Description

- Thermal circuit breaker ,
- 2-pole
- Supplementary protector for general industrial use
- Positively trip-free release
- Method of operation acc. to IEC: S-type
- Bezel / knob snap-on

### Unique Selling Proposition

- Easy actuation with gloves

### Applications

- Power tools
- Industrial appliances
- Equipment for construction
- Cleaning equipment
- Commercial and household kitchen appliances

### References

Available without bezel/knob for customized front panel design

### Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#), [Product News](#)

### Technical Data

|                                        |                                                                                                                                                                  |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Voltage AC                       | IEC: 240 VAC:<br>UL/CSA : 277 VAC                                                                                                                                |
| Rated Voltage DC                       | 60 VDC                                                                                                                                                           |
| Rated current range AC                 | 0.05 20 A                                                                                                                                                        |
| Conditional short circuit capacity Inc | IEC 60934: 0.05...20 A: 2 kA, SC (C1)<br>@ 240 VAC                                                                                                               |
| Degree of Protection                   | from front side IP40 from rear-side acc.<br>to IEC 60529                                                                                                         |
| Dielectric Strength                    | 50Hz: > 2.5 kV<br>Impulse 1.2/50 $\mu$ s: > 4 kV                                                                                                                 |
| Insulation Resistance                  | 500VDC > 100 M $\Omega$                                                                                                                                          |
| Lifetime                               | mechanical 50'000 switching cycles<br>AC: 1 x I <sub>r</sub> , cos $\phi$ 0.6:<br>50'000 switching cycles<br>DC: 1 x I <sub>r</sub> :<br>50'000 switching cycles |

|                           |                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------|
| Overload                  | IEC: min. 40 trips@ 6 x I <sub>r</sub> , cos $\phi$ 0.6<br>: min. 50 trips@ 1.5 x I <sub>r</sub> , cos $\phi$ 0.75   |
| Allowable Operation Temp. | -30 °C to 60 °C                                                                                                      |
| Vibration Resistance      | $\pm$ 0.75 mm @ 10 - 60 Hz<br>acc. to IEC 60068-2-6, test Tc<br>10 G @ 60 - 500 Hz<br>acc. to IEC 60068-2-6, test Tc |
| Shock Resistance          | 30 G / 18 ms<br>acc. to IEC 60068-2-27, test Ea                                                                      |
| Tripping Type             | Thermal                                                                                                              |
| Actuation Type            | Rotary Knob                                                                                                          |
| Weight                    | 60 g                                                                                                                 |

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: TA35

| Approval Logo                                                                    | Certificates  | Certification Body | Description                              |
|----------------------------------------------------------------------------------|---------------|--------------------|------------------------------------------|
|  | VDE Approvals | VDE                | VDE Certificate Number: 40019754         |
|  | UL Approvals  | UL                 | UL File Number: E71572                   |
|  | CCC Approvals | CCC                | CCC Certificate Number: 2020970307001846 |

## Product standards

Product standards that are referenced


| Organization                                                                     | Design                | Standard          | Description                                                           |
|----------------------------------------------------------------------------------|-----------------------|-------------------|-----------------------------------------------------------------------|
|  | Designed according to | IEC 60934         | Circuit-breakers for equipment (CBE)                                  |
|  | Designed according to | UL 1077           | Standard for Supplementary Protectors for Use in Electrical Equipment |
|  | Designed according to | CSA C22.2 No. 235 | Supplementary Protectors                                              |
|  | Designed according to | GB 17701          | Circuit-breaker for equipment                                         |


## Compliances

The product complies with following Guide Lines


| Identification                                                                     | Details                      | Initiator   | Description                                                                                                                                                                                           |
|------------------------------------------------------------------------------------|------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|   | CE declaration of conformity | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | RoHS                         | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863                                                                                                                                                    |
|  | China RoHS                   | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.                                                                                  |
|  | REACH                        | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.                               |

## Dimension [mm]





Cut out



Assembly Instructions



| Approval                                                                            |               | Rated current | Rated Voltage AC | Rated Voltage DC |
|-------------------------------------------------------------------------------------|---------------|---------------|------------------|------------------|
|  | UL 1077       | 0.05...20 A   | 277 V            | 60 V             |
|  | CSA C22.2 235 | 0.05...20 A   | 277 V            | 60 V             |
|  | IEC 60934     | 0.05...20 A   | 240 V            | 60 V             |
|  | GB 17701      | 0.05...20 A   | 240 V            | 60 V             |


## Typical internal resistance per pole

| Rated Current [A] | Internal Resistance [ $\Omega$ ] |
|-------------------|----------------------------------|
| 0.05              | 200.000                          |
| 0.1               | 70.000                           |
| 0.5               | 2.750                            |
| 1.0               | 0.720                            |
| 1.5               | 0.340                            |
| 2.0               | 0.187                            |
| 2.5               | 0.115                            |
| 2.8               | 0.089                            |
| 3.0               | 0.059                            |
| 4.0               | 0.059                            |
| 5.0               | 0.044                            |
| 6.0               | 0.028                            |
| 7.0               | 0.0142                           |
| 8.0               | 0.0142                           |
| 10.0              | 0.0109                           |
| 12.0              | 0.0086                           |
| 13.0 *            | 0.0072                           |
| 14.0 *            | 0.0072                           |
| 15.0 *            | 0.0056                           |
| 16.0 *            | 0.0056                           |
| 18.0 *            | 0.0052                           |
| 20.0 *            | 0.0052                           |

\* 3-Pole max. 12 A


## Time-Current-Curves

### Tripping Characteristics $I_n < 3$ A



Reference Temperature +23°

### Tripping Characteristics $I_n 3 - 20$ A



Reference Temperature +23°

## Effect of ambient temperature

The units are calibrated for an ambient temperature of +23°C. To determine the rated current for a lower or higher ambient temperature, use a correction factor (typical value) from the table below:

| Ambient Temperature [°C] | Correction factor |
|--------------------------|-------------------|
| -30                      | 0.76              |
| -20                      | 0.81              |
| 0                        | 0.90              |
| +23                      | 1.00              |
| +40                      | 1.03              |
| +50                      | 1.04              |
| +60                      | 1.06              |

Example: Rated current = 5 A, Environmental temperature = 50 °C --> Correction factor = 1.04, Resulting current = 5.2 A --> Fount to next higher rated current: 6 A

## Configurations code

| Number of switched poles<br>Number of protected poles | 1-pole<br>1 | 2-pole<br>1 2 | 3-pole<br>3 |
|-------------------------------------------------------|-------------|---------------|-------------|
|                                                       |             |               |             |
| Basic type                                            | EFT         | EBT           | EBD         |

Other versions on request

TA35- **EBT** **T** **F** **120** **C0**

No other features

| Frontbezel and actuation knob |               |              |
|-------------------------------|---------------|--------------|
|                               | Bezel         | Knob         |
| <b>T</b>                      | black         | black        |
| <b>N</b>                      | without bezel | without knob |

| Bezel marking |                 |            |
|---------------|-----------------|------------|
|               | Surface         | Symbol     |
| <b>F</b>      | relief recessed | I 0        |
| <b>N</b>      | no marking      | no marking |

## With thermal overload protection: rated current $I_n$ (A)

| $I_n$ | Code       | $I_n$ | Code       | $I_n$ | Code       | $I_n$ | Code       |
|-------|------------|-------|------------|-------|------------|-------|------------|
| 0.05  | <b>Z05</b> | 1.0   | <b>J10</b> | 4.0   | <b>040</b> | 14.0  | <b>140</b> |
| 0.1   | <b>J01</b> | 1.2   | <b>J12</b> | 5.0   | <b>050</b> | 15.0  | <b>150</b> |
| 0.2   | <b>J02</b> | 1.5   | <b>J15</b> | 6.0   | <b>060</b> | 16.0  | <b>160</b> |
| 0.3   | <b>J03</b> | 2.0   | <b>J20</b> | 7.0   | <b>070</b> | 18.0  | <b>180</b> |
| 0.4   | <b>J04</b> | 2.5   | <b>J25</b> | 8.0   | <b>080</b> | 20.0  | <b>200</b> |
| 0.5   | <b>J05</b> | 3.0   | <b>030</b> | 10.0  | <b>100</b> |       |            |
| 0.8   | <b>J08</b> | 3.5   | <b>035</b> | 12.0  | <b>120</b> |       |            |

Other rated currents on request.

All Variants

| Designation                                                                                                         | Order Number |
|---------------------------------------------------------------------------------------------------------------------|--------------|
| TA35 Drehknopf 2Pol, 20 A, Snap-in version, Quick connect terminals 6.3 x 0.8 mm, 240 VAC, 2-pole, Circuit Breakers | 4435.0074    |
| TA35 Drehknopf 2Pol, 10 A, Snap-in version, Quick connect terminals 6.3 x 0.8 mm, 240 VAC, 2-pole, Circuit Breakers | 4435.0086    |

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А