


**Features**


- Low  $V_{CE(on)}$  Planar IGBT Technology
- Low Switching Losses
- Square RBSOA
- 100% of the Parts Tested for ILM
- Positive  $V_{CE(on)}$  Temperature Coefficient
- Reflow Capable per JDS22-A113
- Lead-Free, RoHS Compliant
- Automotive Qualified \*



$V_{CES} = 1200V$   
 $I_C = 81A @ T_C = 100^\circ C$   
 $V_{CE(on)} \text{ typ.} = 1.47V @ 33A$

**Benefits**

- Device optimized for soft switching applications
- High Efficiency due to Low  $V_{CE(on)}$ , low switching losses
- Rugged transient performance for increased reliability
- Excellent current sharing in parallel operation
- Low EMI



|      |           |         |
|------|-----------|---------|
| G    | C         | E       |
| Gate | Collector | Emitter |

**Application**

- PTC Heater
- Relay Replacement

| Base Part Number | Package Type | Standard Pack |          | Orderable Part Number |
|------------------|--------------|---------------|----------|-----------------------|
|                  |              | Form          | Quantity |                       |
| AUIRGDC0250      | Super-TO-220 | Tube          | 50       | AUIRGDC0250           |

**Absolute Maximum Ratings**

Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only; and functional operation of the device at these or any other condition beyond those indicated in the specifications is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions. Ambient temperature ( $T_A$ ) is  $25^\circ C$ , unless otherwise specified.

|                           | Parameter                                                   | Max.                              | Units      |
|---------------------------|-------------------------------------------------------------|-----------------------------------|------------|
| $V_{CES}$                 | Collector-to-Emitter Voltage                                | 1200                              | V          |
| $I_C @ T_C = 25^\circ C$  | Continuous Collector Current                                | 141 <sup>④</sup>                  | A          |
| $I_C @ T_C = 100^\circ C$ | Continuous Collector Current                                | 81                                |            |
| $I_{CM}$                  | Pulse Collector Current, $V_{GE} = 15V$ <sup>②</sup>        | 99                                |            |
| $I_{LM}$                  | Clamped Inductive Load Current, $V_{GE} = 20V$ <sup>①</sup> | 99                                | V          |
| $V_{GE}$                  | Continuous Gate-to-Emitter Voltage                          | $\pm 20$                          |            |
|                           | Transient Gate-to-Emitter Voltage                           | $\pm 30$                          |            |
| $P_D @ T_C = 25^\circ C$  | Maximum Power Dissipation                                   | 543                               | W          |
| $P_D @ T_C = 100^\circ C$ | Maximum Power Dissipation                                   | 217                               |            |
| $T_J$                     | Operating Junction and                                      | -55 to +150                       | $^\circ C$ |
| $T_{STG}$                 | Storage Temperature Range                                   |                                   |            |
|                           | Soldering Temperature, for 10 sec. (Through Hole Mounting)  | 300 (0.063 in. (1.6mm) from case) |            |

**Thermal Resistance**

|                        | Parameter                                                      | Typ. | Max. | Units        |
|------------------------|----------------------------------------------------------------|------|------|--------------|
| $R_{\theta JC}$ (IGBT) | Thermal Resistance Junction-to-Case (each IGBT) <sup>③</sup>   | —    | 0.23 | $^\circ C/W$ |
| $R_{\theta CS}$        | Thermal Resistance, Case-to-Sink (flat, greased surface)       | 0.50 | —    |              |
| $R_{\theta JA}$        | Thermal Resistance, Junction-to-Ambient (typical socket mount) | —    | 62   |              |

\* Qualification standards can be found at [www.infineon.com](http://www.infineon.com)

**Electrical Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**


|                                 | Parameter                               | Min. | Typ. | Max.      | Units   | Conditions                                                             |
|---------------------------------|-----------------------------------------|------|------|-----------|---------|------------------------------------------------------------------------|
| $V_{(BR)CES}$                   | Collector-to-Emitter Breakdown Voltage  | 1200 | —    | —         | V       | $V_{GE} = 0V, I_C = 250\mu A$                                          |
| $\Delta V_{(BR)CES}/\Delta T_J$ | Temperature Coeff. of Breakdown Voltage | —    | 1.2  | —         | V/°C    | $V_{GE} = 0V, I_C = 1mA (25^\circ\text{C}-150^\circ\text{C})$          |
| $V_{CE(on)}$                    | Collector-to-Emitter Saturation Voltage | —    | 1.47 | 1.8       | V       | $I_C = 33A, V_{GE} = 15V, T_J = 25^\circ\text{C}$                      |
|                                 |                                         | —    | 1.45 | —         |         | $I_C = 33A, V_{GE} = 15V, T_J = 150^\circ\text{C}$                     |
| $V_{GE(th)}$                    | Gate Threshold Voltage                  | 3.0  | —    | 6.0       | V       | $V_{CE} = V_{GE}, I_C = 250\mu A$                                      |
| $\Delta V_{GE(th)}/\Delta T_J$  | Threshold Voltage temp. coefficient     | —    | -15  | —         | mV/°C   | $V_{CE} = V_{GE}, I_C = 250\mu A (25^\circ\text{C}-150^\circ\text{C})$ |
| gfe                             | Forward Transconductance                | —    | 30   | —         | S       | $V_{CE} = 50V, I_C = 33A, PW = 20\mu S$                                |
| $I_{CES}$                       | Collector-to-Emitter Leakage Current    | —    | —    | 250       | $\mu A$ | $V_{GE} = 0V, V_{CE} = 1200V, T_J = 25^\circ\text{C}$                  |
|                                 |                                         | —    | —    | 1000      |         | $V_{GE} = 0V, V_{CE} = 1200V, T_J = 150^\circ\text{C}$                 |
| $I_{GES}$                       | Gate-to-Emitter Leakage Current         | —    | —    | $\pm 100$ | nA      | $V_{GE} = \pm 20V$                                                     |

**Switching Characteristics @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**


|              | Parameter                          | Min.        | Typ. | Max. | Units | Conditions                                                                                                               |
|--------------|------------------------------------|-------------|------|------|-------|--------------------------------------------------------------------------------------------------------------------------|
| $Q_g$        | Total Gate Charge (turn-on)        | —           | 151  | 227  | nC    | $I_C = 33A$<br>$V_{GE} = 15V$<br>$V_{CC} = 600V$                                                                         |
| $Q_{ge}$     | Gate-to-Emitter Charge (turn-on)   | —           | 26   | 39   |       |                                                                                                                          |
| $Q_{gc}$     | Gate-to-Collector Charge (turn-on) | —           | 62   | 93   |       |                                                                                                                          |
| $E_{off}$    | Turn-Off Switching Loss            | —           | 15   | 16   | mJ    | $I_C = 33A, V_{CC} = 600V, V_{GE} = 15V$                                                                                 |
| $t_{d(off)}$ | Turn-Off delay time                | —           | 485  | 616  | ns    | $R_G = 5\Omega, L = 400\mu H, T_J = 25^\circ\text{C}$<br>Energy losses include tail                                      |
| $t_f$        | Fall time                          | —           | 1193 | 1371 |       |                                                                                                                          |
| $E_{off}$    | Turn-Off Switching Loss            | —           | 29   | —    | mJ    | $I_C = 33A, V_{CC} = 600V, V_{GE} = 15V$                                                                                 |
| $t_{d(off)}$ | Turn-Off delay time                | —           | 689  | —    | ns    | $R_G = 5\Omega, L = 400\mu H, T_J = 150^\circ\text{C}$<br>Energy losses include tail                                     |
| $t_f$        | Fall time                          | —           | 2462 | —    |       |                                                                                                                          |
| $C_{ies}$    | Input Capacitance                  | —           | 3804 | —    | pF    | $V_{GE} = 0V$<br>$V_{CC} = 30V$<br>$f = 1.0Mhz$                                                                          |
| $C_{oes}$    | Output Capacitance                 | —           | 161  | —    |       |                                                                                                                          |
| $C_{res}$    | Reverse Transfer Capacitance       | —           | 31   | —    |       |                                                                                                                          |
| RBSOA        | Reverse Bias Safe Operating Area   | FULL SQUARE |      |      |       | $T_J = 150^\circ\text{C}, I_C = 99A$<br>$V_{CC} = 960V, V_p \leq 1200V$<br>$R_g = 5\Omega, V_{GE} = +20V \text{ to } 0V$ |

**Notes:**


- ①  $V_{CC} = 80\% (V_{CES}), V_{GE} = 20V, L = 400\mu H, R_G = 5\Omega.$
- ② Pulse width limited by max. junction temperature.
- ③  $R_\theta$  is measured at  $T_J$  approximately  $90^\circ\text{C}.$
- ④ Calculated continuous current based on maximum allowable junction temperature. Bond wire current limit is 78A.  
Note that current limitations arising from heating of the device leads may occur with some lead mounting arrangements.



**Fig. 1** - Maximum DC Collector Current vs. Case Temperature




**Fig. 2** - Power Dissipation vs. Case Temperature




**Fig. 3** - Forward SOA

$T_C = 25^\circ\text{C}$ ,  $T_J \leq 150^\circ\text{C}$ ;  $V_{GE} = 15\text{V}$




**Fig. 4** - Typical Gate Threshold Voltage (Normalized) vs. Junction Temperature




**Fig. 5** - Reverse Bias SOA


$T_J = 150^\circ\text{C}$ ;  $V_{GE} = 20\text{V}$




**Fig. 6** - Typ. IGBT Output Characteristics  
 $T_J = -40^\circ\text{C}$ ;  $t_p = 20\mu\text{s}$




**Fig. 7 - Typ. IGBT Output Characteristics**  
 $T_J = 25^\circ\text{C}$ ;  $t_p = 20\mu\text{s}$




**Fig. 8 - Typ. IGBT Output Characteristics**  
 $T_J = 150^\circ\text{C}$ ;  $t_p = 20\mu\text{s}$




**Fig. 9 - Typical  $V_{CE}$  vs.  $V_{GE}$**   
 $T_J = -40^\circ\text{C}$









**Fig. 10 - Typical  $V_{CE}$  vs.  $V_{GE}$**   
 $T_J = 25^\circ\text{C}$




**Fig. 11 - Typical  $V_{CE}$  vs.  $V_{GE}$**   
 $T_J = 150^\circ\text{C}$







**Fig. 12 - Typ. Transfer Characteristics**  
 $V_{CE} = 50\text{V}$ ;  $t_p = 20\mu\text{s}$


**Fig. 13 - Typ. Energy Loss vs.  $I_C$** 
 $T_J = 150^\circ\text{C}; L = 400\mu\text{H}; V_{CE} = 600\text{V}, R_G = 5\Omega; V_{GE} = 15\text{V}$ 

**Fig. 14 - Typ. Switching Time vs.  $I_C$** 
 $T_J = 150^\circ\text{C}; L = 400\mu\text{H}; V_{CE} = 600\text{V}, R_G = 5\Omega; V_{GE} = 15\text{V}$ 

**Fig. 15 - Typ. Energy Loss vs.  $R_G$** 
 $T_J = 150^\circ\text{C}; L = 400\mu\text{H}; V_{CE} = 600\text{V}, I_{CE} = 33\text{A}; V_{GE} = 15\text{V}$ 

**Fig. 16 - Typ. Switching Time vs.  $R_G$** 
 $T_J = 150^\circ\text{C}; L = 400\mu\text{H}; V_{CE} = 600\text{V}, I_{CE} = 33\text{A}; V_{GE} = 15\text{V}$ 

**Fig. 17 - Typ. Capacitance vs.  $V_{CE}$**   
 $V_{GE} = 0\text{V}; f = 1\text{MHz}$ 

**Fig. 18 - Typical Gate Charge vs.  $V_{GE}$**   
 $I_{CE} = 33\text{A}; L = 2.0\text{mH}$




**Fig 19.** Maximum Transient Thermal Impedance, Junction-to-Case (IGBT)


**Fig.C.T.1 - Gate Charge Circuit (turn-off)**

**Fig.C.T.2 - RBSOA Circuit**

**Fig.C.T.3 - Switching Loss Circuit**

**Fig. WF1 - Typ. Turn-off Loss Waveform**  
 @  $T_j = 150^\circ\text{C}$  using Fig. CT.3

# Super-TO-220 Package Outline

Dimensions are shown in millimeters (inches)



**NOTES:**

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M-1994
2. DIMENSIONS b1, b3, b5 & c1 APPLY TO BASE METAL ONLY.
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [,.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTER EXTREMES OF THE PLASTIC BODY.
- 4.- ALL DIMENSIONS SHOWN IN MILLIMETERS.
- 5.- CONTROLLING DIMENSION: MILLIMETER.
- 6.- OUTLINE CONFORMS TO JEDEC OUTLINE TO-273AA.

| SYMBO L | DIMENSIONS  |       |          |       | NOTES |
|---------|-------------|-------|----------|-------|-------|
|         | MILLIMETERS |       | INCHES   |       |       |
|         | MIN.        | MAX.  | MIN.     | MAX.  |       |
| A       | 4.34        | 4.74  | .171     | .187  |       |
| A1      | 0.50        | 1.00  | .020     | .039  |       |
| A2      | 2.50        | 3.00  | .098     | .118  |       |
| b       | 0.90        | 1.30  | .035     | .051  |       |
| b1      | 0.80        | 1.10  | .031     | .043  | 2     |
| b2      | 1.25        | 1.65  | .049     | .065  |       |
| b3      | 1.10        | 1.55  | .043     | .061  | 2     |
| b4      | 2.35        | 2.55  | .093     | .100  |       |
| b5      | 2.30        | 2.50  | .091     | .098  | 2     |
| b6      | 1.25        | 1.65  | .049     | .065  |       |
| b7      | 1.10        | 1.55  | .043     | .061  | 2     |
| c       | 0.70        | 1.00  | .028     | .039  |       |
| c1      | 0.60        | 0.90  | .024     | .035  | 2     |
| D       | 14.00       | 15.00 | .0551    | .591  | 3     |
| D1      | 12.50       | 13.50 | .492     | .531  |       |
| E       | 10.00       | 11.00 | .394     | .433  | 3     |
| E1      | 8.00        | 9.00  | .315     | .354  |       |
| e       | 2.55 BSC    |       | .100 BSC |       |       |
| e1      | 3.66 BSC    |       | .144 BSC |       |       |
| L       | 13.00       | 14.50 | .512     | .571  |       |
| L1      | 3.00        | 3.50  | .118     | .138  |       |
| L2      | 0.50        | 1.50  | .020     | .059  |       |
| L3      | 3.50        | 4.00  | .138     | .157  |       |
| L4      | -           | 1.50  | -        | .059  |       |
| ∅       | 42.5*       | 47.5* | 42.5*    | 47.5* |       |
| ∅1      | -           | 42.5* | -        | 42.5* |       |

LEAD ASSIGNMENTS


MOSFET

- 1.- GATE
- 2.- DRAIN
- 3.- SOURCE
- 4.- DRAIN

IGBT

- 1.- GATE
- 2.- COLLECTOR
- 3.- EMITTER
- 4.- COLLECTOR

## Super-TO-220 Part Marking Information





**Qualification Information**

|                                   |                      |                                                                                                                                                                                |      |
|-----------------------------------|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| <b>Qualification Level</b>        |                      | Automotive<br>(per AEC-Q101)                                                                                                                                                   |      |
|                                   |                      | Comments: This part number (s) passed Automotive qualification. Infineon's Industrial and Consumer qualification level is granted by extension of the higher Automotive level. |      |
| <b>Moisture Sensitivity Level</b> |                      | 3L– Super TO-220                                                                                                                                                               | MSL1 |
| <b>ESD</b>                        | Machine Model        | Class M4 <sup>†</sup> (+/- 800V)<br>AEC-Q101-002                                                                                                                               |      |
|                                   | Human Body Model     | Class H3A <sup>†</sup> (+/- 6000V)<br>AEC-Q101-001                                                                                                                             |      |
|                                   | Charged Device Model | Class C5 <sup>†</sup> (+/- 2000V)<br>AEC-Q101-005                                                                                                                              |      |
| <b>RoHS Compliant</b>             |                      | Yes                                                                                                                                                                            |      |

† Highest passing voltage.

**Revision History**

| Revision | Date       | Subjects (major changes since last revision)             |
|----------|------------|----------------------------------------------------------|
| 2.0      | 9/2/2014   | • Final Datasheet                                        |
| 2.1      | 12/1/2014  | • Updated with $V_{(BR)CES}$ and $V_{GE(th)}$ conditions |
| 2.2      | 3/2/2015   | • Updated with minor changes                             |
| 2.3      | 8/31/2017  | • Updated with Infineon logo                             |
| 2.4      | 03/01/2018 | • Updated with qualification level                       |
| 2.5      | 11/06/2018 | • Updated maximum $V_{CE(on)}$                           |

**Published by  
Infineon Technologies AG  
81726 München, Germany  
© Infineon Technologies AG 2018  
All Rights Reserved.**

#### **IMPORTANT NOTICE**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie"). With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

#### **WARNINGS**

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А