

Features:

- 2.4 GHz Frequency Hopping Spread Spectrum Technology
- 460 kb/s over the air data rate
- 115 kb/s RS232 data rate
- 230 kb/s USB data rate
- 32 Hopping Patterns
- FCC Certified and CE marked
- Integral 6 dB patch antenna or external antenna options
- RS-232 asynchronous or USB serial interface


Benefits:

- Exceptional immunity to multipath fading and jamming
- Supports high speed applications needing long range
- Co-location of multiple networks without interference
- License-free application worldwide
- Cost-effective, simple installation
- Connects to PC Serial or USB ports

The HopNet 250 family of modems are versatile, low cost, multi-purpose 2.4 GHz frequency-hopping wireless data modems. Built around the RFM WIT2450 radio, the HN-250, HN-250U, HN-254 and HN254U have integral 6 dB patch antennas creating "single piece" modems. Also built around the WIT2450, the HN250X and HN250UX are equipped with RF connectors instead of patch antennas to allow the use of high gain and/or remote external antennas. Communication with the HN-250, HN250X and HN254 is through a standard RS-232 interface at up to 115.2 kb/s. Communication with the HN-250U, HN250UX and HN-254U is through a 230 kb/s USB interface. All HN series modems communicate over the air at 460 kb/s in both point-to-point and point-to-multipoint networks.

HN-250 HN-250U

2.4 GHz Frequency Hopping Wireless Data Modems



HN-250

Specifications

	HN-250/HN-250U	HN-250X/HN-250UX	HN-254/HN-254U
Frequency Band	2401 - 2475 MHz		
Licensing	No license required under FCC Part 15, Canadian IC RSS-210 or ETSI 300.328		
Number of Channels	86		
Hopping Patterns	User configurable, 32 patterns (networks) available		
RS232 Data Rates	Up to 115.2 kb/s Asynchronous		
USB Data Rate	230 kb/s		
RF Data Rate	460 kb/s		
Line-of-Site Range	> 5 Miles		
RF Bandwidth	750 kHz		
Modulation Type	GFSK		
Output Impedance	50 ohms		
Network Protocol	Dynamically Assigned TDMA with ARQ		
Transmit Power	+10, +18 dBm or +24 dBm		
Receive Sensitivity	-99 dBm for 10-5 BER	-93 dBm for 10-5 BER	-99 dBm for 10-5 BER
Power Requirements	9 Vdc 160 mA typical, 750 mA peak		

Mechanical Specifications

	HN-250/HN-250U	HN-250X/HN-250UX	HN-254/HN-254U
Antenna/Connector	Integral 6 dB Patch	n/a	Integral 6 dB Patch
Case Materials	Polycarbonate, NEMA 4X		
Dimensions (mm)	130 x 79 x 35 (excluding flange)		
Weight Excluding Cable	235 g		
Antenna Connector	n/a	Reverse TNC Male	n/a
Data Connector	9-Pin D or USB B		
Power Connector	2-Pin DIN		

Environmental Specifications

Temperature Range	-30 °C to +70 °C (radio enclosure)
Humidity	95% at +40 °C, Non-condensing



Versatility

The HopNet 250 family of modems are versatile, low cost, multi-purpose 2.4 GHz frequency-hopping wireless data modems. Built around the WIT2450 radio, the HN-250, HN-250U, HN-254 and HN254U have integral 6 dB patch antennas creating "single piece" modems. Also built around the WIT2450 radio, the HN250X and HN250UX are equipped with RF connectors instead of patch antennas to allow the use of high gain and/or remote external antennas. Communication with the HN-250, HN250X and HN254 is through a standard RS-232 interface at up to 115.2 kb/s. Communication with the HN-250U, HN250UX and HN-254U is through a 230 kb/s USB interface. All HN series modems communicate over the air at 460 kb/s in both point-to-point and point-to-multipoint networks.

Simplicity

With a NEMA 4X weatherproof enclosure and aluminum mounting flange, the HN-250 and HN250U are simple to install on the side of a building or attached to a mast. With no antenna to connect, the HN-250 and HN-250U simply mount where the antenna would ordinarily be mounted. This removes the need for long antenna cable runs, expensive both in terms of cost and performance. The HN-250 and HN-250U include 50-foot cables that connect to indoor Serial Adapter Boxes (included) that provide either a standard RS-232 9-pin D connector, or USB type B connector. The HN-254 and HN-254U come with a 4-foot cables where long cable runs are not needed. The Serial Adapter Boxes also provide power to the HN modems through universal 110/220 50/60 wall-mount power supplies (also included).

The integral 6 dB patch antenna provides a line-of-site range of more than five miles, making the HN-250 and HN-250U ideal for a variety of "last mile" applications. For applications requiring more antenna gain, the HN-250X and HN250UX replace the built-in patch antennas with external TNC connectors. The HN modems are also ideal for use in SCADA applications as remote modems in multipoint configurations, and are extremely cost-effective solutions for point-to-point installations. Selectable transmit power levels of +10, +18 and +24 dBm allow HN modems to be used worldwide, even with the gain of the patch antenna.

Useability

Based on the third generation RFM WIT2450 spread spectrum frequency-hopping radio, the HN modems have exceptional multipath fade rejection and immunity to jamming. The WIT2450 is a field proven performer that delivers robust, reliable real world performance. HN modems are both FCC and CE marked. Combined with its operation in the 2.4 GHz ISM band, these wireless modems can be deployed around the world without a license.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А