MJD243, NJVMJD243T4G (NPN), MJD253, NJVMJD253T4G (PNP)

Complementary Silicon Plastic Power Transistor

DPAK−3 for Surface Mount Applications

Designed for low voltage, low−power, high−gain audio amplifier applications.

Features

- Collector−Emitter Sustaining Voltage −
  $V_{CEO(sus)}$ = 100 Vdc (Min) @ I_C = 10 mAdc
- High DC Current Gain −
  h_{FE} = 40 (Min) @ I_C = 200 mAdc = 15 (Min) @ I_C = 1.0 Adc
- Lead Formed for Surface Mount Applications in Plastic Sleeves (No Suffix)
- Straight Lead Version in Plastic Sleeves ("−1" Suffix)
- Low Collector−Emitter Saturation Voltage −
  $V_{CE(sat)}$ = 0.3 Vdc (Max) @ I_C = 500 mAdc = 0.6 Vdc (Max) @ I_C = 1.0 Adc
- High Current−Gain − Bandwidth Product −
  f_T = 40 MHz (Min) @ I_C = 100 mAdc
- Annular Construction for Low Leakage −
  I_{CBO} = 100 nAdc @ Rated V_{CB}
- Epoxy Meets UL 94 V−0 @ 0.125 in
- ESD Ratings:
  - Human Body Model, 3B > 8000 V
  - Machine Model, C > 400 V
- NJV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These are Pb−Free Packages*

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor®

http://onsemi.com

4.0 A, 100 V, 12.5 W
POWER TRANSISTOR



IPAK
CASE 369D
STYLE 1



DPAK−3
CASE 369C
STYLE 1

MARKING DIAGRAMS



IPAK



DPAK

A = Assembly Location
Y = Year
WW = Work Week
x = 4 or 5
G = Pb−Free Package

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

© Semiconductor Components Industries, LLC, 2012

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Base Voltage	V_{CB}	100	Vdc
Collector−Emitter Voltage	V_{CEO}	100	Vdc
Emitter−Base Voltage	V_{EB}	7.0	Vdc
Collector Current Continuous Peak	I_C	 4.0 8.0	Adc
Base Current	I_B	1.0	Adc
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	 12.5 0.1	 W W/°C
Total Device Dissipation @ T_A = 25°C (Note 2) Derate above 25°C	P_D	 1.4 0.011	 W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. When surface mounted on minimum pad sizes recommended.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance Junction−to−Case Junction−to−Ambient (Note 2)	 $R_{\theta JC}$ $R_{\theta JA}$	 10 89.3	°C/W

2. When surface mounted on minimum pad sizes recommended.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (Note 3) (I_C = 10 mAdc, I_B = 0)	$V_{CEO(sus)}$	 100	 –	Vdc
Collector Cutoff Current (V_{CB} = 100 Vdc, I_E = 0) (V_{CB} = 100 Vdc, I_E = 0, T_J = 125°C)	I_{CBO}	 – –	 100 100	 nAdc μAdc
Emitter Cutoff Current (V_{BE} = 7.0 Vdc, I_C = 0)	I_{EBO}	 –	 100	nAdc
DC Current Gain (Note 3) (I_C = 200 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.0 Adc, V_{CE} = 1.0 Vdc)	h_{FE}	 40 15	 180 –	–
Collector−Emitter Saturation Voltage (Note 3) (I_C = 500 mAdc, I_B = 50 mAdc) (I_C = 1.0 Adc, I_B = 100 mAdc)	$V_{CE(sat)}$	 – –	 0.3 0.6	Vdc
Base−Emitter Saturation Voltage (Note 3) (I_C = 2.0 Adc, I_B = 200 mAdc)	$V_{BE(sat)}$	 –	 1.8	Vdc
Base−Emitter On Voltage (Note 3) (I_C = 500 mAdc, V_{CE} = 1.0 Vdc)	$V_{BE(on)}$	 –	 1.5	Vdc
DYNAMIC CHARACTERISTICS				
Current−Gain − Bandwidth Product (Note 4) (I_C = 100 mAdc, V_{CE} = 10 Vdc, f_{test} = 10 MHz)	f_T	 40	 –	MHz
Output Capacitance (V_{CB} = 10 Vdc, I_E = 0, f = 0.1 MHz)	C_{ob}	 –	 50	pF

3. Pulse Test: Pulse Width = 300 μs, Duty Cycle ≈ 2%.
4. $f_T = |h_{FE}| \cdot f_{test}$.



Figure 1. Power Derating



Figure 2. Active Region Maximum Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 2 is based on $T_{J(pk)}$ = 150°C; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq$ 150°C. $T_{J(pk)}$ may be calculated from the data in Figure 3. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.



Figure 3. Thermal Response

NPN
MJD243



PNP
MJD253



Figure 4. DC Current Gain





Figure 5. “On” Voltages





Figure 6. Temperature Coefficients



R_B and R_C VARIED TO OBTAIN DESIRED CURRENT LEVELS
D_1 MUST BE FAST RECOVERY TYPE, e.g.:
1N5825 USED ABOVE $I_B \approx 100$ mA
MSD6100 USED BELOW $I_B \approx 100$ mA
FOR PNP TEST CIRCUIT, REVERSE ALL POLARITIES

Figure 7. Switching Time Test Circuit



Figure 8. Turn−On Time



Figure 9. Turn−Off Time



Figure 10. Capacitance



Figure 11. Capacitance

ORDERING INFORMATION

Device	Package Type	Package	Shipping†
MJD243G	DPAK−3 (Pb−Free)	369C	75 Units / Rail
MJD243T4G	DPAK−3 (Pb−Free)	369C	2,500 / Tape & Reel
NJVMJD243T4G	DPAK−3 (Pb−Free)	369C	2,500 / Tape & Reel
MJD253−1G	IPAK (Pb−Free)	369D	75 Units / Rail
MJD253T4G	DPAK−3 (Pb−Free)	369C	2,500 / Tape & Reel
NJVMJD253T4G	DPAK−3 (Pb−Free)	369C	2,500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

PACKAGE DIMENSIONS

DPAK−3
CASE 369C−01
ISSUE D



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
5. DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
6. DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.086	0.094	2.18	2.38
A1	0.000	0.005	0.00	0.13
b	0.025	0.035	0.63	0.89
b2	0.030	0.045	0.76	1.14
b3	0.180	0.215	4.57	5.46
c	0.018	0.024	0.46	0.61
c2	0.018	0.024	0.46	0.61
D	0.235	0.245	5.97	6.22
E	0.250	0.265	6.35	6.73
e	0.090 BSC		2.29 BSC	
H	0.370	0.410	9.40	10.41
L	0.055	0.070	1.40	1.78
L1	0.108 REF		2.74 REF	
L2	0.020 BSC		0.51 BSC	
L3	0.035	0.050	0.89	1.27
L4	−−−	0.040	−−−	1.01
Z	0.155	−−−	3.93	−−−

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

SOLDERING FOOTPRINT*



SCALE 3:1 $\left(\frac{\text{mm}}{\text{inches}}\right)$

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PACKAGE DIMENSIONS

IPAK
CASE 369D−01
ISSUE C



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.235	0.245	5.97	6.35
B	0.250	0.265	6.35	6.73
C	0.086	0.094	2.19	2.38
D	0.027	0.035	0.69	0.88
E	0.018	0.023	0.46	0.58
F	0.037	0.045	0.94	1.14
G	0.090 BSC		2.29 BSC	
H	0.034	0.040	0.87	1.01
J	0.018	0.023	0.46	0.58
K	0.350	0.380	8.89	9.65
R	0.180	0.215	4.45	5.45
S	0.025	0.040	0.63	1.01
V	0.035	0.050	0.89	1.27
Z	0.155	−−−	3.93	−−−

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

MJD243/D

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А