ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 78124	**Issue: 1**
Page 1 of 2 Pages	**Issue Date: 7/11/2014**
	Effective Date: 9/5/2014

A. Construction — **Diameters (In)**

1)	Component 1	4 X 1 COND	
a)	Conductor	24 (19/36) AWG Tinned Copper	0.025
b)	Insulation	0.007" Wall, Nom. Modified Polyphenylene Ether-PE	0.039
(1)	Color Code	Alpha Wire Color Code E	

Cond	Color	Cond	Color	Cond	Color
1	BLACK	3	RED		
2	BROWN	4	ORANGE		

2)	Cable Assembly	4 Components Cabled	
a)	Twists:	9.6 Twists/foot (min)	
b)	Core Wrap	Nonwoven Polyester Tape, 25% Overlap, Min.	
3)	Shield:	Alum/Mylar Tape, 25% Overlap, Min.	
a)	Foil Direction	Foil Facing In	
b)	Drain Wire	24 (7/32) AWG Tinned Copper	
4)	Jacket	0.015" Wall, Nom.,Modified Polyphenylene Ether-PE	0.132 (0.140 Max.)
a)	Color(s)	SLATE	
b)	Ripcord	1 End 810 Denier Nylon	
c)	Print	ALPHA WIRE-* P/N 78124 4C 24 AWG ECOCABLE(R) MINI RU AWM 21460 80C 300V VW-1 C(RU) AWM I A/B FT1 80C 300V CE ROHS (SEQ FOOTAGE) * = Factory Code	

B. Applicable Specifications

1)	UL	AWM/STYLE 21460 VW-1	80°C / 300 V_{RMS}
2)	CSA International	C(RU) AWM I A/B FT1	80°C / 300 V_{RMS}
3)	Other	Halogen-Free	
4)	CE:	EU Low Voltage Directive 2006/95/EC	

C. Environmental Compliance

1) CE:
EU Directive 2011/65/EU(RoHS2):
This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C.

2) REACH Regulation (EC 1907/2006):
This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.

D. Physical & Mechanical Properties

1)	Temperature Range	-40 to 80°C
2)	Bend Radius	10X Cable Diameter
3)	Pull Tension	18.4 Lbs, Maximum

E. Electrical Properties (For Engineering purposes only)

1)	Voltage Rating	300 V_{RMS}
2)	Capacitance	30 pf/ft @1 kHz, Nominal Conductor to Conductor
3)	Ground Capacitance	54 pf/ft @1 kHz, Nominal
4)	Inductance	0.17 µH/ft, Nominal
5)	Conductor DCR	24.1 Ω/1000ft @20°C, Nominal
6)	OA Shield DCR	19.6 Ω/1000ft @20°C, Nominal

F. Other

1)	Packaging	Flange x Traverse x Barrel (inches)
a)	1000 FT	12 x 4.5 x 3.5 Continuous length
b)	100 FT	6.5 x 2 x 1.9 Continuous length

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711
Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com
www.alphawire.com

c) Bulk(Made-to-order)

[Spool dimensions may vary slightly]

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

711 Lidgerwood Ave Elizabeth, NJ 07207-0711
Toll Free 1-800-52 ALPHA • T: 1-908-925-8000 • F: 908-925-5411 • Email: info@alphawire.com
www.alphawire.com

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А