

# 74AHC1G32; 74AHCT1G32

## 2-input OR gate

Rev. 07 — 14 May 2009

Product data sheet

## 1. General description

74AHC1G32 and 74AHCT1G32 are high-speed Si-gate CMOS devices. They provide a 2-input OR function.

The AHC device has CMOS input switching levels and supply voltage range 2 V to 5.5 V.

The AHCT device has TTL input switching levels and supply voltage range 4.5 V to 5.5 V.

## 2. Features

- Symmetrical output impedance
- High noise immunity
- ESD protection:
  - ◆ HBM JESD22-A114E: exceeds 2000 V
  - ◆ MM JESD22-A115-A: exceeds 200 V
  - ◆ CDM JESD22-C101C: exceeds 1000 V
- Low power dissipation
- Balanced propagation delays
- SOT353-1 and SOT753 package options
- Specified from -40 °C to +125 °C

## 3. Ordering information

Table 1. Ordering information


| Type number                 | Package           |        |                                                                           |          |
|-----------------------------|-------------------|--------|---------------------------------------------------------------------------|----------|
|                             | Temperature range | Name   | Description                                                               | Version  |
| 74AHC1G32GW<br>74AHCT1G32GW | -40 °C to +125 °C | TSSOP5 | plastic thin shrink small outline package; 5 leads;<br>body width 1.25 mm | SOT353-1 |
| 74AHC1G32GV<br>74AHCT1G32GV | -40 °C to +125 °C | SC-74A | plastic surface-mounted package; 5 leads                                  | SOT753   |

4. Marking

Table 2. Marking codes


| Type number  | Marking code |
|--------------|--------------|
| 74AHC1G32GW  | AG           |
| 74AHCT1G32GW | CG           |
| 74AHC1G32GV  | A32          |
| 74AHCT1G32GV | C32          |

5. Functional diagram



6. Pinning information

6.1 Pinning



## 6.2 Pin description

**Table 3.** Pin description

| Symbol          | Pin | Description    |
|-----------------|-----|----------------|
| B               | 1   | data input     |
| A               | 2   | data input     |
| GND             | 3   | ground (0 V)   |
| Y               | 4   | data output    |
| V <sub>CC</sub> | 5   | supply voltage |

## 7. Functional description

**Table 4.** Function table

H = HIGH voltage level; L = LOW voltage level

| Inputs |   | Output |
|--------|---|--------|
| A      | B | Y      |
| L      | L | L      |
| L      | H | H      |
| H      | L | H      |
| H      | H | H      |

## 8. Limiting values

**Table 5.** Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol           | Parameter               | Conditions                                                          | Min              | Max  | Unit |
|------------------|-------------------------|---------------------------------------------------------------------|------------------|------|------|
| V <sub>CC</sub>  | supply voltage          |                                                                     | -0.5             | +7.0 | V    |
| V <sub>I</sub>   | input voltage           |                                                                     | -0.5             | +7.0 | V    |
| I <sub>IK</sub>  | input clamping current  | V <sub>I</sub> < -0.5 V                                             | -20              | -    | mA   |
| I <sub>OK</sub>  | output clamping current | V <sub>O</sub> < -0.5 V or V <sub>O</sub> > V <sub>CC</sub> + 0.5 V | <sup>[1]</sup> - | ±20  | mA   |
| I <sub>O</sub>   | output current          | -0.5 V < V <sub>O</sub> < V <sub>CC</sub> + 0.5 V                   | -                | ±25  | mA   |
| I <sub>CC</sub>  | supply current          |                                                                     | -                | 75   | mA   |
| I <sub>GND</sub> | ground current          |                                                                     | -75              | -    | mA   |
| T <sub>stg</sub> | storage temperature     |                                                                     | -65              | +150 | °C   |
| P <sub>tot</sub> | total power dissipation | T <sub>amb</sub> = -40 °C to +125 °C                                | <sup>[2]</sup> - | 250  | mW   |

[1] The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2] For both TSSOP5 and SC-74A packages: above 87.5 °C the value of P<sub>tot</sub> derates linearly with 4.0 mW/K.

## 9. Recommended operating conditions

**Table 6. Recommended operating conditions**

Voltages are referenced to GND (ground = 0 V).

| Symbol              | Parameter                           | Conditions                      | 74AHC1G32 |     |                 | 74AHCT1G32 |     |                 | Unit |
|---------------------|-------------------------------------|---------------------------------|-----------|-----|-----------------|------------|-----|-----------------|------|
|                     |                                     |                                 | Min       | Typ | Max             | Min        | Typ | Max             |      |
| V <sub>CC</sub>     | supply voltage                      |                                 | 2.0       | 5.0 | 5.5             | 4.5        | 5.0 | 5.5             | V    |
| V <sub>I</sub>      | input voltage                       |                                 | 0         | -   | 5.5             | 0          | -   | 5.5             | V    |
| V <sub>O</sub>      | output voltage                      |                                 | 0         | -   | V <sub>CC</sub> | 0          | -   | V <sub>CC</sub> | V    |
| T <sub>amb</sub>    | ambient temperature                 |                                 | -40       | +25 | +125            | -40        | +25 | +125            | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | V <sub>CC</sub> = 3.3 V ± 0.3 V | -         | -   | 100             | -          | -   | -               | ns/V |
|                     |                                     | V <sub>CC</sub> = 5.0 V ± 0.5 V | -         | -   | 20              | -          | -   | 20              | ns/V |

## 10. Static characteristics

**Table 7. Static characteristics**

Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | 25 °C |     |     | -40 °C to +85 °C |     | -40 °C to +125 °C |     | Unit |
|--------|-----------|------------|-------|-----|-----|------------------|-----|-------------------|-----|------|
|        |           |            | Min   | Typ | Max | Min              | Max | Min               | Max |      |

### For type 74AHC1G32

|                 |                           |                                                                                        |      |     |      |      |      |      |      |    |
|-----------------|---------------------------|----------------------------------------------------------------------------------------|------|-----|------|------|------|------|------|----|
| V <sub>IH</sub> | HIGH-level input voltage  | V <sub>CC</sub> = 2.0 V                                                                | 1.5  | -   | -    | 1.5  | -    | 1.5  | -    | V  |
|                 |                           | V <sub>CC</sub> = 3.0 V                                                                | 2.1  | -   | -    | 2.1  | -    | 2.1  | -    | V  |
|                 |                           | V <sub>CC</sub> = 5.5 V                                                                | 3.85 | -   | -    | 3.85 | -    | 3.85 | -    | V  |
| V <sub>IL</sub> | LOW-level input voltage   | V <sub>CC</sub> = 2.0 V                                                                | -    | -   | 0.5  | -    | 0.5  | -    | 0.5  | V  |
|                 |                           | V <sub>CC</sub> = 3.0 V                                                                | -    | -   | 0.9  | -    | 0.9  | -    | 0.9  | V  |
|                 |                           | V <sub>CC</sub> = 5.5 V                                                                | -    | -   | 1.65 | -    | 1.65 | -    | 1.65 | V  |
| V <sub>OH</sub> | HIGH-level output voltage | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                    |      |     |      |      |      |      |      |    |
|                 |                           | I <sub>O</sub> = -50 µA; V <sub>CC</sub> = 2.0 V                                       | 1.9  | 2.0 | -    | 1.9  | -    | 1.9  | -    | V  |
|                 |                           | I <sub>O</sub> = -50 µA; V <sub>CC</sub> = 3.0 V                                       | 2.9  | 3.0 | -    | 2.9  | -    | 2.9  | -    | V  |
|                 |                           | I <sub>O</sub> = -50 µA; V <sub>CC</sub> = 4.5 V                                       | 4.4  | 4.5 | -    | 4.4  | -    | 4.4  | -    | V  |
|                 |                           | I <sub>O</sub> = -4.0 mA; V <sub>CC</sub> = 3.0 V                                      | 2.58 | -   | -    | 2.48 | -    | 2.40 | -    | V  |
| V <sub>OL</sub> | LOW-level output voltage  | I <sub>O</sub> = -8.0 mA; V <sub>CC</sub> = 4.5 V                                      | 3.94 | -   | -    | 3.8  | -    | 3.70 | -    | V  |
|                 |                           | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>                                    |      |     |      |      |      |      |      |    |
|                 |                           | I <sub>O</sub> = 50 µA; V <sub>CC</sub> = 2.0 V                                        | -    | 0   | 0.1  | -    | 0.1  | -    | 0.1  | V  |
|                 |                           | I <sub>O</sub> = 50 µA; V <sub>CC</sub> = 3.0 V                                        | -    | 0   | 0.1  | -    | 0.1  | -    | 0.1  | V  |
|                 |                           | I <sub>O</sub> = 50 µA; V <sub>CC</sub> = 4.5 V                                        | -    | 0   | 0.1  | -    | 0.1  | -    | 0.1  | V  |
| I <sub>I</sub>  | input leakage current     | I <sub>O</sub> = 4.0 mA; V <sub>CC</sub> = 3.0 V                                       | -    | -   | 0.36 | -    | 0.44 | -    | 0.55 | V  |
|                 |                           | I <sub>O</sub> = 8.0 mA; V <sub>CC</sub> = 4.5 V                                       | -    | -   | 0.36 | -    | 0.44 | -    | 0.55 | V  |
| I <sub>CC</sub> | supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A; V <sub>CC</sub> = 5.5 V | -    | -   | 1.0  | -    | 10   | -    | 40   | µA |
| C <sub>I</sub>  | input capacitance         |                                                                                        | -    | 1.5 | 10   | -    | 10   | -    | 10   | pF |

**Table 7. Static characteristics ...continued**  
 Voltages are referenced to GND (ground = 0 V).

| Symbol              | Parameter                 | Conditions                                                                                                                   | 25 °C |     |      | –40 °C to +85 °C |      | –40 °C to +125 °C |      | Unit |
|---------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------|-------|-----|------|------------------|------|-------------------|------|------|
|                     |                           |                                                                                                                              | Min   | Typ | Max  | Min              | Max  | Min               | Max  |      |
| For type 74AHCT1G32 |                           |                                                                                                                              |       |     |      |                  |      |                   |      |      |
| V <sub>IH</sub>     | HIGH-level input voltage  | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                                             | 2.0   | -   | -    | 2.0              | -    | 2.0               | -    | V    |
| V <sub>IL</sub>     | LOW-level input voltage   | V <sub>CC</sub> = 4.5 V to 5.5 V                                                                                             | -     | -   | 0.8  | -                | 0.8  | -                 | 0.8  | V    |
| V <sub>OH</sub>     | HIGH-level output voltage | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; V <sub>CC</sub> = 4.5 V                                                |       |     |      |                  |      |                   |      |      |
|                     |                           | I <sub>O</sub> = –50 µA                                                                                                      | 4.4   | 4.5 | -    | 4.4              | -    | 4.4               | -    | V    |
|                     |                           | I <sub>O</sub> = –8.0 mA                                                                                                     | 3.94  | -   | -    | 3.8              | -    | 3.70              | -    | V    |
| V <sub>OL</sub>     | LOW-level output voltage  | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub> ; V <sub>CC</sub> = 4.5 V                                                |       |     |      |                  |      |                   |      |      |
|                     |                           | I <sub>O</sub> = 50 µA                                                                                                       | -     | 0   | 0.1  | -                | 0.1  | -                 | 0.1  | V    |
|                     |                           | I <sub>O</sub> = 8.0 mA                                                                                                      | -     | -   | 0.36 | -                | 0.44 | -                 | 0.55 | V    |
| I <sub>I</sub>      | input leakage current     | V <sub>I</sub> = 5.5 V or GND; V <sub>CC</sub> = 0 V to 5.5 V                                                                | -     | -   | 0.1  | -                | 1.0  | -                 | 2.0  | µA   |
| I <sub>CC</sub>     | supply current            | V <sub>I</sub> = V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A; V <sub>CC</sub> = 5.5 V                                       | -     | -   | 1.0  | -                | 10   | -                 | 40   | µA   |
| ΔI <sub>CC</sub>    | additional supply current | per input pin; V <sub>I</sub> = 3.4 V; other inputs at V <sub>CC</sub> or GND; I <sub>O</sub> = 0 A; V <sub>CC</sub> = 5.5 V | -     | -   | 1.35 | -                | 1.5  | -                 | 1.5  | mA   |
| C <sub>I</sub>      | input capacitance         |                                                                                                                              | -     | 1.5 | 10   | -                | 10   | -                 | 10   | pF   |

## 11. Dynamic characteristics

**Table 8. Dynamic characteristics**  
 GND = 0 V; t<sub>r</sub> = t<sub>f</sub> = ≤ 3.0 ns. For waveform see [Figure 5](#). For test circuit see [Figure 6](#).

| Symbol             | Parameter                     | Conditions                                                                                   | 25 °C |     |      | −40 °C to +85 °C |      | −40 °C to +125 °C |      | Unit |
|--------------------|-------------------------------|----------------------------------------------------------------------------------------------|-------|-----|------|------------------|------|-------------------|------|------|
|                    |                               |                                                                                              | Min   | Typ | Max  | Min              | Max  | Min               | Max  |      |
| For type 74AHC1G32 |                               |                                                                                              |       |     |      |                  |      |                   |      |      |
| t <sub>pd</sub>    | propagation delay             | A and B to Y                                                                                 | [1]   |     |      |                  |      |                   |      |      |
|                    |                               | V <sub>CC</sub> = 3.0 V to 3.6 V                                                             | [2]   |     |      |                  |      |                   |      |      |
|                    |                               | C <sub>L</sub> = 15 pF                                                                       | -     | 4.4 | 7.9  | 1.0              | 9.5  | 1.0               | 10.0 | ns   |
|                    |                               | C <sub>L</sub> = 50 pF                                                                       | -     | 6.3 | 11.4 | 1.0              | 13.0 | 1.0               | 14.5 | ns   |
|                    |                               | V <sub>CC</sub> = 4.5 V to 5.5 V                                                             | [3]   |     |      |                  |      |                   |      |      |
|                    |                               | C <sub>L</sub> = 15 pF                                                                       | -     | 3.2 | 5.5  | 1.0              | 6.5  | 1.0               | 7.0  | ns   |
|                    |                               | C <sub>L</sub> = 50 pF                                                                       | -     | 4.6 | 7.5  | 1.0              | 8.5  | 1.0               | 9.5  | ns   |
| C <sub>PD</sub>    | power dissipation capacitance | per buffer;<br>C <sub>L</sub> = 50 pF; f = 1 MHz;<br>V <sub>I</sub> = GND to V <sub>CC</sub> | [4]   | -   | 16   | -                | -    | -                 | -    | pF   |

**Table 8.** Dynamic characteristics ...continued

$GND = 0\text{ V}$ ;  $t_r = t_f \leq 3.0\text{ ns}$ . For waveform see [Figure 5](#). For test circuit see [Figure 6](#).

| Symbol              | Parameter                     | Conditions                                                                                   | 25 °C                                      |     |     | –40 °C to +85 °C |     | –40 °C to +125 °C |     | Unit |
|---------------------|-------------------------------|----------------------------------------------------------------------------------------------|--------------------------------------------|-----|-----|------------------|-----|-------------------|-----|------|
|                     |                               |                                                                                              | Min                                        | Typ | Max | Min              | Max | Min               | Max |      |
| For type 74AHCT1G32 |                               |                                                                                              |                                            |     |     |                  |     |                   |     |      |
| t <sub>pd</sub>     | propagation delay             | A and B to Y;<br>see <a href="#">Figure 5</a> ;<br>V <sub>CC</sub> = 4.5 V to 5.5 V          | <a href="#">[1]</a><br><a href="#">[3]</a> |     |     |                  |     |                   |     |      |
|                     |                               | C <sub>L</sub> = 15 pF                                                                       | -                                          | 3.3 | 6.9 | 1.0              | 8.0 | 1.0               | 9.0 | ns   |
|                     |                               | C <sub>L</sub> = 50 pF                                                                       | -                                          | 4.8 | 7.9 | 1.0              | 9.0 | 1.0               | 10  | ns   |
| C <sub>PD</sub>     | power dissipation capacitance | per buffer;<br>C <sub>L</sub> = 50 pF; f = 1 MHz;<br>V <sub>I</sub> = GND to V <sub>CC</sub> | <a href="#">[4]</a>                        | -   | 17  | -                | -   | -                 | -   | pF   |

[1]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ .

[2] Typical values are measured at  $V_{CC} = 3.3\text{ V}$ .

[3] Typical values are measured at  $V_{CC} = 5.0\text{ V}$ .

[4]  $C_{PD}$  is used to determine the dynamic power dissipation  $P_D$  ( $\mu\text{W}$ ).

$P_D = C_{PD} \times V_{CC}^2 \times f_i + \sum (C_L \times V_{CC}^2 \times f_o)$  where:


$f_i$  = input frequency in MHz;

$f_o$  = output frequency in MHz;

$C_L$  = output load capacitance in pF;

$V_{CC}$  = supply voltage in Volts.


## 12. Waveforms



Measurement points are given in [Table 9](#).

**Fig 5.** The input (A and B) to output (Y) propagation delays**Table 9.** Measurement points

| Type number | Input           |                     | Output              |
|-------------|-----------------|---------------------|---------------------|
|             | $V_I$           | $V_M$               | $V_M$               |
| 74AHC1G32   | GND to $V_{CC}$ | $0.5 \times V_{CC}$ | $0.5 \times V_{CC}$ |
| 74AHCT1G32  | GND to 3.0 V    | 1.5 V               | $0.5 \times V_{CC}$ |



Test data is given in [Table 8](#).

Definitions for test circuit:

$C_L$  = Load capacitance including jig and probe capacitance.

$R_T$  = Termination resistance should be equal to output impedance  $Z_o$  of the pulse generator.

**Fig 6. Load circuitry for switching times**

13. Package outline

TSSOP5: plastic thin shrink small outline package; 5 leads; body width 1.25 mm

SOT353-1




Fig 7. Package outline SOT353-1 (TSSOP5)

Plastic surface-mounted package; 5 leads

SOT753




Fig 8. Package outline SOT753 (SC-74A)

## 14. Abbreviations

Table 10. Abbreviations

| Acronym | Description                 |
|---------|-----------------------------|
| CDM     | Charged Device Model        |
| DUT     | Device Under Test           |
| ESD     | ElectroStatic Discharge     |
| HBM     | Human Body Model            |
| MM      | Machine Model               |
| TTL     | Transistor-Transistor Logic |

## 15. Revision history

Table 11. Revision history

| Document ID                                                                                                                               | Release date | Data sheet status     | Change notice | Supersedes         |
|-------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------|---------------|--------------------|
| 74AHC_AHCT1G32_7                                                                                                                          | 20090514     | Product data sheet    | -             | 74AHC_AHCT1G32_6   |
| Modifications: <ul style="list-style-type: none"><li>Pin configuration SOT353-1 (TSSOP5) and SOT753 (SC-74A) drawing corrected.</li></ul> |              |                       |               |                    |
| 74AHC_AHCT1G32_6                                                                                                                          | 20070702     | Product data sheet    | -             | 74AHC_AHCT1G32_5   |
| 74AHC_AHCT1G32_5                                                                                                                          | 20020605     | Product specification | -             | 74AHC_AHCT1G32_4   |
| 74AHC_AHCT1G32_4                                                                                                                          | 20020326     | Product specification | -             | 74AHC_AHCT1G32_3   |
| 74AHC_AHCT1G32_3                                                                                                                          | 20010222     | Product specification | -             | 74AHC_AHCT1G32_2   |
| 74AHC_AHCT1G32_2                                                                                                                          | 19990127     | Product specification | -             | 74AHC_AHCT1G32_N_1 |
| 74AHC_AHCT1G32_N_1                                                                                                                        | 19981125     | Product specification | -             | -                  |

## 16. Legal information

### 16.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition                                                                            |
|-----------------------------------|-------------------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 16.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 16.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental

damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

### 16.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 17. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 18. Contents

|           |                                               |           |
|-----------|-----------------------------------------------|-----------|
| <b>1</b>  | <b>General description</b> .....              | <b>1</b>  |
| <b>2</b>  | <b>Features</b> .....                         | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....             | <b>1</b>  |
| <b>4</b>  | <b>Marking</b> .....                          | <b>2</b>  |
| <b>5</b>  | <b>Functional diagram</b> .....               | <b>2</b>  |
| <b>6</b>  | <b>Pinning information</b> .....              | <b>2</b>  |
| 6.1       | Pinning .....                                 | 2         |
| 6.2       | Pin description .....                         | 3         |
| <b>7</b>  | <b>Functional description</b> .....           | <b>3</b>  |
| <b>8</b>  | <b>Limiting values</b> .....                  | <b>3</b>  |
| <b>9</b>  | <b>Recommended operating conditions</b> ..... | <b>4</b>  |
| <b>10</b> | <b>Static characteristics</b> .....           | <b>4</b>  |
| <b>11</b> | <b>Dynamic characteristics</b> .....          | <b>5</b>  |
| <b>12</b> | <b>Waveforms</b> .....                        | <b>6</b>  |
| <b>13</b> | <b>Package outline</b> .....                  | <b>8</b>  |
| <b>14</b> | <b>Abbreviations</b> .....                    | <b>10</b> |
| <b>15</b> | <b>Revision history</b> .....                 | <b>10</b> |
| <b>16</b> | <b>Legal information</b> .....                | <b>11</b> |
| 16.1      | Data sheet status .....                       | 11        |
| 16.2      | Definitions .....                             | 11        |
| 16.3      | Disclaimers .....                             | 11        |
| 16.4      | Trademarks .....                              | 11        |
| <b>17</b> | <b>Contact information</b> .....              | <b>11</b> |
| <b>18</b> | <b>Contents</b> .....                         | <b>12</b> |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

founded by

**PHILIPS**

© NXP B.V. 2009.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 14 May 2009

Document identifier: 74AHC\_AHCT1G32\_7

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NXP:](#)

[74AHC1G32GW-R](#) [74AHCT1G32GV](#) [74AHCT1G32GW-R](#) [74AHC1G32GV,125](#) [74AHC1G32GW,125](#)  
[74AHC1G32GW,165](#) [74AHCT1G32GV,125](#) [74AHCT1G32GW,125](#) [74AHCT1G32GW,165](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А