



# High Current Density Surface Mount Trench MOS Barrier Schottky Rectifier

Ultra Low  $V_F = 0.50\text{ V}$  at  $I_F = 4\text{ A}$

## TMBS® eSMP® Series



TO-277A (SMPC)



## FEATURES

- Very low profile - typical height of 1.1 mm
- Ideal for automated placement
- Trench MOS Schottky technology
- Low forward voltage drop, low power losses
- High efficiency operation
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- AEC-Q101 qualified available  
- Automotive ordering code; base P/NHM3
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

AUTOMOTIVE  
GRADE  
Available



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

## TYPICAL APPLICATIONS

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

## MECHANICAL DATA

**Case:** TO-277A (SMPC)

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-M3 - halogen-free, RoHS-compliant, and commercial grade

Base P/NHM3 - halogen-free, RoHS-compliant and AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

M3 and HM3 suffix meets JESD 201 class 2 whisker test

| PRIMARY CHARACTERISTICS              |                |
|--------------------------------------|----------------|
| $I_{F(AV)}$                          | 8 A            |
| $V_{RRM}$                            | 100 V          |
| $I_{FSM}$                            | 140 A          |
| $V_F$ at $I_F = 8\text{ A}$ (125 °C) | 0.60 V         |
| $T_J$ max.                           | 150 °C         |
| Package                              | TO-277A (SMPC) |
| Diode variations                     | Single die     |

| MAXIMUM RATINGS ( $T_A = 25\text{ °C}$ unless otherwise noted)                    |                   |             |      |
|-----------------------------------------------------------------------------------|-------------------|-------------|------|
| PARAMETER                                                                         | SYMBOL            | V8PM10      | UNIT |
| Device marking code                                                               |                   | 8M10        |      |
| Maximum repetitive peak reverse voltage                                           | $V_{RRM}$         | 100         | V    |
| Maximum DC forward current                                                        | $I_{F(AV)}^{(1)}$ | 8           | A    |
|                                                                                   | $I_{F(AV)}^{(2)}$ | 3.2         |      |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load | $I_{FSM}$         | 140         | A    |
| Operating junction and storage temperature range                                  | $T_J, T_{STG}$    | -40 to +150 | °C   |

## Notes

(1) Mounted on 30 mm x 30 mm pad areas aluminum PCB

(2) Free air, mounted on recommended pad area



| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                        |                         |                               |      |      |      |
|----------------------------------------------------------------------------|------------------------|-------------------------|-------------------------------|------|------|------|
| PARAMETER                                                                  | TEST CONDITIONS        |                         | SYMBOL                        | TYP. | MAX. | UNIT |
| Instantaneous forward voltage                                              | I <sub>F</sub> = 4 A   | T <sub>A</sub> = 25 °C  | V <sub>F</sub> <sup>(1)</sup> | 0.57 | -    | V    |
|                                                                            | I <sub>F</sub> = 8 A   |                         |                               | 0.69 | 0.75 |      |
|                                                                            | I <sub>F</sub> = 4 A   | T <sub>A</sub> = 125 °C |                               | 0.50 | -    |      |
|                                                                            | I <sub>F</sub> = 8 A   |                         |                               | 0.60 | 0.66 |      |
| Reverse current                                                            | V <sub>R</sub> = 70 V  | T <sub>A</sub> = 25 °C  | I <sub>R</sub> <sup>(2)</sup> | 0.01 | -    | mA   |
|                                                                            |                        | T <sub>A</sub> = 125 °C |                               | 1.5  | -    |      |
|                                                                            | V <sub>R</sub> = 100 V | T <sub>A</sub> = 25 °C  |                               | -    | 0.06 |      |
|                                                                            |                        | T <sub>A</sub> = 125 °C |                               | 3    | 8    |      |

**Notes**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: Pulse width  $\leq 40\text{ ms}$ 

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise specified) |                       |        |                      |
|------------------------------------------------------------------------------------------|-----------------------|--------|----------------------|
| PARAMETER                                                                                | SYMBOL                | V8PM10 | UNIT                 |
| Typical thermal resistance                                                               | $R_{\theta JA}^{(1)}$ | 75     | $^{\circ}\text{C/W}$ |
|                                                                                          | $R_{\theta JM}^{(2)}$ | 4      |                      |

**Notes**(1) Free air, mounted on recommended copper pad area; thermal resistance  $R_{\theta JA}$  - junction to ambient(2) Mounted on 30 mm x 30 mm pad areas aluminum PCB, thermal resistance  $R_{\theta JM}$  - junction to mount

| ORDERING INFORMATION (Example) |                 |              |               |                                    |
|--------------------------------|-----------------|--------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| V8PM10-M3/H                    | 0.10            | H            | 1500          | 7" diameter plastic tape and reel  |
| V8PM10-M3/I                    | 0.10            | I            | 6500          | 13" diameter plastic tape and reel |
| V8PM10HM3/H <sup>(1)</sup>     | 0.10            | H            | 1500          | 7" diameter plastic tape and reel  |
| V8PM10HM3/I <sup>(1)</sup>     | 0.10            | I            | 6500          | 13" diameter plastic tape and reel |

**Note**<sup>(1)</sup> AEC-Q101 qualified


**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise specified)


Fig. 1 - Maximum Forward Current Derating Curve




Fig. 4 - Typical Reverse Characteristics




Fig. 2 - Forward Power Loss Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 6 - Typical Transient Thermal Impedance



**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)



Conform to JEDEC® TO-277A



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А