

NZ9F2V4T5G, SZNZ9F2V4T5G SERIES

Zener Voltage Regulators

200 mW SOD-923 Surface Mount

This series of Zener diodes is packaged in a SOD-923 surface mount package. They are designed to provide voltage regulation protection and are especially attractive in situations where space is at a premium. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.

Specification Features:

- Standard Zener Breakdown Voltage Range – 2.4 V to 24 V
- Steady State Power Rating of 200 mW
- Small Body Outline Dimensions:
0.039" x 0.024" (1.00 mm x 0.60 mm)
- Low Body Height: 0.016" (0.40 mm)
- ESD Rating of Class 3 (>16 kV) per Human Body Model
- SZ Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These are Pb-Free Devices

Mechanical Characteristics:

CASE: Void-free, transfer-molded, thermosetting plastic
Epoxy Meets UL 94 V-0

LEAD FINISH: 100% Matte Sn (Tin)

MOUNTING POSITION: Any

QUALIFIED MAX REFLOW TEMPERATURE: 260°C
Device Meets MSL 1 Requirements

MAXIMUM RATINGS

| Rating | Symbol | Max | Unit |
|--|-----------------|----------------|-------------|
| Total Device Dissipation FR-5 Board, (Note 1) @ $T_A = 25^\circ\text{C}$ Derate above 25°C | P_D | 250 2.0 | mW mW/°C |
| Thermal Resistance from Junction-to-Ambient | $R_{\theta JA}$ | 500 | °C/W |
| Junction and Storage Temperature Range | T_J, T_{stg} | -65 to +150 | °C |



Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. FR-4 Minimum Pad.




ON Semiconductor®

<http://onsemi.com>



MARKING DIAGRAM



- X = Specific Device Code
 - M = Month Code
 - = Pb-Free Package
- (Note: Microdot may be in either location)

ORDERING INFORMATION

| Device | Package | Shipping† |
|-------------------------------|----------------------|------------------|
| NZ9FxxxxT5G, SZNZ9FxxxxT5G | SOD-923 (Pb-Free) | 8000/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

DEVICE MARKING INFORMATION

See specific marking information in the device marking column of the Electrical Characteristics tables starting on page 3 of this data sheet.

NZ9F2V4T5G, SZNZ9F2V4T5G SERIES

ELECTRICAL CHARACTERISTICS

($T_A = 25^\circ\text{C}$ unless otherwise noted,
 $V_F = 0.9\text{ V Max. @ } I_F = 10\text{ mA}$ for all types)

| Symbol | Parameter |
|---------------|---|
| V_Z | Reverse Zener Voltage @ I_{ZT} |
| I_{ZT} | Reverse Current |
| Z_{ZT} | Maximum Zener Impedance @ I_{ZT} |
| I_{ZK} | Reverse Current |
| Z_{ZK} | Maximum Zener Impedance @ I_{ZK} |
| I_R | Reverse Leakage Current @ V_R |
| V_R | Reverse Voltage |
| I_F | Forward Current |
| V_F | Forward Voltage @ I_F |
| Θ_{VZ} | Maximum Temperature Coefficient of V_Z |
| C | Max. Capacitance @ $V_R = 0$ and $f = 1\text{ MHz}$ |





Figure 1. Steady State Power Derating

NZ9F2V4T5G, SZNZ9F2V4T5G SERIES

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 0.9\text{ V Max.}$ @ $I_F = 10\text{ mA}$ for all types)

| Device*** | Device Marking | Zener Voltage (Note 1) | | Zener Impedance | | | Leakage Current | | θ_{V_Z} (mV/k) @ I_{ZT} | | C @ $V_R = 0$ f = 1 MHz | |
|----------------|----------------|---------------------------|-------|------------------------|---------------------|----------|-----------------|---------------|-------------------------------------|------|-------------------------------|-----|
| | | V_Z (Volts) | | Z_{ZT} @ I_{ZT} | Z_{ZK} @ I_{ZK} | | I_R @ V_R | | | | | |
| | | Min | Max | mA | Ω | Ω | mA | μA | Volts | Min | Max | pF |
| SZ, NZ9F2V4T5G | J | 2.28 | 2.52 | 5 | 100 | 1000 | 1 | 50 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F2V7T5G | E** | 2.57 | 2.84 | 5 | 100 | 1000 | 1 | 20 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F3V0T5G | T** | 2.85 | 3.15 | 5 | 100 | 1000 | 1 | 10 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F3V3T5G | Q | 3.14 | 3.47 | 5 | 100 | 1000 | 1 | 10 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F3V6T5G | 3** | 3.42 | 3.78 | 5 | 100 | 1000 | 1 | 10 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F3V9T5G | V** | 3.71 | 4.10 | 5 | 100 | 1000 | 1 | 5 | 1 | -3.5 | -2.5 | 210 |
| SZ, NZ9F4V3T5G | Y** | 4.09 | 4.52 | 5 | 100 | 1000 | 1 | 5 | 1 | -3.5 | 0 | 210 |
| SZ, NZ9F4V7T5G | 3 | 4.47 | 4.94 | 5 | 100 | 800 | 0.5 | 2 | 1 | -3.5 | 0.2 | 150 |
| SZ, NZ9F5V1T5G | 4 | 4.85 | 5.36 | 5 | 80 | 500 | 0.5 | 2 | 1.5 | -2.7 | 1.2 | 130 |
| SZ, NZ9F5V6T5G | 5 | 5.32 | 5.88 | 5 | 60 | 200 | 0.5 | 1 | 2.5 | -2.0 | 2.5 | 115 |
| SZ, NZ9F6V2T5G | 6 | 5.89 | 6.51 | 5 | 60 | 100 | 0.5 | 1 | 3 | 0.4 | 3.7 | 110 |
| SZ, NZ9F6V8T5G | A* | 6.46 | 7.14 | 5 | 40 | 60 | 0.5 | 0.5 | 3.5 | 1.2 | 4.5 | 105 |
| SZ, NZ9F7V5T5G | D* | 7.13 | 7.88 | 5 | 30 | 60 | 0.5 | 0.5 | 4 | 2.5 | 5.3 | 100 |
| SZ, NZ9F8V2T5G | E* | 7.79 | 8.61 | 5 | 30 | 60 | 0.5 | 0.5 | 5 | 3.2 | 6.2 | 90 |
| SZ, NZ9F9V1T5G | F* | 8.65 | 9.56 | 5 | 30 | 60 | 0.5 | 0.5 | 6 | 3.8 | 7 | 80 |
| SZ, NZ9F10VT5G | J* | 9.50 | 10.50 | 5 | 30 | 60 | 0.5 | 0.1 | 7 | 4.5 | 8 | 80 |
| SZ, NZ9F11VT5G | K* | 10.45 | 11.55 | 5 | 30 | 60 | 0.5 | 0.1 | 8 | 5.4 | 9 | 80 |
| SZ, NZ9F12VT5G | L* | 11.40 | 12.60 | 5 | 30 | 80 | 0.5 | 0.1 | 9 | 6 | 10 | 80 |
| SZ, NZ9F13VT5G | P* | 12.35 | 13.65 | 5 | 37 | 80 | 0.5 | 0.1 | 10 | 7 | 11 | 75 |
| SZ, NZ9F15VT5G | Q* | 14.25 | 15.75 | 5 | 42 | 80 | 0.5 | 0.1 | 11 | 9.2 | 13 | 70 |
| SZ, NZ9F16VT5G | R* | 15.20 | 16.80 | 5 | 50 | 80 | 0.5 | 0.1 | 12 | 10.4 | 14 | 65 |
| SZ, NZ9F18VT5G | T* | 17.10 | 18.90 | 5 | 50 | 80 | 0.5 | 0.1 | 14 | 12.4 | 16 | 60 |
| SZ, NZ9F20VT5G | V* | 19.00 | 21.00 | 5 | 55 | 100 | 0.5 | 0.1 | 15.4 | 14.4 | 18 | 55 |
| SZ, NZ9F22VT5G | Y* | 20.90 | 23.10 | 5 | 55 | 100 | 0.5 | 0.1 | 16.8 | 15.4 | 20 | 55 |
| SZ, NZ9F24VT5G | F | 22.80 | 25.20 | 5 | 70 | 120 | 0.5 | 0.1 | 18.9 | 16.8 | 22 | 50 |

*Rotated 90°.

**Rotated 270°.


***SZ Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

1. Zener voltage is measured with a pulse test current I_Z at an ambient temperature of 25°C.


NZ9F2V4T5G, SZNZ9F2V4T5G SERIES

PACKAGE DIMENSIONS


SOD-923
CASE 514AB
ISSUE C



TOP VIEW



SIDE VIEW




BOTTOM VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | MILLIMETERS | | | INCHES | | |
|----------------|-------------|------|------|-----------|-------|-------|
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | 0.34 | 0.37 | 0.40 | 0.013 | 0.015 | 0.016 |
| b | 0.15 | 0.20 | 0.25 | 0.006 | 0.008 | 0.010 |
| c | 0.07 | 0.12 | 0.17 | 0.003 | 0.005 | 0.007 |
| D | 0.75 | 0.80 | 0.85 | 0.030 | 0.031 | 0.033 |
| E | 0.55 | 0.60 | 0.65 | 0.022 | 0.024 | 0.026 |
| H _E | 0.95 | 1.00 | 1.05 | 0.037 | 0.039 | 0.041 |
| L | 0.19 REF | | | 0.007 REF | | |
| L2 | 0.05 | 0.10 | 0.15 | 0.002 | 0.004 | 0.006 |

SOLDERING FOOTPRINT*



See Application Note AND8455/D for more mounting details

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А