

## Aluminum Electrolytic Capacitors

### Radial Miniature, Low Impedance, High Vibration Capability





Fig. 1

| QUICK REFERENCE DATA                               |                        |
|--|------------------------|
| DESCRIPTION  | VALUE                  |
| Nominal case sizes (Ø D x L in mm)                 | 16 x 20 to 18 x 40     |
| Rated capacitance range, C <sub>R</sub>            | 330 µF to 8200 µF      |
| Tolerance on C <sub>R</sub>                        | ± 20 %                 |
| Rated voltage range, U <sub>R</sub>                | 10 V to 100 V          |
| Category temperature range                         | -55 °C to +105 °C      |
| Endurance test at 105 °C                           | 3000 h to 7000 h       |
| Useful life at 105 °C                              | 7000 h to 10 000 h     |
| Useful life at 40 °C, 1.8 x I <sub>R</sub> applied | 200 000 h to 500 000 h |
| Shelf life at 0 V, 105 °C                          | 1000 h                 |
| Based on sectional specification                   | IEC 60384-4 / EN130300 |
| Climatic category IEC 60068                        | 55 / 105 / 56          |

#### FEATURES

- Very long useful life: 7000 h to 10 000 h at 105 °C, high stability, high reliability
- Very low impedance and low ESR in smaller case sizes than the 136 RVI series
- Excellent ripple current capability
- High vibration resistance up to 50 g
- AEC-Q200 qualified
- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, insulated with a blue sleeve
- Charge and discharge proof
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

 AUTOMOTIVE  
GRADE

**RoHS**  
COMPLIANT

#### APPLICATIONS




- Power supplies (SMPS, DC/DC converters) for general industrial, EDP, audio-video, automotive, and telecommunications
- Smoothing, filtering, buffering

#### MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance (in µF)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (M for ± 20 %)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Code indicating factory of origin
- Name of manufacturer
- Upper category temperature (105 °C)
- Negative terminal identification
- Series number (250)

| SELECTION CHART FOR C <sub>R</sub> , U <sub>R</sub> , AND RELEVANT NOMINAL CASE SIZES (Ø D x L in mm) |                    |         |         |         |         |         |         |
|---|--------------------|---------|---------|---------|---------|---------|---------|
| C <sub>R</sub><br>(µF)  | U <sub>R</sub> (V) |         |         |         |         |         |         |
|   | 10                 | 16      | 25      | 35      | 50      | 63      | 100     |
| 330   | -                  | -       | -       | -       | -       | -       | 18 x 20 |
| 470   | -                  | -       | -       | -       | -       | 16 x 20 | -       |
| 680   | -                  | -       | -       | -       | -       | 16 x 20 | -       |
|   | -                  | -       | -       | -       | -       | 16 x 25 | -       |
| 1000  | -                  | -       | -       | -       | 16 x 25 | 16 x 31 | -       |
|   | -                  | -       | -       | 16 x 20 | -       | -       | -       |
| 1200  | -                  | -       | -       | -       | 16 x 31 | -       | -       |
| 1500  | -                  | -       | -       | 16 x 20 | 16 x 31 | -       | -       |
| 2200  | -                  | -       | 16 x 20 | 16 x 31 | -       | 18 x 40 | -       |
| 3300  | -                  | 16 x 20 | 16 x 31 | 18 x 31 | 18 x 40 | -       | -       |
| 4700  | 16 x 25            | 16 x 31 | 16 x 35 | 18 x 40 | -       | -       | -       |
| 6800  | 16 x 31            | 16 x 35 | 18 x 40 | -       | -       | -       | -       |
| 8200  | -                  | 18 x 40 | -       | -       | -       | -       | -       |

**DIMENSIONS** in millimeters **AND AVAILABLE FORMS**

 Fig. 2 - **Form CA:** Long leads

 Fig. 3 - **Form CB:** Cut leads

 Fig. 4 - **Form TFA:** Taped in box (ammopack)

**Table 1**

| <b>DIMENSIONS</b> in millimeters, <b>MASS AND PACKAGING QUANTITIES</b> |           |                 |                        |            |               |                |                      |         |          |
|--|-----------|-----------------|------------------------|------------|---------------|----------------|----------------------|---------|----------|
| NOMINAL CASE SIZE<br>$\varnothing D \times L$                          | CASE CODE | $\varnothing d$ | $\varnothing D_{max.}$ | $L_{max.}$ | F             | MASS (g)       | PACKAGING QUANTITIES |         |          |
|  |           |                 |                        |            |               |                | FORM CA              | FORM CB | FORM TFA |
| 16 x 20  | 19a       | 0.8             | 16.5                   | 22.0       | $7.5 \pm 0.5$ | $\approx 6.0$  | 250                  | 250     | 250      |
| 16 x 25  | 19        | 0.8             | 16.5                   | 27.0       | $7.5 \pm 0.5$ | $\approx 8.0$  | 250                  | 250     | 250      |
| 16 x 31  | 20        | 0.8             | 16.5                   | 33.5       | $7.5 \pm 0.5$ | $\approx 9.0$  | 100                  | 100     | 250      |
| 16 x 35  | 21        | 0.8             | 16.5                   | 37.5       | $7.5 \pm 0.5$ | $\approx 11.0$ | 100                  | 100     | -        |
| 18 x 20  | 1820      | 0.8             | 18.5                   | 22.0       | $7.5 \pm 0.5$ | $\approx 8.0$  | 100                  | 100     | -        |
| 18 x 31  | 1831      | 0.8             | 18.5                   | 33.5       | $7.5 \pm 0.5$ | $\approx 12.5$ | 100                  | 100     | -        |
| 18 x 40  | 1840      | 0.8             | 18.5                   | 42.5       | $7.5 \pm 0.5$ | $\approx 16.5$ | 100                  | 100     | -        |



| ELECTRICAL DATA |   |
|-----------------|---|
| SYMBOL          | DESCRIPTION                                       |
| $C_R$           | Rated capacitance at 100 Hz, tolerance $\pm 20\%$ |
| $I_R$           | Rated RMS ripple current at 100 kHz, 105 °C       |
| $I_{L2}$        | Maximum leakage current after 2 min at $U_R$      |
| $\tan \delta$   | Maximum dissipation factor at 100 Hz              |
| Z               | Maximum impedance at 100 kHz                      |

**ORDERING EXAMPLE**

Electrolytic capacitor 250 RMI-V series, high vibration resistance

4700  $\mu\text{F}$  / 16 V;  $\pm 20\%$

Nominal case size:  $\varnothing 16\text{ mm} \times 31\text{ mm}$ ; Form TFA

Ordering code: MAL225035472E3

**Note**

- Unless otherwise specified, all electrical values in Table 2 apply at  $T_{\text{amb}} = 20\text{ °C}$ ,  $P = 86\text{ kPa}$  to  $106\text{ kPa}$ ,  $\text{RH} = 45\%$  to  $75\%$ .

**Table 2**

| ELECTRICAL DATA AND ORDERING INFORMATION |                                      |  |                                    |  |                         |  |  |                               |         |          |
|--|--------------------------------------|--|------------------------------------|--|-------------------------|--|--|-------------------------------|---------|----------|
| $U_R$<br>(V)                             | $C_R$<br>100 Hz<br>( $\mu\text{F}$ ) | NOMINAL<br>CASE SIZE<br>$\varnothing D \times L$<br>(mm) | $I_R$<br>100 kHz<br>105 °C<br>(mA) | $I_{L2}$<br>2 min<br>( $\mu\text{A}$ ) | $\tan \delta$<br>100 Hz | Z<br>100 kHz<br>+20 °C<br>( $\Omega$ ) | Z<br>100 kHz<br>-40 °C<br>( $\Omega$ ) | ORDERING CODE<br>MAL2250..... |         |          |
|  |                                      |  |                                    |  |                         |  |  | BULK PACKAGING                |         | TAPED    |
|  |                                      |  |                                    |  |                         |  |  | FORM CA                       | FORM CB | FORM TFA |
| 10                                       | 4700                                 | 16 x 25  | 2390                               | 473                                    | 0.23                    | 0.022                                  | 0.150                                  | 54472E3                       | 64472E3 | 34472E3  |
|  | 6800                                 | 16 x 31  | 2890                               | 683                                    | 0.25                    | 0.019                                  | 0.130                                  | 54682E3                       | 64682E3 | 34682E3  |
| 16                                       | 3300                                 | 16 x 20  | 1840                               | 531                                    | 0.20                    | 0.028                                  | 0.200                                  | 55332E3                       | 65332E3 | 35332E3  |
|  | 4700                                 | 16 x 31  | 2890                               | 755                                    | 0.22                    | 0.019                                  | 0.130                                  | 55472E3                       | 65472E3 | 35472E3  |
|  | 6800                                 | 16 x 35  | 3100                               | 1091                                   | 0.24                    | 0.018                                  | 0.130                                  | 55682E3                       | 65682E3 | -        |
|  | 8200                                 | 18 x 40  | 3500                               | 1315                                   | 0.28                    | 0.018                                  | 0.130                                  | 55822E3                       | 65822E3 | -        |
| 25                                       | 2200                                 | 16 x 20  | 1840                               | 553                                    | 0.16                    | 0.028                                  | 0.200                                  | 56222E3                       | 66222E3 | 36222E3  |
|  | 3300                                 | 16 x 31  | 2890                               | 828                                    | 0.16                    | 0.019                                  | 0.130                                  | 56332E3                       | 66332E3 | 36332E3  |
|  | 4700                                 | 16 x 35  | 3100                               | 1178                                   | 0.18                    | 0.018                                  | 0.130                                  | 56472E3                       | 66472E3 | -        |
|  | 6800                                 | 18 x 40  | 3500                               | 1703                                   | 0.22                    | 0.018                                  | 0.130                                  | 56682E3                       | 66682E3 | -        |
| 35                                       | 1000                                 | 16 x 20  | 1840                               | 353                                    | 0.12                    | 0.028                                  | 0.200                                  | 90105E3                       | 90106E3 | 90103E3  |
|  | 1500                                 | 16 x 20  | 1840                               | 528                                    | 0.12                    | 0.028                                  | 0.200                                  | 50152E3                       | 60152E3 | 30152E3  |
|  | 2200                                 | 16 x 31  | 2890                               | 773                                    | 0.14                    | 0.019                                  | 0.130                                  | 50222E3                       | 60222E3 | 30222E3  |
|  | 3300                                 | 18 x 31  | 3000                               | 1155                                   | 0.16                    | 0.019                                  | 0.130                                  | 50332E3                       | 60332E3 | -        |
|  | 4700                                 | 18 x 40  | 3300                               | 1648                                   | 0.18                    | 0.018                                  | 0.130                                  | 50472E3                       | 60472E3 | -        |
| 50                                       | 1000                                 | 16 x 25  | 1800                               | 503                                    | 0.10                    | 0.034                                  | 0.240                                  | 51102E3                       | 61102E3 | 31102E3  |
|  | 1200                                 | 16 x 31  | 2200                               | 603                                    | 0.10                    | 0.027                                  | 0.190                                  | 51122E3                       | 61122E3 | 31122E3  |
|  | 1500                                 | 16 x 31  | 2200                               | 753                                    | 0.10                    | 0.027                                  | 0.190                                  | 51152E3                       | 61152E3 | 31152E3  |
|  | 3300                                 | 18 x 40  | 3200                               | 1653                                   | 0.14                    | 0.024                                  | 0.168                                  | 51332E3                       | 61332E3 | -        |
| 63                                       | 470                                  | 16 x 20  | 1100                               | 299                                    | 0.10                    | 0.074                                  | 0.520                                  | 98475E3                       | 98476E3 | 98473E3  |
|  | 680                                  | 16 x 20  | 1100                               | 431                                    | 0.10                    | 0.074                                  | 0.520                                  | 58681E3                       | 68681E3 | 38681E3  |
|  | 680                                  | 16 x 25  | 1500                               | 431                                    | 0.10                    | 0.054                                  | 0.380                                  | 98685E3                       | 98686E3 | 98683E3  |
|  | 1000                                 | 16 x 31  | 1900                               | 633                                    | 0.10                    | 0.042                                  | 0.295                                  | 58102E3                       | 68102E3 | 38102E3  |
|  | 2200                                 | 18 x 40  | 3100                               | 1389                                   | 0.12                    | 0.033                                  | 0.231                                  | 58222E3                       | 68222E3 | -        |
| 100                                      | 330                                  | 18 x 20  | 1700                               | 330                                    | 0.07                    | 0.074                                  | 2.0                                    | 90183E3                       | 90185E3 | -        |

**Table 3**

| EXTENDED VIBRATION SPECIFICATIONS |   |   |
|-----------------------------------|---|---|
| PARAMETER                         | PROCEDURE   | REQUIREMENTS  |
| Vibration specifications          | From 10 g to 50 g   | No visible damage;<br>no leakage of electrolyte;<br>marking legible<br>$\Delta\text{C}/\text{C}: \pm 5\%$ with respect to<br>initial measurements |
| Vibration frequency range         | 10 Hz to 2 kHz  |   |
| Vibration profile                 | <ul style="list-style-type: none"> <li>Constant sinus sweep</li> <li>3 directions</li> <li>8 h per direction</li> </ul> |   |





Fig. 5 - Vibration profile

Table 4


| ADDITIONAL ELECTRICAL DATA         |   |   |
|------------------------------------|---|---|
| PARAMETER                          | CONDITIONS  | VALUE                                       |
| <b>Voltage</b>                     |   |   |
| Surge voltage                      |   | $U_S \leq 1.15 \times U_R$                  |
| Reverse voltage                    |   | $U_{rev} \leq 1 V$                          |
| <b>Current</b>                     |   |   |
| Leakage current                    | After 2 min at $U_R$  | $I_{L2} \leq 0.01 C_R \times U_R + 3 \mu A$ |
| <b>Inductance</b>                  |   |   |
| Equivalent series inductance (ESL) | Case $\varnothing D \geq 16 \text{ mm}$                     | Typ. 18 nH                                  |
| <b>Resistance</b>                  |   |   |
| Equivalent series resistance (ESR) | Calculated from $\tan \delta_{max}$ and $C_R$ (see Table 2) | $ESR = \tan \delta / 2 \pi f C_R$           |

**CAPACITANCE (C)**



$C_0$  = typical capacitance at 20 °C, 100 Hz

Fig. 6 - Typical multiplier of capacitance as a function of ambient temperature



$C_0$  = typical capacitance at 20 °C, 100 Hz

Fig. 7 - Typical multiplier of capacitance as a function of frequency

**EQUIVALENT SERIES RESISTANCE (ESR)**




Fig. 8 - Typical multiplier of ESR as a function of ambient temperature




Fig. 9 - Typical multiplier of ESR as a function of frequency

**IMPEDANCE (Z)**




Fig. 10 - Typical multiplier of impedance as a function of ambient temperature




Fig. 11 - Typical impedance as a function of frequency




Fig. 12 - Typical impedance as a function of frequency



**RIPPLE CURRENT AND USEFUL LIFE**

Table 5

| ENDURANCE TEST DURATION AND USEFUL LIFE AS A FUNCTION OF CASE SIZE |           |                               |                                 |
|--|-----------|-------------------------------|---------------------------------|
| NOMINAL CASE SIZE<br>Ø D x L<br>(mm)                               | CASE CODE | ENDURANCE<br>AT 105 °C<br>(h) | USEFUL LIFE<br>AT 105 °C<br>(h) |
| 16 x 20  | 19a       | 3000                          | 7000                            |
| 16 x 25  | 19        | 5000                          | 10 000                          |
| 16 x 31  | 20        | 5000                          | 10 000                          |
| 16 x 35  | 21        | 5000                          | 10 000                          |
| 18 x 20  | 1820      | 3000                          | 7000                            |
| 18 x 31  | 1831      | 6000                          | 10 000                          |
| 18 x 40  | 1840      | 8000                          | 10 000                          |

**Note**

- Multiplier of useful life code: CCC206




Fig. 13 - Multiplier of useful life as a function of ambient temperature and ripple current load



Table 6

| MULTIPLIER OF RIPPLE CURRENT ( $I_R$ ) AS A FUNCTION OF FREQUENCY |      |      |      |        |        |         |
|---|------|------|------|--------|--------|---------|
| FREQUENCY (Hz)  |      |      |      |        |        |         |
| 100   | 300  | 1000 | 3000 | 10 000 | 30 000 | 100 000 |
| $I_R$ MULTIPLIER  |      |      |      |        |        |         |
| 0.76  | 0.85 | 0.91 | 0.94 | 0.96   | 0.98   | 1.00    |

Table 7

| TEST PROCEDURES AND REQUIREMENTS               |   |   |  |
|--|---|---|--|
| TEST   |   | PROCEDURE<br>(quick reference)  | REQUIREMENTS   |
| NAME OF TEST                                   | REFERENCE                                   |   |  |
| Endurance                                      | IEC 60384-4 /<br>EN130300<br>subclause 4.13 | $T_{amb} = 105\text{ °C}$ ; $U_R$ applied;<br>for test duration see Table 3   | $\Delta C/C: \pm 20\%$<br>$\tan \delta \leq 2 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$   |
| Useful life                                    | CECC 30301<br>subclause 1.8.1               | $T_{amb} = 105\text{ °C}$ ; $U_R$ and $I_R$ applied;<br>for test duration see Table 3   | $\Delta C/C: \pm 30\%$<br>$\tan \delta \leq 3 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$<br>no short or open circuit<br>total failure percentage: $\leq 1\%$ |
| Shelf life<br>(storage at high<br>temperature) | IEC 60384-4 /<br>EN130300<br>subclause 4.17 | $T_{amb} = 105\text{ °C}$ ; no voltage applied; 1000 h<br>after test: $U_R$ to be applied for 30 min., 24 h to 48 h<br>before measurement | $\Delta C/C: \pm 20\%$<br>$\tan \delta \leq 2 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$   |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А