

High Reliability NPN Silicon Phototransistor



OP804, OP805 (TX, TXV)

Features:

- TO-18 hermetically sealed package
- Lensed for high sensitivity
- Narrow acceptance angle
- Processed after MIL-PRF-19500
- Mechanically and spectrally matched to high reliability IREDs in the OP235 and OP236 series



Description:

Each device in this series consists of a high reliability NPN silicon phototransistor mounted in a hermetically sealed TO-18 package, which offers high power dissipation and superior hostile environment operation. Device lensing creates a 12° angle when measured from the optical axis to the half power point.

These devices can be matched with a solid state infrared source (such as the high resolution OP235 and OP236 series of IREDs), or can be used to sense infrared content in a visible light source (such as a tungsten bulb or sunlight) for automatic brightness control.


TX and TXV devices are processed to MIL-PRF-19500.

Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.

Applications:

- Space-limited applications
- Hostile environment applications

Part Number	Sensor	Light Current $I_{C(ON)}$ (mA) Min / Max	V_{CE} Typ/Max	Input Power E_e (mW/cm ²)	Viewing Angle	Lead Length
OP804TX	Transistor	7.00 / 22.00	5	5.0	25°	0.50"
OP804TXV						
OP805TX		15.00 / NA				
OP805TXV						



* THIS DIMENSION CONTROLLED AT HOUSING SURFACE.
DIMENSIONS ARE IN INCHES (MILLIMETERS)

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology, Inc.
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
sensors@ttelelectronics.com | www.ttelelectronics.com

High Reliability NPN Silicon Phototransistor



OP804, OP805 (TX, TXV)

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Storage Temperature Range	-65° C to +150° C
Operating Temperature Range	-55° C to +125° C
Collector-Base Voltage	30 V
Collector-Emitter Voltage	30 V
Emitter-Base Voltage	5 V
Emitter-Collector Voltage (applies to all OP800 and OP830 devices)	5 V
Lead Soldering Temperature [1/16 inch (1.6mm) fro case for 5 seconds with soldering iron] ⁽¹⁾	260° C
Power Dissipation ⁽²⁾	250 mW

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Input Diode

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
$I_{C(ON)}$	On-State Collector Current OP804 (TX, TXV) OP805 (TX, TXV)	7.0 15.0		8 22	mA	$V_{CE} = 5.0\text{V}$, $E_e = 20\text{ mW/cm}^{2(3)}$
I_{CEO}	Collector-Emitter Dark Current			100	nA	$V_{CE} = 10.0\text{ V}$, $E_e = 0$
				100	μA	$V_{CE} = 30.0\text{ V}$, $E_e = 0$ $T_A = 100^\circ\text{ C}$
$V_{(BR)CEO}$	Collector-Base Breakdown Voltage	30			V	$I_C = 100\ \mu\text{A}$, $I_B = 0$, $E_e = 0$
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage	7.0			V	$I_C = 100\ \mu\text{A}$, $E_e = 0$
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage			0.40	V	$I_C = 0.4\text{ mA}$, $E_e = 20\text{ mW/cm}^{2(3)}$
t_f	Rise Time OP804 (TX, TXV) OP805 (TX, TXV)			10.0 15.0	μs	$V_{CC} = 30\text{ V}$, $I_C = 1.00\text{ mA}$, $R_L = 100\ \Omega$
	Fall Time OP804 (TX, TXV) OP805 (TX, TXV)			10.0 15.0		

Notes:

- (1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.
- (2) Derate linearly 2.5 mW/° C above 25° C.
- (3) Light source is an unfiltered tungsten lamp operated at a temperature of 2870 K

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTeK Technology, Inc.
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200
sensors@ttelelectronics.com | www.ttelelectronics.com

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А