


**Sxx20x & Sxx25x Series**

RoHS



**Agency Approval**

| Agency  | Agency File Number |
|---|--------------------|
|  | L Package: E71639  |

**Main Features**

| Symbol            | Value       | Unit |
|-------------------|-------------|------|
| $I_{T(RMS)}$      | 20 & 25     | A    |
| $V_{DRM}/V_{RRM}$ | 400 to 1000 | V    |
| $I_{GT}$          | 30 to 35    | mA   |

**Additional Information**



Datasheet



Resources



Samples

**Description**

Excellent unidirectional switches for phase control applications such as heating and motor speed controls. Standard phase control SCRs are triggered with few milliamperes of current at less than 1.5V potential.

**Features & Benefits**


- RoHS compliant
- Glass – passivated junctions
- Voltage capability up to 1000 V
- Surge capability up to 350 A

**Applications**

Typical applications are AC solid-state switches, industrial power tools, exercise equipment, white goods and commercial appliances.

Internally constructed isolated packages are offered for ease of heat sinking with highest isolation voltage.

**Schematic Symbol**



**Absolute Maximum Ratings – 20A SCR**

| Symbol       | Parameter                                 | Test Conditions  | Value      | Unit                   |
|--------------|---|--|------------|------------------------|
| $I_{T(RMS)}$ | RMS on-state current                      | $T_c = 80^\circ\text{C}$   | 20         | A                      |
| $I_{T(AV)}$  | Average on-state current                  | Sxx20x $T_c = 80^\circ\text{C}$  | 12.8       | A                      |
| $I_{TSM}$    | Peak non-repetitive surge current         | single half cycle; $f = 50\text{Hz}$ ;<br>$T_j(\text{initial}) = 25^\circ\text{C}$ | 255        | A                      |
|              |   | single half cycle; $f = 60\text{Hz}$ ;<br>$T_j(\text{initial}) = 25^\circ\text{C}$ | 300        |                        |
| $I^2t$       | $I^2t$ Value for fusing                   | $t_p = 8.3 \text{ ms}$   | 374        | $\text{A}^2\text{s}$   |
| $di/dt$      | Critical rate of rise of on-state current | $f = 60\text{Hz}$ ; $T_j = 125^\circ\text{C}$                                      | 125        | $\text{A}/\mu\text{s}$ |
| $I_{GM}$     | Peak gate current                         | $T_j = 125^\circ\text{C}$  | 3          | A                      |
| $P_{G(AV)}$  | Average gate power dissipation            | $T_j = 125^\circ\text{C}$  | 0.6        | W                      |
| $T_{stg}$    | Storage temperature range                 |  | -40 to 150 | $^\circ\text{C}$       |
| $T_j$        | Operating junction temperature range      |  | -40 to 125 | $^\circ\text{C}$       |

### Absolute Maximum Ratings — 25A SCR

| Symbol       | Parameter                                 | Test Conditions  | Value                     | Unit                   |   |
|--------------|---|--|---------------------------|------------------------|---|
| $I_{T(RMS)}$ | RMS on-state current                      | Sxx25L: $T_c = 75^\circ\text{C}$   | 25                        | A                      |   |
|              |   | Sxx25R/Sxx25N: $T_c = 100^\circ\text{C}$                                       |                           |                        |   |
| $I_{T(AV)}$  | Average on-state current                  | Sxx25L   | $T_c = 75^\circ\text{C}$  | 16.0                   | A |
|              |   | Sxx25R/Sxx25N  | $T_c = 100^\circ\text{C}$ |                        |   |
| $I_{TSM}$    | Peak non-repetitive surge current         | single half cycle; $f = 50\text{Hz}$ ;<br>$T_J$ (initial) = $25^\circ\text{C}$ | 300                       | A                      |   |
|              |   | single half cycle; $f = 60\text{Hz}$ ;<br>$T_J$ (initial) = $25^\circ\text{C}$ | 350                       |                        |   |
| $I^2t$       | $I^2t$ Value for fusing                   | $t_p = 8.3 \text{ ms}$   | 510                       | $\text{A}^2\text{s}$   |   |
| $di/dt$      | Critical rate of rise of on-state current | $f = 60\text{Hz}$ ; $T_J = 125^\circ\text{C}$                                  | 150                       | $\text{A}/\mu\text{s}$ |   |
| $I_{GM}$     | Peak gate current                         | $T_J = 125^\circ\text{C}$  | 3.5                       | A                      |   |
| $P_{G(AV)}$  | Average gate power dissipation            | $T_J = 125^\circ\text{C}$  | 0.8                       | W                      |   |
| $T_{stg}$    | Storage temperature range                 |  | -40 to 150                | $^\circ\text{C}$       |   |
| $T_J$        | Operating junction temperature range      |  | -40 to 125                | $^\circ\text{C}$       |   |

### Electrical Characteristics ( $T_J = 25^\circ\text{C}$ , unless otherwise specified)

| Symbol   | Test Conditions   | Value  |        | Unit |                  |
|----------|---|--------|--------|------|------------------|
|          |   | Sxx20L | Sxx25x |      |                  |
| $I_{GT}$ | $V_D = 12\text{V}$ ; $R_L = 30\Omega$                                     | MAX.   | 30     | 35   | mA               |
|          |   | MIN.   | 1      | 1    |                  |
| $V_{GT}$ |   | MAX.   | 1.5    |      | V                |
| $dv/dt$  | $V_D = V_{DRM}$ ; gate open; $T_J = 100^\circ\text{C}$                    | 400V   | 450    |      | V/ $\mu\text{s}$ |
|          |   | 600V   | 425    |      |                  |
|          |   | 800V   | 400    |      |                  |
|          |   | 1000V  | MIN.   | 200  |                  |
|          | $V_D = V_{DRM}$ ; gate open; $T_J = 125^\circ\text{C}$                    | 400V   | 350    |      |                  |
|          |   | 600V   | 325    |      |                  |
| 800V     |   | 300    |        |      |                  |
| $V_{GD}$ | $V_D = V_{DRM}$ ; $R_L = 3.3 \text{ k}\Omega$ ; $T_J = 125^\circ\text{C}$ | MIN.   | 0.2    |      | V                |
| $I_H$    | $I_T = 400\text{mA}$ (initial)  | MAX.   | 40     | 50   | mA               |
| $t_g$    | (1)   | MAX.   | 35     |      | $\mu\text{s}$    |
| $t_{gt}$ | $I_G = 2 \times I_{GT}$ ; $PW = 15\mu\text{s}$ ; $I_T = 40\text{A}$       | TYR.   | 2      |      | $\mu\text{s}$    |

Notes :  
 xx = voltage, x = package  
 (1)  $I_T = 2\text{A}$ ;  $t_g = 50\mu\text{s}$ ;  $dv/dt = 5\text{V}/\mu\text{s}$ ;  $di/dt = 30\text{A}/\mu\text{s}$

**Static Characteristics**


| Symbol              | Test Conditions                           |                     |             | Value | Unit |         |
|---------------------|---|---------------------|-------------|-------|------|---------|
| $V_{TM}$            | 20A Device $I_T = 40A$ ; $t_p = 380\mu s$ |                     |             | MAX.  | 1.6  | V       |
|                     | 25A Device $I_T = 50A$ ; $t_p = 380\mu s$ |                     |             |       |      |         |
| $I_{DRM} / I_{RRM}$ | $V_{DRM} / V_{RRM}$                       | $T_J = 25^\circ C$  | 400 – 600V  | MAX.  | 10   | $\mu A$ |
|                     |   |                     | 800 – 1000V |       | 20   |         |
|                     |   | $T_J = 100^\circ C$ | 400 – 600V  |       | 500  |         |
|                     |   |                     | 800V        |       | 1000 |         |
|                     |   |                     | 1000V       |       | 3000 |         |
|                     |   | $T_J = 125^\circ C$ | 400 – 600V  |       | 1000 |         |
|                     |   |                     | 800V        |       | 2000 |         |

**Thermal Resistances**


| Symbol            | Parameter             |                 | Value | Unit         |
|-------------------|-----------------------|-----------------|-------|--------------|
| $R_{\theta(J-C)}$ | Junction to case (AC) | Sxx25R / Sxx25N | 1.0   | $^\circ C/W$ |
|                   |                       | Sxx20L          | 2.4   |              |
|                   |                       | Sxx25L          | 2.35  |              |
| $R_{\theta(J-A)}$ | Junction to ambient   | Sxx25R          | 40    | $^\circ C/W$ |
|                   |                       | Sxx20L / Sxx25L | 50    |              |

Note: xx = voltage


**Figure 1: Normalized DC Gate Trigger Current vs. Junction Temperature**




**Figure 2: Normalized DC Gate Trigger Voltage vs. Junction Temperature**




**Figure 3: Normalized DC Holding Current vs. Junction Temperature**




**Figure 4: On-State Current vs. On-State Voltage (Typical)**




**Figure 5: Power Dissipation (Typical) vs. RMS On-State Current**



**Figure 6: Maximum Allowable Case Temperature vs. RMS On-State Current**



**Figure 7: Maximum Allowable Case Temperature vs. Average On-State Current**



**Figure 8: Maximum Allowable Ambient Temperature vs. RMS On-State Current**




**Figure 9: Maximum Allowable Ambient Temperature vs. Average On-State Current**




Note: xx = voltage


**Figure 10: Peak Capacitor Discharge Current**



**Figure 11: Peak Capacitor Discharge Current Derating**



**Figure 12: Surge Peak On-State Current vs. Number of Cycles**




SUPPLY FREQUENCY: 60 Hz Sinusoidal  
LOAD: Resistive  
RMS On-State Current: [ $I_{T(RMS)}$ ]: Maximum Rated Value at Specified Case Temperature

Notes:

1. Gate control may be lost during and immediately following surge current interval.
2. Overload may not be repeated until junction temperature has returned to steady-state rated value.

### Soldering Parameters

|  |                                    |                         |
|--|------------------------------------|-------------------------|
| Reflow Condition                                       |                                    | Pb – Free assembly      |
| Pre Heat   | - Temperature Min ( $T_{s(min)}$ ) | 150°C                   |
|  | - Temperature Max ( $T_{s(max)}$ ) | 200°C                   |
|  | - Time (min to max) ( $t_s$ )      | 60 – 180 secs           |
| Average ramp up rate (Liquidus Temp) ( $T_L$ ) to peak |                                    | 5°C/second max          |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                    | 5°C/second max          |
| Reflow   | - Temperature ( $T_L$ ) (Liquidus) | 217°C                   |
|  | - Temperature ( $t_l$ )            | 60 – 150 seconds        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds         |
| Ramp-down Rate   |                                    | 5°C/second max          |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes Max.          |
| Do not exceed  |                                    | 280°C                   |



### Physical Specifications

|                        |   |
|------------------------|---|
| <b>Terminal Finish</b> | 100% Matte Tin-plated   |
| <b>Body Material</b>   | UL recognized epoxy meeting flammability classification 94V-0 |
| <b>Lead Material</b>   | Copper Alloy  |


### Design Considerations

Careful selection of the correct device for the application's operating parameters and environment will go a long way toward extending the operating life of the Thyristor. Good design practice should limit the maximum continuous current through the main terminals to 75% of the device rating. Other ways to ensure long life for a power discrete semiconductor are proper heat sinking and selection of voltage ratings for worst case conditions. Overheating, overvoltage (including dv/dt), and surge currents are the main killers of semiconductors. Correct mounting, soldering, and forming of the leads also help protect against component damage.

### Environmental Specifications


| Test                             | Specifications and Conditions  |
|----------------------------------|--|
| <b>AC Blocking</b>               | MIL-STD-750, M-1040, Cond A Applied Peak AC voltage @ 125°C for 1008 hours   |
| <b>Temperature Cycling</b>       | MIL-STD-750, M-1051, 100 cycles; -40°C to +150°C; 15-min dwell-time  |
| <b>Temperature/Humidity</b>      | EIA / JEDEC, JESD22-A101 1008 hours; 320V - DC: 85°C; 85% rel humidity   |
| <b>High Temp Storage</b>         | MIL-STD-750, M-1031, 1008 hours; 150°C   |
| <b>Low-Temp Storage</b>          | 1008 hours; -40°C  |
| <b>Thermal Shock</b>             | MIL-STD-750, M-1056 10 cycles; 0°C to 100°C; 5-min dwelltime at each temperature; 10 sec (max) transfer time between temperature |
| <b>Autoclave</b>                 | EIA / JEDEC, JESD22-A102 168 hours (121°C at 2 ATMs) and 100% R/H  |
| <b>Resistance to Solder Heat</b> | MIL-STD-750 Method 2031  |
| <b>Solderability</b>             | ANSI/J-STD-002, category 3, Test A   |
| <b>Lead Bend</b>                 | MIL-STD-750, M-2036 Cond E   |

**Dimensions — TO-220AB (R-Package) — Non-Isolated Mounting Tab Common with Center Lead**




| Dimension | Inches |       | Millimeters |       |
|-----------|--------|-------|-------------|-------|
|           | Min    | Max   | Min         | Max   |
| A         | 0.380  | 0.420 | 9.65        | 10.67 |
| B         | 0.105  | 0.115 | 2.67        | 2.92  |
| C         | 0.230  | 0.250 | 5.84        | 6.35  |
| D         | 0.590  | 0.620 | 14.99       | 15.75 |
| E         | 0.142  | 0.147 | 3.61        | 3.73  |
| F         | 0.110  | 0.130 | 2.79        | 3.30  |
| G         | 0.540  | 0.575 | 13.72       | 14.61 |
| H         | 0.025  | 0.035 | 0.64        | 0.89  |
| J         | 0.195  | 0.205 | 4.95        | 5.21  |
| K         | 0.095  | 0.105 | 2.41        | 2.67  |
| L         | 0.060  | 0.075 | 1.52        | 1.91  |
| M         | 0.085  | 0.095 | 2.16        | 2.41  |
| N         | 0.018  | 0.024 | 0.46        | 0.61  |
| O         | 0.178  | 0.188 | 4.52        | 4.78  |
| P         | 0.045  | 0.060 | 1.14        | 1.52  |
| R         | 0.038  | 0.048 | 0.97        | 1.22  |

**Dimensions — TO-220AB (L-Package) — Isolated Mounting Tab**



| Dimension | Inches |       | Millimeters |       |
|-----------|--------|-------|-------------|-------|
|           | Min    | Max   | Min         | Max   |
| A         | 0.380  | 0.420 | 9.65        | 10.67 |
| B         | 0.105  | 0.115 | 2.67        | 2.92  |
| C         | 0.230  | 0.250 | 5.84        | 6.35  |
| D         | 0.590  | 0.620 | 14.99       | 15.75 |
| E         | 0.142  | 0.147 | 3.61        | 3.73  |
| F         | 0.110  | 0.130 | 2.79        | 3.30  |
| G         | 0.540  | 0.575 | 13.72       | 14.61 |
| H         | 0.025  | 0.035 | 0.64        | 0.89  |
| J         | 0.195  | 0.205 | 4.95        | 5.21  |
| K         | 0.095  | 0.105 | 2.41        | 2.67  |
| L         | 0.060  | 0.075 | 1.52        | 1.91  |
| M         | 0.085  | 0.095 | 2.16        | 2.41  |
| N         | 0.018  | 0.024 | 0.46        | 0.61  |
| O         | 0.178  | 0.188 | 4.52        | 4.78  |
| P         | 0.045  | 0.060 | 1.14        | 1.52  |
| R         | 0.038  | 0.048 | 0.97        | 1.22  |

**Dimensions –TO- 263AB (N-package) – D<sup>2</sup>-Pak Surface Mount**



| Dimension | Inches |       | Millimeters |       |
|-----------|--------|-------|-------------|-------|
|           | Min    | Max   | Min         | Max   |
| A         | 0.360  | 0.370 | 9.14        | 9.40  |
| B         | 0.380  | 0.420 | 9.65        | 10.67 |
| C         | 0.178  | 0.188 | 4.52        | 4.78  |
| D         | 0.025  | 0.035 | 0.64        | 0.89  |
| E         | 0.045  | 0.060 | 1.14        | 1.52  |
| F         | 0.060  | 0.075 | 1.52        | 1.91  |
| G         | 0.095  | 0.105 | 2.41        | 2.67  |
| H         | 0.092  | 0.102 | 2.34        | 2.59  |
| J         | 0.018  | 0.024 | 0.46        | 0.61  |
| K         | 0.090  | 0.110 | 2.29        | 2.79  |
| S         | 0.590  | 0.625 | 14.99       | 15.88 |
| V         | 0.035  | 0.045 | 0.89        | 1.14  |
| U         | 0.002  | 0.010 | 0.05        | 0.25  |
| W         | 0.040  | 0.070 | 1.016       | 1.78  |

**Product Selector**

| Part Number | Voltage |      |      |       | Gate Sensitivity | Type         | Package |
|-------------|---------|------|------|-------|------------------|--------------|---------|
|             | 400V    | 600V | 800V | 1000V |                  |              |         |
| Sxx20L      | X       | X    | X    | X     | 30mA             | Standard SCR | TO-220L |
| Sxx25L      | X       | X    | X    | X     | 35mA             | Standard SCR | TO-220L |
| Sxx25R      | X       | X    | X    | X     | 35mA             | Standard SCR | TO-220R |
| Sxx25N      | X       | X    | X    | X     | 35mA             | Standard SCR | TO-263  |

Note: xx = Voltage

**Packing Options**


| Part Number | Marking | Weight | Packing Mode     | Base Quantity     |
|-------------|---------|--------|------------------|-------------------|
| Sxx20L      | Sxx20L  | 2.2g   | Bulk             | 500               |
| Sxx20LTP    | Sxx20L  | 2.2g   | Tube             | 500 (50 per tube) |
| Sxx25L      | Sxx25L  | 2.2g   | Bulk             | 500               |
| Sxx25LTP    | Sxx25L  | 2.2g   | Tube             | 500 (50 per tube) |
| Sxx25R      | Sxx25R  | 2.2g   | Bulk             | 500               |
| Sxx25RTP    | Sxx25R  | 2.2g   | Tube             | 500 (50 per tube) |
| Sxx25NTP    | Sxx25N  | 1.6g   | Tube             | 500 (50 per tube) |
| Sxx25NRP    | Sxx25N  | 1.6g   | Embossed Carrier | 500               |

Note: xx = Voltage




**TO-263 Embossed Carrier Reel Pack (RP) Specifications**

Meets all EIA-481-2 Standards




**Part Numbering System**



**Part Marking System**

TO-220 AB - (L and R Package)  
TO-263 AB - (N Package)



Date Code Marking  
Y: Year Code  
M: Month Code  
XXX: Lot Trace Code

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А