



OeM4214-20.00M TCVCXO Oscillator

November 2010

- Pletronics' OeM4 is from the OeXO™ Series of temperature compensated voltage controlled crystal oscillator with a CMOS output.
- Tube packaging is available
- Hermetically sealed Metal Package to replace DIP/DIL OCXOs
- Supply Voltage range: 3.10 to 12.0V

Pletronics Inc. certifies this device is in accordance with the RoHS 6/6 (2002/95/EC) and WEEE (2002/96/EC) directives.

Pletronics Inc. guarantees the device does not contain the following:
Cadmium, Hexavalent Chromium, Lead, Mercury, PBB's, PBDE's
Weight of the Device: 4.00 grams
Moisture Sensitivity Level: 1 As defined in J-STD-020D.1
Second Level Interconnect code: e1



Absolute Maximum Ratings:

| Parameter | Unit |
|--------------------------------|-----------------------------------|
| V _{CC} Supply Voltage | -0.5V to +12.0V |
| V _{CONTROL} Voltage | -0.5V to +3.0V or limited to ±5mA |
| V _o Output Voltage | -0.5V to +6.0V |


Thermal Characteristics

The maximum die or junction temperature is 155°C
The thermal resistance junction to board is 120°C/Watt depending on the solder pads, ground plane and construction of the PCB.

ESD Rating

| Model | Minimum Voltage | Conditions |
|----------------------|-----------------|-------------------------|
| Human Body Model | 1500 | MIL-STD-883 Method 3115 |
| Charged Device Model | 1000 | JESD 22-C101 |

Part Marking:



PLE = Pletronics
 OEM4 = Model number of the series
 20.00 = frequency in MHZ
 4214 = Model number
 YMD = Year, Month and Date of manufacture
 zz = internal factory code

Codes for Date Code YMD

| Code | 0 | 1 | 2 | 3 | 4 | Code | A | B | C | D | E | F | G | H | J | K | L | M |
|------|------|------|------|------|------|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Year | 2010 | 2011 | 2012 | 2013 | 2014 | Month | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOV | DEC |

| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | A | B | C | D | E | F | G |
|------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|
| Day | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |

| Code | H | J | K | L | M | N | P | R | T | U | V | W | X | Y | Z |
|------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Day | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 |

Reliability: Environmental Compliance

| Parameter | Condition |
|------------------|--------------------------------------|
| Mechanical Shock | MIL-STD-883 Method 2002, Condition B |
| Vibration | MIL-STD-883 Method 2007, Condition A |
| Solderability | MIL-STD-883 Method 2003 |
| Thermal Shock | MIL-STD-883 Method 1011, Condition A |

Package Labeling

Label is 1" x 2.6" (25.4mm x 66.7mm)





Font is Courier New

Bar code is 39-Full ASCII

The bar code will show the actual Part Number OEM4214-20.00M

Label is 1" x 2.6" (25.4mm x 66.7mm)

Font is Arial

| |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| P/N:  OEM4xxx-ff.fFM Customer P/N:  123456 Qty:  1000 D/C  0GD MSL: 1 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|


| |
|---------------------------------------------------------------------------------------------------|
| RoHS Compliant 2nd Lvl Interconnect Category=e4 Max Safe Temp=260C for 10s 2X Max |
|---------------------------------------------------------------------------------------------------|

Electrical Specification over the specified temperature range.

| Item | Min | TYP | Max | Unit | Condition |
|----------------------------------------------------------------------|----------------------------|--------------------------------------------|----------------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Stability over temperature | -250 | - | 250 | ppb | Over -40°C to 85°C at fixed supply voltage + load (reference to midpoint min/max frequency) |
| Holdover | -250 -125 | 0 0 | 250 125 | ppb ppb | Over -40°C to 85°C for 24 hours Over $\pm 5^\circ\text{C}$ change for 24 hours |
| Frequency Calibration | -2.0 | - | 2.0 | ppm | Frequency offset at 25°C, 60 minutes after reflow. |
| Supply voltage stability | -10 | 0 | 10 | ppb | $\pm 2\%$ variation in supply voltage |
| Load sensitivity | -5 | - | 5 | ppb | 10K ohm $\pm 10\%$ 15 pF $\pm 10\%$ |
| Warm Up | - | 0.4 | 3.0 | S | Time to reach specified frequency |
| Aging rate following reflow | - - - | ± 10 ± 3 ± 1 | - - - | ppb/day | 1 day after reflow 7 days after reflow 30 days after reflow |
| Long term stability (Aging) | -1000 -1500 -4600 | - - - | 1000 1500 4600 | ppb | after 1 year after 5 years after 15 years |
| Output Waveform | CMOS | | | | |
| Output V_{HIGH} | 2.80 | - | - | V | Load: 10K ohm $\pm 10\%$ 15 pF $\pm 10\%$ Vth: T_{R} and T_{F} 10% and 90% of amplitude Vth: D.C. 50% of amplitude |
| Output V_{LOW} | - | - | 0.20 | V | |
| T_{RISE} and T_{FALL} | - | - | 4.0 | nS | |
| Duty Cycle | 40 | 50 | 60 | % | |
| Phase Noise 1 Hz 10 Hz 100 Hz 1 KHz 10 KHz 100 KHz | - - - - - - | -71 -92 -115 -135 -148 -149 | - - - - - - | dBc/Hz | at 25°C |
| Jitter | - | - | 0.6 | pS | Frequency offset from carrier 12kHz to 20MHz |
| V Supply Range ¹ V_{CC} | 3.10 | - | 12.0 | Volts | |
| Supply Current I_{CC} | - | - | 5.0 | mA | |
| V_{CONTROL} Range | 0.5 | - | 2.50 | Volts | 1.50 volts nominal |
| V_{CONTROL} Input Current | -50 | - | 50 | uA | |
| Frequency Pullability | 5 | - | 10 | \pm ppm | Slope positive |
| Linearity | - | 0.05 | 2.0 | % | In accordance with MIL-PRF-55310 |
| Operating Temperature | -40 | - | +85 | °C | |
| Storage Temperature | -55 | - | +95 | °C | |

Note: ¹ For correct operation a 10nF supply de-coupling capacitor should be placed next to the device.

Mechanical:



| | Inches | mm |
|----------------|--------------|-------------|
| A | 0.787 ±0.005 | 20.00 ±0.13 |
| B | 0.487 ±0.005 | 12.37 ±0.13 |
| C | 0.225 ±0.011 | 5.72 ±0.28 |
| D ¹ | 0.250 | 6.35 |
| E ¹ | 0.020 | 0.51 |
| F ¹ | 0.031 | 0.79 |
| G ¹ | 0.094 | 2.37 |
| H ¹ | 0.300 | 7.62 |
| I ¹ | 0.600 | 15.24 |
| J ¹ | 0.094 | 2.37 |

Cover:
Kovar
Electroless Nickel Plated
1 µinch (25 µm) typical
Resistance welded to base

Base:
Kovar
Glass to metal sealed leads

Label:
Laser marked

Pin 7 Connected to case

¹ Nominal dimension

Not to scale

| Pin | Name | Function |
|-----|----------------------|-----------------------------------------------------------------------------|
| 1 | V _{CONTROL} | EFC, electronics frequency control. 1.5V is nominal input |
| 7 | Ground (case) | |
| 8 | Output | CMOS output |
| 14 | V _{CC} | Power supply. Be sure to bypass near the pin with 10nF low noise capacitor. |

Layout and application information

For Optimum Stability and Jitter Performance, Pletronics recommends:

- a ground plane under the device
- no large transient signals (both current and voltage) should be routed under the device
- do not layout near a large magnetic field such as a high frequency switching power supply
- do not place near piezoelectric buzzers or mechanical fans.
- minimize air flow across the device

PCB Mounting (typical for lead free processing)

Hand soldering is recommended.

Wave solder at 255°C to 280°C with maximum wave exposure of 15 seconds

Reflow solder maximum exposure of 245°C for 15 seconds

Soldering done in a nitrogen atmosphere enhances the solder joint quality.

IMPORTANT NOTICE

Pletronics Incorporated (PLE) reserves the right to make corrections, improvements, modifications and other changes to this product at anytime. PLE reserves the right to discontinue any product or service without notice. Customers are responsible for obtaining the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to PLE's terms and conditions of sale supplied at the time of order acknowledgment.

PLE warrants performance of this product to the specifications applicable at the time of sale in accordance with PLE's limited warranty. Testing and other quality control techniques are used to the extent PLE deems necessary to support this warranty. Except where mandated by specific contractual documents, testing of all parameters of each product is not necessarily performed.

PLE assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using PLE components. To minimize the risks associated with the customer products and applications, customers should provide adequate design and operating safeguards.

PLE products are not designed, intended, authorized or warranted to be suitable for use in life support applications, devices or systems or other critical applications that may involve potential risks of death, personal injury or severe property or environmental damage. Inclusion of PLE products in such applications is understood to be fully at the risk of the customer. Use of PLE products in such applications requires the written approval of an appropriate PLE officer. Questions concerning potential risk applications should be directed to PLE.

PLE does not warrant or represent that any license, either express or implied, is granted under any PLE patent right, copyright, artwork or other intellectual property right relating to any combination, machine or process which PLE product or services are used. Information published by PLE regarding third-party products or services does not constitute a license from PLE to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from PLE under the patents or other intellectual property of PLE.

Reproduction of information in PLE data sheets or web site is permissible only if the reproduction is without alteration and is accompanied by associated warranties, conditions, limitations and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. PLE is not responsible or liable for such altered documents.

Resale of PLE products or services with statements different from or beyond the parameters stated by PLE for that product or service voids all express and implied warranties for the associated PLE product or service and is an unfair or deceptive business practice. PLE is not responsible for any such statements.

Contacting Pletronics Inc.

Pletronics Inc.
19013 36th Ave. West
Lynnwood, WA 98036-5761 USA

Tel: 425-776-1880
Fax: 425-776-2760
E-mail: ple-sales@pletronics.com
URL: www.pletronics.com

Copyright © 2010, Pletronics Inc.



OeM4214-20.00M TCVCXO Oscillator

November 2010

Pletronics Purchasing

This requires a TEW 3.2x5 20.00MHz TCXO made with the 5032D crystal. No substitution is allowed!!!

This device will be programmed and tested at Pletronics.

Based on using the On Semi Voltage regulator similar to:

NCP551SN29T1G

NCP623MN-30R2G

Output buffer Fairchild NC7SZ04

FR4 PCB assembly inside



PLETRONICS INC. DOCUMENT CONTROL

This is the document control page. **This is not printed or part of the PDF that can be downloaded on the web site.** This is to keep the history of the datasheet document and all revisions.

Part Number Family: OeXO
Document File Name: oem4214-20.00m.wpd
PDF File Name: oem4214-20.00m.pdf
Written By: D. Kenny, D. Marston, B. Gubser

Revision History:

| | |
|-------------------|---------------------------------------------------------------------------------------------------------|
| August 31, 2010 | Initial Release |
| November 16, 2010 | Modified the hold over specification for both a wide and narrow range and defined loads to 10K 10pF Rag |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А