Round Water-resistant Connectors (M8)
XS3

Compact, Watertight, Round Connectors

- Water-resistive, compact connector meets IP67 requirements.
- Ideal for a wide variety of FA and OA applications.
- Using connectors for wiring ensures ease of equipment maintenance and reduces downtime required for equipment maintenance.

■ Ratings and Specifications

Rated current	3A
Rated voltage	125 VDC
Contact resistance	60 mΩ max. (20 mV max., 100 mA max.)
Insulation resistance	1,000 MΩ min. (at 500 VDC)
Dielectric strength	1,000 VAC for 1 min (leakage current: 1 mA max.)
Degree of protection	IP67 (IEC60529)
Insertion tolerance	200 times min.

■ Material

Contact / Surface	Copper Alloy / Nickel base, Au0.4 μm
Connector housing	PBT resin (UL94V-0)
Nut / Surface	Copper Alloy / Nickel plated
Cover	PBT resin (UL94V-0)

■ PVC Cable

Item	3 cores	4 cores
Color	Black	
Outer diameter	5 mm dia.	4.8 mm dia.
Conductor size	AWG22 0.34 mm^2 (43 × 0.1)	0.25 mm^2 (32 × 0.1)
Approvals	AWM	
Features	Flame retardant	
Temperature range	-25 to +70°C	

■ PVC Cable(For IP69K)

Item	Standard
Color	Dark Gray
Outer diameter	4 mm dia.
Conductor size	AWG24 0.2 mm^2 (18 × 0.12)
Approvals	- - -
Features	- - -
Temperature range	-25 to +70°C

■ PUR Cable

Item	3 cores	4 cores
Color	Black	
Outer diameter	4.3 mm dia.	4.7 mm dia.
Conductor size	AWG22 0.34 mm^2 (43 × 0.1)	
Approvals	AWM	
Features	Flame retardant Halogen free Oil resistance	
Temperature range	Cable fixed: -50 to +80°C / Cable moved: -25 to +80°C	

■ Socket Appearance

3 poles		4 poles	
Male	**Female**	**Male**	**Female**
			

Connectors with Cable Attached

■ XS3F - M8 Socket on One Cable End

XS3F-M8PVC□□□□M PVC Cable
XS3F-M8PUR□□□□M PUR Cable

Dimensions

(Unit: mm)

Straight



Angled



Wiring Diagram

3 Poles	4 Poles
	

Ordering Information

Connector	Size	Cable material	Poles	Type	Length (m)	Product description
Socket	M8	PVC	3	Angled	2	**XS3F-M8PVC3A2M**
					5	**XS3F-M8PVC3A5M**
					10	**XS3F-M8PVC3A10M**
				Straight	2	**XS3F-M8PVC3S2M**
					5	**XS3F-M8PVC3S5M**
					10	**XS3F-M8PVC3S10M**
			4	Angled	2	**XS3F-M8PVC4A2M**
					5	**XS3F-M8PVC4A5M**
					10	**XS3F-M8PVC4A10M**
				Straight	2	**XS3F-M8PVC4S2M**
					5	**XS3F-M8PVC4S5M**
					10	**XS3F-M8PVC4S10M**
		PUR	3	Angled	2	**XS3F-M8PUR3A2M**
					5	**XS3F-M8PUR3A5M**
					10	**XS3F-M8PUR3A10M**
				Straight	2	**XS3F-M8PUR3S2M**
					5	**XS3F-M8PUR3S5M**
					10	**XS3F-M8PUR3S10M**
			4	Angled	2	**XS3F-M8PUR4A2M**
					5	**XS3F-M8PUR4A5M**
					10	**XS3F-M8PUR4A10M**
				Straight	2	**XS3F-M8PUR4S2M**
					5	**XS3F-M8PUR4S5M**
					10	**XS3F-M8PUR4S10M**

Model Number Legend

Use this model number legend to identify products from their model number.
When ordering, use a model number from the table in *Ordering Information.*

XS3F - M8 □□□ □ □ □□M
1 2 3 4 5

1. Screw Type
M8: M8 size
2. Cable type
PVC: PVC cable
PUR: PUR cable
3. Number of Poles
3: 3 poles
4: 4 poles
4. Shape
A: Angled
S: Straight
5. Cable Length
2M: 2 m
5M: 5 m
10M: 10 m

■ XS3F - Sockets on One Cable End with IP69K rating

Dimensions

(Unit: mm)

Straight



Angled





Wiring Diagram

4 cores



Ordering Information

Connector	Size	Cable material	Cores	Shape	Length (m)	Product description
Socket	M8	PVC	4	Angled	2	**XS3F-E422-402-A**
					5	**XS3F-E422-405-A**
					10	**XS3F-E422-410-A**
				Straight	2	**XS3F-E421-402-A**
					5	**XS3F-E421-405-A**
					10	**XS3F-E421-410-A**

Model Number Legend

Use this model number legend to identify products from their model number.
When ordering, use a model number from the table in *Ordering Information.*

XS3F - E42□ - 4□□ - A
1 2 3 4 5 6 7

1. **Nut Material**
   E: Stainless
2. **Number of Poles**
   4: 4 cores
3. **Contact Plating**
   2: 0.4-μm gold plating
4. **Shape**
   1: Straight
   2: Angled
5. **Connections**
   4: Brown, White, Blue, Black
6. **Cable Length**
   02: 2 m
   05: 5 m
   10: 10 m
7. **Cable Specification**
   A: Standard Cable

■ XS3H - M8 Plugs on One Cable End

XS3H-M8PVC□□□□M PVC Cable
XS3H-M8PUR□□□□M PUR Cable

Dimensions

(Unit: mm)

Straight





Angled





Wiring Diagram

3 Poles	4 Poles
	

Ordering Information

Connector	Size	Cable material	Poles	Type	Length (m)	Product description
plug	M8	PVC	3	Angled	0.3	**XS3H-M8PVC3A03M**
					1	**XS3H-M8PVC3A1M**
				Straight	0.3	**XS3H-M8PVC3S03M**
					1	**XS3H-M8PVC3S1M**
			4	Angled	0.3	**XS3H-M8PVC4A03M**
					1	**XS3H-M8PVC4A1M**
				Straight	0.3	**XS3H-M8PVC4S03M**
					1	**XS3H-M8PVC4S1M**
		PUR	3	Angled	0.3	**XS3H-M8PUR3A03M**
					1	**XS3H-M8PUR3A1M**
				Straight	0.3	**XS3H-M8PUR3S03M**
					1	**XS3H-M8PUR3S1M**
			4	Angled	0.3	**XS3H-M8PUR4A03M**
					1	**XS3H-M8PUR4A1M**
				Straight	0.3	**XS3H-M8PUR4S03M**
					1	**XS3H-M8PUR4S1M**

Model Number Legend

Use this model number legend to identify products from their model number.
When ordering, use a model number from the table in *Ordering Information.*

XS3H - M8 □□□ □ □ □□M
1 2 3 4 5

1. Screw Type
M8: M8 size
2. Cable type
PVC: PVC cable
PUR: PUR cable
3. Number of Poles
3: 3 poles
4: 4 poles
4. Shape
A: Angled
S: Straight
5. Cable Length
03M: 0.3 m
1M: 1 m

■ XS3W - M8 Sockets and M8 Plugs on Cable Ends

XS3W-M8PVC□□□□□M PVC Cable
XS3W-M8PUR□□□□□M PUR Cable

Dimensions

(Unit: mm)

Straight/Straight



Straight/Angled



Angled/Angled



Angled/Straight



Wiring Diagram

3 Poles	4 Poles
	

Model Number Legend

Use this model number legend to identify products from their model number.
When ordering, use a model number from the table in *Ordering Information.*

XS3W - M8 □□□ □ □□ □□M
1 2 3 4 5

1. Screw Type
M8: M8 size
2. Cable type
PVC: PVC cable
PUR: PUR cable
3. Number of Poles
3: 3 poles
4: 4 poles
4. Shape
SS: Straight / Straight
AA: Angled / Angled
SA; Straight / Angled
AS: Angled / Straight
5. Cable Length
2M: 2 m
5M: 5 m
1M: 10 m

Ordering Information

Connector	Size	Cable material	Poles	Shape		Length (m)	Product description
				Plug	Socket		
Both	M8	PVC	3	Angled	Angled	2	**XS3W-M8PVC3AA2M**
						5	**XS3W-M8PVC3AA5M**
						10	**XS3W-M8PVC3AA10M**
				Straight	Straight	2	**XS3W-M8PVC3SS2M**
						5	**XS3W-M8PVC3SS5M**
						10	**XS3W-M8PVC3SS10M**
				Angled	Straight	2	**XS3W-M8PVC3AS2M**
						5	**XS3W-M8PVC3AS5M**
						10	**XS3W-M8PVC3AS10M**
				Straight	Angled	2	**XS3W-M8PVC3SA2M**
						5	**XS3W-M8PVC3SA5M**
						10	**XS3W-M8PVC3SA10M**
			4	Angled	Angled	2	**XS3W-M8PVC4AA2M**
						5	**XS3W-M8PVC4AA5M**
						10	**XS3W-M8PVC4AA10M**
				Straight	Straight	2	**XS3W-M8PVC4SS2M**
						5	**XS3W-M8PVC4SS5M**
						10	**XS3W-M8PVC4SS10M**
				Angled	Straight	2	**XS3W-M8PVC4AS2M**
						5	**XS3W-M8PVC4AS5M**
						10	**XS3W-M8PVC4AS10M**
				Straight	Angled	2	**XS3W-M8PVC4SA2M**
						5	**XS3W-M8PVC4SA5M**
						10	**XS3W-M8PVC4SA10M**
		PUR	3	Angled	Angled	2	**XS3W-M8PUR3AA2M**
						5	**XS3W-M8PUR3AA5M**
						10	**XS3W-M8PUR3AA10M**
				Straight	Straight	2	**XS3W-M8PUR3SS2M**
						5	**XS3W-M8PUR3SS5M**
						10	**XS3W-M8PUR3SS10M**
				Angled	Straight	2	**XS3W-M8PUR3AS2M**
						5	**XS3W-M8PUR3AS5M**
						10	**XS3W-M8PUR3AS10M**
				Straight	Angled	2	**XS3W-M8PUR3SA2M**
						5	**XS3W-M8PUR3SA5M**
						10	**XS3W-M8PUR3SA10M**
			4	Angled	Angled	2	**XS3W-M8PUR4AA2M**
						5	**XS3W-M8PUR4AA5M**
						10	**XS3W-M8PUR4AA10M**
				Straight	Straight	2	**XS3W-M8PUR4SS2M**
						5	**XS3W-M8PUR4SS5M**
						10	**XS3W-M8PUR4SS10M**
				Angled	Straight	2	**XS3W-M8PUR4AS2M**
						5	**XS3W-M8PUR4AS5M**
						10	**XS3W-M8PUR4AS10M**
				Straight	Angled	2	**XS3W-M8PUR4SA2M**
						5	**XS3W-M8PUR4SA5M**
						10	**XS3W-M8PUR4SA10M**

Y-Joint M8 Plug / M8 Socket Connectors

■ XS3R

XS3R-M426-1□□□-A With Standard Cable
XS3R-M426-□ Without Cable

Dimensions

(Unit: mm)

XS3R-M426-1□□1-A
Connectors on Both Cable Ends (Y-Joint Plug/Socket)



XS3R-M426-1□□0-A
Connector on One Cable End (Y-Joint/Socket)



XS3R-M426-□
Connector on Both Ends (Y-Joint Plug/Socket) without Cable



Wiring Diagram

XS3R-M426-1□□1-A



XS3R-M426-1□□0-A



XS3R-M426-1



XS3R-M426-5



Mating Connectors

Item	Model
XS3R(M8)	XS3F(M8)
	XS3H(M8)
	XS3W(M8)
	XS3P(M8)

Ordering Information

For M8 Connectors

Cable	Connector	Cable length L (m)	Model	Minimum order
With cable	Connectors on both cable ends	0.5	**XS3R-M426-1C51-A**	5
		1	**XS3R-M426-1011-A**	
		2	**XS3R-M426-1021-A**	
		3	**XS3R-M426-1031-A**	
	Connector on one cable end	2	**XS3R-M426-1020-A**	
		5	**XS3R-M426-1050-A**	
Without cable	Connectors on both cable ends	—	**XS3R-M426-1**	10
			XS3R-M426-5	

Panel-mount Connectors

■ XS3P - M8 Sockets

XS3P-M421-1 **M8 Screw-mount sockets with Through-hole PCB Pins (front or rear lock)**
XS3P-M421-2 **M8 Screw-mount sockets with Solder Cup Pins (front or rear lock)**
XS3P-M422-2 **M8 Screw-mount sockets with Solder Cup Pins (rear lock, slim model)**

Dimensions

(Unit: mm)

XS3P-M421-1 (Through-hole PCB Pins)



XS3P-M421-2 (Solder Cup Pins)



XS3P-M422-2 (Solder Cup Pins), Rear Lock Slim Models



Mounting Dimensions for XS3P Screw-on Models and Snap-in Models

(Unit: mm)

Panel Cutouts

XS3P-□421



XS3P-M422-2



Note: The panel thickness is 1 to 3 mm.

PCB-mounting Dimensions



Note: The panel thickness is 2.4 mm maximum.

Panel-mounting Configuration

Rear Lock



Front Lock



Ordering Information

Connection method	Panel mounting	Pin shape	Model	Minimum order
M8 screw-mounting	Front lock or rear lock	Through-hole PCB pins	**XS3P-M421-1**	50
		Solder cup pins	**XS3P-M421-2**	
	Rear lock	Solder cup pins	**XS3P-M422-2**	

Note: Orders are accepted in multiples of the minimum order.

Safety Precautions

In addition to the following information, also refer to the 'Precautions' section at the end of this datasheet

■ Correct Use - Panel Mounting

- When mounting XS3P Panel-mount Connectors to panels, refer to *Panel-mounting Configuration* and provide rubber bushings and nuts for the Connectors. Apply a tightening torque of between 0.4 and 0.6 N·m to mount the Connectors.

Connectors for Embedding in Sensors

■ XS3M - Plugs

XS3M-K421-1 **Embedded Plugs with Screw Threads and Through-hole PCB Pins**
XS3M-K421-2 **Embedded plugs with Screw Threads and Solder Cup Pins**

Dimensions

(Unit: mm)

XS3M-K421-1
Embedded Model with Through-hole PCB Pins



Mounting Dimensions



XS3M-K421-2
Embedded Model with Solder Cup Pins



Mounting Dimensions



Mating Connectors

Item	Model
XS3M	XS3F, XS3W

Ordering Information

Connection method	Pin shape	Model	Minimum order
Embedded model	Through-hole PCB pins	**XS3M-K421-1**	200
	Solder cup pins	**XS3M-K421-2**	

Note: Orders are accepted in multiples of the minimum order.

Accessories

Dust Covers

XS3Z-13



XS3Z-15



Model	Material	Suitable connector	
		Model	Mounting portion
XS3Z-13	Acrylic resin/transparent	XS3H/XS3M	M8 plug
XS3Z-15		XS3F	M8 socket

Note: The Dust Covers are for dust prevention and do not ensure IP67 sealability. When mounting a Dust Cover to a Connector, be sure to press the Dust Cover onto the Connector until the Connector is fully inserted into the Dust Cover.

Precautions

■ Correct Use

Do not use the product in atmospheres or environments that exceed product ratings.

Connections

- The XS3 and XS2 Sensor I/O Connectors cannot be connected to each other.
- When using Sensors with Connectors or Limit Switches, use the Sensor I/O Connectors specified in the catalog.

Connector Connection and Disconnection

- Before connecting or disconnecting Connectors, make sure that no power is being supplied to the Connectors.
- When connecting or disconnecting Connectors, be sure to hold the Connectors by hand. Do not disconnect the Connectors by pulling the cable.
- Do not touch the engagement side of any Connector with wet hands. If there is any water on the Connector or near the Connector, be sure to wipe off the water before connecting or disconnecting the Connector, otherwise the Connector may short-circuit internally or not ensure good insulation.
- Make sure that engagement side of any Connector is free of metal dust or power.
- Do not use pliers to tighten mounting the thread bracket, otherwise the thread bracket may be damaged. Be sure to tighten each thread bracket by hand within a torque of 0.2 N·m. If the thread bracket is not tightened securely, the Connector may not maintain its proper degree of protection or the thread bracket may fall off due to vibration.

Cable Wire Color

- The M8 Sensor I/O Connectors use the following lead wire colors.

Model		Pin No.			
		1	2	3	4
For DC	8-mm-dia. DC4	Brown	White	Blue	Black

Degree of Protection

- Do not impose external force continuously on the joints of pin blocks and covers, otherwise the Connectors may not keep its proper degree of protection (i.e., IP67).
- Connectors are not fully watertight. Do not use them underwater.
- The Connectors are not oil-resistant. Do not use them where they would be subject to oil.
- If Connectors are used in places with vibration or shock, secure the engaged side of each Connector, otherwise the Connectors may be disconnected or fail to maintain their proper degree of protection.
- Connectors are of resin mold construction. Do not impose excessive force on them.

Storage

Do not store Connectors for long periods of time in the following locations

- Locations subject to dust or high humidity
- Locations subject to ammonia gas or sulfide gas

Installation

- Do not make any cable bends near the base of the Unit.
- Any bends made must have a minimum radius of 36 mm.

OMRON

All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON

OMRON ELECTRONIC COMPONENTS LLC
55 E. Commerce Drive, Suite B
Schaumburg, IL 60173
847-882-2288

OMRON ON-LINE
Global - http://www.omron.com
USA - http://www.components.omron.com

Cat. No. X304-E-1b 08/12 Specifications subject to change without notice Printed in USA

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А