



Agency Approval

| Agency | Agency File Number |
|--------|--------------------|
| | L Package : E71639 |

Schematic Symbol



Main Features

| Symbol | Value | Unit |
|---------------------|------------|------|
| $I_{T(RMS)}$ | 4 to 15 | A |
| V_{DRM} / V_{RRM} | 400 to 600 | V |
| DIAC V_{BO} | 33 to 43 | V |

Description

The Quadrac is an internally triggered Triac designed for AC switching and phase control applications. It is a Triac and DIAC in a single package, which saves user expense by eliminating the need for separate Triac and DIAC components.

Standard type devices normally operate in Quadrants I & III triggered from AC line.

Alternistor type Quadracs are used in circuits requiring high dv/dt capability.

Features & Benefits

- RoHS Compliant
- Glass – passivated junctions
- Voltage capability up to 600 V
- Surge capability up to 200 A

Applications

Excellent for AC switching and phase control applications such as lighting and heating. Typical applications are AC solid-state switches, light dimmers, power tools, home/ brown goods and white goods appliances.

Alternistor Quadracs (no snubber required) are used in applications with extremely inductive loads requiring highest commutation performance.

Internally constructed isolated package is offered for ease of heat sinking with highest isolation voltage.

Absolute Maximum Ratings

| Symbol | Parameter | Value | | | | | Unit | |
|--------------|---|---|--------------------|--------------------|--------------------|--------------------|------------------------|---|
| | | Qxx04LT | Qxx06LT / Qxx06LTH | Qxx08LT / Qxx08LTH | Qxx10LT / Qxx10LTH | Qxx15LT / Qxx15LTH | | |
| $I_{T(RMS)}$ | RMS forward current | Qxx04LT: $T_C = 95^\circ\text{C}$ Qxx06LT/Qxx08LT/Qxx10LT: $T_C = 90^\circ\text{C}$ Qxx15LT: $T_C = 80^\circ\text{C}$ | | | | | A | |
| I_{TSM} | Peak non-repetitive surge current | single half cycle; $f = 50\text{Hz}$; T_J (initial) = 25°C | 46 | 65 | 83 | 100 | 167 | A |
| | | single half cycle; $f = 60\text{Hz}$; T_J (initial) = 25°C | 55 | 80 | 100 | 120 | 200 | |
| I^2t | I^2t value for fusing | $t_p = 8.3\text{ms}$ | | | | | A^2s | |
| di/dt | Critical rate-of-rise of on-state current | $f = 60\text{Hz}$; $T_J = 125^\circ\text{C}$ | | | | | $\text{A}/\mu\text{s}$ | |
| I_{GM} | Peak gate current | $T_J = 125^\circ\text{C}$ | | | | | A | |
| T_{stg} | Storage temperature range | -40 to 150 | | | | | $^\circ\text{C}$ | |
| T_J | Operating junction temperature range | -40 to 125 | | | | | $^\circ\text{C}$ | |

Note: xx = voltage

Electrical Characteristics ($T_J = 25^\circ\text{C}$, unless otherwise specified) – Standard Quadrac

| Symbol | Test Conditions | | Value | | | | | Unit | |
|------------|---|------|---------|---------|---------|---------|---------------|------------------------|------------------------|
| | | | Qxx04LT | Qxx06LT | Qxx08LT | Qxx10LT | Qxx15LT | | |
| I_H | $I_T = 200\text{mA}$ (initial) | MAX. | 40 | 50 | 60 | 60 | 70 | mA | |
| dv/dt | $V_D = V_{DRM}$; gate open; $T_J = 100^\circ\text{C}$ | MIN. | 400V | 75 | 150 | 175 | 200 | 300 | $\text{V}/\mu\text{s}$ |
| | | MIN. | 600V | 50 | 125 | 150 | 175 | 200 | |
| dv/dt | $V_D = V_{DRM}$; gate open; $T_J = 125^\circ\text{C}$ | MIN. | 400V | 50 | 100 | 120 | 150 | 200 | $\text{V}/\mu\text{s}$ |
| | | MIN. | 600V | 50 | 85 | 100 | 120 | 150 | |
| $dv/dt(c)$ | $di/dt(c) = 0.54 \times I_{T(RMS)} / \text{ms}$; $T_J = 125^\circ\text{C}$ | MIN. | 3 | 4 | | | | $\text{V}/\mu\text{s}$ | |
| t_{gt} | (note 1) | TYP. | 3 | | | | μs | | |

(1) Reference test circuit in figure 10 and waveform in figure 11; $C_T = 0.1\mu\text{F}$ with $0.1\mu\text{s}$ rise time.

Note: xx = voltage

Electrical Characteristics ($T_J = 25^\circ\text{C}$, unless otherwise specified) – Alternistor Quadrac

| Symbol | Test Conditions | | Value | | | | Unit | |
|------------|---|------|----------|----------|----------|----------|------------------------|------------------------|
| | | | Qxx06LTH | Qxx08LTH | Qxx10LTH | Qxx15LTH | | |
| I_H | $I_T = 20\text{mA}$ (initial) | MAX. | 50 | 50 | 60 | 70 | mA | |
| dv/dt | $V_D = V_{DRM}$; gate open; $T_J = 100^\circ\text{C}$ | MIN. | 400V | 575 | | 925 | | $\text{V}/\mu\text{s}$ |
| | | MIN. | 600V | 425 | | 775 | | |
| dv/dt | $V_D = V_{DRM}$; gate open; $T_J = 125^\circ\text{C}$ | MIN. | 400V | 450 | | 700 | | $\text{V}/\mu\text{s}$ |
| | | MIN. | 600V | 350 | | 600 | | |
| $dv/dt(c)$ | $di/dt(c) = 0.54 \times I_{T(RMS)} / \text{ms}$; $T_J = 125^\circ\text{C}$ | MIN. | 25 | | 30 | | $\text{V}/\mu\text{s}$ | |
| t_{gt} | (note 1) | TYP. | 3 | | | | μs | |

(1) Reference test circuit in figure 10 and waveform in figure 11; $C_T = 0.1\mu\text{F}$ with $0.1\mu\text{s}$ rise time.

Note: xx = voltage

Trigger DIAC Specifications

| Symbol | Test Conditions | | Value | Unit |
|--------------------|---|------|-------|---------|
| ΔV_{BO} | Breakover Voltage Symmetry | MAX. | 3 | V |
| V_{BO} | Breakover Voltage, forward and reverse | MIN. | 33 | V |
| | | MAX. | 43 | |
| $[\Delta V_{\pm}]$ | Dynamic Breakback Voltage, forward and reverse (note 1) | MIN. | 5 | V |
| I_{BO} | Peak Breakover Current | MAX. | 25 | μA |
| C_T | Trigger Firing Capacitance | MAX. | 0.1 | μF |

(1) Reference test circuit in figure 10 and waveform in figure 11.

Static Characteristics

| Symbol | Test Conditions | | Value | Unit | |
|---------------------|--|---------------------|-------|------|---------|
| V_{TM} | $I_T = 1.41 \times I_{T(rms)}$ A; $t_p = 380\mu s$ | MAX. | 1.6 | V | |
| I_{DRM} / I_{RRM} | V_{DRM} / V_{RRM} | $T_J = 25^\circ C$ | MAX. | 10 | μA |
| | | $T_J = 100^\circ C$ | | 500 | |
| | | $T_J = 125^\circ C$ | | 2000 | |

Thermal Resistances

| Symbol | Parameter | | Value | Unit |
|-------------------|-----------------------|--------------------|-------|--------------|
| $R_{\theta(J-C)}$ | Junction to case (AC) | Qxx04LT | 3.6 | $^\circ C/W$ |
| | | Qxx06LT / Qxx06LTH | 3.3 | |
| | | Qxx08LT / Qxx08LTH | 2.8 | |
| | | Qxx10LT / Qxx10LTH | 2.6 | |
| | | Qxx15LT / Qxx15LTH | 2.1 | |
| $R_{\theta(J-A)}$ | Junction to ambient | | 50 | $^\circ C/W$ |

Note : xx = voltage

Figure 1: Normalized DC Holding Current vs. Junction Temperature



Figure 2: On-State Current vs. On-State Voltage (Typical) (4A)



Figure 3: On-State Current vs. On-State Voltage (Typical) (6A to 15A)




Figure 4: Power Dissipation vs. RMS On-State Current (Typical) (4A)




Figure 5: Power Dissipation vs. RMS On-State Current (Typical) (6A to 15A)




Figure 6: Maximum Allowable Case Temperature vs. RMS On-State Current





Figure 7: Surge Peak On-State Current vs. Number of Cycles



Note: xx = voltage


Figure 8: DIAC V_{BO} Change vs. Junction Temperature



Figure 9: Test Circuit



Figure 10: Test Circuit Waveform



Soldering Parameters

| | | |
|--|------------------------------------|------------------------|
| Reflow Condition | | Pb – Free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (min to max) (t_s) | 60 – 180 secs |
| Average ramp up rate (Liquidus Temp (T_L) to peak) | | 5°C/second max |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 5°C/second max |
| Reflow | - Temperature (T_L) (Liquidus) | 217°C |
| | - Temperature (t_L) | 60 – 150 seconds |
| Peak Temperature (T_p) | | 260°C ^{+0/-5} |
| Time within 5°C of actual peak Temperature (t_p) | | 20 – 40 seconds |
| Ramp-down Rate | | 5°C/second max |
| Time 25°C to peak Temperature (T_p) | | 8 minutes Max. |
| Do not exceed | | 280°C |



Physical Specifications

| | |
|------------------------|---|
| Terminal Finish | 1005 Matte Tin-plated |
| Body Material | UL Recognized epoxy meeting flammability classification 94v-0 |
| Lead Material | Copper Alloy |


Design Considerations

Careful selection of the correct device for the application's operating parameters and environment will go a long way toward extending the operating life of the Thyristor. Good design practice should limit the maximum continuous current through the main terminals to 75% of the device rating. Other ways to ensure long life for a power discrete semiconductor are proper heat sinking and selection of voltage ratings for worst case conditions. Overheating, overvoltage (including dv/dt), and surge currents are the main killers of semiconductors. Correct mounting, soldering, and forming of the leads also help protect against component damage.

Environmental Specifications

| Test | Specifications and Conditions |
|--|--|
| High Temperature Voltage Blocking | MIL-STD-750: Method 1040, Condition A Rated V_{DRM} (VAC-peak), 125°C, 1008 hours |
| Temperature Cycling | MIL-STD-750: Method 1051 -40°C to 150°C, 15-minute dwell, 100 cycles |
| Biased Temperature & Humidity | EIA/JEDEC: JESD22-A101 320VDC, 85°C, 85%RH, 1008 hours |
| High Temp Storage | MIL-STD-750: Method 1031 150°C, 1008 hours |
| Low-Temp Storage | -40°C, 1008 hours |
| Thermal Shock | MIL-STD-750: Method 1056 0°C to 100°C, 5-minute dwell, 10-second transfer, 10 cycles |
| Autoclave (Pressure Cooker Test) | EIA/JEDEC: JESD22-A102 121°C, 100%RH, 2atm, 168 hours |
| Resistance to Solder Heat | MIL-STD-750: Method 2031 260°C, 10 seconds |
| Solderability | ANSI/J-STD-002, Category 3, Test A |
| Lead Bend | MIL-STD-750: Method 2036, Condition E |

Dimensions — TO-220AB (L-Package) — Isolated Mounting Tab



Note: Maximum torque to be applied to mounting tab is 8 in-lbs. (0.904 Nm).

| Dimension | Inches | | Millimeters | |
|-----------|--------|-------|-------------|-------|
| | Min | Max | Min | Max |
| A | 0.380 | 0.420 | 9.65 | 10.67 |
| B | 0.105 | 0.115 | 2.67 | 2.92 |
| C | 0.230 | 0.250 | 5.84 | 6.35 |
| D | 0.590 | 0.620 | 14.99 | 15.75 |
| E | 0.142 | 0.147 | 3.61 | 3.73 |
| F | 0.110 | 0.130 | 2.79 | 3.30 |
| G | 0.540 | 0.575 | 13.72 | 14.61 |
| H | 0.025 | 0.035 | 0.64 | 0.89 |
| J | 0.195 | 0.205 | 4.95 | 5.21 |
| K | 0.095 | 0.105 | 2.41 | 2.67 |
| L | 0.060 | 0.075 | 1.52 | 1.91 |
| M | 0.085 | 0.095 | 2.16 | 2.41 |
| N | 0.018 | 0.024 | 0.46 | 0.61 |
| O | 0.178 | 0.188 | 4.52 | 4.78 |
| P | 0.045 | 0.060 | 1.14 | 1.52 |
| R | 0.038 | 0.048 | 0.97 | 1.22 |

Product Selector

| Part Number | Voltage | | | | Type | Package |
|-------------|---------|------|------|-------|---------------------|---------|
| | 400V | 600V | 800V | 1000V | | |
| Qxx04LT | X | X | | | Quadrac | TO-220L |
| Qxx06LT | X | X | | | Quadrac | TO-220L |
| Qxx06LTH | X | X | | | Alternistor Quadrac | TO-220L |
| Qxx08LT | X | X | | | Quadrac | TO-220L |
| Qxx08LTH | X | X | | | Alternistor Quadrac | TO-220L |
| Qxx10LT | X | X | | | Quadrac | TO-220L |
| Qxx10LTH | X | X | | | Alternistor Quadrac | TO-220L |
| Qxx15LT | X | X | | | Quadrac | TO-220L |
| Qxx15LTH | X | X | | | Alternistor Quadrac | TO-220L |

Note: xx = Voltage

Packing Options

| Part Number | Marking | Weight | Packing Mode | Base Quantity |
|-------------|----------|--------|--------------|-------------------|
| Qxx04LT | Qxx04LT | 2.2 g | Bulk | 500 |
| Qxx04LTTP | Qxx04LT | 2.2 g | Tube | 500 (50 per tube) |
| Qxx06LT | Qxx06LT | 2.2 g | Bulk | 500 |
| Qxx06LTTP | Qxx06LT | 2.2 g | Tube | 500 (50 per tube) |
| Qxx06LTH | Qxx06LTH | 2.2 g | Bulk | 500 |
| Qxx06LTHTP | Qxx06LTH | 2.2 g | Tube | 500 (50 per tube) |
| Qxx08LT | Qxx08LT | 2.2 g | Bulk | 500 |
| Qxx08LTTP | Qxx08LT | 2.2 g | Tube | 500 (50 per tube) |
| Qxx08LTH | Qxx08LTH | 2.2 g | Bulk | 500 |
| Qxx08LTHTP | Qxx08LTH | 2.2 g | Tube | 500 (50 per tube) |
| Qxx10LT | Qxx10LT | 2.2 g | Bulk | 500 |
| Qxx10LTTP | Qxx10LT | 2.2 g | Tube | 500 (50 per tube) |
| Qxx10LTH | Qxx10LTH | 2.2 g | Bulk | 500 |
| Qxx10LTHTP | Qxx10LTH | 2.2 g | Tube | 500 (50 per tube) |
| Qxx15LT | Qxx15LT | 2.2 g | Bulk | 500 |
| Qxx15LTTP | Qxx15LT | 2.2 g | Tube | 500 (50 per tube) |
| Qxx15LTH | Qxx15LTH | 2.2 g | Bulk | 500 |
| Qxx15LTHTP | Qxx15LTH | 2.2 g | Tube | 500 (50 per tube) |

Note: xx = Voltage

Part Numbering System



Part Marking System

TO-220 AB – (L Package)



Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А