



**Is Now Part of**



**ON Semiconductor®**

**To learn more about ON Semiconductor, please visit our website at**  
**[www.onsemi.com](http://www.onsemi.com)**


Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at [www.onsemi.com](http://www.onsemi.com). Please email any questions regarding the system integration to [Fairchild\\_questions@onsemi.com](mailto:Fairchild_questions@onsemi.com).

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## BD434/436/438

### Medium Power Linear and Switching Applications

- Complement to BD433, BD435 and BD437 respectively



### PNP Epitaxial Silicon Transistor

#### Absolute Maximum Ratings $T_C=25^\circ\text{C}$ unless otherwise noted

| Symbol    | Parameter                                        | Value      | Units            |
|-----------|--------------------------------------------------|------------|------------------|
| $V_{CBO}$ | Collector-Base Voltage                           |            |                  |
|           | : BD434                                          | - 22       | V                |
|           | : BD436                                          | - 32       | V                |
|           | : BD438                                          | - 45       | V                |
| $V_{CES}$ | Collector-Emitter Voltage                        |            |                  |
|           | : BD434                                          | - 22       | V                |
|           | : BD436                                          | - 32       | V                |
|           | : BD438                                          | - 45       | V                |
| $V_{CEO}$ | Collector-Emitter Voltage                        |            |                  |
|           | : BD434                                          | - 22       | V                |
|           | : BD436                                          | - 32       | V                |
|           | : BD438                                          | - 45       | V                |
| $V_{EBO}$ | Emitter-Base Voltage                             | - 5        | V                |
| $I_C$     | Collector Current (DC)                           | - 4        | A                |
| $I_{CP}$  | *Collector Current (Pulse)                       | - 7        | A                |
| $I_B$     | Base Current                                     | - 1        | A                |
| $P_C$     | Collector Dissipation ( $T_C=25^\circ\text{C}$ ) | 36         | W                |
| $T_J$     | Junction Temperature                             | 150        | $^\circ\text{C}$ |
| $T_{STG}$ | Storage Temperature                              | - 65 ~ 150 | $^\circ\text{C}$ |

**Electrical Characteristics**  $T_C=25^{\circ}\text{C}$  unless otherwise noted

| Symbol         | Parameter                                                                             | Test Condition                                                                                                                     | Min.                       | Typ.                    | Max.                    | Units                                           |
|----------------|---------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|-------------------------|-------------------------|-------------------------------------------------|
| $V_{CEO(sus)}$ | Collector-Emitter Sustaining Voltage<br>: BD434<br>: BD436<br>: BD438                 | $I_C = -100\text{mA}, I_B = 0$                                                                                                     | - 22<br>- 32<br>- 45       |                         |                         | V<br>V<br>V                                     |
| $I_{CBO}$      | Collector Cut-off Current<br>: BD434<br>: BD436<br>: BD438                            | $V_{CB} = -22\text{V}, I_E = 0$<br>$V_{CB} = -32\text{V}, I_E = 0$<br>$V_{CB} = -45\text{V}, I_E = 0$                              |                            |                         | - 100<br>- 100<br>- 100 | $\mu\text{A}$<br>$\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{CEO}$      | Collector Cut-off Current<br>: BD434<br>: BD436<br>: BD438                            | $V_{CE} = -22\text{V}, V_{BE} = 0$<br>$V_{CE} = -32\text{V}, V_{BE} = 0$<br>$V_{CE} = -45\text{V}, V_{BE} = 0$                     |                            |                         | - 100<br>- 100<br>- 100 | $\mu\text{A}$<br>$\mu\text{A}$<br>$\mu\text{A}$ |
| $I_{EBO}$      | Emitter Cut-off Current                                                               | $V_{EB} = -5\text{V}, I_C = 0$                                                                                                     |                            |                         | - 1                     | mA                                              |
| $h_{FE}$       | * DC Current Gain<br>: BD434/436<br>: BD438<br>: ALL DEVICE<br>: BD434/436<br>: BD438 | $V_{CE} = -5\text{V}, I_C = -10\text{mA}$<br>$V_{CE} = -1\text{V}, I_C = -500\text{mA}$<br>$V_{CE} = -1\text{V}, I_C = -2\text{A}$ | 40<br>30<br>85<br>50<br>40 | 140<br>140<br>140       |                         |                                                 |
| $V_{CE(sat)}$  | * Collector-Emitter Saturation Voltage<br>: BD434<br>: BD436<br>: BD438               | $I_C = -2\text{A}, I_B = -0.2\text{A}$                                                                                             |                            | - 0.2<br>- 0.2<br>- 0.2 | - 0.5<br>- 0.5<br>- 0.6 | V<br>V<br>V                                     |
| $V_{BE(on)}$   | * Base-Emitter ON Voltage<br>: BD434<br>: BD436<br>: BD438                            | $V_{CE} = -1\text{V}, I_C = -2\text{A}$                                                                                            |                            |                         | - 1.1<br>- 1.1<br>- 1.2 | V<br>V<br>V                                     |
| $f_T$          | Current Gain Bandwidth Product                                                        | $V_{CE} = -1\text{V}, I_C = -250\text{mA}$                                                                                         | 3                          |                         |                         | MHz                                             |

\* Pulse Test: PW=300 $\mu\text{s}$ , duty Cycle=1.5% Pulsed

## Typical Characteristics




Figure 1. DC current Gain




Figure 2. Collector-Emitter Saturation Voltage




Figure 3. Base-Emitter On Voltage




Figure 4. Collector-Base Capacitance




Figure 5. Safe Operating Area




Figure 6. Power Derating

## BD434/436/438

Technical drawing of a mechanical part, showing front, side, and top views with dimensions.

**Front View (Left):**

- Top flange width:  $8.00 \pm 0.30$
- Top flange height:  $3.90 \pm 0.10$
- Central hole diameter:  $\varnothing 3.20 \pm 0.10$
- Overall height:  $14.20 \text{ MAX}$
- Bottom section height:  $13.06 \pm 0.30$
- Bottom section width segments:  $0.75 \pm 0.10$ ,  $1.60 \pm 0.10$ ,  $0.75 \pm 0.10$
- Bottom section width:  $2.28 \text{ TYP}$  [ $2.28 \pm 0.20$ ]
- Feature #1 points to the central hole.

**Side View (Right):**

- Top flange width:  $3.25 \pm 0.20$
- Top flange height:  $11.00 \pm 0.20$
- Internal width segments:  $(1.00)$ ,  $(0.50)$
- Internal width:  $1.75 \pm 0.20$
- Overall height:  $16.10 \pm 0.20$
- Bottom section width:  $0.50^{+0.10}_{-0.05}$

**Top View (Bottom):**

- Shows three rectangular features on a base.

©2001 Fairchild Semiconductor Corporation

Rev. A1, June 2001

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                      |                     |                              |                       |
|----------------------|---------------------|------------------------------|-----------------------|
| ACE <sup>x</sup> ™   | FAST <sup>®</sup>   | OPTOPLANAR™                  | SuperSOT™-3           |
| Bottomless™          | FASTr™              | PACMAN™                      | SuperSOT™-6           |
| CoolFET™             | FRFET™              | POP™                         | SuperSOT™-8           |
| CROSSVOLT™           | GlobalOptoisolator™ | PowerTrench <sup>®</sup>     | SyncFET™              |
| DenseTrench™         | GTO™                | QFET™                        | TinyLogic™            |
| DOME™                | HiSeC™              | QS™                          | UHC™                  |
| EcoSPARK™            | ISOPLANAR™          | QT Optoelectronics™          | UltraFET <sup>®</sup> |
| E <sup>2</sup> CMOS™ | LittleFET™          | Quiet Series™                | VCX™                  |
| EnSigna™             | MicroFET™           | SLIENT SWITCHER <sup>®</sup> |                       |
| FACT™                | MICROWIRE™          | SMART START™                 |                       |
| FACT Quiet Series™   | OPTOLOGIC™          | Stealth™                     |                       |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                                            |
|--------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                                    |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.                                                       |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.                                                   |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[BD436S](#) [BD436STU](#)

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели,  
кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А