


RV5MJKUXX-S1 Modular Connectors - REVConnect Jack CAT5E UTP



For more Information
please call

1-800-Belden1



General Description:

REVConnect CAT5E UTP Modular Jack, T568 A/B, Single Pack

Usage (Overall)

| | |
|-------------------------------|---|
| Suitable Applications: | 1200 System, TIA Category 5E, ISO Class D, 1GBASE-T |
| Related Parts: | Compatible with KeyConnect Faceplates, Adapters, Boxes and Patch Panels |

Physical Characteristics (Connectivity)

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 0.940 | 0.640 | 1.337 |

Materials

Materials:

| Description | Type | Material |
|------------------|------------|--|
| Front Connection | RJ45 | Copper Clad Flexible PCB, 50uin Gold plated contacts over Nickel |
| Rear Connection | REVConnect | Copper alloy, Gold plated contacts over Nickel |
| Connector Body | N/A | PBT glass reinforced UL94V-0 |

Color

Color: Almond, Black, Blue, Blue (TIA 606), Brown, Brown (TIA 606), Elec. White, Gray, Green, Green (TIA 606), Ivory, Orange, Orange (TIA 606), Purple, Purple (TIA 606), Red, Red (TIA 606), Yellow, Yellow (TIA 606)

Wiring Scheme

Wiring Scheme: T568A/B

Weight

Weight: 0.016 lbs.

Packaging

Packaging: Individually packaged in a plastic bag.

Mechanical Characteristics (Connectivity)

Footprint/Type: KeyConnect

Plug / Jack Compatibility: RJ45, RJ11

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|------------------|--------------|
| Front | Mated Connection | 750 cycles |
| Rear | Mated Connection | 20 cycles |

Cable/Connector Retention: 15 lbs.

Connector/Hardware Retention: 20 lbs.

Plug/Connector Retention: 11.250 lbs.

Storage Temperature Range: -40°C To +70°C

RV5MJKUXX-S1 Modular Connectors - REVConnect Jack CAT5E UTP

| | |
|---------------------------------|---|
| Installation Temperature Range: | -10°C To +60°C |
| Operating Temperature Range: | -10°C To +60°C |
| Tool Compatibility: | REVConnect Termination Tool (p/n RVUTT01) |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|--|
| UL Rating: | UL94V-0 |
| IEEE Specification: | Power Over Ethernet (PoE) IEEE 802.3at type 1 and 2 (up to 30W), IEEE802.3bt/D1.7 type 3 and 4 (up to 100W), CISCO UPOE (up to 60W), Power over HDBaseTTM (up to 100W) |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2006 |
| MII Order #39 (China RoHS): | EUP 50 |
| Telecommunications Standards: | Category 5e - TIA 568.C.2, Category 5 - ISO/IEC 11801:2002 Ed.2 |
| Safety Listing: | c(UL)us Listed |
| Other Specification: | UL1863, IEC 60603-7, FCC part 68-F |

Flame Test

| | |
|----------------|----------------------------|
| UL Flame Test: | UL2043 Air Handling Spaces |
|----------------|----------------------------|

Suitability

| | |
|-----------------------|--------------|
| Suitability - Indoor: | Yes - Indoor |
|-----------------------|--------------|

Transmission Characteristics (Connectivity)

Mated Connection Table 1:

| Frequency (MHz) | Max. Insertion Loss TIA* (dB) | Max. Insertion Loss Belden** (dB) | Min. NEXT TIA* (dB) | Min. NEXT Belden** (dB) | Min. FEXT TIA* (dB) | Min. FEXT Belden** (dB) |
|-----------------|-------------------------------|-----------------------------------|---------------------|-------------------------|---------------------|-------------------------|
| 1.000 | 0.100 | 0.100 | 65.000 | 77.000 | 65.000 | 77.000 |
| 4.000 | 0.100 | 0.100 | 65.000 | 73.800 | 63.100 | 74.800 |
| 8.000 | 0.100 | 0.100 | 64.900 | 67.700 | 57.000 | 68.700 |
| 10.000 | 0.100 | 0.100 | 63.000 | 65.800 | 55.100 | 66.800 |
| 16.000 | 0.100 | 0.100 | 58.900 | 61.700 | 51.000 | 62.700 |
| 20.000 | 0.100 | 0.100 | 57.000 | 59.800 | 49.100 | 60.800 |
| 25.000 | 0.100 | 0.100 | 55.000 | 57.800 | 47.100 | 58.800 |
| 31.250 | 0.110 | 0.100 | 53.100 | 55.900 | 45.200 | 56.900 |
| 62.500 | 0.160 | 0.120 | 47.100 | 49.900 | 39.200 | 50.900 |
| 100.000 | 0.200 | 0.160 | 43.000 | 45.800 | 35.100 | 46.800 |
| 160.000 | | 0.210 | | 41.700 | | 42.700 |

Mated Connection Table - Footnote:

* TIA/EIA-568-C.2 Category 5E Standard.
 ** Worst-case performance for a CAT5E mated connection using CAT5E modular plugs.

Mated Connection Table 2:

| Frequency (MHz) | Min. Return Loss TIA* (dB) | Min. Return Loss Belden** (dB) | Min. Balanced TCL Belden** (dB) |
|-----------------|----------------------------|--------------------------------|---------------------------------|
| 1.000 | 30.000 | 32.000 | 42.000 |
| 4.000 | 30.000 | 32.000 | 42.000 |
| 8.000 | 30.000 | 32.000 | 42.000 |
| 10.000 | 30.000 | 32.000 | 42.000 |
| 16.000 | 30.000 | 32.000 | 42.000 |
| 20.000 | 30.000 | 32.000 | 42.000 |
| 25.000 | 30.000 | 32.000 | 42.000 |
| 31.250 | 30.000 | 32.000 | 42.000 |
| 62.500 | 24.000 | 31.100 | 36.100 |
| 100.000 | 20.000 | 27.000 | 32.000 |
| 160.000 | | 22.900 | 27.900 |

| | |
|--------------------------|--|
| Dielectric Strength: | 1,000 V RMS @ 60 Hz for 1 minute (Signals to Ground) |
| Current Rating: | 1.300 A |
| Insulation Resistance: | 500 M-Ohm Minimum |
| Max. Contact Resistance: | 20 m-Ohm |
| Termination Resistance: | 2.5 m-Ohm |

Notes (Overall)

Notes: Please see Installation Guide PX106434.

RV5MJKUXX-S1 Modular Connectors - REVConnect Jack CAT5E UTP

Product Family

Part Number List:

| Item Number | Color |
|--------------|--------------|
| RV5MJKUGY-S1 | Gray |
| RV5MJKUAL-S1 | Almond |
| RV5MJKUEW-S1 | Elec. White |
| RV5MJKUBK-S1 | Black |
| RV5MJKUIV-S1 | Ivory |
| RV5MJKUBR-S1 | Brown |
| RV5MJKURD-S1 | Red |
| RV5MJKUOR-S1 | Orange |
| RV5MJKUYL-S1 | Yellow |
| RV5MJKUGN-S1 | Green |
| RV5MJKUBL-S1 | Blue |
| RV5MJKUPR-S1 | Purple |
| RV5MJKUTN-S1 | Brown (TIA) |
| RV5MJKUTR-S1 | Red (TIA) |
| RV5MJKUTO-S1 | Orange (TIA) |
| RV5MJKUTY-S1 | Yellow (TIA) |
| RV5MJKUTG-S1 | Green (TIA) |
| RV5MJKUTB-S1 | Blue (TIA) |
| RV5MJKUTP-S1 | Purple (TIA) |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0 Revision Date: 04-19-2017

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А