

SPC, Encapsulated Double Metallized, Size 2824 – 6560, 100 – 630 VDC

Overview

Film capacitor for surface mounting with a double-sided metallized film as the electrode and a plain PPS as the dielectric. A rugged-box encapsulation in a self-extinguishing material meets the requirements of UL 94 V-0. SPC capacitors meet the standards according to IEC 60384-20.

Applications

The SPC Series is designed for high frequency coupling and decoupling as well as general high speed applications requiring high dV/dt such as pulse operation in switched-mode power supply (SMPS). Not suitable for across-the-line application (see suppressor capacitors).

Benefits

- Rated voltage: 100 – 630 VDC
- Rated voltage: 63 – 350 VAC
- Capacitance range: 0.00047 – 0.68 μ F
- EIA Size: 2824 – 6560
- Capacitance tolerance: \pm 2%, \pm 2.5%, \pm 5%, \pm 10%
- Climatic category: 55/125/56
- RoHS Compliant and lead-free terminations
- Operating temperature range of -55°C to $+125^{\circ}\text{C}$



Customer Part Number

| SPC | 7.3 | 471 | K | 100 | K33 | TR12 |
|-----------------------|-----------------------------|--|---|--------------------------|---------------------|----------------------------|
| Series | Chip Length (mm) | Capacitance Code (μ F) | Capacitance Tolerance | Rated Voltage (VDC) | Size Code | Packaging |
| Double Metallized PPS | 7.3 10.2 12.7 16.5 | First two digits represent significant figures. The third digit specifies number of zeros. | G = \pm 2% H = \pm 2.5% J = \pm 5% K = \pm 10% | 100 250 400 630 | See Dimension Table | See Ordering Options Table |

KEMET Internal Part Number

| F | 127 | S | L | 471 | K | 100 | V |
|-----------------|-----------------------|--|---------------------|--|---|--------------------------|----------------------------|
| Capacitor Class | Series | Chip Size | Size Code | Capacitance Code (μ F) | Capacitance Tolerance | Rated Voltage (VDC) | Packaging |
| F = Film | Double Metallized PPS | S = 2824 W = 4036 Y = 5045 Z = 6560 | See Dimension Table | First two digits represent significant figures. The third digit specifies number of zeros. | G = \pm 2% R = \pm 2.5% J = \pm 5% K = \pm 10% | 100 250 400 630 | See Ordering Options Table |

Ordering Options Table

| Chip Size (EIA) | Packaging Type | KEMET Packaging Code | Legacy Packaging Code |
|-----------------|--|----------------------|-----------------------|
| 2824 | Standard Packaging Options | | |
| | Tape & Reel (Standard Reel) | V | TR12 |
| | Bulk (Bag) | A | BULK |
| 4036 | Standard Packaging Options | | |
| | Tape & Reel (Horizontal Orientation Standard Reel) | V | TR16 |
| | Bulk (Bag) | A | BULK |
| | Other Packaging Options | | |
| | Tape & Reel (Vertical Orientation Standard Reel) | Y | TV24 |
| 5045 | Standard Packaging Options | | |
| | Tape & Reel (Standard Reel) | V | TR24 |
| | Bulk (Bag) | A | BULK |
| | Other Packaging Options | | |
| | Tape & Reel (Vertical Orientation Standard Reel) | Y | TV24 |
| 6560 | Standard Packaging Options | | |
| | Tape & Reel (Standard Reel) | V | TR24 |
| | Bulk (Bag) | A | BULK |
| | Other Packaging Options | | |
| | Tape & Reel (Vertical Orientation Standard Reel) | Y | TV44 |

Dimensions – Millimeters



| KEMET Size Code | Legacy Size Code | Chip Size (EIA) | B | | H | | L | | F | |
|--------------------|---------------------|--------------------|---------|-----------|---------|-----------|---------|-----------|---------|-----------|
| | | | Nominal | Tolerance | Nominal | Tolerance | Nominal | Tolerance | Nominal | Tolerance |
| SL | K33 | 2824 | 6.0 | ±0.2 | 3.0 | ±0.2 | 7.3 | ±0.2 | 0.5 | Nominal |
| SP | K35 | 2824 | 6.0 | ±0.2 | 3.5 | ±0.2 | 7.3 | ±0.2 | 0.5 | Nominal |
| ST | K37 | 2824 | 6.0 | ±0.2 | 4.5 | ±0.2 | 7.3 | ±0.2 | 0.5 | Nominal |
| WP | A31 | 4036 | 9.1 | ±0.2 | 5.5 | ±0.2 | 10.2 | ±0.2 | 0.5 | Nominal |
| YR | B31 | 5045 | 11.5 | ±0.2 | 6.5 | ±0.2 | 12.7 | ±0.2 | 0.5 | Nominal |
| ZS | C31 | 6560 | 15.0 | ±0.2 | 7.0 | ±0.2 | 16.5 | ±0.2 | 0.5 | Nominal |

Environmental Compliance

All KEMET surface mount capacitors are RoHS Compliant.



Performance Characteristics

| | | | | |
|-------------------------------------|---|---------------------------|-------------------------------------|----------------|
| Rated Voltage (VDC) | 100 | 250 | 400 | 630 |
| Rated Voltage (VAC) | 63 | 160 | 250 | 350 |
| Capacitance Range (μF) | 0.00047 – 0.68 | 0.00047 – 0.33 | 0.00047 – 0.15 | 0.00047 – 0.10 |
| Chip Size (EIA) | 2824 – 6560 | | | |
| Capacitance Tolerance | $\pm 2\%$, $\pm 2.5\%$, $\pm 5\%$, $\pm 10\%$ | | | |
| Category Temperature Range | -55°C to $+125^\circ\text{C}$ | | | |
| Rated Temperature | $+100^\circ\text{C}$ | | | |
| Voltage Derating | The rated voltage should be decreased with $1.25\%/^\circ\text{C}$ from $+100^\circ\text{C}$ to $+125^\circ\text{C}$ and $1.5\%/^\circ\text{C}$ from $+125^\circ\text{C}$ to 175°C | | | |
| Climatic Category | 55/125/56 | | | |
| Test Voltage | $1.6 \times V_R$, 60 seconds | | | |
| Insulation Resistance | Measured at $+20^\circ\text{C}$ According to IEC 60384-19 | | | |
| | Between Terminals | | | |
| | | $C \leq 0.33 \mu\text{F}$ | $C > 0.33 \mu\text{F}$ | |
| | $V_R \leq 100$ | 15,000 M Ω | 5,000 M $\Omega \cdot \mu\text{F}$ | |
| | $V_R > 100$ | 30,000 M Ω | 10,000 M $\Omega \cdot \mu\text{F}$ | |
| Dissipation Factor | Maximum Values at $+23^\circ\text{C}$ | | | |
| | | $C \leq 0.1 \mu\text{F}$ | $0.1 < C < 0.68 \mu\text{F}$ | |
| | 1 kHz | 0.10% | 0.10% | |
| | 10 kHz | 0.15% | 0.15% | |
| | 100 kHz | 0.20% | 0.40% | |
| Pulse Rise Time | The capacitors can withstand an unlimited number of pulses with a dV/dt , according to Table 1. For voltages (V) lower than the rated voltage (V_R), the specified dV/dt can be multiplied by V_R/V . | | | |

Capacitance vs. Temperature



Dissipation Factor vs. Temperature



Table 1 – Ratings & Part Number Reference

| VDC | VAC | Capacitance Value (µF) | Size Code (New/Legacy) | Dimensions in mm | | | Chip Size | dV/dt (V/µs) | New KEMET Part Number | Legacy Part Number |
|-----|-----|------------------------|------------------------|------------------|--------|--------|-----------|--------------|-----------------------|------------------------|
| | | | | B | H | L | | | | |
| 100 | 63 | 0.00047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL471(1)100(2) | SPC7.3471(1)100K33(2) |
| 100 | 63 | 0.00068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL681(1)100(2) | SPC7.3681(1)100K33(2) |
| 100 | 63 | 0.0010 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL102(1)100(2) | SPC7.3102(1)100K33(2) |
| 100 | 63 | 0.0015 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL152(1)100(2) | SPC7.3152(1)100K33(2) |
| 100 | 63 | 0.0022 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL222(1)100(2) | SPC7.3222(1)100K33(2) |
| 100 | 63 | 0.0033 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL332(1)100(2) | SPC7.3332(1)100K33(2) |
| 100 | 63 | 0.0047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL472(1)100(2) | SPC7.3472(1)100K33(2) |
| 100 | 63 | 0.0068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL682(1)100(2) | SPC7.3682(1)100K33(2) |
| 100 | 63 | 0.010 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL103(1)100(2) | SPC7.3103(1)100K33(2) |
| 100 | 63 | 0.015 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 800 | F127SL153(1)100(2) | SPC7.3153(1)100K33(2) |
| 100 | 63 | 0.022 | SP/K35 | 6.0 | 3.5 | 7.3 | 2824 | 800 | F127SP223(1)100(2) | SPC7.3223(1)100K35(2) |
| 100 | 63 | 0.033 | ST/K37 | 6.0 | 4.5 | 7.3 | 2824 | 800 | F127ST333(1)100(2) | SPC7.3333(1)100K37(2) |
| 100 | 63 | 0.0068 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP682(1)100(2) | SPC10.2682(1)100A31(2) |
| 100 | 63 | 0.010 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP103(1)100(2) | SPC10.2103(1)100A31(2) |
| 100 | 63 | 0.015 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP153(1)100(2) | SPC10.2153(1)100A31(2) |
| 100 | 63 | 0.022 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP223(1)100(2) | SPC10.2223(1)100A31(2) |
| 100 | 63 | 0.033 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP333(1)100(2) | SPC10.2333(1)100A31(2) |
| 100 | 63 | 0.047 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP473(1)100(2) | SPC10.2473(1)100A31(2) |
| 100 | 63 | 0.068 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP683(1)100(2) | SPC10.2683(1)100A31(2) |
| 100 | 63 | 0.10 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 600 | F127WP104(1)100(2) | SPC10.2104(1)100A31(2) |
| 100 | 63 | 0.15 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 400 | F127YR154(1)100(2) | SPC12.7154(1)100B31(2) |
| 100 | 63 | 0.22 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 400 | F127YR224(1)100(2) | SPC12.7224(1)100B31(2) |
| 100 | 63 | 0.33 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 150 | F127ZS334(1)100(2) | SPC16.5334(1)100C31(2) |
| 100 | 63 | 0.47 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 150 | F127ZS474(1)100(2) | SPC16.5474(1)100C31(2) |
| 100 | 63 | 0.68 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 150 | F127ZS684(1)100(2) | SPC16.5684(1)100C31(2) |
| 250 | 160 | 0.00047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL471(1)250(2) | SPC7.3471(1)250K33(2) |
| 250 | 160 | 0.00068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL681(1)250(2) | SPC7.3681(1)250K33(2) |
| 250 | 160 | 0.0010 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL102(1)250(2) | SPC7.3102(1)250K33(2) |
| 250 | 160 | 0.0015 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL152(1)250(2) | SPC7.3152(1)250K33(2) |
| 250 | 160 | 0.0022 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL222(1)250(2) | SPC7.3222(1)250K33(2) |
| 250 | 160 | 0.0033 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL332(1)250(2) | SPC7.3332(1)250K33(2) |
| 250 | 160 | 0.0047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL472(1)250(2) | SPC7.3472(1)250K33(2) |
| 250 | 160 | 0.0068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1200 | F127SL682(1)250(2) | SPC7.3682(1)250K33(2) |
| 250 | 160 | 0.010 | SP/K35 | 6.0 | 3.5 | 7.3 | 2824 | 1200 | F127SP103(1)250(2) | SPC7.3103(1)250K35(2) |
| 250 | 160 | 0.015 | ST/K37 | 6.0 | 4.5 | 7.3 | 2824 | 1200 | F127ST153(1)250(2) | SPC7.3153(1)250K37(2) |
| 250 | 160 | 0.0068 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP682(1)250(2) | SPC10.2682(1)250A31(2) |
| 250 | 160 | 0.010 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP103(1)250(2) | SPC10.2103(1)250A31(2) |
| 250 | 160 | 0.015 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP153(1)250(2) | SPC10.2153(1)250A31(2) |
| 250 | 160 | 0.022 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP223(1)250(2) | SPC10.2223(1)250A31(2) |
| 250 | 160 | 0.033 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP333(1)250(2) | SPC10.2333(1)250A31(2) |
| VDC | VAC | Capacitance Value (µF) | Size Code (New/Legacy) | B (mm) | H (mm) | L (mm) | Chip Size | dV/dt (V/µs) | New KEMET Part Number | Legacy Part Number |

- (1) G = ±2%, R = ±2.5% (Legacy code = H), J = ±5%, K = ±10%.
 (2) Insert ordering code for lead type and packaging. See Ordering Options Table for available options.

Table 1 – Ratings & Part Number Reference cont.

| VDC | VAC | Capacitance Value (µF) | Size Code (New/Legacy) | Dimensions in mm | | | Chip Size | dV/dt (V/µs) | New KEMET Part Number | Legacy Part Number |
|-----|-----|------------------------|------------------------|------------------|--------|--------|-----------|--------------|-----------------------|------------------------|
| | | | | B | H | L | | | | |
| 250 | 160 | 0.047 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1000 | F127WP473(1)250(2) | SPC10.2473(1)250A31(2) |
| 250 | 160 | 0.068 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 700 | F127YR683(1)250(2) | SPC12.7683(1)250B31(2) |
| 250 | 160 | 0.10 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 700 | F127YR104(1)250(2) | SPC12.7104(1)250B31(2) |
| 250 | 160 | 0.15 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 350 | F127ZS154(1)250(2) | SPC16.5154(1)250C31(2) |
| 250 | 160 | 0.22 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 350 | F127ZS224(1)250(2) | SPC16.5224(1)250C31(2) |
| 250 | 160 | 0.33 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 350 | F127ZS334(1)250(2) | SPC16.5334(1)250C31(2) |
| 400 | 250 | 0.00047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL471(1)400(2) | SPC7.3471(1)400K33(2) |
| 400 | 250 | 0.00068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL681(1)400(2) | SPC7.3681(1)400K33(2) |
| 400 | 250 | 0.0010 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL102(1)400(2) | SPC7.3102(1)400K33(2) |
| 400 | 250 | 0.0015 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL152(1)400(2) | SPC7.3152(1)400K33(2) |
| 400 | 250 | 0.0022 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL222(1)400(2) | SPC7.3222(1)400K33(2) |
| 400 | 250 | 0.0033 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 1600 | F127SL332(1)400(2) | SPC7.3332(1)400K33(2) |
| 400 | 250 | 0.0047 | SP/K35 | 6.0 | 3.5 | 7.3 | 2824 | 1600 | F127SP472(1)400(2) | SPC7.3472(1)400K35(2) |
| 400 | 250 | 0.0068 | ST/K37 | 6.0 | 4.5 | 7.3 | 2824 | 1600 | F127ST682(1)400(2) | SPC7.3682(1)400K37(2) |
| 400 | 250 | 0.0068 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1300 | F127WP682(1)400(2) | SPC10.2682(1)400A31(2) |
| 400 | 250 | 0.010 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1300 | F127WP103(1)400(2) | SPC10.2103(1)400A31(2) |
| 400 | 250 | 0.015 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1300 | F127WP153(1)400(2) | SPC10.2153(1)400A31(2) |
| 400 | 250 | 0.022 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1300 | F127WP223(1)400(2) | SPC10.2223(1)400A31(2) |
| 400 | 250 | 0.033 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 900 | F127YR333(1)400(2) | SPC12.7333(1)400B31(2) |
| 400 | 250 | 0.047 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 900 | F127YR473(1)400(2) | SPC12.7473(1)400B31(2) |
| 400 | 250 | 0.068 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 450 | F127ZS683(1)400(2) | SPC16.5683(1)400C31(2) |
| 400 | 250 | 0.10 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 450 | F127ZS104(1)400(2) | SPC16.5104(1)400C31(2) |
| 400 | 250 | 0.15 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 450 | F127ZS154(1)400(2) | SPC16.5154(1)400C31(2) |
| 630 | 350 | 0.00047 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 2000 | F127SL471(1)630(2) | SPC7.3471(1)630K33(2) |
| 630 | 350 | 0.00068 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 2000 | F127SL681(1)630(2) | SPC7.3681(1)630K33(2) |
| 630 | 350 | 0.0010 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 2000 | F127SL102(1)630(2) | SPC7.3102(1)630K33(2) |
| 630 | 350 | 0.0015 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 2000 | F127SL152(1)630(2) | SPC7.3152(1)630K33(2) |
| 630 | 350 | 0.0022 | SL/K33 | 6.0 | 3.0 | 7.3 | 2824 | 2000 | F127SL222(1)630(2) | SPC7.3222(1)630K33(2) |
| 630 | 350 | 0.0033 | SP/K35 | 6.0 | 3.5 | 7.3 | 2824 | 2000 | F127SP332(1)630(2) | SPC7.3332(1)630K35(2) |
| 630 | 350 | 0.0047 | ST/K37 | 6.0 | 4.5 | 7.3 | 2824 | 2000 | F127ST472(1)630(2) | SPC7.3472(1)630K37(2) |
| 630 | 350 | 0.0068 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1600 | F127WP682(1)630(2) | SPC10.2682(1)630A31(2) |
| 630 | 350 | 0.010 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1600 | F127WP103(1)630(2) | SPC10.2103(1)630A31(2) |
| 630 | 350 | 0.015 | WP/A31 | 9.1 | 5.5 | 10.2 | 4036 | 1600 | F127WP153(1)630(2) | SPC10.2153(1)630A31(2) |
| 630 | 350 | 0.022 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 1100 | F127YR223(1)630(2) | SPC12.7223(1)630B31(2) |
| 630 | 350 | 0.033 | YR/B31 | 11.5 | 6.5 | 12.7 | 5045 | 1100 | F127YR333(1)630(2) | SPC12.7333(1)630B31(2) |
| 630 | 350 | 0.047 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 550 | F127ZS473(1)630(2) | SPC16.5473(1)630C31(2) |
| 630 | 350 | 0.068 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 550 | F127ZS683(1)630(2) | SPC16.5683(1)630C31(2) |
| 630 | 350 | 0.10 | ZS/C31 | 15.0 | 7.0 | 16.5 | 6560 | 550 | F127ZS104(1)630(2) | SPC16.5104(1)630C31(2) |
| VDC | VAC | Capacitance Value (µF) | Size Code (New/Legacy) | B (mm) | H (mm) | L (mm) | Chip Size | dV/dt (V/µs) | New KEMET Part Number | Legacy Part Number |

- (1) G = ±2%, R = ±2.5% (Legacy code = H), J = ±5%, K = ±10%.
 (2) Insert ordering code for lead type and packaging. See Ordering Options Table for available options.

Soldering Process

Reflow soldering temperature is measured on the top surface of the component: Preheating temperature should be less than 170°C. The time above 217°C should be less than 50 seconds. The peak temperature must not exceed 260°C.



Construction



Marking



| Rated Voltage | Code |
|---------------|------|
| 100 VDC | D |
| 250 VDC | H |
| 400 VDC | K |
| 630 VDC | M |

| Manufacturing Date Code (IEC 60062) | | | |
|-------------------------------------|------|-----------|------|
| Year | Code | Month | Code |
| 2010 | A | January | 1 |
| 2011 | B | February | 2 |
| 2012 | C | March | 3 |
| 2013 | D | April | 4 |
| 2014 | E | May | 5 |
| 2015 | F | June | 6 |
| 2016 | H | July | 7 |
| 2017 | J | August | 8 |
| 2018 | K | September | 9 |
| 2019 | L | October | 0 |
| 2020 | M | November | N |
| 2021 | N | December | D |
| 2022 | P | | |
| 2023 | R | | |
| 2024 | S | | |
| 2025 | T | | |
| 2026 | U | | |
| 2027 | V | | |
| 2028 | W | | |
| 2029 | X | | |
| 2030 | A | | |

Flux & Cleaning

KEMET recommends using a no-clean flux with a halogen content lower than 0.1%. To clean the PCB assembly KEMET recommends to use a suitable solvent like Isopropyl alcohol, deionized water, or neutral pH detergents. Aggressive solvents shall not be used. For any different cleaning solvent used please contact KEMET Technical Services to analyze the potential impact on KEMET products.

Storage and Moisture Recommendations

KEMET SMD Film Capacitors are supplied in a MBB (Moisture Barrier Bag) Class 1. We can guarantee a 24 month shelf life (temperature $\leq 40^{\circ}\text{C}$ /relative humidity $\leq 90\%$). After the MBB has been opened, components may stay in areas with controlled temperature and humidity (temperature $\leq 30^{\circ}\text{C}$ /relative humidity $\leq 60\%$) for 696 hours [MSL 2a]. For longer periods of time and/or higher temperature and/or higher relative humidity values, it is absolutely necessary to protect the components against humidity. If the reel inside the MBB is partially used, KEMET recommends to re-use the same MBB or to avoid areas without controlled temperature and humidity (see above). If the above conditions are not respected, components require a baking (minimum time: 48 hours at $55 \pm 5^{\circ}\text{C}$) before the reflow.

Packaging Quantities

| Chip Size (EIA) | Base (mm) | Height (mm) | Length (mm) | Bulk | Reel Horizontal Orientation | Reel Vertical Orientation |
|-----------------|-----------|-------------|-------------|-------|-----------------------------|---------------------------|
| 2824 | 6.0 | 3.0 | 7.3 | 2,000 | 2,500 | |
| 2824 | 6.0 | 3.5 | 7.3 | 2,000 | 2,300 | |
| 2824 | 6.0 | 4.5 | 7.3 | 1,000 | 1,700 | |
| 4036 | 9.1 | 5.5 | 10.2 | 1,000 | 800 | 500 |
| 5045 | 11.5 | 6.5 | 12.7 | 1,000 | 600 | 400 |
| 6560 | 15.0 | 7.0 | 16.5 | 800 | 500 | 200 |

Landing

| Mounting | Chip Size | Dimensions in mm | | |
|------------|-----------|------------------|-----|-----|
| | | A | B | X |
| Horizontal | 2220 | 5.1 | 1.5 | 3.0 |
| | 2824 | 6.1 | 1.5 | 3.8 |
| | 4036 | 9.1 | 2.0 | 5.5 |
| | 5045 | 11.6 | 2.5 | 7.0 |
| | 6560 | 15.0 | 3.0 | 9.0 |
| Vertical | 4022 | 5.6 | 2.0 | 5.5 |
| | 5026 | 6.6 | 2.5 | 7.0 |
| | 6528 | 7.1 | 3.0 | 9.0 |



Carrier Taping & Packaging (IEC 60286-2)

Horizontal Taping Orientation



| Chip Size (EIA) Horizontal Mounting | Dimensions in mm | | | Taping Specification | | | | | | | |
|---|------------------|---------|---------|----------------------|----------------|----------------|----------------|----------------|------|----------------|----------------|
| | B | H | L | W | P ₁ | A ₀ | B ₀ | K ₀ | D | W ₁ | W ₂ |
| | Nominal | Nominal | Nominal | -0/+0.3 | ±0.1 | Nominal | Nominal | Nominal | ±2.0 | -0/+2 | Maximum |
| 2220 | 5.0 | 3.0 | 5.7 | 12.0 | 8.0 | 5.5 | 6.0 | 3.3 | 330 | 12.4 | 22.0 |
| 2220 | 5.0 | 4.0 | 5.7 | 12.0 | 8.0 | 5.5 | 6.0 | 4.3 | 330 | 12.4 | 22.0 |
| 2824 | 6.0 | 3.0 | 7.3 | 12.0 | 8.0 | 6.5 | 7.5 | 3.3 | 330 | 12.4 | 22.0 |
| 2824 | 6.0 | 3.5 | 7.3 | 12.0 | 8.0 | 6.5 | 7.5 | 3.8 | 330 | 12.4 | 22.0 |
| 2824 | 6.0 | 4.5 | 7.3 | 16.0 | 8.0 | 6.6 | 7.9 | 5.5 | 330 | 16.0 | 20.0 |
| 4036 | 9.1 | 5.5 | 10.2 | 16.0 | 16.0 | 9.5 | 10.5 | 5.8 | 330 | 16.4 | 22.0 |
| 5045 | 11.5 | 6.5 | 12.7 | 24.0 | 16.0 | 11.9 | 13.1 | 6.8 | 330 | 24.4 | 30.0 |
| 6560 | 15.0 | 7.0 | 16.5 | 24.0 | 20.0 | 15.4 | 16.8 | 7.3 | 330 | 24.4 | 30.0 |

Carrier Taping & Packaging (IEC 60286-2) cont.

Vertical Taping Orientation



| Size Code Vertical Mounting | Dimensions in mm | | | Taping Specification | | | | | | | |
|-----------------------------------|------------------|---------|---------|----------------------|----------------|----------------|----------------|----------------|------|----------------|----------------|
| | B | H | L | W | P ₁ | A ₀ | B ₀ | K ₀ | D | W ₁ | W ₂ |
| | Nominal | Nominal | Nominal | -0/+0.3 | ±0.1 | Nominal | Nominal | Nominal | ±2.0 | -0/+2 | Maximum |
| 4022 | 5.5 | 9.1 | 10.2 | 24.0 | 16.0 | 6.0 | 10.5 | 9.3 | 330 | 24.4 | 30.0 |
| 5026 | 6.5 | 11.5 | 12.7 | 24.0 | 16.0 | 6.9 | 13.1 | 11.8 | 330 | 24.4 | 30.0 |
| 6528 | 7.0 | 15.0 | 16.5 | 44.0 | 20.0 | 7.5 | 17.0 | 15.3 | 330 | 44.5 | 49.5 |

Note: Chip dimensions B and H correspond to dimensions H and B in the horizontal mounting table.

KEMET Electronics Corporation Sales Offices

For a complete list of our global sales offices, please visit www.kemet.com/sales.

Disclaimer

All product specifications, statements, information and data (collectively, the "Information") in this datasheet are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Statements of suitability for certain applications are based on KEMET Electronics Corporation's ("KEMET") knowledge of typical operating conditions for such applications, but are not intended to constitute – and KEMET specifically disclaims – any warranty concerning suitability for a specific customer application or use. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by KEMET with reference to the use of KEMET's products is given gratis, and KEMET assumes no obligation or liability for the advice given or results obtained.

Although KEMET designs and manufactures its products to the most stringent quality and safety standards, given the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required.

KEMET is a registered trademark of KEMET Electronics Corporation.

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».



JONHON

«**JONHON**» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«**FORSTAR**» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А