


## Description

The AVO100B-48S1V5 DC-DC converter is a next-generation industry standard eighth-brick with optimized ultra-high efficiency. This module can provide up to 40A output current at 1.5V output voltage, industry standard eighth-brick 57.9mm × 22.9mm × 9.6mm (2.28" × 0.9" × 0.378"), which makes it an ideal choice for small space, telecom and datacom applications. The AVO100B-48S1V5 is standard eighth-brick pin-out configuration, with baseplate option. It provides CNT remote control, trim and sense functions, with OVP, OCP, OTP full protection method. This product can achieve ultra-high efficiency of 90.7% at 60% load. A heatsink can be installed for better thermal performance.



## Operational Features

- Up to 40A output current
- Ultra-high efficiency 90.7% typ. at 60% load
- Wide input range: 36V ~ 75V
- Excellent thermal performance
- No minimum load requirement
- Intended for reflow or wave soldering
- RoHS 6 compliant

## Control Features

- Remote control function
- Remote output sense
- Trim function: 80% ~ 110%
- .

## Protection Features

- Input under-voltage lockout
- Output over-current protection
- Output over-voltage protection
- Over-temperature protection

## Mechanical Features

- Industry standard eighth-brick
- With baseplate option
- Pin length option: 3.8mm

## Safety & EMC

- Meets safety standards UL 60950-1 2nd edition, IEC/EN 60950-1 2nd edition and GB4943
- Approved by UL and TUV
- Meets the Low Voltage Directives 2006/95/EEC with the Amendment Directive 93/68/EEC which facilitates CE marking in user's end product
- Materials meet UL94,V-0 flammability rating
- Meets conducted emission's requirements of FCC Class A and EN55022 Class A with external filter

## Electrical Characteristics

Full operating ambient temperature range is -40°C to +85°C.

Specifications are subject to change without notice. Test condition: Ta: 25°C. Air velocity: 300LFM.

| Parameter                                  |                            | Min. | Typ.  | Max.  | Unit | Notes & conditions                                |
|--|----------------------------|------|-------|-------|------|---|
| <b>Absolute max. ratings</b>               |                            |      |       |       |      |   |
| Input voltage                              | Non-operating              | -    | -     | 100   | V    | 100ms   |
|  | Operating                  | -    | -     | 80    | V    | Continuous  |
| Operating temperature                      |                            | -40  | -     | +85   | °C   | -   |
| Storage temperature                        |                            | -55  | -     | +125  | °C   | -   |
| Voltage at remote ON/OFF pin               |                            | -0.7 | -     | 12    | V    | -   |
| <b>Input characteristics</b>               |                            |      |       |       |      |   |
| Operating input voltage range              |                            | 36   | 48    | 75    | V    | -   |
| Input under-voltage lockout                | Turn-on voltage threshold  | 31   | -     | 36    | V    | -   |
|  | Turn-off voltage threshold | 30   | -     | 35    | V    | -   |
|  | Lockout voltage hysteresis | 1    | -     | 3     | V    | -   |
| Max. input current                         |                            | -    | -     | 3.5   | A    | 36V <sub>in</sub> , full load                     |
| No-load input current                      |                            | -    | 0.05  | -     | A    |   |
| Standby input current                      |                            | -    | 0.005 | 0.015 | A    | Remote OFF  |
| Inrush current transient rating            |                            | -    | -     | 1     | A2s  | Figure 15   |
| Input reflected ripple current             |                            | -    | -     | 40    | mA   | Through 12μH inductor; Figure 15                  |
| Recommended input fuse                     |                            | -    | -     | 10    | A    | External fast blow fuse is recommended; Figure 11 |
| Recommended external input capacitance     |                            | 100  | -     | -     | μF   | Low ESR capacitor is recommended; Figure 11       |
| <b>Output characteristics</b>              |                            |      |       |       |      |   |
| Output voltage set point (standard option) |                            | 1.48 | 1.5   | 1.52  | V    | 48V <sub>in</sub> , half load                     |
| Output voltage line regulation             |                            | -    | ±0.1  | ±0.2  | %    | -   |
|  |                            | -    | -     | -     | mV   | -   |
| Output voltage load regulation             |                            | -    | ±0.1  | ±0.5  | %    | -   |
|  |                            | -    | -     | -     | mV   | -   |
| Output voltage temperature regulation      |                            | -    | -     | 0.02  | %/°C | -   |

| Parameter                         |                                    | Min. | Typ. | Max.  | Unit | Notes & conditions  |
|-----------------------------------|------------------------------------|------|------|-------|------|---|
| Total output voltage range        |                                    | 1.45 | 1.5  | 1.55  | V    | Over sample, line, load, temperature & life   |
| Output voltage ripple and noise   |                                    | -    | 55   |       | mVpp | Figure 2<br>20MHz bandwidth; Figure 15  |
| Output voltage ripple and noise   |                                    | -    | 50   | -     | mVpp | Ta: 25°C, Air velocity: 300LFM,<br>Vin: 48V, Vonom, Ionom, 10u<br>tantalum (ESR ≤ 100mΩ)//1u<br>ceramic capacitor, output ≤ 12V |
| Operating output current range    |                                    | 0    | -    | 40    | A    | -   |
| Output DC current-limit inception |                                    | 42   | -    | 57    | A    | Hiccup: auto-restart when<br>over-current condition is removed  |
| Output capacitance                |                                    | 330  | -    | 40000 | μF   | High frequency and low ESR are<br>recommended   |
| <b>Dynamic characteristics</b>    |                                    |      |      |       |      |   |
| Dynamic<br>response               | 25% ~ 50% ~ 25%<br>Io,max, 0.1A/μs | -    | 40   | -     | mV   | Figure 4<br>Test condition: 25°C, nominal<br>input voltage, Figure 10   |
|                                   | Settling time                      | -    | 150  | -     | μs   | Recovery to within 1% V <sub>o,nom</sub>  |
|                                   | 25% ~ 50% ~ 25%<br>Io,max, 1A/μs   | -    | 100  | -     | mV   | Figure 5<br>Test condition: 25°C, nominal<br>input voltage, Figure 11   |
|                                   | Settling time                      | -    | 200  | -     | μs   | Recovery to within 1% V <sub>o,nom</sub>  |
| Turn-on<br>transient              | Rise time                          | -    | 5    | 50    | ms   | Full load, Figure 6   |
|                                   | Turn-on delay time                 | -    | 62   | 200   | ms   | -   |
|                                   | Output voltage<br>overshoot        | -    | 0    | -     | %Vo  | -   |
| <b>Efficiency</b>                 |                                    |      |      |       |      |   |
| 100% load                         |                                    | -    | 89   | -     | %    | Figure 1  |
| 60% load                          |                                    | -    | 90.7 | -     | %    | Figure 1  |
| 20% load                          |                                    | -    | 87.5 | -     | %    | Figure 1  |

## Electrical Characteristics (Continued)

| Parameter   | Min.              | Typ. | Max. | Unit | Notes & conditions   |           |
|---|-------------------|------|------|------|--|-----------|
| <b>Isolation characteristics</b>                                    |                   |      |      |      |  |           |
| Isolation voltage (conditions: 1mA for 60s, slew rate of 2000V/10s) | 2250              | -    | -    | V    | Basic insulation, pollution degree 2, input to output  |           |
| <b>Feature characteristics</b>                                      |                   |      |      |      |  |           |
| Switching frequency   | -                 | 165  | -    | kHz  | -  |           |
| Remote ON/OFF control (positive logic)                              | Off-state voltage | -0.7 | -    | 1.2  | V  | Figure 12 |
|   | On-state voltage  | 3.5  | -    | 12   | V  |           |
| Remote ON/OFF control (negative logic)                              | Off-state voltage | 3.5  | -    | 12   | V  |           |
|   | On-state voltage  | -0.7 | -    | 1.2  | V  |           |
| Output voltage trim range   | 1.2               | -    | 1.65 | V    | See <i>Trim Characteristics of Application Note</i>  |           |
| Output voltage remote sense range                                   | -                 | -    | 0.12 | V    | -  |           |
| Output over-voltage protection (dynamic)                            | 1.75              | -    | 2.6  | V    | Hiccup: auto-restart when over-voltage condition is removed  |           |
| Over-temperature shutdown   | -                 | 120  | -    | °C   | Auto recovery; over-temperature protection (OTP) test point: Figure 10. Tested under thermal balance condition |           |
| Over-temperature hysteresis   | -                 | 5    | -    | °C   | -  |           |
| <b>Reliability characteristics</b>                                  |                   |      |      |      |  |           |
| Calculated MTBF (telcordia)   | -                 | 1.5  | -    | 106h | Telcordia SR-332-2006; 80% load, 300LFM, 40°C Ta   |           |

## Electromagnetic Compatibility Characteristics

| Test item   | Regulations  | Criteria | Notes & conditions      |
|---|--|----------|-------------------------|
| Conducted emission  | EN 55022<br>DC input port, class A limits  | /        | See EMC Test Conditions |
| Immunity to electrostatic discharge                                     | IEC/EN61000-4-2<br>Enclosure port, level 3   | B        |                         |
| Immunity to electrical fast transient                                   | IEC/EN61000-4-4<br>DC input port, level 3  | B        |                         |
| Immunity to surges  | IEC/EN61000-4-5<br>DC input port<br>Line to ground (earth): 600V<br>Line to line: 600V | B        |                         |
| Immunity to continuous conducted interference                           | IEC/EN61000-4-6<br>DC input port, level 2  | A        |                         |
| Immunity to voltage dips and short interruptions and voltage variations | EN 61000-4-29<br>DC input port   | B        |                         |

Criterion A: Normal performance during and after test.

Criterion B: For EFT and surges, low-voltage protection or reset is not allowed. Temporary output voltage fluctuation ceases after disturbances ceases, and from which the EUT recovers its normal performance automatically. For dips and ESD, output voltage fluctuation or reset is allowed during the test, but recovers to its normal performance automatically after the disturbance ceases.

## Qualification Testing

| Parameter        | Unit (pcs) | Test condition  |
|------------------|------------|---|
| Halt test        | 4 ~ 5      | Ta, min-10°C to Ta, max+10°C, 5°C step, Vin = min to max, 0 ~ 105% load   |
| Vibration        | 3          | Frequency range: 5Hz ~ 20Hz, 20Hz ~ 200Hz, A.S.D: 1.0m2/s3, -3db/oct,<br>axes of vibration: X/Y/Z.<br>Time: 30 min/axis |
| Mechanical shock | 3          | 30g, 6ms, 3 axes, 6 directions, 3 time/direction  |
| Thermal shock    | 3          | -40°C to +100°C, unit temperature 20 cycles   |
| Thermal cycling  | 3          | -40°C to +55°C, temperature change rate: 1°C/min, cycles: 2 cycles  |
| Humidity         | 3          | 40°C, 95%RH, 48h  |
| Solder ability   | 15         | IPC J-STD-002C-2007   |

# Characteristic Curves




Figure 1 Efficiency vs. output current, Ta = 25°C, Vo = 1.5V, Air velocity = 300LFM




Figure 2 Output ripple & noise (5µs/div, 50mV/div), see Figure 15 for test configuration




Figure 3 Input reflected ripple current (5µs/div, 10mA/div), see Figure 15 for test configuration




Figure 4 Dynamic response for 25% load step (25% ~ 50% ~ 25%) and 0.1A/µs slew rate, (2ms/div), see Figure 11 for test configuration; CH1-output voltage (100mV/div); CH2-output current (10A/div)




Figure 5 Dynamic response for 25% load step (25% ~ 50% ~ 25%) and 1A/µs slew rate, (2ms/div), see Figure 11 for test configuration; CH1-output voltage (100mV/div); CH2-output current (10A/div)




Figure 6 Output voltage startup by power-on, (50ms/div), see Figure 11 for test configuration; CH1-input voltage (20V/div); CH2-output voltage (1V/div)




Figure 7 Output voltage shutdown by power-off, (100ms/div), see Figure 11 for test configuration; CH1-input voltage (20V/div); CH2-output voltage (1V/div)




Figure 8 Output voltage startup by remote ON, (20ms/div), see Figure 11 for test configuration; CH1-output voltage (1V/div); CH2-remote ON voltage (2V/div) (Negative logic)




Figure 9 Output voltage shutdown by remote OFF, (20ms/div), see Figure 11 for test configuration; CH1-output voltage (1V/div); CH2-remote OFF voltage (2V/div) (Negative logic)




Figure 10 OTP test point

# Application Note

## Typical Application




Figure 11 Typical application

Recommended input fuse: LITTLEFUSE 216010.P 10A

C1: SMD eramic-100V-100nF-±10%-X7R-1206

C2: 100µF/100V electrolytic capacitor, high frequency and low ESR

C3:1000µF/10V electrolytic capacitor, high frequency and low ESR

C4: SMD ceramic-100V-1000nF-X7R-1210


C5, C6: SMD ceramic-47nF/1000V/X7R-1210

L1: 1320uH-±25%-4A-R5K-21mm × 21mm × 12.5mm

## Remote ON/OFF

Either positive or negative remote ON/OFF logic is available in AVO100B-48S1V5. The logic is CMOS and TTL compatible.

The voltage between pin Remote ON/OFF and pin Vin- must not exceed the range listed in *Feature Characteristics* to ensure proper operation. The external remote ON/OFF circuit in AVO100B-48S1V5 is highly recommended as shown in Figure 12.



Isolated remote ON/OFF circuit

non-isolated remote ON/OFF circuit

Figure 12 External remote ON/OFF circuit



### Trim Characteristics

Connecting an external resistor between Trim pin and Vo- pin will decrease the output voltage, while connecting it between Trim and Vo+ will increase the output voltage. The following equations determine the external resistance to obtain the trimmed output voltage.

$$R_{adj\_down} = \left( \frac{511}{\Delta\%} - 10.22 \right) k\Omega$$

$$R_{adj\_up} = \left( \frac{5.11 V_{out} (100 + \Delta\%)}{V_{ref} \Delta\%} - \frac{511}{\Delta\%} - 10.22 \right) k\Omega$$

$R_{adj\_down}$  : Value of the external adjustment resistor which shall be connected between Trim and S- for trimming down.

$\Delta\%$  : Output voltage change rate against nominal output voltage.

$R_{adj\_up}$  : Value of the external adjustment resistor which shall be connected between Trim and S+ for trimming up.

$V_{out}$ : Nominal output voltage.

$V_{ref} = 1.225V$

When trimming up, the output current should be decreased accordingly so as not to exceed the maximum output power as shown in below figure.




Figure 13 Trim up




Figure 14 Trim down

### Sense Characteristics

If the load is far from the unit, connect S+ and S- to the terminals of the load respectively to compensate the voltage drop on the transmission line.

If the sense compensate function is not necessary, connect S+ to Vo+ and S- to Vo- directly.

## Input Ripple & Inrush Current And Output Ripple & Noise Test Configuration




Figure 15 Input ripple & inrush current, output ripple & noise test configuration

Vdc: DC power supply

L1: 12μH

Cin: 220μF/100V typical

C1: SMD ceramic-100V-100nF-±10%-X7R-1206

C2: 100μF/100V electrolytic capacitor, high frequency and low ESR

C3: SMD ceramic-10V-1μF-±10%-X7R-1206

C4: 1000μF/10V electrolytic capacitor, high frequency and low ESR

Note: It is recommended to use a coaxial cable with series 50Ω resistor and 0.68μF ceramic capacitor or a ground ring of probe to test output ripple & noise.

## EMC Test Conditions

See Figure11.

## Thermal Considerations

The converter is designed to operate in different thermal environments and sufficient cooling must be provided. Proper cooling of the DC-DC converter can be verified by measuring the temperature at the test points as shown in Figure 16 and Figure 17. The temperature at these points should not exceed the maximum values in Table 1 when the module is operating.

For a typical application, forced airflow direction is from Vin- to Vin+. Figure 18 shows the derating of output current vs. ambient air temperature at different air velocity.




Figure 16 Thermal test point (top)




Figure 17 Thermal test point (bottom)

Table 1 Temperature limit of the test points

| Test point   | Temperature limit |
|--------------|-------------------|
| Test point 1 | 114°C             |
| Test point 2 | 118°C             |
| Test point 3 | 115°C             |





Figure 18 Output power derating, 48Vin, air flowing across the converter from Vin- and Vin+

### Mechanical Diagram



Unit: mm[inch]

Bottom view: pin on upside

Tolerance: X.Xmm±0.5mm[X.X in.±0.02in.]

X.XXmm±0.25mm[X.XX in.±0.01in.]

Figure 19 Mechanical diagram

### Pin Length Option

| Device code suffix | L              |
|--------------------|----------------|
| -4                 | 4.8mm ± 0.25mm |
| -6                 | 3.8mm ± 0.25mm |
| -8                 | 2.8mm ± 0.25mm |
| None               | 5.8mm ± 0.25mm |

## Pin Designations

| Pin No. | Name          | Function                |
|---------|---------------|-------------------------|
| 1       | Vin+          | Positive input voltage  |
| 2       | Remote ON/OFF | Remote control          |
| 3       | Vin-          | Negative input voltage  |
| 4       | Vo-           | Negative output voltage |
| 5       | S-            | Negative remote sense   |
| 6       | Trim          | Output voltage trim     |
| 7       | S+            | Positive remote sense   |
| 8       | Vo+           | Positive output voltage |

## Soldering

For R6 product, it is intended for standard manual, reflow or wave soldering.

When reflow soldering is used, the temperature on pins is specified to maximum 260°C for maximum 10s.

When wave soldering is used, the temperature on pins is specified to maximum 260°C for maximum 7s.

When manual soldering is used, the iron temperature should be maintained at 300°C ~ 380°C and applied to the converter pins for less than 10s. Longer exposure can cause internal damage to the converter.

Cleaning of solder joint can be performed with cleaning solvent IPA or simulative.

For R5 product, it is intended for standard manual, reflow or wave soldering.

When reflow soldering is used, the temperature on pins is specified to maximum 230°C for maximum 10s.

When wave soldering is used, the temperature on pins is specified to maximum 255°C for maximum 7s.

When manual soldering is used, the iron temperature should be maintained at 300°C ~ 380°C and applied to the converter pins for less than 10s. Longer exposure can cause internal damage to the converter.

Cleaning of solder joint can be performed with cleaning solvent IPA or simulative.

## Ordering Information

|               |          |           |          |            |   |   |          |          |          |
|---------------|----------|-----------|----------|------------|---|---|----------|----------|----------|
| <b>AVO100</b> | <b>-</b> | <b>48</b> | <b>S</b> | <b>1V5</b> |   |   | <b>-</b> | <b>6</b> | <b>L</b> |
| ①             |          | ②         | ③        | ④          | ⑤ | ⑥ |          | ⑦        | ⑧        |

|   |                      |  |
|---|----------------------|--|
| ① | Model series         | AVO: series name, 100: output power 100W           |
| ② | Input voltage        | 48: 36V ~ 75V input range, rated input voltage 48V |
| ③ | Output number        | S: single output                                   |
| ④ | Rated output voltage | 1V5: 1.5V output                                   |
| ⑤ | Remote ON/OFF logic  | Default: negative; P: positive logic               |
| ⑥ | Baseplate            | Default: without baseplate; B: with baseplate      |
| ⑦ | Pin length           | 6: 3.8mm   |
| ⑧ | RoHS status          | L: RoHS, R6; Y: RoHS, R5                           |

| Model number        | Description   |
|---------------------|---|
| AVO100B-48S1V5-6L   | 3.8mm pin length; negative on/off logic; open frame, R6 compliant                                     |
| AVO100B-48S1V5P-6L  | 3.8mm pin length; positive on/off logic; open frame, R6 compliant                                     |
| AVO100B-48S1V5B-6L  | 3.8mm pin length; negative on/off logic; with baseplate; R6 compliant, see <i>AVO100B-48S1V5B TRN</i> |
| AVO100B-48S1V5PB-6L | 3.8mm pin length; positive on/off logic; with baseplate; R6 compliant, see <i>AVO100B-48S1V5B TRN</i> |
| AVO100B-48S1V5-6Y   | 3.8mm pin length; negative on/off logic; open frame, R5 compliant                                     |
| AVO100B-48S1V5P-6Y  | 3.8mm pin length; positive on/off logic; open frame, R5 compliant                                     |
| AVO100B-48S1V5B-6Y  | 3.8mm pin length; negative on/off logic; with baseplate; R5 compliant, see <i>AVO100B-48S1V5B TRN</i> |
| AVO100B-48S1V5PB-6Y | 3.8mm pin length; positive on/off logic; with baseplate; R5 compliant, see <i>AVO100B-48S1V5B TRN</i> |

## Hazardous Substances Announcement (RoHS Of China)

| Parts   | Hazardous substances |    |    |                  |     |      |
|---|----------------------|----|----|------------------|-----|------|
|   | Pb                   | Hg | Cd | Cr <sup>6+</sup> | PBB | PBDE |
| AVO100 -48S1V5  | ○                    | ○  | ○  | ○                | ○   | ○    |
| <p>○: Means the content of the hazardous substances in all the average quality materials of the part is within the limits specified in SJ/T-11363-2006</p> <p>√: Means the content of the hazardous substances in at least one of the average quality materials of the part is outside the limits specified in SJ/T11363-2006</p> <p>Emerson Network Power Co., Ltd. has been committed to the design and manufacturing of environment-friendly products. It will reduce and eventually eliminate the hazardous substances in the products through unremitting efforts in research. However, limited by the current technical level, the following parts still contain hazardous substances due to the lack of reliable substitute or mature solution:</p> <ol style="list-style-type: none"> <li>1. Solders (including high-temperature solder in parts) contain plumbum.</li> <li>2. Glass of electric parts contains plumbum.</li> <li>3. Copper alloy of pins contains plumbum</li> </ol> |                      |    |    |                  |     |      |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



## JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: [ocean@oceanchips.ru](mailto:ocean@oceanchips.ru)

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А