
Positive Lock Receptacles

Product Facts

- **Reduced insertion force**
- **Locks onto tabs containing holes**
- **Housing insulates and serves as a removal tool**
- **"Snap" action tells assembler receptacle is mated properly**
- **Terminated by automatic or semi-automatic equipment**
- **Single and multiple circuit housings available**
- **Recognized under the Component Program of Underwriters Laboratories Inc., File Nos. E66717 and E28476**
- **Certified by Canadian Standards Association File No. LR7189A**



Positive Lock receptacles are specifically designed to provide ease of assembly and secure retention to mating tabs. These unique features are attainable by the reduced insertion force of the product and the locking dimple. The receptacle locks onto mating tabs containing holes and is removable only by deflecting an integrally designed depressor prior to withdrawal. The depressor can be deflected manually by thumb pressure, or automatically by a cam inside a specially designed nylon housing. If the housing is employed, removal of the terminal from the tab is performed by simply applying withdrawal force to the housing. In addition to providing a means of disconnecting the terminal, the housing performs its traditional insulating function.

Aside from reduced insertion forces, Positive Lock receptacles give the assembler a definite mechanical "snap" when the terminal is correctly seated over the mating tab. This facilitates correct assembly in hard-to-reach areas such as under dashboards, recessed switch tabs, etc.

Safety is enhanced by the locking capability of the product. Unless the depressor is deliberately deflected, either manually or by withdrawal force applied directly to the optional housing, a terminal will not easily come off of the tab. Thus, the potential of exposed live parts or disruption of critical circuitry due to improperly seated or accidentally removed terminals is greatly reduced.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)


Mark I

250 Series Receptacles

Stock Thickness — .016 [0.41]

Fits Tab — .032 [0.81]

Recognized under the Component Program of Underwriters Laboratories Inc., UL File No. E28476




Wire Range AWG	Insulation Diameter	Material and Finish	Part Numbers				
			Receptacle	UL	CSA	Quick Change Applicator No.[2]	Hand Tool
20-16	**.090-.130** 2.29-3.30	Brass/Pre-Tin	1-160759-1	X	X	567181-2	654174-1
18-14	**.135-.195** 3.43-4.95	Brass/Tin	63812-1[1]	X	X	680140-2	—
	.095-.155 2.41-3.94	Brass/Tin	154718-3	X	—	466542-3	525651
14-11	**.140-.170** 3.56-4.32	Brass/Tin	154717-3	X	—	466883-2	525651
12-10	**.135-.200** 3.43-5.08	Brass/Pre-Tin	790319-3	—	—	567417-2	—

[1] "A" Style Housing only.
[2] Quick-Change Applicator for AMP-O-LECTRIC Machine 565435-5. For AMPOMATOR Machine and other machines not listed, contact Tyco Electronics.

Receptacle Housings

Material — 94 V-2, 6/6 Nylon


1 Position



Style	Color	Part No.
A	Black	154719-0
	Natural	154719-1
B	Black	520961-1[1]
H	Black	926521-2
T	Black	926522-1
	Natural	926522-2

[1] Press-to-release with secondary lock.

2 Position



Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803


South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)

Mark I

250 Series Flag Receptacle

Stock Thickness — .016 [0.41]
Fits Tab — .032 [0.81]




Wire Range AWG	Insulation Diameter	Material and Finish	Part Numbers	
			Receptacle	Quick Change Applicator No. [1]
20-16	**.087-.130** 2.21-3.30	Brass/Pre-Tin	926820-4	680436-2

[1] Quick-Change Applicator for AMP-O-LECTRIC Machine 565435-5.
For AMPOMATOR Machine and other machines not listed, contact Tyco Electronics.

Mark I

250 Series
Receptacle Housings

Material — 94 V-2, 6/6 Nylon



Color	Part Number
Black	926291-1

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208


Positive Lock Receptacles (Continued)

Mark II
250 Series
Straight Receptacles




Wire Range AWG	Tab Thickness	Insulation Diameter	Material and Finish	Stock Thickness	L (Overall Length)			Terminal Part No.
22-18	**.032** 0.81	**.060-.100** 1.52-2.54	Brass, Tin Plated	**.016** 0.41	**.886** 22.50	X	X	63119-1
	.032 0.81	**.059-.122** 1.50-3.10	Pre-Tin Brass	**.016** 0.41	**.976** 24.80	X	X	170327-1
18-14	**.032** 0.81	**.090-.155** 2.29-3.94	Brass	**.016** 0.41	**.886** 22.50	X	X	63097-2
	.032 0.81	**.090-.155** 2.29-3.94	Brass, Tin Plated	**.016** 0.41	**.886** 22.50	X	X	63097-1
	.025 0.64	**.090-.155** 2.29-3.94	Brass, Tin Plated	**.016** 0.41	**.886** 22.50	X	X	63809-1
	.020 0.51	**.090-.155** 2.29-3.94	Brass, Tin Plated	**.016** 0.41	**.886** 22.50	X	X	63442-1
	.032 0.81	**.090-.135** 2.29-3.43	Pre-Tin Brass	**.016** 0.41	**1.015** 25.80	X	X	170328-1
15-10	**.032** 0.81	**.110-.200** 2.79-5.08	Pre-Tin Brass	**.016** 0.41	**1.015** 25.80	X	X	170329-1
12-10	**.032** 0.81	**.150-.200** 3.81-5.08	Brass, Tin Plated	**.018** 0.46	**.913** 23.20	X	X	63239-1

Mark II
250 Series
Receptacle Housings
1 Circuit



A



B

Style	Material	UL 94	Color			Part Number
A	6/6 Nylon	V2	Natural	—	—	172076-1
			Black	—	—	172076-2
			Yellow	—	—	172076-4
			Green	—	—	172076-5
			Blue	—	—	172076-6
			Red	—	—	172076-7
		V0	Natural	—	—	2-172076-1
			Black	—	—	2-172076-2
			Yellow	—	—	2-172076-4
			Green	—	—	2-172076-5
			Blue	—	—	2-172076-6
			Red	—	—	2-172076-7
B	6/6 Nylon	V0	Natural	X	X	177627-1
			Yellow	X	X	177627-4
			Green	—	—	177627-5
			Blue	—	—	177627-6
			Red	—	—	177627-7
			Black	—	—	177627-9

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803


South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)


Mark II
250 Series
Receptacle Housings
2 Circuit



A




B



C

Style	Material	UL 94	Color			Part Number
A	6/6 Nylon	V2	Natural	X	X	520935-1
			Red	X	X	520935-2
			Black	—	—	520935-3
			Green	—	—	520935-4
			Blue	—	—	520935-5
			Yellow	—	—	520935-6
			Brown	—	—	520935-7
		V0	Natural	—	—	1-520935-1
			Red	—	—	1-520935-2
			Blue	—	—	1-520935-5
B	6/6 Nylon	V0	Natural	X	X	521229-1
			Red	—	—	521229-2
		V2	Natural	—	—	521588-1
C	6/6 Nylon	V0	Natural	—	—	178833-1
			Yellow	—	—	178833-4
			Blue	—	—	178833-6
			Red	—	—	178833-7

Mark II
250 Series
Receptacle Housings
4 Circuit



A

Style	Material	UL 94	Color			Part Number
A	6/6 Nylon	V2	Natural	X	X	174429-1

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.


USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)

Mark II


250 Series
Flag Receptacles
Stock Thickness — .016 [0.41]
Fits Tab — .032 [0.81]



Wire Range AWG	Insulation Diameter	Material and Finish	UL	CSA	TÜV	Terminal Part No.
22-18	**0.59-.110** 1.50-2.80	Pre-Tin Brass	X	—	X	172761-1
18-14	**.110-.205** 2.80-5.20	Pre-Tin Brass	X	—	X	172763-1
12-10	**.110-.205** 2.80-5.20	Pre-Tin Brass	X	—	X	172765-1

Mark II

250 Series
Flag Style Receptacle Housing
1 Circuit



A

Style	Material	UL 94	Color	TÜV	CSA	Part Number
A	6/6 Nylon	V2	Natural	X	X	172469-1
			Blue	X	X	172469-2
			Green	—	—	172469-4
			Red	—	—	172469-7
		V0	Natural	—	—	1-172469-1
			Blue	—	—	1-172469-2
			Yellow	—	—	1-172469-3

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803


South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)

Mark II
187 Series
Straight Receptacles



A




B


Wire Range AWG	Style	Tab Fit	Insulation Diameter	Material and Finish	Stock Thickness	L (Overall Length)	UL	CSA	Terminal Part No.
24-20	A	**.020** 0.51	**.060-.110** 1.52-2.79	Brass, Post Tin Plated	**.012** 0.30	**.755** 19.17	X	X	63196-1
	B	**.020** 0.51	**.060-.105** 1.52-2.67	Pre-Tin Brass	**.012** 0.30	**.850** 21.60	X	X	170324-1
	A	**.020** 0.51	**.060-.110** 1.52-2.79	Pre-Tin Brass	**.012** 0.30	**.755** 19.17	X	X	63407-2[1]
	B	**.020** 0.51	**.060-.105** 1.52-2.67	Phos. Bronze, Nickel Plated	**.012** 0.30	**.850** 21.60	X	X	170324-2
		.020 0.51	**.060-.105** 1.52-2.67	Pre-Tin Phos. Bronze	**.012** 0.30	**.850** 21.60	—	—	170324-5
20-16	B	**.020** 0.51	**.074-.134** 1.87-3.40	Pre-Tin Brass	**.012** 0.30	**.850** 21.60	X	X	170325-1
		.020 0.51	**.074-.134** 1.87-3.40	Pre-Tin Phos. Bronze	**.012** 0.30	**.850** 21.60	—	—	170325-3
	A	**.020** 0.51	**.090-.130** 2.29-3.30	Brass, Tin Plated	**.012** 0.30	**.755** 19.17	X	X	63195-1
		.020 0.51	**.090-.130** 2.29-3.30	Brass, Pre-Tin	**.012** 0.30	**.755** 19.17	X	X	63232-1[1]
		.032 0.81	**.060-.110** 1.52-2.79	Brass, Tin Plated	**.012** 0.30	**.740** 18.80	X	X	63498-1[2]
		.032 0.81	**.090-.130** 2.29-3.30	Brass, Tin Plated	**.012** 0.30	**.755** 19.17	X	X	63313-1[1]
18-14 (2) 18	B	**.020** 0.51	**.083-.142** 2.11-3.61 (2) **.216** 5.49	Brass, Pre-Tin	**.012** 0.30	**.850** 21.60	—	—	170326-1

[1] Low profile — not for use in housing.
[2] For use with housing 521125.

Mark II
187 Series
Receptacle Housings
1 Circuit



A — Use with (.187 x .020 [4.74 x 0.51])



B — Use with (.187 x .032 [4.75 x 0.81])

Style	Material	UL 94	Color	UL	CSA	Part Number
A	6/6 Nylon	V2	Natural	X	X	172074-1
			Black	—	—	172074-2
			Yellow	—	—	172074-4
			Green	—	—	172074-5
			Blue	—	—	172074-6
			Red	—	—	172074-7
		V0	Natural	X	X	173974-1
			Black	—	—	173974-2
			Yellow	—	—	173974-4
			Green	—	—	173974-5
			Blue	—	—	173974-6
			Red	—	—	173974-7
B	6/6 Nylon	V2	Natural	—	—	521125-1

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803


South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)


Mark II
187 Series
Receptacle Housings
2 Circuit




A — 6 mm Pitch




B — 6 mm Pitch, with Polarized Guide



C — 7 mm Pitch




D — 10 mm Pitch




E — 15 mm Pitch, for Electro-Magnetic

Style	Material	UL 94	Color	UL	CSA	Part Number
A	6/6 Nylon	V2	Natural	—	—	172210-1
			Black	—	—	172210-2
			Yellow	—	—	172210-4
			Blue	—	—	172210-6
		V0	Natural	X	X	1-172210-1
			Black	X	X	1-172210-2
			Yellow	—	—	1-172210-4
			Green	—	—	1-172210-5
			Blue	—	—	1-172210-6
			Red	—	—	1-172210-7
B	6/6 Nylon	V2	Natural	X	X	174587-1
			Yellow	—	—	174587-4
		V0	Natural	—	—	1-174587-1
			Yellow	—	—	1-174587-4
			Green	—	—	1-174587-5
			Blue	—	—	1-174587-6
			Red	—	—	1-174587-7

Style	Material	UL 94	Color	UL	CSA	Part Number
C	6/6 Nylon	V2	Natural	X	X	175578-1
			Black	—	—	175578-2
			Yellow	X	X	175578-4
			Blue	—	—	175578-6
		V0	Natural	—	—	1-175578-1
			Black	—	—	1-175578-2
			Yellow	—	—	1-175578-4
			Green	—	—	1-175578-5
			Blue	—	—	1-175578-6
			Red	—	—	1-175578-7
D	6/6 Nylon	V0	Natural	—	—	179720-1
			Black	—	—	179720-2
			Yellow	—	—	179720-4
			Blue	—	—	179720-6
			Red	—	—	179720-7
E	6/6 Nylon	V0	Natural	X	X	176498-1
			Black	—	—	176498-2
			Yellow	—	—	176498-4
			Blue	—	—	176498-6



F — 16 mm Pitch



G — For Microswitch

Style	Material	UL 94	Color	UL	CSA	Part Number
F	6/6 Nylon	V0	Natural	—	—	353148-1
			Yellow	—	—	353148-4
			Green	—	—	353148-5
			Blue	—	—	353148-6
G	6/6 Nylon	V2	Natural	X	X	174712-1
		V0	Natural	—	—	1-174712-1
			Yellow	—	—	1-174712-4
			Blue	—	—	1-174712-6
			Red	—	—	1-174712-7

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803


South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

Positive Lock Receptacles (Continued)


Mark II

187 Series
Receptacle Housings

3 Circuit and
4 Circuit



A — 3 Circuit
For Micro-Switch



B — 4 Circuit
For Timer


Style	Material	UL 94	Color			Part Number
A	6/6 Nylon	V2	Natural	X	X	172075-1
			Yellow	X	X	172075-4
			Blue	—	—	172075-6
		V0	Natural	—	—	1-172075-1
			Yellow	—	—	1-172075-4
B	6/6 Nylon	V0	Natural	X	X	174513-1

Note: All part numbers are RoHS compliant.

Positive Lock Receptacles (Continued)

Mark III
250 Series Receptacles


Stock Thickness — .016
Accepts .032 Tab




Wire Range AWG	Insulation Diameter	Material and Finish			Part Number	
					Receptacles	Quick Change Applicator No.[1]
22-18	.060-.110 1.52-2.79	Brass	X	X	63933-1	680161-2
		Brass/Tin	X	X	63933-2	680161-2
18-14	.090-.155 2.28-3.93	Brass	X	X	63854-1	680411-2
		Brass/Tin	X	X	63854-2	680411-2
16-12 or (2) 18 or (2) 16 or (1) 18 and (1) 16	.120-.170 3.04-4.31	Brass	X	X	1217092-1	680646-2
		Brass/Tin	X	X	1217092-2	680646-2

[1] Quick-Change applicator Part No. with -1 is for a "T" terminating unit used in automatic machines; -2 is for a "K" AMP-O-LECTRIC bench machine.


Mark III
Receptacle Housings




One Circuit Housing
A




Two Circuit Wax Motor Housing
B



Two Circuit Water Valve Housing
C



Two Circuit Water Valve Housing with Latch
D



Two Circuit Housing
E

Style	Material	UL 94[1]	Color[2]	Part Number	Accepts		
A	Nylon	V2	Natural	521120-1	250 Series Positive Lock Mark III Terminals.	X	X
B	Nylon	V0	Natural	521766-1	250 Series FASTON and Positive Lock Mark III Terminals. Examples include 63306 and 63854.	X	X
D	Nylon	V2	Natural	521253-1	250 Series FASTON and Positive Lock Mark III Terminals. Examples Include 63306 and 63854	X	X
			Red	521253-2		X	X
		V0	Red	1-521253-2		X	X
			Green	1-521253-3		X	X
			Blue	1-521253-7		X	X
C	Nylon	V2	Natural	521119-1		X	X
			Putty	521119-2			
			Blue	521119-4			
E	Nylon	V0	Natural	521955-1	250 Series MK III Positive Lock Receptacles 63993, 63854, 1217092	X	X

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208


Positive Lock Receptacles (Continued)

Mark III
187 Series Receptacles




Wire Range AWG	Insulation Dia.	Mating Tab Thickness	Material and Finish	Terminal Part No.	UL	CSA	Applicator
22-18	**.090-.130** 2.29-3.30	**.020** 0.51	Tin Plated Brass	1217113-2	—	—	680645-2
		.032 0.81	Tin Plated Brass	1217097-2	—	—	680645-2
18-14	**.150-.200** 3.81-5.08	**.020** 0.51	Brass	1217114-1	—	—	680652-2
		.020 0.51	Tin Plated Brass	1217114-2	—	—	680652-2
18-14 (2) 18	**.150-.200** 3.81-5.08	**.032** 0.81	Brass	1217096-1	X	X	680652-2

Mark III
187 Series Receptacle Housings



Part Number 521187-1




Part Number 521198-1


Material	UL 94	Color	UL	CSA	Part Number
Nylon	V2	Natural	X	X	521187-1
Nylon	V2	Natural	X	—	521198-1

Mark III
HVAC Motor Receptacle Housings

Material	Color	UL	CSA	Part Number
Nylon	Natural	X	X	521780-1
Nylon	Natural	X	X	521781-1



Part Number 521781-1
4-Position



Part Number 521780-1
5-Position

Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.


Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208


Positive Lock Receptacles (Continued)

110 Series
Straight Receptacles




Wire Range AWG	Tab Fit	Insulation Diameter	Material and Finish	Stock Thickness	UL	CSA	Terminal Part No.
24-20	**.020** 0.51	**.040-.070** 1.02-1.78	Pre-Tin Brass	**.010** 0.25	—	—	175411-1
20-16	**.020** 0.51	**.080-.122** 2.03-3.10	Pre-Tin Brass	**.010** 0.25	—	—	174777-1

Receptacle Housing
Applicable Contact
Part Number 175411, 174777



A — For 1 Circuit




B — For 3 Circuit

Style	Material	UL 94	Color	UL	CSA	Part Number
A	6/6 Nylon	V2	Natural	X	X	174779-1
B	6/6 Nylon	V0	Natural	—	—	178832-1
			Yellow	—	—	178832-4
			Blue	—	—	178832-6
			Red	—	—	178832-7

Tab Dimension
For Signal Circuit

For 1 Circuit

Top View




Side View




Type A
(When using tab shoulder for butting)

Top View




Side View




Type B
(When using resin, etc., for butting)

Sagging of the tab's hole must not exceed 0.08 mm.




Section X-X



Housing Outline

For 3 Circuit



Note: All part numbers are RoHS compliant.

Catalog 82004
Revised 10-07

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208

OCEAN CHIPS
Океан Электроники
Поставка электронных компонентов

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «**JONHON**», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «**FORSTAR**».

AVIC JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).

FORSTAR®

Телефон: 8 (812) 309-75-97 (многоканальный)
Факс: 8 (812) 320-03-32
Электронная почта: ocean@oceanchips.ru
Web: http://oceanchips.ru/
Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А