

Please read this notice before using the TAIYO YUDEN products.

REMINDERS

- Product information in this catalog is as of October 2018. All of the contents specified herein are subject to change without notice due to technical improvements, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

- Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available.
- Please conduct validation and verification of our products in actual condition of mounting and operating environment before using our products.
- The products listed in this catalog are intended for use in general electronic equipment (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and medical equipment classified as Class I or II by IMDRF. Please be sure to contact TAIYO YUDEN for further information before using the products for any equipment which may directly cause loss of human life or bodily injury (e.g., transportation equipment including, without limitation, automotive powertrain control system, train control system, and ship control system, traffic signal equipment, disaster prevention equipment, medical equipment classified as Class III by IMDRF, highly public information network equipment including, without limitation, telephone exchange, and base station).

Please do not incorporate our products into any equipment requiring high levels of safety and/or reliability (e.g., aerospace equipment, aviation equipment*, medical equipment classified as Class IV by IMDRF, nuclear control equipment, undersea equipment, military equipment).

*Note: There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

When our products are used even for high safety and/or reliability-required devices or circuits of general electronic equipment, it is strongly recommended to perform a thorough safety evaluation prior to use of our products and to install a protection circuit as necessary.

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

- Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.
- Please note that the scope of warranty for our products is limited to the delivered our products themselves and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a fault or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement.
- The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.
- Caution for Export
Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.

RADIAL LEADED INDUCTORS



WAVE

■ PARTS NUMBER

*Operating Temp. : -25~+105°C (Including self-generated heat)

| | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| L | H | △ | L | △ | 0 | 8 | T | B | 1 | 0 | 1 | K | △ | △ | △ |
| ① | ② | ③ | ④ | ⑤ | ⑥ | ⑦ | | | | | | | | | |

△=Blank space

① Series name

| Code | Series name |
|------|------------------------|
| LH△ | Radial leaded inductor |

② Characteristics

| Code | Characteristics |
|------|--------------------------------|
| L△ | Standard type Taping available |
| LC | High current type |

③ Dimensions (D)

| Code | Dimensions (D) [mm max.] |
|------|--------------------------|
| 08 | 9.0 |
| 10 | 11.0 |

④ Packaging

| Code | Packaging |
|------|----------------------|
| NB | Bulk (LHL) |
| TB | Ammo packaging (LHL) |

⑤ Nominal inductance

| Code (example) | Nominal inductance [μH] |
|----------------|-------------------------|
| 1R0 | 1.0 |
| 150 | 15 |
| 102 | 1000 |

※R=Decimal point

⑥ Inductance tolerance

| Code | Inductance tolerance |
|------|----------------------|
| J | ±5% |
| K | ±10% |
| M | ±20% |
| N | ±30% |

⑦ Internal code

| Code | Internal code |
|------|---------------|
| △△△ | Standard |

■ STANDARD EXTERNAL DIMENSIONS / STANDARD QUANTITY

LHL / LHLC



| Type | D | H ₂ | l | F | φ d | Standard quantity [pcs] | | |
|---------|-------------------------|-------------------------|--------------------------|--------------------------|---------------------------|-------------------------|------|--------|
| | | | | | | Box | Bulk | Taping |
| LH L 08 | 9.0 max (0.354 max) | 9.5 max (0.374 max) | 5.0±1.0 (0.197±0.039) | 5.0±1.0 (0.197±0.039) | 0.6±0.05 (0.024±0.002) | — | 100 | 1000 |
| LH L 10 | 11.0 max (0.433 max) | 14.0 max (0.551 max) | 5.0±1.0 (0.197±0.039) | 5.0±1.0 (0.197±0.039) | 0.6±0.05 (0.024±0.002) | — | 50 | 500 |

Unit: mm (inch)

● LHL08

| Parts number | EHS | Nominal inductance [μ H] | Inductance tolerance | Q (min.) | Self-resonant frequency [MHz] (min.) | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Measuring frequency [MHz] |
|--------------|------|----------------------------------|-------------------------|-------------|--|--------------------------------------|-----------------------------|------------------------------|
| LH L 08□1R0N | RoHS | 1.0 | ±30% | 40 | 76 | 0.013 | 4.7 | 7.96 |
| LH L 08□1R5M | RoHS | 1.5 | ±20% | 40 | 65 | 0.014 | 4.4 | 7.96 |
| LH L 08□2R2M | RoHS | 2.2 | ±20% | 40 | 56 | 0.017 | 4.1 | 7.96 |
| LH L 08□2R7M | RoHS | 2.7 | ±20% | 40 | 48 | 0.019 | 3.5 | 7.96 |
| LH L 08□3R3M | RoHS | 3.3 | ±20% | 40 | 41 | 0.021 | 3.2 | 7.96 |
| LH L 08□3R9M | RoHS | 3.9 | ±20% | 40 | 33 | 0.024 | 3.1 | 7.96 |
| LH L 08□4R7M | RoHS | 4.7 | ±20% | 40 | 30 | 0.025 | 3.0 | 7.96 |
| LH L 08□5R6M | RoHS | 5.6 | ±20% | 40 | 23 | 0.028 | 2.9 | 7.96 |
| LH L 08□6R8M | RoHS | 6.8 | ±20% | 40 | 21 | 0.030 | 2.8 | 7.96 |
| LH L 08□8R2M | RoHS | 8.2 | ±20% | 40 | 19 | 0.034 | 2.5 | 7.96 |
| LH L 08□100K | RoHS | 10 | ±10% | 65 | 17 | 0.041 | 2.4 | 2.52 |
| LH L 08□120K | RoHS | 12 | ±10% | 65 | 16 | 0.044 | 2.3 | 2.52 |
| LH L 08□150K | RoHS | 15 | ±10% | 50 | 13 | 0.053 | 2.0 | 2.52 |
| LH L 08□180K | RoHS | 18 | ±10% | 50 | 12 | 0.060 | 1.9 | 2.52 |
| LH L 08□220K | RoHS | 22 | ±10% | 50 | 11 | 0.068 | 1.8 | 2.52 |
| LH L 08□270K | RoHS | 27 | ±10% | 50 | 10 | 0.091 | 1.5 | 2.52 |
| LH L 08□330K | RoHS | 33 | ±10% | 40 | 8.8 | 0.10 | 1.4 | 2.52 |
| LH L 08□390K | RoHS | 39 | ±10% | 40 | 8.4 | 0.12 | 1.3 | 2.52 |
| LH L 08□470K | RoHS | 47 | ±10% | 40 | 8.2 | 0.15 | 1.2 | 2.52 |
| LH L 08□560K | RoHS | 56 | ±10% | 40 | 7.9 | 0.17 | 1.1 | 2.52 |
| LH L 08□680K | RoHS | 68 | ±10% | 35 | 7.0 | 0.20 | 1.0 | 2.52 |
| LH L 08□820K | RoHS | 82 | ±10% | 35 | 6.5 | 0.22 | 0.90 | 2.52 |
| LH L 08□101K | RoHS | 100 | ±10% | 25 | 5.7 | 0.32 | 0.79 | 0.796 |
| LH L 08□121K | RoHS | 120 | ±10% | 25 | 5.2 | 0.36 | 0.70 | 0.796 |
| LH L 08□151K | RoHS | 150 | ±10% | 20 | 4.7 | 0.41 | 0.64 | 0.796 |
| LH L 08□181K | RoHS | 180 | ±10% | 35 | 4.2 | 0.66 | 0.60 | 0.796 |
| LH L 08□221K | RoHS | 220 | ±10% | 35 | 3.7 | 0.73 | 0.53 | 0.796 |
| LH L 08□271K | RoHS | 270 | ±10% | 25 | 3.5 | 0.85 | 0.51 | 0.796 |
| LH L 08□331K | RoHS | 330 | ±10% | 25 | 3.2 | 0.97 | 0.44 | 0.796 |
| LH L 08□391K | RoHS | 390 | ±10% | 20 | 2.9 | 1.1 | 0.41 | 0.796 |
| LH L 08□471K | RoHS | 470 | ±10% | 25 | 2.4 | 1.3 | 0.38 | 0.796 |
| LH L 08□561K | RoHS | 560 | ±10% | 25 | 2.2 | 1.5 | 0.35 | 0.796 |
| LH L 08□681K | RoHS | 680 | ±10% | 25 | 2.0 | 1.8 | 0.32 | 0.796 |
| LH L 08□821K | RoHS | 820 | ±10% | 30 | 1.6 | 2.3 | 0.30 | 0.796 |
| LH L 08□102J | RoHS | 1000 | ±5% | 55 | 1.5 | 2.7 | 0.25 | 0.252 |
| LH L 08□122J | RoHS | 1200 | ±5% | 45 | 1.4 | 3.2 | 0.22 | 0.252 |
| LH L 08□152J | RoHS | 1500 | ±5% | 55 | 1.3 | 4.1 | 0.20 | 0.252 |
| LH L 08□182J | RoHS | 1800 | ±5% | 55 | 1.2 | 4.8 | 0.19 | 0.252 |
| LH L 08□222J | RoHS | 2200 | ±5% | 55 | 1.1 | 5.6 | 0.16 | 0.252 |
| LH L 08□272J | RoHS | 2700 | ±5% | 55 | 1.0 | 7.5 | 0.15 | 0.252 |
| LH L 08□332J | RoHS | 3300 | ±5% | 55 | 0.85 | 8.5 | 0.14 | 0.252 |
| LH L 08□392J | RoHS | 3900 | ±5% | 55 | 0.78 | 9.7 | 0.11 | 0.252 |
| LH L 08□472J | RoHS | 4700 | ±5% | 65 | 0.68 | 14 | 0.10 | 0.252 |
| LH L 08□562J | RoHS | 5600 | ±5% | 65 | 0.62 | 16 | 0.093 | 0.252 |
| LH L 08□682J | RoHS | 6800 | ±5% | 65 | 0.61 | 18 | 0.092 | 0.252 |
| LH L 08□822J | RoHS | 8200 | ±5% | 65 | 0.60 | 20 | 0.084 | 0.252 |
| LH L 08□103J | RoHS | 10000 | ±5% | 60 | 0.48 | 32 | 0.070 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□123J | RoHS | 12000 | ±5% | 60 | 0.44 | 36 | 0.064 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□153J | RoHS | 15000 | ±5% | 60 | 0.35 | 62 | 0.051 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□183J | RoHS | 18000 | ±5% | 60 | 0.30 | 72 | 0.048 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□223J | RoHS | 22000 | ±5% | 60 | 0.28 | 82 | 0.044 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□273J | RoHS | 27000 | ±5% | 60 | 0.25 | 90 | 0.042 | L: 1kHz, Q: 0.0796MHz |
| LH L 08□333J | RoHS | 33000 | ±5% | 60 | 0.23 | 100 | 0.040 | L: 1kHz, Q: 0.0796MHz |

□ Please specify the packaging code. (TB: Taping, NB: Bulk)

● LHL10

| Parts number | EHS | Nominal inductance [μH] | Inductance tolerance | Q (min.) | Self-resonant frequency [MHz] (min.) | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Measuring frequency [MHz] |
|--------------|------|----------------------------|-------------------------|-------------|--|-----------------------------|-----------------------------|------------------------------|
| LH L 10□3R3M | RoHS | 3.3 | ±20% | 50 | 46 | 0.019 | 4.2 | 7.96 |
| LH L 10□3R9M | RoHS | 3.9 | ±20% | 50 | 40 | 0.022 | 4.1 | 7.96 |
| LH L 10□4R7M | RoHS | 4.7 | ±20% | 50 | 38 | 0.024 | 4.0 | 7.96 |
| LH L 10□5R6M | RoHS | 5.6 | ±20% | 50 | 34 | 0.025 | 3.8 | 7.96 |
| LH L 10□6R8M | RoHS | 6.8 | ±20% | 50 | 30 | 0.028 | 3.4 | 7.96 |
| LH L 10□8R2M | RoHS | 8.2 | ±20% | 50 | 24 | 0.031 | 3.3 | 7.96 |
| LH L 10□100K | RoHS | 10 | ±10% | 90 | 19 | 0.034 | 3.2 | 2.52 |
| LH L 10□120K | RoHS | 12 | ±10% | 90 | 16 | 0.038 | 2.8 | 2.52 |
| LH L 10□150K | RoHS | 15 | ±10% | 90 | 12 | 0.042 | 2.6 | 2.52 |
| LH L 10□180K | RoHS | 18 | ±10% | 90 | 9.2 | 0.046 | 2.4 | 2.52 |
| LH L 10□220K | RoHS | 22 | ±10% | 60 | 8.6 | 0.061 | 2.1 | 2.52 |
| LH L 10□270K | RoHS | 27 | ±10% | 60 | 7.1 | 0.069 | 2.0 | 2.52 |
| LH L 10□330K | RoHS | 33 | ±10% | 60 | 6.8 | 0.078 | 1.9 | 2.52 |
| LH L 10□390K | RoHS | 39 | ±10% | 60 | 6.7 | 0.085 | 1.8 | 2.52 |
| LH L 10□470K | RoHS | 47 | ±10% | 50 | 6.2 | 0.093 | 1.7 | 2.52 |
| LH L 10□560K | RoHS | 56 | ±10% | 50 | 5.2 | 0.10 | 1.6 | 2.52 |
| LH L 10□680K | RoHS | 68 | ±10% | 40 | 4.9 | 0.12 | 1.5 | 2.52 |
| LH L 10□820K | RoHS | 82 | ±10% | 40 | 4.7 | 0.13 | 1.4 | 2.52 |
| LH L 10□101K | RoHS | 100 | ±10% | 40 | 3.8 | 0.18 | 1.2 | 0.796 |
| LH L 10□121K | RoHS | 120 | ±10% | 40 | 3.2 | 0.25 | 1.0 | 0.796 |
| LH L 10□151K | RoHS | 150 | ±10% | 40 | 2.9 | 0.29 | 0.95 | 0.796 |
| LH L 10□181K | RoHS | 180 | ±10% | 40 | 2.6 | 0.40 | 0.80 | 0.796 |
| LH L 10□221K | RoHS | 220 | ±10% | 40 | 2.3 | 0.44 | 0.75 | 0.796 |
| LH L 10□271K | RoHS | 270 | ±10% | 30 | 2.1 | 0.50 | 0.70 | 0.796 |
| LH L 10□331K | RoHS | 330 | ±10% | 30 | 2.0 | 0.56 | 0.68 | 0.796 |
| LH L 10□391K | RoHS | 390 | ±10% | 30 | 1.8 | 0.62 | 0.63 | 0.796 |
| LH L 10□471K | RoHS | 470 | ±10% | 30 | 1.7 | 0.84 | 0.57 | 0.796 |
| LH L 10□561K | RoHS | 560 | ±10% | 30 | 1.5 | 0.93 | 0.52 | 0.796 |
| LH L 10□681K | RoHS | 680 | ±10% | 30 | 1.4 | 1.0 | 0.48 | 0.796 |
| LH L 10□821K | RoHS | 820 | ±10% | 30 | 1.3 | 1.4 | 0.42 | 0.796 |
| LH L 10□102J | RoHS | 1000 | ±5% | 50 | 1.2 | 1.8 | 0.41 | 0.252 |
| LH L 10□122J | RoHS | 1200 | ±5% | 50 | 0.87 | 2.3 | 0.33 | 0.252 |
| LH L 10□152J | RoHS | 1500 | ±5% | 50 | 0.83 | 2.7 | 0.30 | 0.252 |
| LH L 10□182J | RoHS | 1800 | ±5% | 50 | 0.75 | 3.0 | 0.29 | 0.252 |
| LH L 10□222J | RoHS | 2200 | ±5% | 50 | 0.70 | 3.9 | 0.25 | 0.252 |
| LH L 10□272J | RoHS | 2700 | ±5% | 50 | 0.67 | 4.3 | 0.24 | 0.252 |
| LH L 10□332J | RoHS | 3300 | ±5% | 50 | 0.56 | 5.8 | 0.21 | 0.252 |
| LH L 10□392J | RoHS | 3900 | ±5% | 50 | 0.54 | 6.4 | 0.20 | 0.252 |
| LH L 10□472J | RoHS | 4700 | ±5% | 50 | 0.49 | 7.1 | 0.19 | 0.252 |
| LH L 10□562J | RoHS | 5600 | ±5% | 50 | 0.41 | 9.0 | 0.17 | 0.252 |
| LH L 10□682J | RoHS | 6800 | ±5% | 50 | 0.38 | 10 | 0.16 | 0.252 |
| LH L 10□822J | RoHS | 8200 | ±5% | 50 | 0.36 | 12 | 0.15 | 0.252 |
| LH L 10□103J | RoHS | 10000 | ±5% | 60 | 0.29 | 19 | 0.12 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□123J | RoHS | 12000 | ±5% | 60 | 0.27 | 21 | 0.11 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□153J | RoHS | 15000 | ±5% | 60 | 0.24 | 34 | 0.090 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□183J | RoHS | 18000 | ±5% | 60 | 0.21 | 38 | 0.081 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□223J | RoHS | 22000 | ±5% | 60 | 0.20 | 43 | 0.075 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□273J | RoHS | 27000 | ±5% | 40 | 0.15 | 67 | 0.060 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□333J | RoHS | 33000 | ±5% | 40 | 0.14 | 76 | 0.056 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□393J | RoHS | 39000 | ±5% | 40 | 0.13 | 84 | 0.053 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□473J | RoHS | 47000 | ±5% | 40 | 0.12 | 96 | 0.050 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□563J | RoHS | 56000 | ±5% | 30 | 0.10 | 170 | 0.036 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□683J | RoHS | 68000 | ±5% | 30 | 0.095 | 200 | 0.035 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□823J | RoHS | 82000 | ±5% | 30 | 0.088 | 210 | 0.033 | L: 1kHz, Q: 0.0796MHz |
| LH L 10□104J | RoHS | 100000 | ±5% | 30 | 0.085 | 240 | 0.031 | L: 1kHz, Q: 0.0252MHz |
| LH L 10□124J | RoHS | 120000 | ±5% | 30 | 0.070 | 260 | 0.030 | L: 1kHz, Q: 0.0252MHz |
| LH L 10□154J | RoHS | 150000 | ±5% | 30 | 0.069 | 300 | 0.028 | L: 1kHz, Q: 0.0252MHz |

□ Please specify the packaging code. (TB: Taping, NB: Bulk)

LHLC08

| Parts number | EHS | Nominal inductance [μ H] | Inductance tolerance | Q (min.) | Self-resonant frequency [MHz] (min.) | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Measuring frequency [MHz] |
|--------------|------|----------------------------------|-------------------------|-------------|--|--------------------------------------|-----------------------------|------------------------------|
| LH LC08□1R0N | RoHS | 1.0 | ±30% | 40 | 76 | 0.013 | 5.4 | 7.96 |
| LH LC08□1R5M | RoHS | 1.5 | ±20% | 40 | 65 | 0.014 | 5.2 | 7.96 |
| LH LC08□2R2M | RoHS | 2.2 | ±20% | 40 | 56 | 0.017 | 4.8 | 7.96 |
| LH LC08□2R7M | RoHS | 2.7 | ±20% | 40 | 48 | 0.019 | 4.2 | 7.96 |
| LH LC08□3R3M | RoHS | 3.3 | ±20% | 40 | 41 | 0.021 | 3.8 | 7.96 |
| LH LC08□3R9M | RoHS | 3.9 | ±20% | 40 | 33 | 0.024 | 3.7 | 7.96 |
| LH LC08□4R7M | RoHS | 4.7 | ±20% | 40 | 30 | 0.025 | 3.6 | 7.96 |
| LH LC08□5R6M | RoHS | 5.6 | ±20% | 40 | 23 | 0.028 | 3.5 | 7.96 |
| LH LC08□6R8M | RoHS | 6.8 | ±20% | 40 | 21 | 0.030 | 3.4 | 7.96 |
| LH LC08□8R2M | RoHS | 8.2 | ±20% | 40 | 19 | 0.034 | 3.0 | 7.96 |
| LH LC08□100K | RoHS | 10 | ±10% | 65 | 17 | 0.041 | 2.9 | 2.52 |
| LH LC08□120K | RoHS | 12 | ±10% | 65 | 16 | 0.044 | 2.8 | 2.52 |
| LH LC08□150K | RoHS | 15 | ±10% | 50 | 13 | 0.053 | 2.6 | 2.52 |
| LH LC08□180K | RoHS | 18 | ±10% | 50 | 12 | 0.060 | 2.4 | 2.52 |
| LH LC08□220K | RoHS | 22 | ±10% | 50 | 11 | 0.068 | 2.3 | 2.52 |
| LH LC08□270K | RoHS | 27 | ±10% | 50 | 10 | 0.091 | 2.0 | 2.52 |
| LH LC08□330K | RoHS | 33 | ±10% | 40 | 8.8 | 0.10 | 1.9 | 2.52 |
| LH LC08□390K | RoHS | 39 | ±10% | 40 | 8.4 | 0.12 | 1.7 | 2.52 |
| LH LC08□470K | RoHS | 47 | ±10% | 40 | 8.2 | 0.15 | 1.5 | 2.52 |
| LH LC08□560K | RoHS | 56 | ±10% | 40 | 7.9 | 0.17 | 1.4 | 2.52 |
| LH LC08□680K | RoHS | 68 | ±10% | 35 | 7.0 | 0.20 | 1.3 | 2.52 |
| LH LC08□820K | RoHS | 82 | ±10% | 35 | 6.5 | 0.22 | 1.2 | 2.52 |
| LH LC08□101K | RoHS | 100 | ±10% | 25 | 5.7 | 0.32 | 1.0 | 0.796 |
| LH LC08□121K | RoHS | 120 | ±10% | 25 | 5.2 | 0.36 | 0.96 | 0.796 |
| LH LC08□151K | RoHS | 150 | ±10% | 20 | 4.7 | 0.41 | 0.88 | 0.796 |
| LH LC08□181K | RoHS | 180 | ±10% | 35 | 4.2 | 0.66 | 0.71 | 0.796 |
| LH LC08□221K | RoHS | 220 | ±10% | 35 | 3.7 | 0.73 | 0.66 | 0.796 |
| LH LC08□271K | RoHS | 270 | ±10% | 25 | 3.5 | 0.85 | 0.63 | 0.796 |
| LH LC08□331K | RoHS | 330 | ±10% | 25 | 3.2 | 0.97 | 0.59 | 0.796 |
| LH LC08□391K | RoHS | 390 | ±10% | 20 | 2.9 | 1.1 | 0.55 | 0.796 |
| LH LC08□471K | RoHS | 470 | ±10% | 25 | 2.4 | 1.3 | 0.49 | 0.796 |
| LH LC08□561K | RoHS | 560 | ±10% | 25 | 2.2 | 1.5 | 0.47 | 0.796 |
| LH LC08□681K | RoHS | 680 | ±10% | 25 | 2.0 | 1.8 | 0.44 | 0.796 |
| LH LC08□821K | RoHS | 820 | ±10% | 30 | 1.6 | 2.3 | 0.38 | 0.796 |
| LH LC08□102J | RoHS | 1000 | ±5% | 55 | 1.5 | 2.7 | 0.35 | 0.252 |
| LH LC08□122J | RoHS | 1200 | ±5% | 45 | 1.4 | 3.2 | 0.31 | 0.252 |
| LH LC08□152J | RoHS | 1500 | ±5% | 55 | 1.3 | 4.1 | 0.29 | 0.252 |
| LH LC08□182J | RoHS | 1800 | ±5% | 55 | 1.2 | 4.8 | 0.26 | 0.252 |
| LH LC08□222J | RoHS | 2200 | ±5% | 55 | 1.1 | 5.6 | 0.23 | 0.252 |
| LH LC08□272J | RoHS | 2700 | ±5% | 55 | 1.0 | 7.5 | 0.21 | 0.252 |
| LH LC08□332J | RoHS | 3300 | ±5% | 55 | 0.85 | 8.5 | 0.19 | 0.252 |
| LH LC08□392J | RoHS | 3900 | ±5% | 55 | 0.78 | 9.7 | 0.18 | 0.252 |
| LH LC08□472J | RoHS | 4700 | ±5% | 65 | 0.68 | 14 | 0.16 | 0.252 |
| LH LC08□562J | RoHS | 5600 | ±5% | 65 | 0.62 | 16 | 0.15 | 0.252 |
| LH LC08□682J | RoHS | 6800 | ±5% | 65 | 0.61 | 18 | 0.14 | 0.252 |
| LH LC08□822J | RoHS | 8200 | ±5% | 65 | 0.60 | 20 | 0.13 | 0.252 |
| LH LC08□103J | RoHS | 10000 | ±5% | 60 | 0.48 | 32 | 0.11 | L:1kHz, Q:0.0796MHz |
| LH LC08□123J | RoHS | 12000 | ±5% | 60 | 0.44 | 36 | 0.084 | L:1kHz, Q:0.0796MHz |
| LH LC08□153J | RoHS | 15000 | ±5% | 60 | 0.35 | 62 | 0.068 | L:1kHz, Q:0.0796MHz |
| LH LC08□183J | RoHS | 18000 | ±5% | 60 | 0.30 | 72 | 0.066 | L:1kHz, Q:0.0796MHz |
| LH LC08□223J | RoHS | 22000 | ±5% | 60 | 0.28 | 82 | 0.057 | L:1kHz, Q:0.0796MHz |
| LH LC08□273J | RoHS | 27000 | ±5% | 60 | 0.25 | 90 | 0.054 | L:1kHz, Q:0.0796MHz |
| LH LC08□333J | RoHS | 33000 | ±5% | 60 | 0.23 | 100 | 0.053 | L:1kHz, Q:0.0796MHz |

□ Please specify the packaging code. (TB: Taping, NB: Bulk)

LHLC10

| Parts number | EHS | Nominal inductance [μ H] | Inductance tolerance | Q (min.) | Self-resonant frequency [MHz] (min.) | DC Resistance [Ω] (max.) | Rated current [A] (max.) | Measuring frequency [MHz] |
|--------------|------|----------------------------------|-------------------------|-------------|--|--------------------------------------|-----------------------------|------------------------------|
| LH LC10□3R3M | RoHS | 3.3 | ±20% | 50 | 46 | 0.019 | 5.0 | 7.96 |
| LH LC10□3R9M | RoHS | 3.9 | ±20% | 50 | 40 | 0.022 | 4.8 | 7.96 |
| LH LC10□4R7M | RoHS | 4.7 | ±20% | 50 | 38 | 0.024 | 4.7 | 7.96 |
| LH LC10□5R6M | RoHS | 5.6 | ±20% | 50 | 34 | 0.025 | 4.5 | 7.96 |
| LH LC10□6R8M | RoHS | 6.8 | ±20% | 50 | 30 | 0.028 | 4.1 | 7.96 |
| LH LC10□8R2M | RoHS | 8.2 | ±20% | 50 | 24 | 0.031 | 3.9 | 7.96 |
| LH LC10□100K | RoHS | 10 | ±10% | 90 | 19 | 0.034 | 3.6 | 2.52 |
| LH LC10□120K | RoHS | 12 | ±10% | 90 | 16 | 0.038 | 3.4 | 2.52 |
| LH LC10□150K | RoHS | 15 | ±10% | 90 | 12 | 0.042 | 3.2 | 2.52 |
| LH LC10□180K | RoHS | 18 | ±10% | 90 | 9.2 | 0.046 | 3.0 | 2.52 |
| LH LC10□220K | RoHS | 22 | ±10% | 60 | 8.6 | 0.061 | 2.8 | 2.52 |
| LH LC10□270K | RoHS | 27 | ±10% | 60 | 7.1 | 0.069 | 2.7 | 2.52 |
| LH LC10□330K | RoHS | 33 | ±10% | 60 | 6.8 | 0.078 | 2.6 | 2.52 |
| LH LC10□390K | RoHS | 39 | ±10% | 60 | 6.7 | 0.085 | 2.4 | 2.52 |
| LH LC10□470K | RoHS | 47 | ±10% | 50 | 6.2 | 0.093 | 2.3 | 2.52 |
| LH LC10□560K | RoHS | 56 | ±10% | 50 | 5.2 | 0.10 | 2.1 | 2.52 |
| LH LC10□680K | RoHS | 68 | ±10% | 40 | 4.6 | 0.12 | 2.0 | 2.52 |
| LH LC10□820K | RoHS | 82 | ±10% | 40 | 4.7 | 0.13 | 1.8 | 2.52 |
| LH LC10□101K | RoHS | 100 | ±10% | 40 | 3.8 | 0.18 | 1.5 | 0.796 |
| LH LC10□121K | RoHS | 120 | ±10% | 40 | 3.2 | 0.25 | 1.3 | 0.796 |
| LH LC10□151K | RoHS | 150 | ±10% | 40 | 2.9 | 0.29 | 1.2 | 0.796 |
| LH LC10□181K | RoHS | 180 | ±10% | 40 | 2.6 | 0.40 | 1.0 | 0.796 |
| LH LC10□221K | RoHS | 220 | ±10% | 40 | 2.3 | 0.44 | 0.97 | 0.796 |
| LH LC10□271K | RoHS | 270 | ±10% | 30 | 2.1 | 0.50 | 0.90 | 0.796 |
| LH LC10□331K | RoHS | 330 | ±10% | 30 | 2.0 | 0.56 | 0.86 | 0.796 |
| LH LC10□391K | RoHS | 390 | ±10% | 30 | 1.8 | 0.62 | 0.75 | 0.796 |
| LH LC10□471K | RoHS | 470 | ±10% | 30 | 1.7 | 0.84 | 0.65 | 0.796 |
| LH LC10□561K | RoHS | 560 | ±10% | 30 | 1.5 | 0.93 | 0.61 | 0.796 |
| LH LC10□681K | RoHS | 680 | ±10% | 30 | 1.4 | 1.0 | 0.57 | 0.796 |
| LH LC10□821K | RoHS | 820 | ±10% | 30 | 1.3 | 1.4 | 0.50 | 0.796 |
| LH LC10□102J | RoHS | 1000 | ±5% | 50 | 1.2 | 1.8 | 0.48 | 0.252 |
| LH LC10□122J | RoHS | 1200 | ±5% | 50 | 0.87 | 2.3 | 0.40 | 0.252 |
| LH LC10□152J | RoHS | 1500 | ±5% | 50 | 0.83 | 2.7 | 0.37 | 0.252 |
| LH LC10□182J | RoHS | 1800 | ±5% | 50 | 0.75 | 3.0 | 0.36 | 0.252 |
| LH LC10□222J | RoHS | 2200 | ±5% | 50 | 0.70 | 3.9 | 0.32 | 0.252 |
| LH LC10□272J | RoHS | 2700 | ±5% | 50 | 0.67 | 4.3 | 0.30 | 0.252 |
| LH LC10□332J | RoHS | 3300 | ±5% | 50 | 0.56 | 5.8 | 0.26 | 0.252 |
| LH LC10□392J | RoHS | 3900 | ±5% | 50 | 0.54 | 6.4 | 0.25 | 0.252 |
| LH LC10□472J | RoHS | 4700 | ±5% | 50 | 0.49 | 7.1 | 0.24 | 0.252 |
| LH LC10□562J | RoHS | 5600 | ±5% | 50 | 0.41 | 9.0 | 0.21 | 0.252 |
| LH LC10□682J | RoHS | 6800 | ±5% | 50 | 0.38 | 10 | 0.20 | 0.252 |
| LH LC10□822J | RoHS | 8200 | ±5% | 50 | 0.36 | 12 | 0.18 | 0.252 |
| LH LC10□103J | RoHS | 10000 | ±5% | 60 | 0.29 | 19 | 0.14 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□123J | RoHS | 12000 | ±5% | 60 | 0.27 | 21 | 0.13 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□153J | RoHS | 15000 | ±5% | 60 | 0.24 | 34 | 0.11 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□183J | RoHS | 18000 | ±5% | 60 | 0.21 | 38 | 0.10 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□223J | RoHS | 22000 | ±5% | 60 | 0.20 | 43 | 0.095 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□273J | RoHS | 27000 | ±5% | 40 | 0.15 | 67 | 0.076 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□333J | RoHS | 33000 | ±5% | 40 | 0.14 | 76 | 0.068 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□393J | RoHS | 39000 | ±5% | 40 | 0.13 | 84 | 0.065 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□473J | RoHS | 47000 | ±5% | 40 | 0.12 | 96 | 0.061 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□563J | RoHS | 56000 | ±5% | 30 | 0.10 | 170 | 0.045 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□683J | RoHS | 68000 | ±5% | 30 | 0.095 | 200 | 0.043 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□823J | RoHS | 82000 | ±5% | 30 | 0.088 | 210 | 0.041 | L: 1kHz, Q: 0.0796MHz |
| LH LC10□104J | RoHS | 100000 | ±5% | 30 | 0.085 | 240 | 0.038 | L: 1kHz, Q: 0.0252MHz |
| LH LC10□124J | RoHS | 120000 | ±5% | 30 | 0.070 | 260 | 0.037 | L: 1kHz, Q: 0.0252MHz |
| LH LC10□154J | RoHS | 150000 | ±5% | 30 | 0.069 | 300 | 0.035 | L: 1kHz, Q: 0.0252MHz |

□ Please specify the packaging code. (TB: Taping, NB: Bulk)

RADIAL LEADED INDUCTORS

PACKAGING

① Minimum Quantity

| Type (EIA) | Standard quantity [pcs] | |
|------------|-------------------------|-------|
| | Bulk | Taped |
| LHL 08 | 100 | 1000 |
| LHL 10 | 50 | 500 |
| LHLC08 | 100 | 1000 |
| LHLC10 | 50 | 500 |

② Bulk dimensions

LHL08, LHL10



| Type | Dimensions | | | | |
|-------|-----------------|-----------------|--|--|---|
| | ϕD (max) | H_2 (max) | F^* | l | ϕd |
| LHL08 | 9.0 (0.354) | 9.5 (0.374) | 5.0 ± 1.0 (0.197 ± 0.039) | 5.0 ± 1.0 (0.197 ± 0.039) | 0.6 ± 0.05 (0.024 ± 0.002) |
| LHL10 | 11.0 (0.433) | 14.0 (0.551) | 5.0 ± 1.0 (0.197 ± 0.039) | 5.0 ± 1.0 (0.197 ± 0.039) | 0.6 ± 0.05 (0.024 ± 0.002) |

Unit: mm (inch)

*Measured at the base of the leads.



| | LHL08 | LHL10 |
|----------|---|---|
| D | $\phi 9.0$ max ($\phi 0.354$ max) | $\phi 11.0$ max ($\phi 0.433$ max) |
| H_1 | 30.5 max (1.20 max) | 34.0 max (1.34 max) |
| H | $18.0 + 2.0 / - 0.0$ ($0.709 + 0.079 / - 0.000$) | $18.0 + 2.0 / - 0.0$ ($0.709 + 0.079 / - 0.000$) |
| H_2 | 9.5 max (0.374 max) | 14.0 max (0.551 max) |
| P | 12.7 ± 1.0 (0.500 ± 0.039) | 12.7 ± 1.0 (0.500 ± 0.039) |
| P_0 | $12.7 \pm 0.3^{*1}$ (0.500 ± 0.012) | $12.7 \pm 0.3^{*1}$ (0.500 ± 0.012) |
| P_1 | 3.85 ± 0.7 (0.152 ± 0.028) | 3.85 ± 0.7 (0.152 ± 0.028) |
| P_2 | 6.35 ± 1.3 (0.250 ± 0.051) | 6.35 ± 1.3 (0.250 ± 0.051) |
| F | $5.0 + 0.8 / - 0.2$ ($0.197 + 0.031 / 0.008$) | $5.0 + 0.8 / - 0.2$ ($0.197 + 0.031 / - 0.008$) |
| h | 0.0 ± 2.0 (0.0 ± 0.079) | 0.0 ± 2.0 (0.0 ± 0.079) |
| W | $18.0 + 1.0 / - 0.5$ ($0.709 + 0.039 / - 0.020$) | $18.0 + 1.0 / - 0.5$ ($0.709 + 0.039 / - 0.020$) |
| W_0 | 12.5 min (0.492 min) | 12.5 min (0.492 min) |
| W_1 | 9.0 ± 0.5 (0.354 ± 0.020) | 9.0 ± 0.5 (0.354 ± 0.020) |
| W_2 | 3.0 max ^{*2} (0.118 max) | 3.0 max ^{*2} (0.118 max) |
| D_0 | $\phi 4.0 \pm 0.2$ ($\phi 0.158 \pm 0.008$) | $\phi 4.0 \pm 0.2$ ($\phi 0.158 \pm 0.008$) |
| ϕd | $\phi 0.6 \pm 0.05$ ($\phi 0.024 \pm 0.002$) | $\phi 0.6 \pm 0.05$ ($\phi 0.024 \pm 0.002$) |
| t | 0.6 ± 0.3 (0.024 ± 0.012) | 0.6 ± 0.3 (0.024 ± 0.012) |

Unit: mm (inch)

*1 Accumulated error for 20 pitches is 1mm.

*2 Bonding tape must not protrude from the base tape.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

● LHLC08, LHLC10



| Type | Dimensions | | | | |
|--------|-----------------|-----------------|--|--|---|
| | ϕD (max) | H_2 (max) | F^* | l | ϕd |
| LHLC08 | 9.0 (0.354) | 9.5 (0.374) | 5.0 ± 1.0 (0.197 ± 0.039) | 5.0 ± 1.0 (0.197 ± 0.039) | 0.6 ± 0.05 (0.024 ± 0.002) |
| LHLC10 | 11.0 (0.433) | 14.0 (0.551) | 5.0 ± 1.0 (0.197 ± 0.039) | 5.0 ± 1.0 (0.197 ± 0.039) | 0.6 ± 0.05 (0.024 ± 0.002) |

Unit: mm (inch)

*Measured at the base of the leads.



| | LHLC08 | LHLC10 |
|----------|---|---|
| D | $\phi 9.0 \text{max}$ ($\phi 0.354 \text{max}$) | $\phi 11.0 \text{max}$ ($\phi 0.433 \text{max}$) |
| H_1 | 30.5max (1.20max) | 34.0max (1.34max) |
| H | $18.0 + 2.0 / - 0.0$ ($0.709 + 0.079 / - 0.000$) | $18.0 + 2.0 / - 0.0$ ($0.709 + 0.079 / - 0.000$) |
| H_2 | 9.5max (0.374max) | 14.0max (0.551max) |
| P | 12.7 ± 1.0 (0.500 ± 0.039) | 12.7 ± 1.0 (0.500 ± 0.039) |
| P_0 | $12.7 \pm 0.3^{*1}$ (0.500 ± 0.012) | $12.7 \pm 0.3^{*1}$ (0.500 ± 0.012) |
| P_1 | 3.85 ± 0.7 (0.152 ± 0.028) | 3.85 ± 0.7 (0.152 ± 0.028) |
| P_2 | 6.35 ± 1.3 (0.250 ± 0.051) | 6.35 ± 1.3 (0.250 ± 0.051) |
| F | $5.0 + 0.8 / - 0.2$ ($0.197 + 0.031 / - 0.008$) | $5.0 + 0.8 / - 0.2$ ($0.197 + 0.031 / - 0.008$) |
| H | 0.0 ± 2.0 (0.0 ± 0.079) | 0.0 ± 2.0 (0.0 ± 0.079) |
| W | $18.0 + 1.0 / - 0.5$ ($0.709 + 0.039 / - 0.020$) | $18.0 + 1.0 / - 0.5$ ($0.709 + 0.039 / - 0.020$) |
| W_0 | 12.5min (0.492min) | 12.5min (0.492min) |
| W_1 | 9.0 ± 0.5 (0.354 ± 0.020) | 9.0 ± 0.5 (0.354 ± 0.020) |
| W_2 | 3.0max^{*2} (0.118max) | 3.0max^{*2} (0.118max) |
| D_0 | $\phi 4.0 \pm 0.2$ ($\phi 0.158 \pm 0.008$) | $\phi 4.0 \pm 0.2$ ($\phi 0.158 \pm 0.008$) |
| ϕd | $\phi 0.6 \pm 0.05$ ($\phi 0.024 \pm 0.002$) | $\phi 0.6 \pm 0.05$ ($\phi 0.024 \pm 0.002$) |
| t | 0.6 ± 0.3 (0.024 ± 0.012) | 0.6 ± 0.3 (0.024 ± 0.012) |

Unit: mm (inch)

※1 Accumulated error for 20 pitches is 1mm.

※2 Bonding tape must not protrude from the base tape.

AXIAL LEADED INDUCTORS (CAL Type)、 RADIAL LEADED INDUCTORS (LH Type)、 LEADED FERRITE BEAD INDUCTORS (FB Series A Type/R Type)

RELIABILITY DATA

| 1. Operating temperature Range | | |
|--------------------------------|--|--|
| Specified Value | CAL45 Type | -25 ~ + 105°C |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type | Including self-generated heat |
| | LHL□□□ | |
| | FBA/FBR | |
| 2. Storage temperature Range | | |
| Specified Value | CAL45 Type | -40 ~ + 85°C (Except for taping condition) |
| | LHL□□□ | |
| | FBA/FBR | |
| 3. Rated current | | |
| Specified Value | CAL45 Type | Within the specified tolerance |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : The maximum DC value having inductance within 10% and temperature increase within 40°C by the application of DC bias. | |
| | LHL□□□ : The maximum DC value having inductance decrease within 10% (LHLC08, LHLC10: within 30%) and temperature increase within the following specified temperature by the application of DC bias. Reference temperature : 25°C (LHL08, LHL10) : 40°C (LHLC08, LHLC10) | |
| | FBA/FBR : No disconnection or appearance abnormality by continuous current application for 30 min. Change after the application shall be within ±20% of the initial value. This is not guaranteed for electrical characteristics during current application. | |
| 4. Impedance | | |
| Specified Value | CAL45 Type | Within the specified tolerance |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | FBA/FBR : Measuring equipment : Impedance analyzer (HP4191A) or its equivalent Measuring frequency : Specified frequency | |
| | | |
| 5. Inductance | | |
| Specified Value | CAL45 Type | Within the specified tolerance |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : Measuring equipment : LCR meter (HP4285A + HP42851A or its equivalent) Measuring frequency : Specified frequency | |
| | LHL□□□ : Measuring equipment : LCR meter (HP4285A + HP42851A or its equivalent) : LCR meter (HP4263A) or its equivalent (at 1kHz) | |
| | Measuring frequency : Specified frequency | |
| | | |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| 6. Q | | |
|--------------------------|--|--------------------------------|
| Specified Value | CAL45 Type | |
| | LHL□□□ | Within the specified tolerance |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□ Measuring equipment : LCR meter (HP4285A + HP42851A or its equivalent) : LCR meter (HP4263A) or its equivalent (at 1kHz) Measuring frequency : Specified frequency | |

| 7. DC Resistance | | |
|--------------------------|-----------------------------------|--------------------------------|
| Specified Value | CAL45 Type | |
| | LHL□□□ | Within the specified tolerance |
| | FBA/FBR | |
| Test Methods and Remarks | Measuring equipment : DC ohmmeter | |

| 8. Self resonance frequency | | |
|-----------------------------|---|--------------------------------|
| Specified Value | CAL45 Type | |
| | LHL□□□ | Within the specified tolerance |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□ Measuring equipment : (HP4191A, 4192A) its equivalent | |

| 9. Temperature characteristic | | | | | | | | | | | | | | | |
|-------------------------------|--|---------------------------------|------------------|--------|---|----|---|-------------------------------|---|---------------------------|---|-------------------------------|---|----|--|
| Specified Value | CAL45 Type | | | | | | | | | | | | | | |
| | LHL□□□ | $\Delta L/L$: Within $\pm 7\%$ | | | | | | | | | | | | | |
| | FBA/FBR | | | | | | | | | | | | | | |
| Test Methods and Remarks | Change of maximum inductance deviation in step 1 to 5 | | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th rowspan="2">Step</th> <th>Temperature (°C)</th> </tr> <tr> <th>LHL□□□</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>20</td> </tr> <tr> <td>2</td> <td>Minimum operating temperature</td> </tr> <tr> <td>3</td> <td>20 (Standard temperature)</td> </tr> <tr> <td>4</td> <td>Maximum operating temperature</td> </tr> <tr> <td>5</td> <td>20</td> </tr> </tbody> </table> | Step | Temperature (°C) | LHL□□□ | 1 | 20 | 2 | Minimum operating temperature | 3 | 20 (Standard temperature) | 4 | Maximum operating temperature | 5 | 20 | |
| Step | Temperature (°C) | | | | | | | | | | | | | | |
| | LHL□□□ | | | | | | | | | | | | | | |
| 1 | 20 | | | | | | | | | | | | | | |
| 2 | Minimum operating temperature | | | | | | | | | | | | | | |
| 3 | 20 (Standard temperature) | | | | | | | | | | | | | | |
| 4 | Maximum operating temperature | | | | | | | | | | | | | | |
| 5 | 20 | | | | | | | | | | | | | | |

| 10. Tensile strength test | | | | | | | | | | | | | | | | |
|---|--|--|--------------|----|----|---|-----------|--------------|-------------------------|---|------------|-------------------------|----|-------------------------|----|--|
| Specified Value | CAL45 Type | | | | | | | | | | | | | | | |
| | LHL□□□ | No abnormality such as cut lead, or looseness. | | | | | | | | | | | | | | |
| | FBA/FBR | | | | | | | | | | | | | | | |
| Test Methods and Remarks | <p>CAL45 Type : Apply the stated tensile force progressively in the direction to draw terminal.</p> <table border="1"> <thead> <tr> <th>force (N)</th> <th>duration (s)</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>10</td> </tr> </tbody> </table> <p>LHL□□□ : Apply the stated tensile force progressively in the direction to draw terminal.</p> <table border="1"> <thead> <tr> <th>Nominal wire diameter tensile ϕd (mm)</th> <th>force (N)</th> <th>duration (s)</th> </tr> </thead> <tbody> <tr> <td>$0.3 < \phi d \leq 0.5$</td> <td>5</td> <td rowspan="3">30 \pm 5</td> </tr> <tr> <td>$0.5 < \phi d \leq 0.8$</td> <td>10</td> </tr> <tr> <td>$0.8 < \phi d \leq 1.2$</td> <td>25</td> </tr> </tbody> </table> <p>FBA/FBR : The body of a component shall be fixed and a tensile force of 20 \pm 1N shall be applied to the lead wire in the axial direction of the component during 10 \pm 1 seconds.</p> | force (N) | duration (s) | 10 | 10 | Nominal wire diameter tensile ϕd (mm) | force (N) | duration (s) | $0.3 < \phi d \leq 0.5$ | 5 | 30 \pm 5 | $0.5 < \phi d \leq 0.8$ | 10 | $0.8 < \phi d \leq 1.2$ | 25 | |
| force (N) | duration (s) | | | | | | | | | | | | | | | |
| 10 | 10 | | | | | | | | | | | | | | | |
| Nominal wire diameter tensile ϕd (mm) | force (N) | duration (s) | | | | | | | | | | | | | | |
| $0.3 < \phi d \leq 0.5$ | 5 | 30 \pm 5 | | | | | | | | | | | | | | |
| $0.5 < \phi d \leq 0.8$ | 10 | | | | | | | | | | | | | | | |
| $0.8 < \phi d \leq 1.2$ | 25 | | | | | | | | | | | | | | | |

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| 11. Over current | | |
|--------------------------|---|--|
| Specified Value | CAL45 Type | No emission of smoke no firing. |
| | LHL□□□ | There shall be no scorch or short of wire. LHLC08, LHLC10 : There shall be no firing. |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□·CAL45 Type : Measuring current : Rated current × 2 Duration : 5 min. Number of measuring : one time | |

| 12. Terminal strength : bending | | | | | | | | | | | | | | |
|---|---|--|-------------------------------|---------------|-----------------------|-------------------------|-----|------|-------------------------|---|------|-------------------------|----|-----|
| Specified Value | CAL45 Type | No abnormality such as cut lead, or looseness. | | | | | | | | | | | | |
| | LHL□□□ | | | | | | | | | | | | | |
| | FBA/FBR | | | | | | | | | | | | | |
| Test Methods and Remarks | CAL45 Type : Suspend a weight of specified mass at the end of the terminals and incline the body through the angle of 90 degrees and return it to the initial position. This operation is done over a period of 2-3 sec. Then second bend in the opposite direction shall be made. Number of bends : Two times. | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th>Nominal wire diameter tensile</th> <th>Bending force</th> <th>Mass reference weight</th> </tr> </thead> <tbody> <tr> <td>$0.3 < \phi d \leq 0.5$</td> <td>2.5</td> <td>0.25</td> </tr> <tr> <td>$0.5 < \phi d \leq 0.8$</td> <td>5</td> <td>0.50</td> </tr> </tbody> </table> | | Nominal wire diameter tensile | Bending force | Mass reference weight | $0.3 < \phi d \leq 0.5$ | 2.5 | 0.25 | $0.5 < \phi d \leq 0.8$ | 5 | 0.50 | | | |
| | Nominal wire diameter tensile | Bending force | Mass reference weight | | | | | | | | | | | |
| $0.3 < \phi d \leq 0.5$ | 2.5 | 0.25 | | | | | | | | | | | | |
| $0.5 < \phi d \leq 0.8$ | 5 | 0.50 | | | | | | | | | | | | |
| LHL□□□·FBA/FBR : Suspend a weight of specified mass at the end of the terminals and incline the body through the angle of 90 degrees and return it to the initial position. This operation is done over a period of 2-3 sec. Then second bend in the opposite direction shall be made. Number of bends : Two times. | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Nominal wire diameter tensile</th> <th>Bending force</th> <th>Mass reference weight</th> </tr> </thead> <tbody> <tr> <td>$0.3 < \phi d \leq 0.5$</td> <td>2.5</td> <td>0.25</td> </tr> <tr> <td>$0.5 < \phi d \leq 0.8$</td> <td>5</td> <td>0.5</td> </tr> <tr> <td>$0.8 < \phi d \leq 1.2$</td> <td>10</td> <td>1.0</td> </tr> </tbody> </table> | | | Nominal wire diameter tensile | Bending force | Mass reference weight | $0.3 < \phi d \leq 0.5$ | 2.5 | 0.25 | $0.5 < \phi d \leq 0.8$ | 5 | 0.5 | $0.8 < \phi d \leq 1.2$ | 10 | 1.0 |
| Nominal wire diameter tensile | Bending force | Mass reference weight | | | | | | | | | | | | |
| $0.3 < \phi d \leq 0.5$ | 2.5 | 0.25 | | | | | | | | | | | | |
| $0.5 < \phi d \leq 0.8$ | 5 | 0.5 | | | | | | | | | | | | |
| $0.8 < \phi d \leq 1.2$ | 10 | 1.0 | | | | | | | | | | | | |

| 13. Insulation resistance : between the terminals and body | | |
|--|---|-------------|
| Specified Value | CAL45 Type | 100M Ω min. |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□ : Applied voltage : 500 VDC Duration : 60 sec. | |

| 14. Insulation resistance : between terminals and core | | |
|--|--|-----------|
| Specified Value | CAL45 Type | 1M Ω min. |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | FBA/FBR : Applied voltage : 100 VDC Duration : 60±5 sec. | |

| 15. Withstanding : between the terminals and body | | |
|---|---|--|
| Specified Value | CAL45 Type | No abnormality such as insulation damage |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□ : According to JIS C5101-1. Metal global method Applied voltage : 500 VDC Duration : 60 sec. | |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| 16. DC bias characteristic | | |
|----------------------------|---|-------------------------------|
| Specified Value | CAL45 Type | $\Delta L/L$: Within -10% |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : Measure inductance with application of rated current using LCR meter to compare it with the initial value. | |

| 17. Body strength | | |
|--------------------------|--|--|
| Specified Value | CAL45 Type | No abnormality as damage. |
| | LHL□□□ | |
| | FBA/FBR | No abnormality such as cracks on body. |
| Test Methods and Remarks | <p>CAL45 Type :</p> <p>Applied force : 50N Duration : 10 sec. Speed : Shall attain to specified force in 2 sec.</p> <p>FBA :</p> <p>Applied force : 50 ± 3N Duration : 30 ± 1 sec.</p>  | |

| 18. Resistance to vibration | | |
|-----------------------------|---|--|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 5\%$ |
| | LHL□□□ | Appearance : No abnormality $\Delta L/L$: Within $\pm 5\%$ Q change : Within $\pm 30\%$ |
| | FBA/FBR | Appearance : No abnormality Impedance change : Within $\pm 20\%$ |
| Test Methods and Remarks | <p>CAL45 Type :</p> <p>Directions : 2 hrs each in X, Y and Z directions total : 6hrs. Frequency range : 10 to 55 to 10Hz (1min.) Amplitude : 1.5mm Mounting method : Soldering onto printed board. Recovery : At least 1hr of recovery under the standard condition after the test, followed by the measurement within 2hrs.</p> <p>LHL□□□·FBA/FBR :</p> <p>Directions : 2 hrs each in X, Y and Z directions total : 6hrs. Frequency range : 10 to 55 to 10Hz (1min.) Amplitude : 1.5mm Mounting method : Soldering onto printed board.</p> | |

| 19. Resistance to shock | | |
|--------------------------|---|--|
| Specified Value | CAL45 Type | No significant abnormality in appearance |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | <p>CAL45 Type :</p> <p>Drop test</p> <p>Impact material : concrete or vinyl tile Height : 1m Total number of drops : 10 times</p> | |

| 20. Solderability | | |
|--------------------------|---|--|
| Specified Value | CAL45 Type | At least 75% of terminal electrode is covered by new solder. |
| | LHL□□□ | At least 75% of terminal electrode is covered by new solder. |
| | FBA/FBR | At least 90% of terminal electrode is covered by new solder. |
| Test Methods and Remarks | CAL45 Type : Solder temperature : 230±5°C Duration : 2±0.5 sec. LHL□□□ : Solder temperature : 235±5°C Duration : 2±0.5 sec. Immersion depth : Up to 1.5mm from bottom of case. FBA/FBR : Solder temperature : 230±5°C Duration : 3±1 sec. Immersion depth : Up to 1.5mm from terminal root. | |

| 21. Resistance to soldering heat | | |
|----------------------------------|--|--|
| Specified Value | CAL45 Type | ΔL/L : Within ±5% |
| | LHL□□□ | No significant abnormality in appearance Inductance change : Within ±5% Q change : Within ±30% |
| | FBA/FBR | No significant abnormality in appearance Impedance change : Within ±20% |
| Test Methods and Remarks | CAL45 Type : Solder temperature : 270±5°C Duration : 5±0.5 sec. One time Immersed conditions : Inserted into substrate with t=1.6mm Recovery : At least 1hr of recovery under the standard condition after the test, followed by the measurement within 2hrs. LHL□□□ : Solder bath method : Solder temperature : 260±5°C Duration : 10±1 sec. : Up to 1.5mm from the bottom of case. Manual soldering : Solder temperature : 350±10°C (At the tip of soldering iron) Duration : 5±1 sec. : Up to 1.5mm from the bottom of case. Caution : No excessive pressing shall be applied to terminals. Recovery : 1 to 2hrs of recovery under the standard condition after the test. FBA/FBR : Solder bath method: Condition 1 : Solder temperature : 260±5°C Duration : 10±1 sec. Immersion depth : Up to 1.5mm from the terminal root. Condition 2 : Solder temperature : 350±5°C Duration : 3±1 sec. Immersion depth : Up to 1.5mm from the terminal root. Recovery : 3hrs of recovery under the standard condition after the test. | |

| 22. Resistance to solvent | | |
|---------------------------|--|--|
| Specified Value | CAL45 Type | Please avoid the ultrasonic cleaning of this product. |
| | LHL□□□ | |
| | FBA/FBR | No significant abnormality in appearance Impedance change : Within ±20% |
| Test Methods and Remarks | FBA/FBR : Solvent temperature : 20~25°C Duration : 30±5 sec. Solvent type : Acetone Recovery : 3hrs of recovery under the standard condition after the test. | |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| 23. Thermal shock | | | | | | | | | | | | | | | | | |
|---|---|--|------------------|-----------------|-------------------------------|------------|-----------|------------------|------------------|----------|-------------------------------|------------|-----------|------------------|------------------|----------|--|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 10\%$ | | | | | | | | | | | | | | | |
| | LHL□□□ | Appearance : No abnormality Inductance change : Within $\pm 10\%$ Q change : Within $\pm 30\%$ | | | | | | | | | | | | | | | |
| | FBA/FBR | Appearance : No abnormality Impedance change : Within $\pm 20\%$ | | | | | | | | | | | | | | | |
| Test Methods and Remarks | CAL45 Type: Conditions for 1 cycle | | | | | | | | | | | | | | | | |
| | <table border="1"> <thead> <tr> <th>Step</th> <th>Temperature (°C)</th> <th>Duration (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>$-25+0/-3$</td> <td>30 ± 3</td> </tr> <tr> <td>2</td> <td>Room temperature</td> <td>Within 3</td> </tr> <tr> <td>3</td> <td>$+85+2/-0$</td> <td>30 ± 3</td> </tr> <tr> <td>4</td> <td>Room temperature</td> <td>Within 3</td> </tr> </tbody> </table> | Step | Temperature (°C) | Duration (min.) | 1 | $-25+0/-3$ | 30 ± 3 | 2 | Room temperature | Within 3 | 3 | $+85+2/-0$ | 30 ± 3 | 4 | Room temperature | Within 3 | |
| | Step | Temperature (°C) | Duration (min.) | | | | | | | | | | | | | | |
| | 1 | $-25+0/-3$ | 30 ± 3 | | | | | | | | | | | | | | |
| | 2 | Room temperature | Within 3 | | | | | | | | | | | | | | |
| 3 | $+85+2/-0$ | 30 ± 3 | | | | | | | | | | | | | | | |
| 4 | Room temperature | Within 3 | | | | | | | | | | | | | | | |
| Number of cycles : 5 cycles | | | | | | | | | | | | | | | | | |
| Recovery : At least 1hr of recovery under the standard condition after the removal from test chamber, followed by the measurement within 2hrs. | | | | | | | | | | | | | | | | | |
| LHL□□□•FBA/FBR: According to JIS C60068-2-14. Conditions for 1 cycle | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th>Step</th> <th>Temperature (°C)</th> <th>Duration (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Minimum operating temperature</td> <td>30 ± 3</td> </tr> <tr> <td>2</td> <td>Room temperature</td> <td>Within 3</td> </tr> <tr> <td>3</td> <td>Maximum operating temperature</td> <td>30 ± 3</td> </tr> <tr> <td>4</td> <td>Room temperature</td> <td>Within 3</td> </tr> </tbody> </table> | Step | Temperature (°C) | Duration (min.) | 1 | Minimum operating temperature | 30 ± 3 | 2 | Room temperature | Within 3 | 3 | Maximum operating temperature | 30 ± 3 | 4 | Room temperature | Within 3 | | |
| Step | Temperature (°C) | Duration (min.) | | | | | | | | | | | | | | | |
| 1 | Minimum operating temperature | 30 ± 3 | | | | | | | | | | | | | | | |
| 2 | Room temperature | Within 3 | | | | | | | | | | | | | | | |
| 3 | Maximum operating temperature | 30 ± 3 | | | | | | | | | | | | | | | |
| 4 | Room temperature | Within 3 | | | | | | | | | | | | | | | |
| Number of cycles : 10 cycles [LHL□□□] | | | | | | | | | | | | | | | | | |
| Recovery : 5 cycles (FBA/ FBR) : 1 to 2hrs of recovery under the standard condition after the removal from the test chamber. [LHL□□□] : 3hrs of recovery under the standard condition after the removal from the test chamber. (FBA/ FBR) | | | | | | | | | | | | | | | | | |

| 24. Damp heat | | |
|--------------------------|--|---|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 10\%$ |
| | LHL□□□ | |
| | FBA/FBR | Appearance : No abnormality Impedance change : Within $\pm 20\%$ |
| Test Methods and Remarks | CAL45 Type : | |
| | Temperature | : $40\pm 2^{\circ}\text{C}$ |
| | Humidity | : 90~95%RH |
| | Duration | : 1000 hrs |
| | Recovery | : At least 1hr of recovery under the standard removal from test chamber, followed by the measurement within 2hrs. |
| FBA/FBR : | | |
| Temperature | : $60\pm 2^{\circ}\text{C}$ | |
| Humidity | : 90~95%RH | |
| Duration | : 1000 hrs | |
| Recovery | : 3hrs of recovery under the standard condition after the removal from the test chamber. | |

| 25. Loading under damp heat | | |
|-----------------------------|--|--|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 10\%$ |
| | LHL□□□ | Appearance : No abnormality Inductance change : Within $\pm 10\%$ Q change : Within $\pm 30\%$ |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : Temperature : $40 \pm 2^\circ\text{C}$ Humidity : $90 \sim 95\%RH$ Duration : 1000 hrs Applied current : Rated current Recovery : At least 1hr of recovery under the standard removal from test chamber, followed by the measurement within 2hrs. LHL□□□ : Temperature : $40 \pm 2^\circ\text{C}$ Humidity : $90 \sim 95\%RH$ Duration : $1000 + 48 / -0$ hrs Applied current : Rated current Recovery : 1 to 2hrs of recovery under the standard condition after the removal from the test chamber. | |

| 26. Loading at high temperature | | |
|---------------------------------|--|----------------------------------|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 10\%$ |
| | LHL□□□ | |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : Temperature : $85 \pm 2^\circ\text{C}$ Duration : 1000 hrs Applied current : Rated current Recovery : At least 1hr of recovery under the standard removal from test chamber, followed by the measurement within 2hrs. | |

| 27. Low temperature life test | | |
|-------------------------------|--|--|
| Specified Value | CAL45 Type | $\Delta L/L$: Within $\pm 10\%$ |
| | LHL□□□ | Appearance : No abnormality Inductance change : Within $\pm 10\%$ Q change : Within $\pm 30\%$ |
| | FBA/FBR | |
| Test Methods and Remarks | CAL45 Type : Temperature : $-25 \pm 2^\circ\text{C}$ Duration : 1000 hrs Recovery : At least 1hr of recovery under the standard removal from test chamber, followed by the measurement within 2hrs. LHL□□□ : Temperature : $-40 \pm 3^\circ\text{C}$ Duration : $1000 + 48 / -0$ hrs Recovery : 1 to 2hrs of recovery under the standard condition after the removal from the test chamber. | |

| 28. High temperature life test | | |
|--------------------------------|--|--|
| Specified Value | CAL45 Type | |
| | LHL□□□ | Appearance : No abnormality Inductance change : Within $\pm 10\%$ Q change : Within $\pm 30\%$ |
| | FBA/FBR | |
| Test Methods and Remarks | LHL□□□ : Temperature : $105 \pm 2^\circ\text{C}$ Duration : $1000 + 48 / -0$ hrs Recovery : 1 to 2hrs of recovery under the standard condition after the removal from the test chamber. | |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification.
 For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

AXIAL LEADED INDUCTORS (CAL Type)、 RADIAL LEADED INDUCTORS (LH Type)、 LEADED FERRITE BEAD INDUCTORS (FB Series A Type/R Type)

■ PRECAUTIONS

| 1. Circuit Design | |
|---|--|
| Precautions | <p>◆Operating environment</p> <p>1. The products described in this specification are intended for use in general electronic equipment,(office supply equipment, telecommunications systems, measuring equipment, and household equipment). They are not intended for use in mission-critical equipment or systems requiring special quality and high reliability (traffic systems, safety equipment, aerospace systems, nuclear control systems and medical equipment including life-support systems,) where product failure might result in loss of life, injury or damage. For such uses, contact TAIYO YUDEN Sales Department in advance.</p> |
| 2. PCB Design | |
| Precautions | <p>◆Design</p> <p>1. Please design insertion pitches as matching to that of leads of the component on PCBs.</p> |
| Technical considerations | <p>◆Design</p> <p>1. When Inductors are mounted onto a PC board, hole dimensions on the board should match the lead pitch of the component, if not, it will cause breakage of the terminals or cracking of terminal roots covered with resin as excess stress travels through the terminal legs.</p> |
| 3. Considerations for automatic placement | |
| Precautions | <p>◆Adjustment of mounting machine</p> <p>1. Excessive impact load should not be imposed on the products when mounting onto the PC boards. 2. Mounting and soldering conditions should be checked beforehand.</p> |
| Technical considerations | <p>◆Adjustment of mounting machine</p> <p>1. When installing products, care should be taken not to apply distortion stress as it may deform the products.</p> |
| 4. Soldering | |
| Precautions | <p>◆Wave soldering</p> <p>1. Please refer to the specifications in the catalog for a wave soldering. 2. Do not immerse the entire inductor in the flux during the soldering operation.</p> <p>◆Lead free soldering</p> <p>1. When using products with lead free soldering, we request to use them after confirming adhesion, temperature of resistance to soldering heat, soldering etc sufficiently.</p> <p>◆Recommended conditions for using a soldering iron:</p> <ul style="list-style-type: none"> •Put the soldering iron on the land-pattern. •Soldering iron's temperature – Below 350°C •Duration – 3 seconds or less •The soldering iron should not directly touch the inductor. <p>◆Reflow soldering</p> <p>1. As for reflow soldering, please contact our sales staff.</p> |
| Technical considerations | <p>◆Lead free soldering</p> <p>1. If products are used beyond the range of the recommended conditions, heat stresses may deform the products, and consequently degrade the reliability of the products.</p> <p>◆Recommended conditions for using a soldering iron</p> <p>If products are used beyond the range of the recommended conditions, heat stresses may deform the products, and consequently degrade the reliability of the products.</p> |
| 5. Cleaning | |
| Precautions | <p>◆Cleaning conditions</p> <p>1. CAL type, LH type Please do not do cleaning by a supersonic wave.</p> |
| Technical considerations | <p>◆Cleaning conditions</p> <p>1. CAL type, LH type, If washing by supersonic waves, supersonic waves may deform products.</p> |

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our specification. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our Web site (<http://www.ty-top.com/>).

| 6. Handling | |
|--------------------------|---|
| Precautions | <ul style="list-style-type: none"> ◆ Handling <ol style="list-style-type: none"> 1. Keep the inductors away from all magnets and magnetic objects. ◆ Mechanical considerations <ol style="list-style-type: none"> 1. Please do not give the inductors any excessive mechanical shocks. 2. LH type <ul style="list-style-type: none"> If inductors are dropped onto the floor or a hard surface they should not be used. ◆ Packing <ol style="list-style-type: none"> 1. Please do not give the inductors any excessive mechanical shocks. <ul style="list-style-type: none"> In loading, please pay attention to handling indication mentioned in a packing box (a loading direction / number of maximum loading / fragile item). |
| Technical considerations | <ul style="list-style-type: none"> ◆ Handling <ol style="list-style-type: none"> 1. There is a case that a characteristic varies with magnetic influence. ◆ Mechanical considerations <ol style="list-style-type: none"> 1. There is a case to be damaged by a mechanical shock. 2. LH type <ul style="list-style-type: none"> There is a case to be broken by a fall. ◆ Packing <ol style="list-style-type: none"> 1. There is a case that a lead wire could be deformed by a fall or an excessive shock. |
| 7. Storage conditions | |
| Precautions | <ul style="list-style-type: none"> ◆ Storage <ol style="list-style-type: none"> 1. To maintain the solderability of terminal electrodes and to keep the packing material in good condition, temperature and humidity in the storage area should be controlled. <ul style="list-style-type: none"> Recommended conditions • Ambient temperature 0~40°C • Humidity Below 70% RH <p>The ambient temperature must be kept below 30°C. Even under ideal storage conditions, solderability of products electrodes may decrease as time passes.</p> <p>For this reason, inductors should be used within one year from the time of delivery.</p> <p>In case of storage over 6 months, solderability shall be checked before actual usage.</p> |
| Technical considerations | <ul style="list-style-type: none"> ◆ Storage <ol style="list-style-type: none"> 1. Under a high temperature and humidity environment, problems such as reduced solderability caused by oxidation of terminal electrodes and deterioration of taping/packaging materials may take place. |

Компания «Океан Электроники» предлагает заключение долгосрочных отношений при поставках импортных электронных компонентов на взаимовыгодных условиях!

Наши преимущества:

- Поставка оригинальных импортных электронных компонентов напрямую с производств Америки, Европы и Азии, а так же с крупнейших складов мира;
- Широкая линейка поставок активных и пассивных импортных электронных компонентов (более 30 млн. наименований);
- Поставка сложных, дефицитных, либо снятых с производства позиций;
- Оперативные сроки поставки под заказ (от 5 рабочих дней);
- Экспресс доставка в любую точку России;
- Помощь Конструкторского Отдела и консультации квалифицированных инженеров;
- Техническая поддержка проекта, помощь в подборе аналогов, поставка прототипов;
- Поставка электронных компонентов под контролем ВП;
- Система менеджмента качества сертифицирована по Международному стандарту ISO 9001;
- При необходимости вся продукция военного и аэрокосмического назначения проходит испытания и сертификацию в лаборатории (по согласованию с заказчиком);
- Поставка специализированных компонентов военного и аэрокосмического уровня качества (Xilinx, Altera, Analog Devices, Intersil, Interpoint, Microsemi, Actel, Aeroflex, Peregrine, VPT, Syfer, Eurofarad, Texas Instruments, MS Kennedy, Miteq, Cobham, E2V, MA-COM, Hittite, Mini-Circuits, General Dynamics и др.);

Компания «Океан Электроники» является официальным дистрибьютором и эксклюзивным представителем в России одного из крупнейших производителей разъемов военного и аэрокосмического назначения «JONHON», а так же официальным дистрибьютором и эксклюзивным представителем в России производителя высокотехнологичных и надежных решений для передачи СВЧ сигналов «FORSTAR».



JONHON

«JONHON» (основан в 1970 г.)

Разъемы специального, военного и аэрокосмического назначения:

(Применяются в военной, авиационной, аэрокосмической, морской, железнодорожной, горно- и нефтедобывающей отраслях промышленности)

«FORSTAR» (основан в 1998 г.)

ВЧ соединители, коаксиальные кабели, кабельные сборки и микроволновые компоненты:

(Применяются в телекоммуникациях гражданского и специального назначения, в средствах связи, РЛС, а так же военной, авиационной и аэрокосмической отраслях промышленности).



Телефон: 8 (812) 309-75-97 (многоканальный)

Факс: 8 (812) 320-03-32

Электронная почта: ocean@oceanchips.ru

Web: <http://oceanchips.ru/>

Адрес: 198099, г. Санкт-Петербург, ул. Калинина, д. 2, корп. 4, лит. А